Example 15.3.2 -1

```
import sqlite3

connection = sqlite3.connect ("Academy.db")

cursor = connection.cursor()

sql_command = """

CREATE TABLE Student (

Rollno INTEGER PRIMARY KEY , Sname VARCHAR(20), Grade CHAR(1),

gender CHAR(1), Average DECIMAL (5, 2), birth_date DATE);"""

cursor.execute(sql_command)

sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average,
    birth_date) VALUES (NULL, "Akshay", "B", "M","87.8", "2001-12-12");"""

cursor.execute(sql_command)

sql_command = """INSERT INTO Student (Rollno, Sname, Grade, gender, Average,
    birth_date) VALUES (NULL, "Aravind", "A", "M","92.50","2000-08-17");"""

cursor.execute(sql_command)

# never forget this, if you want the changes to be saved:

connection.commit()

connection.close()

print("STUDENT TABLE CREATED")
```

OUTPUT

```
    STUDENT TABLE CREATED
```

Of course, in most cases, you will not literally insert data into a SQL table. You will rather have a lot of data inside of some Python data type e.g. a dictionary or a list, which has to be used as the input of the insert statement.

The following working example, assumes that you have an already existing database Academy.db and a table Student. We have a list with data of persons which will be used in the INSERT statement: