- At one particular position, the refracted ray begins to retrace its path. The position where the refracted image returns is the position of minimum deviation.
- The telescope is fixed in this position and is adjusted until the vertical cross-wire coincides with the refracted image of the slit.
- The readings are taken from both vernier scales.
- The prism is now removed and the telescope is rotated to obtain the direct ray image and the readings are taken.
- The readings are tabulated and the difference between these two readings gives the angle of minimum deviation D.
- From the values of A and D, the refractive index of the material of the glass prism is determined.

Least count

1 MSD = 30′

Number of vernier scale divisions = 30

For spectrometer, 30 vernier scale divisions will cover 29 main scale divisions.

$\therefore$ 30 VSD = 29 MSD

Or 1 VSD = $\left(\frac{29}{30}\right)$ MSD

Least count (LC) = 1 MSD – 1 VSD

$$= \left(\frac{1}{30}\right)\text{MSD} = \left(\frac{1}{30}\right) \times 30'$$

$$= 1'$$

OBSERVATION

Table 1 To find the angle of the prism (A)

Image	Vernier A (Degree)			Vernier B (Degree)		
	MSR	VSC	TR	MSR	VSC	TR
Reflected image from face 1						
Reflected image from face 2						
Difference 2A						

Mean 2A =

Mean A =

XII-Physics_Vol-1) PRACTICAL.indd 298 08-12-2022 11:00:35