8. Bundling two values together into one can be considered as

(A) Pair (B) Triplet (C) single (D) quadrat

9. Which of the following allow to name the various parts of a multi-item object?

(A) Tuples (B) Lists (C) Classes (D) quadrats

10. Which of the following is constructed by placing expressions within square brackets?

(A) Tuples (B) Lists (C) Classes (D) quadrats

Part - II

Answer the following questions **(2 Marks)**

1. What is abstract data type?
2. Differentiate constructors and selectors.
3. What is a Pair? Give an example.
4. What is a List? Give an example.
5. What is a Tuple? Give an example.

Part - III

Answer the following questions **(3 Marks)**

1. Differentiate Concrete data type and abstract datatype.
2. Which strategy is used for program designing? Define that Strategy.
3. Identify Which of the following are constructors and selectors?

(a) N1:=number() (b) accetnum(n1) (c) displaynum(n1)

(d) eval(a/b) (e) x,y:= makeslope (m), makeslope(n)

(f) display()

4. What are the different ways to access the elements of a list. Give example.
5. Identify Which of the following are List, Tuple and class ?

(a) arr [1, 2, 34] (b) arr (1, 2, 34) (c) student [rno, name, mark]

(d) day:= ('sun', 'mon', 'tue', 'wed') (e) x:= [2, 5, 6.5, [5, 6], 8.2]

(f) employee [eno, ename, esal, eaddress]

12th Computer Science_EM Chapter 2.indd 19 26-12-2022 17:25:50