Now compare the search element with the value stored at mid value location 4. The value stored at location or index 4 is 50, which is not match with search element. As the search value 60 is greater than 50.

Now we change our low to mid + 1 and find the new mid value again using the formula.

low = mid + 1

mid = low + (high - low) / 2

Our new mid is 7 now. We compare the value stored at location 7 with our target value 60.



The value stored at location or index 7 is not a match with search element, rather it is more than what we are looking for. So, the search element must be in the lower part from the current mid value location



The search element still not found. Hence, we calculated the mid again by using the formula.

high = mid -1

mid = low + (high - low)/2

Now the mid value is 5.



Now we compare the value stored at location 5 with our search element. We found that it is a match.



We can conclude that the search element 60 is found at lcoation or index 5. For example if we take the search element as 95, For this value this binary search algorithm return unsuccessful result.

4.5 Sorting Techniques

4.5.1 Bubble sort algorithm

Bubble sort is a simple sorting algorithm. The algorithm starts at the beginning of the list of values stored in an array. It compares each pair of adjacent elements and swaps them if they are in the unsorted order. This comparison and passed to be continued until no swaps are needed, which indicates that the list of values stored in an array is sorted. The algorithm is a comparison sort, is named for the way smaller elements "bubble" to the top of the list. Although the algorithm is simple, it is too slow and less efficient when compared to insertion sort and other sorting methods.

Assume list is an array of n elements. The swap function swaps the values of the given array elements.

Procedure

1. Start with the first element i.e., index = 0, compare the current element with the next element of the array.
2. If the current element is greater than the next element of the array, swap them.
3. If the current element is less than the next or right side of the element, move to the next element. Go to Step 1 and repeat until end of the index is reached.

12th Computer Science_EM Chapter 4.indd 38 21-12-2022 15:55:00