%=	Taken modulus(Remainder) using two operands and assign the result to left operand	>>> x%=3 # x=x%3
**=	Performed exponential (power) calculation on operators and assign value to the left operand	>>> x**=2 # x=x**2
//=	Performed floor division on operators and assign value to the left operand	>>> x//=3

Program 5.4 To test Assignment Operators:

Program Coding	Output

#Demo Program to test Assignment Operators
x=int (input("Type a Value for X : "))
print ("X = ",x)
print ("The x is =",x)
x+=20
print ("The x += 20 is =",x)
x-=5
print ("The x -= 5 is = ",x)
x*=5
print ("The x *= 5 is = ",x)
x/=2
print ("The x /= 2 is = ",x)
x%=3
print ("The x %= 3 is = ",x)
x**=2
print ("The x **= 2 is = ",x)
x//=3
print ("The x //= 3 is = ",x)
#Program End
	Type a Value for X : 10
	X = 10
	The x is = 10
	The x += 20 is = 30
	The x -= 5 is = 25
	The x *= 5 is = 125
	The x /= 2 is = 62.5
	The x %= 3 is = 2.5
	The x **= 2 is = 6.25
	The x //= 3 is = 2.0

(v) Conditional operator

Ternary operator is also known as conditional operator that evaluate something based on a condition being true or false. It simply allows testing a condition in a single line replacing the multiline if-else making the code compact.

12th Computer Science_EM Chapter 5.indd 60 26-12-2022 17:27:29