Example

```
#A string defined within single quotes
>>> print ('Greater Chennai Corporation')
        Greater Chennai Corporation

#single quoted string defined within single quotes
>>> print ('Greater Chennai Corporation's student')
        SyntaxError: invalid syntax

#A string defined within double quotes
>>>print ("Computer Science")
        Computer Science

#double quoted string defined within double quotes
>>> print ('' "Computer Science" '')
        "Computer Science"

#single and double quoted multiline string defined within triple quotes
>>> print ('' "Strings are immutable in 'Python',
                which means you can't make any changes
                once you declared" '')

        "Strings are immutable in 'Python',
        which means you can't make any changes once you declared"
```

8.3 Accessing characters in a String

Once you define a string, python allocate an index value for its each character. These index values are otherwise called as subscript which are used to access and manipulate the strings. The subscript can be positive or negative integer numbers.

The positive subscript **0** is assigned to the first character and **n-1** to the last character, where n is the number of characters in the string. The negative index assigned from the last character to the first character in reverse order begins with **-1**.

Example

String	S	C	H	O	O	L
Positive subscript	0	1	2	3	4	5
Negative subscript	-6	-5	-4	-3	-2	-1

12th Computer Science_EM Chapter 8.indd 115 21-12-2022 15:28:38