Example

```
Marks = [10, 23, 41, 75]
Fruits = ["Apple", "Orange", "Mango", "Banana"]
MyList = [ ]
```

In the above example, the list Marks has four integer elements; second list Fruits has four string elements; third is an empty list. The elements of a list need not be homogenous type of data. The following list contains multiple type elements.

Mylist = ["Welcome", 3.14, 10, [2, 4, 6]]

In the above example, Mylist contains another list as an element. This type of list is known as **"Nested List".**

Nested list is a list containing another list as an element.

9.1.2 Accessing List elements

Python assigns an automatic index value for each element of a list begins with zero. Index value can be used to access an element in a list. In python, index value is an integer number which can be positive or negative.

Example

Marks = [10, 23, 41, 75]

Marks	10	23	41	75
Index (Positive)	0	1	2	3
IndexNegative)	-4	-3	-2	-1

Positive value of index counts from the beginning of the list and negative value means counting backward from end of the list (i.e. in reverse order).

To access an element from a list, write the name of the list, followed by the index of the element enclosed within square brackets.

Syntax:

```
List_Variable = [E1, E2, E3 …… En]
print (List_Variable[index of a element])
```


12th Computer Science_EM Chapter 9.indd 133 21-12-2022 15:37:02