During the first iteration, the value of **i** is **0**, where the condition is true. Now, the following statement **print (Marks [i])** gets executed and prints the value of Marks [0] element ie. 10.

The next statement **i = i + 1** increments the value of **i** from **0** to **1**. Now, the flow of control shifts to the while statement for checking the test condition. The process repeats to print the remaining elements of **Marks** list until the test condition of while loop becomes false.

The following table shows that the execution of loop and the value to be print.

Iteration	i	while i < 4	print (Marks[i])	i = i + 1
1	0	0 < 4 True	Marks [0] = 10	0 + 1 = 1
2	1	1 < 4 True	Marks [1] = 23	1 + 1 = 2
3	2	2 < 4 True	Marks [2] = 41	2 + 1 = 3
4	3	3 < 4 True	Marks [3] = 75	3 + 1 = 4
5	4	4 < 4 False	--	--

(ii) Reverse Indexing

Python enables reverse or negative indexing for the list elements. Thus, python lists index in opposite order. The python sets -1 as the index value for the last element in list and -2 for the preceding element and so on. This is called as **Reverse Indexing.**

Example

```
Marks = [10, 23, 41, 75]
i = -1
while i >= -4:
        print (Marks[i])
        i = i + -1
```

Output

```
75
41
23
10
```

The following table shows the working process of the above python coding

12th Computer Science_EM Chapter 9.indd 135 21-12-2022 15:37:02