```
CREATE TABLE Student
(
Admno integer NOT NULL UNIQUE, → Unique constraint
Name char (20) NOT NULL,
Gender char (1),
Age integer,
Place char (10),
);
```

The **UNIQUE** constraint can be applied only to fields that have also been declared as **NOT NULL**.

When two constraints are applied on a single field, it is known as multiple constraints. In the above Multiple constraints **NOT NULL** and **UNIQUE** are applied on a single field Admno, the constraints are separated by a space and at the end of the field definition a comma(,) is added. By adding these two constraints the field Admno must take some value ie. will not be **NULL** and should not be duplicated.

12.7.2.2 Primary Key Constraint

This constraint declares a field as a Primary key which helps to uniquely identify a record. It is similar to unique constraint except that only one field of a table can be set as primary key. The primary key does not allow **NULL** values.

Example showing Primary Key Constraint in the student table:

```
CREATE TABLE Student
(
Admno integer   PRIMARY KEY, → Primary Key constraint
Name char(20)  NOT NULL,
Gender char(1),
Age integer,
Place char(10),
);
```

In the above example the Admno field has been set as primary key and therefore will help us to uniquely identify a record, it is also set **NOT NULL**, therefore this field value cannot be empty.

12.7.2.3 DEFAULT Constraint

The **DEFAULT** constraint is used to assign a default value for the field. When no value is given for the specified field having **DEFAULT** constraint, automatically the default value will be assigned to the field.

12th Computer Science_EM Chapter 12.indd 206 22-12-2022 11:54:47