```
CREATE TABLE Student 1
(
Admno integer        NOT NULL,
Firstname char(20),
Lastname char(20),
Gender char(1),
Age integer,
Place char(10),
PRIMARY KEY (Firstname, Lastname) → Table constraint
);
```

In the above example, the two fields, Firstname and Lastname are defined as Primary key which is a Table constraint.

12.7.3 DML COMMANDS

Once the schema or structure of the table is created, values can be added to the table. The DML commands consist of inserting, deleting and updating rows into the table.

12.7.3.1 INSERT command

The **INSERT** command helps to add new data to the database or add new records to the table. The command is used as follows:

INSERT INTO <table-name> [column-list] VALUES (values);

INSERT INTO Student (Admno, Name, Gender, Age, Place)

VALUES (100, 'Ashish', 'M', 17, 'Chennai');

INSERT INTO Student (Admno, Name, Gender, Age, Place)

VALUES (101, 'Adarsh', 'M', 18, 'Delhi');

Two new records are added to the table as shown below:

Admno	Name	Gender	Age	Place
100	Ashish	M	17	Chennai
101	Adarsh	M	18	Delhi

The order of values must match the order of columns in the **CREATE TABLE** command. Specifying the column names is optional if data is to be added for all columns. The command to add values into the student table can also be used in the following way:

INSERT INTO Student VALUES (102, 'Akshith', 'M', 17, 'Bangalore');

102	Akshith	M	17	Bangalore

The above command inserts the record into the student table.

To add data to only some columns in a record by specifying the column name and their data, it can be done by:

12th Computer Science_EM Chapter 12.indd 208 22-12-2022 11:54:47