The table can be deleted by **DROP TABLE** command in the following way:

DROP TABLE table-name;

For example to delete the Student table:

DROP TABLE Student;

DELETE, TRUNCATE AND DROP statement:

DELETE	The **DELETE** command deletes only the rows from the table based on the condition given in the where clause or deletes all the rows from the table if no condition is specified. But it does not free the space containing the table.
TRUNCATE	The **TRUNCATE** command is used to delete all the rows, the structure remains in the table and free the space containing the table.
DROP	The **DROP** command is used to remove an object from the database. If you drop a table, all the rows in the table is deleted and the table structure is removed from the database. Once a table is dropped we cannot get it back.

12.7.5 DQL COMMAND– SELECT command

One of the most important tasks when working with SQL is to generate Queries and retrieve data. A Query is a command given to get a desired result from the database table. The **SELECT** command is used to query or retrieve data from a table in the database. It is used to retrieve a subset of records from one or more tables. The **SELECT** command can be used in various forms:

Syntax of **SELECT** command :

SELECT <column-list>FROM<table-name>;

- Table-name is the name of the table from which the information is retrieved.
- Column-list includes one or more columns from which data is retrieved.

For example to view only admission number and name of students from the Student table the command is given as follows:

If the Student table has the following data:

12th Computer Science_EM Chapter 12.indd 212 22-12-2022 11:54:47