12.7.5.2 ALL Keyword

The **ALL** keyword retains duplicate rows. It will display every row of the table without considering duplicate entries.

SELECT ALL Place FROM Student;

The above command will display all values of place field from every row of the table without eliminating the duplicate entries.

Place
Chennai
Delhi
Bangalore
Delhi
Chennai
Chennai
Bangalore
Chennai

The **WHERE** clause in the **SELECT** command specifies the criteria for getting the desired result. The general form of **SELECT** command with **WHERE** Clause is:

SELECT <column-name>[,<column-name>,….] FROM <table-name>WHERE condition>;

For example to display the students admission number and name of only those students who belong to Chennai, the **SELECT** command is used in the following way :

SELECT Admno, Name, Place FROM Student WHERE Place = 'Chennai';

Admno	Name	Place
100	Ashish	Chennai
104	Abinandh	Chennai
105	Revathi	Chennai
107	Hema	Chennai

SELECT Admno, Name, Age FROM Student WHERE Age >= 18;

Admno	Name	Age
101	Adarsh	18
103	Ayush	18
104	Abinandh	18
105	Revathi	19
106	Devika	19

The relational operators like =, <, <=, >, >=, <> can be used to compare two values in the **SELECT** command used with **WHERE** clause. The logical operaors **OR, AND** and **NOT**

12th Computer Science_EM Chapter 12.indd 214 22-12-2022 11:54:47