12.7.6.3 SAVEPOINT command

The **SAVEPOINT** command is used to temporarily save a transaction so that you can rollback to the point whenever required. The different states of our table can be saved at anytime using different names and the rollback to that state can be done using the **ROLLBACK** command.

```
SAVEPOINT savepoint_name;
```

Example showing **COMMIT, SAVEPOINT** and **ROLLBACK** in the student table having the following data:

Admno	Name	Gender	Age	Place
105	Revathi	F	19	Chennai
106	Devika	F	19	Bangalore
103	Ayush	M	18	Delhi
101	Adarsh	M	18	Delhi
104	Abinandh	M	18	Chennai

```
INSERT INTO Student  VALUES (107, 'Beena', 'F', 20 , 'Cochin');
COMMIT;
```

Admno	Name	Gender	Age	Place
105	Revathi	F	19	Chennai
106	Devika	F	19	Bangalore
103	Ayush	M	18	Delhi
101	Adarsh	M	18	Delhi
104	Abinandh	M	18	Chennai
107	Beena	F	20	Cochin

```
UPDATE Student SET Name = 'Mini' WHERE  Admno=105;
SAVEPOINT A;
```

Admno	Name	Gender	Age	Place
105	Mini	F	19	Chennai
106	Devika	F	19	Bangalore
103	Ayush	M	18	Delhi
101	Adarsh	M	18	Delhi
104	Abinandh	M	18	Chennai
107	Beena	F	20	Cochin

12th Computer Science_EM Chapter 12.indd 220 22-12-2022 11:54:47