```
import csv
row = ['3', 'Meena','Bangalore']
with open('student.csv', 'r', newline='=') as readFile:
    reader = csv.reader(readFile)
    lines = list(reader)        #  list()- to store each row of data as a list
    lines[3] = row
with open('student.csv', 'w') as writeFile:
#  returns the writer object which converts the user data with delimiter
    writer = csv.writer(writeFile)
#writerows()method writes multiple rows to a csv file
    writer.writerows(lines)
readFile.close()
writeFile.close()
```

When we open the student.csv file with text editor, then it will show:

Roll No, Name, City

1, Harshini, Chennai

2, Adhith, Mumbai

3, Meena, Bangalore

4, Krishna, Tiruchy

5, Venkat, Madurai

In the above program,the third row of "student.csv" is modified and saved. First the "student.csv" file is read by using csv.reader() function. Then, the list() stores each row of the file. The statement "lines[3] = row", changed the third row of the file with the new content in "row". The file object writer using writerows (lines) writes the values of the list to "student.csv" file.

13.7.2.1 ADDING NEW ROW

Sometimes, you may need to add new rows in the existing CSVfile. Adding a new row at the end of the file is called appending a row.

The following program add a new row to the existing "student.csv" file.

12th Computer Science_EM Chapter 13.indd 248 23-12-2022 15:39:38