cursor object. Usually, **a cursor in SQL and databases is a control structure to traverse over the records in a database.** So it's used for the fetching of the results.



Note

Cursor is used for performing all SQL commands.

The cursor object is created by calling the cursor() method of connection. The cursor is used to traverse the records from the result set. You **can define a SQL command with a triple quoted string in Python.** The reason behind the triple quotes is sometime the values in the table might contain single or double quotes.

Example 15.3.1

```
sql_command = """
CREATE TABLE Student (
Rollno INTEGER PRIMARY KEY ,
Sname VARCHAR(20),
Grade CHAR(1),
gender CHAR(1),
Average DECIMAL(5,2),
birth_date DATE);"""
```

In the above example the Rollno field as "INTEGER PRIMARY KEY" A column which is labeled like this will be automatically auto-incremented in SQLite3. To put it in other words: **If a column of a table is declared to be an INTEGER PRIMARY KEY, then whenever a NULL will be used as an input for this column, the NULL will be automatically converted into an integer which will one larger than the highest value so far used in that column.** If the table is empty, the value **1** will be used.

15.3.2 Adding Records

To populate (add record) the table "INSERT" command is passed to SQLite. “execute” method executes the SQL command to perform some action. The following example 15.3.2 is a complete working example. To run the program you should uncomment the "DROP TABLE" line in the SQL command, if the program has been executed already.

12th Computer Science_EM Chapter 15.indd 280 23-12-2022 15:33:41