

GLOSSARY

XTZCQ

Terminology	Meaning
Access control	*security technique that regulates who or what can view or use resources in a computing environment*
Access modifiers	*Private , Protected and Public*
Alternative	*One of two choices*
append()	*Used to add an element in a list*
Argument	*Argument is the actual value of this variable that gets passed to function.*
argv	*An array containing the values passed through command line argument*
Attribute	*Data items that makes up an object*
Authorization	*Giving permission or access*
Block	*Set of Statements*
Boolean	*means Logical*
break	*Exit the control*
c = sqlite3.connect('test. db')	*create a database connection to the SQLite database 'test.db'. You can also supply the special name :memory: to create a database in RAM.*
c.close()	*To release the connection of the database*
c.commit()	*To save the changes made in the table*
c.execute()	*Executes all SQL commands .Accepts two kinds of placeholders: question marks ? ("qmark style") and named placeholders :name ("named style").*
Cartesian product	*Cartesian operation is helpful to merge columns from two relations*
cd	*cd command refers to change directory*
Class	*Template of creating objects.*
Class variable	*An ordinary variable declared inside a class*
cls	*To clear the screen in command window*
Comma(,)	*Comma is used to separate each data in a csv file*

12th Std - CS EM Glossary Pages.indd 321 23-12-2022 11:35:04