compiler	*Scans the entire program and translates it as a whole into machine code. It generates the error message only after scanning the whole program. Hence debugging is comparatively hard.*
Conjunction	*Concurrence, coincidence*
Constraint	*Restriction or limitation*
Constructor	*A special function get execution automatically when an object enter into scope.*
continue	*To skip the remaining part and start with next iteration.*
CRUD	*Create, Read, Update and Delete*
csv.reader()	*The reader function is designed to take each line of the file and make a list of all columns*
csv.register_dialect()	*A dialect describes the format of the csv file that is to be read*
CsvQuote All	*If quoting is set to csvquote all, then writerow() will quote all fields.*
cur = c.cursor()	*Creating cursor object*
cur.fetchall()	*method to get a list of the matching rows.*
cur.fetchmany()	*method that returns the next number of rows (n) of the result set*
cur.fetchone()	*method to retrieve a single matching row*
CWI	*Centrum Wiskunde & Informatica*
DBA	*DataBase Adminstrator*
DBMS	*Database Management System*
def	*This keyword is used to define function.*
Destructor	*A special function get execution automatically when an object exit from its scope.*
dict()	*It is used to print the data in dictionary format without orderdict*
Dictionary	*Collection of Key-Value pairs*
DictReader()	*Works by reading in the first line of the CSV and using each column comma separated value in this line as a dictionary key.*
Dictwriter()	*Write dictionary data into a CSV file*
elif	*else…if*
Embedded	*Firmly attached*
Enter key	*Enter key or newline is used to create rows in a csv file*

12th Std - CS EM Glossary Pages.indd 322 23-12-2022 11:35:04