

Data Structures and Algorithms 120

Lecture 7a: Linked Lists



Copyright Warning

COMMONWEALTH OF AUSTRALIA

Copyright Regulation 1969

WARNING

This material has been copied and communicated to you by or on behalf of Curtin University of Technology pursuant to Part VB of the Copyright Act 1968 (the Act)

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice



This Week

- Linked Lists
 - Simple linked lists
- Variants
 - Double-ended
 - Doubly-linked
 - Sorted linked lists
- Time complexity analysis
 - Big-O notation



Arrays Aren't Everything


- As a data structure, arrays have their disadvantages
 - **Fixed size** – cannot grow/shrink to fit num elements
 - » If we don't know how many elements in advance, we'll need to overestimate the array's length, and thus waste space
 - **Insertion** – inserting an element between two existing elements will require shuffling later elements up by one
 - » Similar issues plague **removal** from the front/middle (*e.g.*, queues)
 - **Contiguous** – all elements must fit in a contiguous block
 - » This is sometimes a disadvantage – it's a bit inflexible
- We'd like a data structure that doesn't suffer from these
 - ... but still does a similar job to arrays (storing list of data)
 - Fortunately, it's already been invented: the linked list



Linked Lists

- The idea behind a linked list is that each element stores a **value** *and* a **reference** to the *next* element
 - The list is essentially a chain of links
 - The list itself only stores a reference to the *first* element
 - » This is often called the ‘head’
 - Since each element only points to the next, it is *singly-linked*
 - Since the list only points at the head, it is *single-ended*
- More complicated variants on the basic single-ended singly-linked list
 - Double-ended, doubly-linked, etc
 - We’ll examine some of these variants later

Simple Linked List





Anatomy of a Linked List

- Each element is not just data but also a reference to the next element
 - Thus we need to create a composite of `value` + `next` ref
 - » Classes are ideally suited to this – make `value`, `next` class fields
 - Typically called `ListNode`, or less commonly `ListLink`
 - » In pre-OO languages, use structs (C) or records (Pascal)
- Head is the only member field of `LinkedList` class
 - Points at the first `ListNode` in the list
- Last node's `next` points at null
 - Indicates the end of the linked list



ListNode Members

- ListNode only exists as a container for the data and the next pointer
- Thus it is really only a couple of member fields with associated getters/setters:
 - One member field for the data value, usually an Object so that the list can be general-purpose
 - A member `ListNode next` that is a reference to the next node in the list's chain
 - » This points at null if the `ListNode` is the last node in the chain



Traversing Linked Lists

- A linked list is just a chain of connected-but-independent nodes
 - Each node could be anywhere in memory
 - Only a node's predecessor knows where to find a given node (in memory)
 - So the only way to get to the fourth node is to first get to the third node
 - » which in turns requires us to have made it to the second node
 - » ... and we can only get to that via the first node



Traversing Linked Lists

- Only the first node is available directly (via head)
 - Thus getting to a particular node requires that we traverse from the head (first) node, through all the next pointers until we reach the desired node
 - » This obviously can be pretty slow
 - Compare this to an array, which can get to *any* element in *one step*
 - » via a little bit of arithmetic – it works because the array elements are all stored in a contiguous block
 - » But linked lists aren't contiguous, so we have to do traversing
 - This is the main disadvantage of linked lists: **access time**



Linked List Methods

- isEmpty()
- insertFirst(), insertLast(),
insertBefore(<dataType> valueToFind)
 - Insert a new item into the list
 - Should require a data item as import, NOT a ListNode
 - » ListNode is an **internal** detail of LinkedList's implementation
- removeFirst(), removeLast(),
remove(<dataType> valueToFind)
 - Delete an item from the list
- peekFirst(), peekLast(), peek(<dataType> valueToFind)
 - Return the **data value** of an item in the list (not ListNode)
- find(<dataType> valueToFind)
 - Search whether a given data value exists in the list




Inserting a ListNode

- There are four possible scenarios for node insertion:
 - The list is empty and we are inserting the first node
 - We are inserting before the head node
 - We are inserting after the tail of the list
 - We are inserting somewhere in the middle of the list
- In code, some of these cases turn out to be the same thing, but when designing a solution you should *always* be thinking through all the possibilities


Inserting First ListNode

- Initial: empty list
(ie: head points at null)




- Step 1: Create new ListNode with (say) value of 3.8

```
ListNode newNd;  
newNd = new ListNode(3.8);
```




- Step 2: Point head at the newNd to make it the first node




Inserting ListNode Before Head

- Initial: a few nodes in the list




- Step 1: Create new ListNode with (say) value of 15.2

```
ListNode newNd;  
newNd = new ListNode(15.2);
```




- Step 2&3: Fix links to make newNd first

```
newNd.next = head;  
head = newNd;
```




Inserting ListNode After Tail


- Initial: a few nodes in the list



- Step 1: Create new ListNode with (say) value of 100




- Step 2: Make last node in the chain point at the newNd




Inserting ListNode In The Middle


- Initial: a few nodes in the list



- Step 1: Create new ListNode with (say) value of 10.3



- Step 2: 'Fix up' links to make it fit correctly in the list






Removing a ListNode

- As with insertion, there are four cases:
 - Removing the head ListNode
 - Removing the tail ListNode
 - Removing a ListNode in the middle of the list
 - Removing the sole remaining ListNode in the list
- And as with insertion, some of these cases end up being the same in the code

Removing Head ListNode

- Initial: a few nodes in the list




- Step 1: Point head at second node

```
head = head.next;
```

First node is now

no longer part of the list


and its memory usage will be garbage-collected by Java
(in C/C++, you would have to explicitly free it)




- The fact that Node 15.2 still points at the second node is not relevant: nothing points *at* Node 15.2, therefore it will be garbage-collected

Removing Tail ListNode

- Initial: a few nodes in the list



- Step 1: Point second-last node at null.
Last node is now no longer part of the list




```
ListNode currNd, prevNd;  
currNd = head;  
prevNd = null;  
  
// Traverse to last node  
while (currNd.next != null) {  
    prevNd = currNd;  
    currNd = currNd.next;  
}  
prevNd.next = null;
```

Removing ListNode In The Middle

- Initial: a few nodes in the list;


Node 10.3 is to be removed



- Step 1: Have predecessor node point at Node 10.3's next node.


Node 10.3 is

now no longer part of the list




Removing Last Remaining ListNode

- Initial: one node remains in the list



- Step 1: Point head at null

Node is now
no longer part of list



```
// Same as removing first node  
head = head.next;
```



ListNode - Pseudo-code

```
Class DSAListNode
Class fields : value (Object), next (DSAListNode) // Could make these public members
                                                    // and avoid the need for getters/setters since
                                                    // ListNode is only used INSIDE LinkedList

Alternate constructor IMPORT inValue (Object)      // Only need one constructor
    value ← inValue                                // No need for validation
    next ← NULL

ACCESSOR getValue IMPORT none EXPORT value

MUTATOR setValue IMPORT inValue (Object) EXPORT none
    value ← inValue

ACCESSOR getNext IMPORT none EXPORT next

MUTATOR setNext IMPORT newNext (DSAListNode) EXPORT none
    next ← newNext
```



Simple LinkedList - Pseudo-code

```
Class DSALinkedList
Class fields : head (DSAListNode)

Default constructor
    head ← NULL

MUTATOR insertFirst IMPORT newValue (Object) EXPORT none
    newNd ← allocate DSAListNode(newValue)
    IF isEmpty() THEN
        head ← newNd
    ELSE
        newNd.setNext(head)
        head ← newNd
    ENDIF

MUTATOR insertLast IMPORT newValue (Object) EXPORT none
    newNd ← allocate DSAListNode(newValue)
    IF isEmpty() THEN
        head ← newNd
    ELSE
        currNd ← head
        WHILE currNd.getNext() <> NULL DO           // Traverse to last node
            currNd ← currNd.getNext()
        ENDWHILE
        currNd.setNext(newNd)
    ENDIF
```

<continued next slide>



Simple LinkedList - Pseudo-code

```
ACCESSOR isEmpty IMPORT none EXPORT empty (boolean)
  empty ← (head = NULL)
```

```
ACCESSOR peekFirst IMPORT none EXPORT nodeValue (Object)
  IF isEmpty() THEN
    abort
  ELSE
    nodeValue ← head.getValue()
  ENDIF
```

```
ACCESSOR peekLast IMPORT none EXPORT nodeValue (Object)
  IF isEmpty() THEN
    abort
  ELSE
    currNd ← head
    WHILE currNd.getNext() <> NULL DO           // Traverse to last node
      currNd ← currNd.getNext()
    ENDWHILE
    nodeValue ← currNd.getValue()
  ENDIF
```

<continued next slide>

Simple LinkedList - Pseudo-code

```
MUTATOR removeFirst IMPORT none EXPORT nodeValue (Object)
  IF isEmpty() THEN
    abort
  ELSE
    nodeValue ← head.getValue()
    head ← head.getNext()
  ENDIF
```

```
MUTATOR removeLast IMPORT none EXPORT nodeValue (Object)
  IF isEmpty() THEN
    abort
  ELSEIF head.getNext() = NULL THEN
    nodeValue ← head.getValue()
    head ← NULL
  ELSE
    prevNd ← NULL
    currNd ← head
    WHILE currNd.getNext() <> NULL DO
      prevNd ← currNd
      currNd ← currNd.getNext()
    ENDWHILE
    prevNd.setNext(NULL)
    nodeValue ← currNd.getValue()
  ENDIF
```

```
// Traverse to last node
// We need to get the second-last node
// in order to 'drop' the last node from the list

// Remove currNd from list
// Return value of node that is being removed
```



Private Inner classes - Java

```
public class DSALinkedList
{
    private class DSAListNode
    {    // Private inner class
        private Object m_value;
        private DSAListNode m_next;
        //could make the classfields public as they can
        //only be seen inside DSALinkedList
        public DSAListNode(Object inValue)
        {
            m_value = inValue;
            m_next = null;
        }
        // normal accessors and mutators if required
    }    // end private inner class DSAListNode
    // class DSALinkedList continues
```



Simple LinkedList / ListNode

– NOTE WELL:

- In the practicals, you are supposed to implement a *double-ended* linked list by adjusting this pseudocode
 - » (this pseudocode is just a single-ended linked list)
 - » We will be discussing double-ended lists in a moment



Linked Lists vs Arrays

- Advantages of linked lists over arrays
 - ✓ Can grow and shrink with data - no space wasted
 - ✓ No limits on size (besides memory available)
 - ✓ Easy to insert items at any part of the list
 - » Arrays are only easy to add items to the end
- Disadvantages
 - ✗ Time to access any given element: $N/2$ steps (on average)
 - » Where N is the number of nodes in the list
 - » Array is direct access: only takes 1 step
 - ✗ `next` pointer is an overhead in terms of memory usage
 - » Adds 1 word (memory address) extra per element in addition to actual data



Order of Complexity

- lets analyse LinkedList find() in Big-O notation
 - Best case: the head is the node to find
 - » This is one step, so $O(1)$
 - Worst case: last node is the match, which is N node hops
 - » $O(N)$ in Big-O notation
 - » Each hop involves multiple CPU instructions, but we aren't concerned with these details, so we don't talk about $O(5N)$
 - Average case: On average, we must go halfway: $N/2$ hops
 - » $O(N)$ – again, the constant multiplying factor of $1/2$ is irrelevant
 - We are mostly interested in the average and worst cases



Double-Ended Linked Lists


- We often want to work at the start *and* end of a list
 - *e.g.*, queue adds to end, takes from front
- Simple list is slowest when doing anything at the end
 - Takes $O(N)$ to reach the end – we'd like to do better!
- **Solution:** add another pointer to point at the last node
 - Call it `tail`
 - Put it with `head` as a member field of the `LinkedList`
 - That way we can access both `head` and `tail` in $O(1)$
- No disadvantage to this
 - Only adding one pointer to the whole linked list
 - Some code gets more complex, but other code gets easier



Double-Ended vs Single-Ended Lists

- Adding a tail pointer changes how many of the LinkedList methods work
 - insertLast() obviously becomes as easy/fast as insertFirst()
 - » Same with peekLast()
 - insertFirst() and removeFirst() now have to potentially set tail as well in the case of a one-node list
 - » *i.e.*, must maintain tail as well as head everywhere in the code
 - Counter-intuitively, removeLast() isn't helped much
 - » We need to get at the *second*-last node to do removeLast()!

Double-Ended Linked List







Doubly-Linked Lists

- Sometimes it's useful to be able to traverse both forwards *and backwards* through a list
 - *e.g.*, undo method in an application: in order to allow redo, must be able to go back and forth one node at a time
- Doubly-linked lists add another pointer to each ListNode: `prev`
 - **Issue:** Now overheads are *two* references per ListNode
 - » That's 2 words extra *per node* (8 bytes in a 32-bit machine; 16 bytes for 64-bit)
 - » Given that **ints** are only 4 bytes, it can easily *treble* space usage!
 - **Benefit:** `removeLast()` is easy if double-ended as well

Doubly-Linked List



Double-Ended, Doubly-Linked List





Sorted Linked Lists

- Since it's easy to insert new elements at any position in a linked list, it can also be convenient to insert them in **sorted order**
 - When adding a new element, find where it would fit (in sorted order) in the list and insert it there
- This is a variant on the Insertion Sort algorithm
 - A Doubly-Linked List makes this simple
 - » no moving elements – just search backwards then update links!



Saving Linked Lists to file

- We need to serialize our list.
 - we must put all the data together into a single block
- Only a few data structures are organised in blocks
 - Pretty much only arrays, and even then you need to add more info to define what the array's data type is
 - Each node of our linked list can be located in a completely different area of RAM
 - Remember, pointers cannot be made persistent
 - » You cannot save a pointer and expect it to be useful after re-loading it since the pointer says where the data used to be in the old run of the application!
 - » When the application runs again, it won't place objects in the same place – every time new is called, it returns a different address



Saving Linked Lists to file

- And it is not just our Linked List structure we have to worry about
 - our generic Object class for storing the data does not have file I/O methods!
- Create a new Abstract class that forces save/load methods
 - All of our data must then inherit from this class
- Or, simply use Java's object serialization!



Time Complexity Comparison

- Comparison of data structure speeds has many facets
 - Insertion, deletion, accessing and finding
 - » Access = getting the value at a known index
 - » Finding = searching through the data set to find the value
 - Best case, worst case, average case
 - » Usually corresponding to front, rear and middle
 - ... but not necessarily in that order!

Complexity: Array vs Simple LinkedList

Array vs List		Insert	Delete	Access	Find
Array	At front	$O(N)$	$O(N)$	$O(1)$	$O(1)$
	At end	$O(1)$	$O(1)$	$O(1)$	$O(N)$
	In middle	$O(N)$	$O(N)$	$O(1)$	$O(N)$
Linked List (single-ended)	At front	$O(1)$	$O(1)$	$O(1)$	$O(1)$
	At end	$O(N)$	$O(N)$	$O(N)$	$O(N)$
	In middle	$O(N)$	$O(N)$	$O(N)$	$O(N)$

NOTE: Although linked lists are fast to insert/delete, it still takes $O(N)$ to traverse the list and make it to the place to insert/delete

Complexity: List Variants vs Simple List

List variants vs single-ended		Insert	Delete	Access	Find
Linked List (double-ended)	At front	$O(1)$	$O(1)$	$O(1)$	$O(1)$
	At end	$O(1)$	$O(N)$	$O(1)$	$O(N)$
	In middle	$O(N)$	$O(N)$	$O(N)$	$O(N)$
Linked List (doubly-linked) <u>Same as singly-linked single-ended!</u>	At front	$O(1)$	$O(1)$	$O(1)$	$O(1)$
	At end	$O(N)$	$O(N)$	$O(N)$	$O(N)$
	In middle	$O(N)$	$O(N)$	$O(N)$	$O(N)$

Complexity: Sorted List vs Simple List

Sorted list vs single-ended		Insert	Delete	Access	Find
Linked List (sorted) <u>Same as singly-linked single-ended!</u>	At front	$O(1)$	$O(1)$	$O(1)$	$O(1)$
	At end	$O(N)$	$O(N)$	$O(N)$	$O(N)$
	In middle	$O(N)$	$O(N)$	$O(N)$	$O(N)$

- Sorting will help only a little bit for find():
 - If the value *isn't* in the list ,we only need to search up to the point the number *should* be at, and then we can abort
 - » Other lists are forced to search through all elements
- But it **doesn't** resolve poor scaling with larger N



Notes on Comparisons

- Arrays are unbeatable at $O(1)$ for access time
 - » This makes them **indispensable**. Why? Because you often only add/remove an element *once*, but access an element *many times*
 - » But if you only need to work on the **ends**, linked lists are better
- Single-ended lists are only good at working with **one end** (the head), double-ended lists are good at working with **both ends** (head and tail)
 - » Otherwise, you might as well be using an array, UNLESS you need the ability to dynamically grow and shrink efficiently
- Doubly-*linked* lists don't help access/find time
 - » How can you know it will be faster to go *backwards*?
 - » Their real strength is application-specific back-and-forthing



Traversal

- Iterating over elements in a data set is a common task
 - *e.g.*, to calculate the average of an array of ages:

```
public double calcAverageAge(double[] ages) {  
    double sum = 0.0;  
    for (int ii = 0; ii < ages.length; ii++) {  
        sum += ages[ii];  
    }  
    return sum / (double)ages.length;  
}
```

» An array's $O(1)$ time to access *any* element makes this efficient

- We could do the same with a LinkedList, but only if it provided some way to get at each element
 - **Solution 1:** Provide a peek(int index) method
 - **Solution 2:** Provide an *iterator* object



Inefficient LinkList Traversal - Indexing

- The problem with Solution 1 is that it is inefficient
 - `peek(int index)` must start at the beginning of the list every time it is called
 - » *i.e.*, it must traverse through the list from the beginning until it reaches the desired index
 - Thus a for loop to visit N elements will cause `peek()` to make N *traversals* of the list:

```
for (int ii = 0; ii < numAges; ii++)  
    sum += ages.peek(ii);
```

 - » Steps: $1 + 2 + 3 + 4 + \dots + N = N(N+1)/2$ steps $\approx N^2$
 - Complexity: $O(N^2)$ (!!)
 - » Truly awful scalability for a simple ‘access each element’ task



Efficient LinkedList Traversal - Iterators

- Solution 2 seeks to solve this inefficiency problem
 - Keep a reference to the *last visited* (‘current’) node
 - » Sometimes called a **cursor**, since it indicates where you are
 - Every time the next node is requested, it only needs to make one hop forward
- Naïve approach: make `curr` a member of `LinkedList`
 - **Issue:** What if *two* loops access the list at the same time?
 - » Commonly happens with nested for loops
 - But there’s only *one* `curr` node in the `LinkedList`
 - » Can’t share it among many for loops
 - You can examine a proper solution to this in the generics slide set

Not the End

- There's still a second half to go.

