



# Data Structures and Algorithms

## Lecture 7b: Iterators, Generics



# Copyright Warning

---

## **COMMONWEALTH OF AUSTRALIA**

Copyright Regulation 1969

### **WARNING**

This material has been copied and communicated to you by or on behalf of Curtin University of Technology pursuant to Part VB of the Copyright Act 1968 (the Act)

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice



# Iterators

---

- A LinkedList with a single ‘current’ cursor is limiting
  - Assumes only one ‘user/client’ of the LinkedList at a time
  - It would be better if every client had its own current cursor
- Iterators are designed to solve this problem
  - Each Java container (list) class has an `iterator()` method
    - » Note that it’s not `getIterator()` - a bit inconsistent of Java!
  - Returns an **Iterator** (or more precisely, an object that inherits from the Java **Iterator** interface)
    - » You don’t need to know the exact object type - knowing it is an **Iterator** is enough (the power of interfaces and polymorphism!)
    - » **Enumeration** is an older Java interface for the same idea



# Iterator Interface

---

- Quite simple; only three methods
  - `hasNext()` - queries if more items exist in the list
  - `next()` - move the cursor to the next item in the list
  - `remove()` - optional ability to remove the current item
    - » throw `UnsupportedOperationException` if you don't support it
  - These just give standard names to a common task
- No `prev()` - inherit from interface `ListIterator` for that
- Only limit is that behaviour is undefined if element removed by one client while another client iterating
  - Depends on the underlying list being iterated over
  - Some can handle this scenario (*e.g.*, linked list) others can't



# Using an Iterator

---

## – Using the iterator directly:

```
public void iterateOverList(LinkedList theList) {  
    MyClass c;  
    Iterator iter = theList.iterator();  
    while (iter.hasNext()) {  
        c = (MyClass)iter.next();           ← Get next item and cast from Object to MyClass  
        doSomething(c);  
    }  
}
```

## – Using the ‘for-each’ looping structure:

- Added to Java in 1.5 to simplify coding iterations
- Requires list class to implement Iterable interface

```
public void iterateOverList(LinkedList theList) {  
    MyClass c;  
    for (Object o : theList) {  
        c = (MyClass)o;                     ← Cast to MyClass  
        doSomething(c);  
    }  
}
```

- Also handles nested loops without causing iteration errors

# Writing Your Own Iterator

- Iterators are well-suited to being implemented by **private inner classes** - clients only need to know about Iterator

```
public class MyLinkedList implements Iterable {    ← so for-each loop can be used. Only defines iterator() method
    ...
    public Iterator iterator() {                ← Return a new Iterator of internal type MyLinkedListIterator
        return new MyLinkedListIterator(this);  ← Hook the iterator to this MyLinkedList object
    }

    private class MyLinkedListIterator implements Iterator { ← Private class inside MyLinkedList
        private MyListNode iterNext;            ← Cursor (assuming MyListNode is the node class of MyLinkedList)
        public MyLinkedListIterator(MyLinkedList theList) {
            iterNext = theList.head;            ← NOTE: Able to access private field of MyLinkedList
        }
        // Iterator interface implementation
        public boolean hasNext() { return (iterNext != null) }
        public Object next() {
            Object value;
            if (iterNext == null)
                value = null;
            else {
                value = iterNext.getValue();      ← Get the value in the node
                iterNext = iterNext.getNext();    ← Ready for subsequent calls to next()
            }
            return value;
        }
        public void remove() { throw new UnsupportedOperationException("Not supported"); }
    }
}
```



# Private Inner Classes

---

- Note that the iterator class was able to access the ‘head’ field of the list class
  - Even though ‘head’ is a private field!
  - Works because the inner class is also part of the list class
    - » The inner class has **access to all private fields** of the outer class
  - This is a very useful property of inner classes that are exploited in many contexts
    - » *e.g.*, event handling in GUIs, helper classes, and Iterators
    - » Replaces the terrible concept of **friend** classes in C++
  - You could always pass the head instead of the list though



# Generics

---

- You’ll notice in the Java 1.5/1.6 Docs that Iterator, and indeed most of the container classes, have this funny ‘<E>’ thing appended to their class names
  - *e.g.*, Stack<E>, Iterator<E> ArrayList<E>
  - These represent what are called generic classes
    - » The same concept is in C#, and called templates in C++
- Generics allow you to parameterise the *class itself* by providing the types that the class operates on
  - *e.g.*, Stack<Plate> means “create a Stack of Plates”





# Generics - Why Bother?

---

- When writing a container without generics, to make it general-purpose you must have Objects for fields
  - Otherwise you will be limiting what can be stored
  - But this means that the client of your container must downcast from Object to the class they actually put in
    - » Annoying, and risks a ClassCastException at runtime
  - Also, primitives are not Objects and so cannot be stored
    - » Must use the wrapper classes - Integer, Float, Double, etc
    - » Which requires *both* a downcast *and* a call to (say) .intValue()

# Generics vs Containing an Object

## – Example:

```
ArrayList squareNums = new ArrayList();
for (int ii = 0; ii < 5; ii++)          // Set up an array of square values
    squareNums.add(new Integer(ii * ii));    ← Must wrap int into Integer object

int iSumOfSquares = 0;                  // Go thru array and sum up the squares
for (int ii = 0; ii < 5; ii++) {
//    iSumOfSquares += squareNums.get(ii);    ← Compiler error (int assigned an Object)
//    iSumOfSquares += ((Float)squareNums.get(ii)).intValue();    ← Run-time ClassCastException
    iSumOfSquares += ((Integer)squareNums.get(ii)).intValue();    ← Correct
}
```

## – Generics allow the client to define what type to store

- Eliminates the need for casting
  - » Code becomes much cleaner and simpler
- The compiler can ensure that everything is the right type
  - » Catches many logic errors at compile time
- Unfortunately, Java generics **don't** support primitives
  - » Most other languages with generics do support primitives

# Using a Generic Class

- *Using* a generic class is pretty easy - just add `<type>`

```
ArrayList<Integer> squareNums = new ArrayList<Integer>();  
for (int ii = 0; ii < 5; ii++)           // Set up an array of square values  
    squareNums.add(new Integer(ii * ii));    ← Still must wrap int into Integer object  
  
int iSumOfSquares = 0;                   // Sum up the squares  
for (int ii = 0; ii < 5; ii++) {  
    iSumOfSquares += squareNums.get(ii).intValue();    ← No need for cast to Integer  
}
```

- There are more complicated things you can do with generics, but the basic concept remains the same
  - For example: can have more than one data type parameter
    - » e.g., `Hashtable<String, Double>`: `String` = key/lookup type,  
`Double` = value/stored type
    - code: `Hashtable<String, Double> h = new Hashtable<String, Double>();`



# Creating a Generic Class

- *Building* a generic class is slightly different
  - It requires you to put in a ‘placeholder’ name for the data type instead of the data type itself (like a parameter)
  - The clients of your class then later provide the *real* type
  - Let’s take a hypothetical MyListNode class:

```
public class MyListNode<E> {  
    public E data;  
    public MyListNode next;  
}
```

- ← Class definition with parameter E for generic placeholder type
- ← Can use generic type E like a real type, just don’t know *exact* type yet

- The E (any name will do) is a placeholder for the real type that is only defined when MyListNode is actually *used*

```
public static void main() {  
    MyListNode<Double> aNode;  
    // etc  
}
```

- ← E now is ‘redefined’ to be Double, but only for aNode

# Writing Your Own Iterator Revisited

- To make it use generics, just add `<E>`s and replace `Object`

```
public class MyLinkedList<E> implements Iterable<E> {
    ...
    public Iterator<E> iterator() {
        return new MyLinkedListIterator<E>(this);
    }

    private class MyLinkedListIterator<E> implements Iterator<E> {
        private MyLinkedList<E>.MyListNode<E> iterNext;
        public MyLinkedListIterator(MyLinkedList<E> theList) {
            iterNext = theList.head;
        }
        // Iterator interface implementation
        public boolean hasNext() { return (iterNext != null) }
        public E next() {
            E value;
            if (iterNext == null)
                value = null;
            else {
                value = iterNext.getValue();
                iterNext = iterNext.getNext();
            }
            return value;
        }
        public void remove() { throw new UnsupportedOperationException("Not supported"); }
    }
}
```

← Weird issue: Java generics require *full* scoping  
← NOTE: No `<E>` in c'tor name



# Writing Your Own Iterator Revisited

---

– ...as compared to how it was back in Slide 6

```
public class MyLinkedList implements Iterable {
    ...
    public Iterator iterator() {
        return new MyLinkedListIterator(this);
    }

    private class MyLinkedListIterator implements Iterator {
        private MyListNode iterNext;
        public MyLinkedListIterator(MyLinkedList theList) {
            iterNext = theList.head;
        }
        // Iterator interface implementation
        public boolean hasNext() { return (iterNext != null) }
        public Object next() {
            Object value;
            if (iterNext == null)
                value = null;
            else {
                value = iterNext.getValue();
                iterNext = iterNext.getNext();
            }
            return value;
        }
        public void remove() { throw new UnsupportedOperationException("Not supported"); }
    }
}
```



# Java Generics Under the Covers

---

- So how do generics actually work underneath it all?
- Java uses *type erasure*
  - The generic type E only exists for duration of compiling
    - » Temporarily replaced with real type (*e.g.*, Double) which is then used to check for type safety
  - After compilation, all the E's are converted to Object
    - » Type safety is lost at runtime – it's a compile-time-only check
    - » Explains why primitives aren't supported!



# Java Generics Under the Covers

---

- Why did Java's creators use type erasure?
  - Backwards compatibility: they wanted to avoid having to change the .class binary format
    - » Compiling generics to Object means only Objects go in the .class
  - Unfortunately, it makes for some weird behaviour
    - » *e.g.*, Can't create arrays of generics: `E[] anArray;` is illegal
    - » *e.g.*, Don't even have to give the generic parameter:  
`MyListNode` and `MyListNode<Double>` are *both legal*
- Other languages do it differently
  - C#/C++: every used type gets its *own copy of the class*
    - » C++ actually *recompiles the generic class source code* each time
    - » C# is smarter: substitutes generic type within *compiled code*





# Auto-boxing/unboxing

---

- Embedding a primitive into its class equivalent is referred to as ‘boxing’ in Java
  - *e.g.*, `new Integer(-5)` boxes -5 into an Integer object
- Java will automatically do boxing for you if possible
  - ... and also does automatic unboxing too

```
Integer intObj;  
int intVal;  
intObj = 10;  
intVal = intObj;
```

← Auto-boxing hides need to do `intObj = new Integer(10)`  
← Auto-unboxing hides need to call `intObj.intValue()`

- *Slightly* offsets Java’s lack of generic support for primitives
- **Problems:** 1) Slow. 2) `Integer ==` differs from `int ==`
  - » `Integer ==` is a reference comparison, `int ==` is `Integer.equals()`
  - » So try not to rely too much on auto-boxing/auto-unboxing!

# Next Week

## – Binary Trees

