

```

CREATE DATABASE IF NOT EXISTS `montgomery_county_police_db` /*!40100 DEFAULT
CHARACTER SET utf8mb3 */ /*!80016 DEFAULT ENCRYPTION='N' */;
USE `montgomery_county_police_db`;
-- MySQL dump 10.13 Distrib 8.0.32, for Win64 (x86_64)
--
-- Host: localhost    Database: montgomery_county_police_db
-- -----
-- Server version 8.0.32

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!50503 SET NAMES utf8 */;
/*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
/*!40103 SET TIME_ZONE='+00:00' */;
/*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
/*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
/*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
/*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;

--
-- Temporary view structure for view `bethesda_police_locations`
--

DROP TABLE IF EXISTS `bethesda_police_locations`;
/*!50001 DROP VIEW IF EXISTS `bethesda_police_locations`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `bethesda_police_locations` AS SELECT
  1 AS `Police_District_ID`,
  1 AS `Police_District_Name`,
  1 AS `Sector`,
  1 AS `Beat`,
  1 AS `PRA`*/;
SET character_set_client = @saved_cs_client;

--
-- Table structure for table `coordinates`
--

DROP TABLE IF EXISTS `coordinates`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `coordinates` (
  `Coordinates_ID` int NOT NULL AUTO_INCREMENT,
  `Latitude` double NOT NULL,
  `Longitude` double NOT NULL,
  PRIMARY KEY (`Coordinates_ID`)
) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `coordinates`
--

LOCK TABLES `coordinates` WRITE;
/*!40000 ALTER TABLE `coordinates` DISABLE KEYS */;
INSERT INTO `coordinates` VALUES (1,39.15232807,-77.19597464),(2,39.17919601,-
77.27581962),(3,0,0),(4,39.07533,-77.1529),(5,39.03984,-76.9907),(6,38.97339,-

```

```

77.086),(7,39.15425,-77.0643);
/*!40000 ALTER TABLE `coordinates` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `crime_incidents`
--

DROP TABLE IF EXISTS `crime_incidents`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `crime_incidents` (
  `Incidents_ID` int NOT NULL,
  `Crimes_ID` int NOT NULL,
  KEY `fk_Incidents_has_Crimes_Crimes1_idx` (`Crimes_ID`),
  KEY `fk_Incidents_has_Crimes_Incidents1_idx` (`Incidents_ID`),
  CONSTRAINT `fk_Incidents_has_Crimes_Crimes1` FOREIGN KEY (`Crimes_ID`) REFERENCES
`crimes` (`Crimes_ID`),
  CONSTRAINT `fk_Incidents_has_Crimes_Incidents1` FOREIGN KEY (`Incidents_ID`)
REFERENCES `incidents` (`Incidents_ID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `crime_incidents`
--

LOCK TABLES `crime_incidents` WRITE;
/*!40000 ALTER TABLE `crime_incidents` DISABLE KEYS */;
INSERT INTO `crime_incidents` VALUES (1,1),(2,2),(3,3),(4,4),(5,5),(6,6),(7,7),
(8,8),(9,9),(10,10),(11,11),(12,12),(13,13),(14,14),(15,15),(16,5),(17,16),(18,16),
(19,16),(20,16),(21,16),(22,16),(23,17),(24,17),(25,17),(26,18),(27,18),(28,18),
(29,19),(30,19),(31,20),(32,21),(33,8),(34,22);
/*!40000 ALTER TABLE `crime_incidents` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `crimes`
--

DROP TABLE IF EXISTS `crimes`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `crimes` (
  `Crimes_ID` int NOT NULL,
  `Crime_Type` varchar(88) NOT NULL,
  `Crime_Category` varchar(168) NOT NULL,
  `Crime_Name` varchar(184) NOT NULL,
  PRIMARY KEY (`Crimes_ID`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `crimes`
--

LOCK TABLES `crimes` WRITE;
/*!40000 ALTER TABLE `crimes` DISABLE KEYS */;
INSERT INTO `crimes` VALUES (1,'Crime Against

```

```

Property','Counterfeiting/Forgery','FORGERY OF CHECKS'),(2,'Crime Against
Property','All other Larceny','LARCENY - POSTAL'),(3,'Crime Against Person','Simple
Assault','ASSAULT - SIMPLE'),(4,'Crime Against
Property','Destruction/Damage/Vandalism of Property','DAMAGE PROPERTY - PRIVATE'),
(5,'Crime Against Society','All Other Offenses','OBSTRUCT POLICE - RESISTING
OFFICER'),(6,'Crime Against Society','Disorderly Conduct','PUBLIC PEACE -
DISORDERLY CONDUCT'),(7,'Crime Against Person','Simple Assault','ASSAULT - 2ND
DEGREE'),(8,'Crime Against Society','All Other Offenses','OBSTRUCT GOVT - VIOLATION
OF A COURT ORDER'),(9,'Crime Against Society','Drug/Narcotic Violations','DRUGS -
HEROIN - POSSESS'),(10,'Crime Against Society','Drug Equipment Violations','DRUGS -
NARCOTIC EQUIP - POSSESS'),(11,'Other','All Other Offenses','RECOVERED PROPERTY -
OTHER'),(12,'Crime Against Property','Stolen Property Offenses','STOLEN PROPERTY -
POSSESS'),(13,'Crime Against Society','Drug/Narcotic Violations','DRUGS - MARIJUANA
- POSSESS'),(14,'Crime Against Society','Drug Equipment Violations','DRUGS -
NARCOTIC EQUIP - POSSESS'),(15,'Crime Against Society','All Other
Offenses','OBSTRUCT POLICE - OBSTRUCT CRIMINAL INVEST'),(16,'Crime Against
Person','Kidnapping/Abduction','ABDUCT - NO RANSOM OR ASSAULT'),(17,'Crime Against
Property','Motor Vehicle Theft','AUTO THEFT - VEHICLE THEFT'),(18,'Crime Against
Property','Embezzlement','EMBEZZLE - BUSINESS PROP'),(19,'Other','All Other
Offenses','LOST PROPERTY'),(20,'Crime Against
Property','Destruction/Damage/Vandalism of Property','DAMAGE PROPERTY - BUSINESS'),
(21,'Crime Against Society','Drug/Narcotic Violations','DRUGS - OPIUM OR DERIVATIVE
- POSSESS'),(22,'Crime Against Person','Aggravated Assault','ASSAULT - AGGRAVATED -
FAMILY-STRONG-ARM');
/*!40000 ALTER TABLE `crimes` ENABLE KEYS */;
UNLOCK TABLES;

```

```

--
-- Temporary view structure for view
`frequency_of_coordinates_in_location_addresses`
--

```

```

DROP TABLE IF EXISTS `frequency_of_coordinates_in_location_addresses`;
/*!50001 DROP VIEW IF EXISTS `frequency_of_coordinates_in_location_addresses`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `frequency_of_coordinates_in_location_addresses` AS SELECT
  1 AS `Coordinates ID`,
  1 AS `Latitude`,
  1 AS `Longitude`,
  1 AS `Frequency of Coordinates in Location Addresses`*/;
SET character_set_client = @saved_cs_client;

```

```

--
-- Table structure for table `incidents`
--

```

```

DROP TABLE IF EXISTS `incidents`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `incidents` (
  `Incidents_ID` int NOT NULL AUTO_INCREMENT,
  `Incidents_Number` int NOT NULL,
  `Offence_Code` int NOT NULL,
  `NIBRS_Code` varchar(12) NOT NULL,
  `Victims` int NOT NULL,
  `Dispatch_Date_Time` datetime DEFAULT NULL,
  `Police_District_ID` int NOT NULL,
  PRIMARY KEY (`Incidents_ID`),

```

```

    KEY `fk_Incidents_Police_District1_idx` (`Police_District_ID`),
    CONSTRAINT `fk_Incidents_Police_District1` FOREIGN KEY (`Police_District_ID`)
REFERENCES `police_district` (`Police_District_ID`)
) ENGINE=InnoDB AUTO_INCREMENT=35 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `incidents`
--

LOCK TABLES `incidents` WRITE;
/*!40000 ALTER TABLE `incidents` DISABLE KEYS */;
INSERT INTO `incidents` VALUES (1,201408298,2501,'250',1,'2023-01-10 16:16:00',3),
(2,201408298,2316,'23H',1,'2023-01-10 16:16:00',3), (3,201408215,1313,'13B',1,'2023-01-10 00:08:30',3), (4,201408215,2902,'290',1,'2023-01-10 00:08:30',3),
(5,201408215,4801,'90Z',1,'2023-01-10 00:08:30',3), (6,201408215,5311,'90C',1,'2023-01-10 00:08:30',3), (7,201408210,1399,'13B',1,'2023-01-10 01:02:26',2),
(8,201408210,5016,'90Z',1,'2023-01-10 01:02:26',2), (9,201407198,2804,'280',1,'2023-01-02 21:36:23',4), (10,201407198,3550,'90Z',1,'2023-01-02 21:36:23',4),
(11,201407198,9109,'35A',1,'2023-01-02 21:36:23',4),
(12,201407198,2804,'35B',1,'2023-01-02 21:36:23',4),
(13,201406724,3562,'35A',1,'2022-12-29 01:08:39',5),
(14,201406724,3550,'35B',1,'2022-12-29 01:08:39',5),
(15,201406724,4802,'90Z',1,'2022-12-29 01:08:39',5),
(16,201406724,4801,'90Z',1,'2022-12-29 01:08:39',5),
(17,201169041,1008,'100',1,'2018-01-02 09:19:53',6),
(18,201180236,1008,'100',1,NULL,5), (19,201189230,1008,'100',1,'2018-05-23 15:25:36',5), (20,201202334,1008,'100',1,'2018-08-20 10:38:49',5),
(21,201310992,1008,'100',1,'2020-11-28 13:49:05',5),
(22,201360635,1008,'100',1,'2022-01-17 11:11:36',7),
(23,201344854,2404,'240',1,'2021-09-10 10:06:35',3),
(24,201344935,2404,'240',1,'2021-09-11 00:51:59',1),
(25,201344952,2404,'240',1,'2021-09-11 12:46:35',4),
(26,201155425,2701,'270',1,'2017-09-28 17:22:11',1),
(27,201156654,2701,'270',1,'2017-10-10 16:43:33',5),
(28,201157753,2701,'270',1,'2017-10-17 14:02:23',5),
(29,201250719,9105,'90Z',1,'2019-07-31 13:46:28',5),
(30,201250720,9105,'90Z',1,'2019-07-31 14:07:08',3),
(31,201087433,2901,'290',1,NULL,5), (32,201087433,3522,'35A',1,NULL,5),
(33,201088178,1399,'13B',1,NULL,7), (34,201088178,1303,'13A',1,NULL,7);
/*!40000 ALTER TABLE `incidents` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Temporary view structure for view
`incidents_with_less_than_the_average_number_of_victims`
--

DROP TABLE IF EXISTS `incidents_with_less_than_the_average_number_of_victims`;
/*!50001 DROP VIEW IF EXISTS
`incidents_with_less_than_the_average_number_of_victims`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `incidents_with_less_than_the_average_number_of_victims` AS
SELECT
    1 AS `Incident ID`,
    1 AS `Incidents Number With Less Than the Average Number of Victims`*/;
SET character_set_client = @saved_cs_client;
```

```
--
-- Table structure for table `location_addresses`
--
```

```
DROP TABLE IF EXISTS `location_addresses`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `location_addresses` (
  `Location_Addresses_ID` int NOT NULL AUTO_INCREMENT,
  `Address_Number` int NOT NULL,
  `Street_Name` varchar(72) NOT NULL,
  `Street_Type` varchar(12) NOT NULL,
  `City` varchar(52) NOT NULL,
  `State` varchar(8) NOT NULL,
  `Zipcode` int NOT NULL,
  `Place` varchar(120) NOT NULL,
  `Place_Description` varchar(120) DEFAULT NULL,
  `Coordinates_ID` int NOT NULL,
  `Incidents_ID` int NOT NULL,
  PRIMARY KEY (`Location_Addresses_ID`),
  KEY `fk_Location_Addresses_Locations1_idx` (`Coordinates_ID`),
  KEY `fk_Location_Addresses_Incidents1_idx` (`Incidents_ID`),
  CONSTRAINT `fk_Location_Addresses_Locations1` FOREIGN KEY (`Coordinates_ID`)
REFERENCES `coordinates` (`Coordinates_ID`),
  CONSTRAINT `fk_Location_Addresses_Incidents1` FOREIGN KEY (`Incidents_ID`)
REFERENCES `incidents` (`Incidents_ID`)
) ENGINE=InnoDB AUTO_INCREMENT=10 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;
```

```
--
-- Dumping data for table `location_addresses`
--
```

```
LOCK TABLES `location_addresses` WRITE;
/*!40000 ALTER TABLE `location_addresses` DISABLE KEYS */;
INSERT INTO `location_addresses` VALUES (1,300,'Odend
Hal','Ave','Gaithersburg','MD',20886,'Government Building','',1,31),(2,300,'Odend
Hal','Ave','Gaithersburg','MD',20886,'Street','In Vehicle',1,32),(3,13500,'KILDARE
HILLS','Ter','Germantown','MD',20874,'Parking Lot','Commercial',2,33),
(4,13500,'KILDARE
HILLS','Ter','Germantown','MD',20874,'Residence','Apartment/Condo',2,34),
(5,11600,'WHITTIER','BLV','Bethesda','MD',20817,'Other ','Unknown',3,1),
(6,700,'Monroe','ST','Rockville','MD',20850,'Residence','Apartment/Condo',4,7),
(7,11200,'NEW HAMPSHIRE','AVE','SILVER SPRING','MD',20904,'Street','In
Vehicle',5,9),(8,100,'ELM','AVE','TAKOMA
PARK','MD',20912,'Street','Residential',6,17),(9,18300,'VILLAGE
CENTER','DR','OLNEY','MD',20832,'Retail','Mall',7,26);
/*!40000 ALTER TABLE `location_addresses` ENABLE KEYS */;
UNLOCK TABLES;
```

```
--
-- Temporary view structure for view `number_of_abduction_incidents`
--
```

```
DROP TABLE IF EXISTS `number_of_abduction_incidents`;
/*!50001 DROP VIEW IF EXISTS `number_of_abduction_incidents`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `number_of_abduction_incidents` AS SELECT
```

```

1 AS `Number of Abduction Incidents After May 23, 2018`*/;
SET character_set_client = @saved_cs_client;

--
-- Temporary view structure for view
`number_of_total_incidents_per_police_district`
--

DROP TABLE IF EXISTS `number_of_total_incidents_per_police_district`;
/*!50001 DROP VIEW IF EXISTS `number_of_total_incidents_per_police_district`*/;
SET @saved_cs_client      = @@character_set_client;
/*!50503 SET character_set_client = utf8mb4 */;
/*!50001 CREATE VIEW `number_of_total_incidents_per_police_district` AS SELECT
  1 AS `Police District`,
  1 AS `Police District Number`,
  1 AS `Incident Count`*/;
SET character_set_client = @saved_cs_client;

--
-- Table structure for table `police_district`
--

DROP TABLE IF EXISTS `police_district`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `police_district` (
  `Police_District_ID` int NOT NULL AUTO_INCREMENT,
  `Police_District_Name` varchar(52) NOT NULL,
  `Police_District_Number` varchar(16) NOT NULL,
  `Agency` varchar(16) NOT NULL,
  PRIMARY KEY (`Police_District_ID`)
) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `police_district`
--

LOCK TABLES `police_district` WRITE;
/*!40000 ALTER TABLE `police_district` DISABLE KEYS */;
INSERT INTO `police_district` VALUES (1,'WHEATON','4D','MCPD'),
(2,'ROCKVILLE','1D','MCPD'),(3,'Bethesda','2D','MCPD'),(4,'Silver
Spring','3D','MCPD'),(5,'MONTGOMERY VILLAGE','6D','MCPD'),(6,'CITY OF TAKOMA
PARK','8D','MCPD'),(7,'GERMANTOWN','5D','MCPD');
/*!40000 ALTER TABLE `police_district` ENABLE KEYS */;
UNLOCK TABLES;

--
-- Table structure for table `police_locations`
--

DROP TABLE IF EXISTS `police_locations`;
/*!40101 SET @saved_cs_client      = @@character_set_client */;
/*!50503 SET character_set_client = utf8mb4 */;
CREATE TABLE `police_locations` (
  `Police_Locations_ID` int NOT NULL AUTO_INCREMENT,
  `Sector` varchar(4) NOT NULL,
  `Beat` varchar(32) NOT NULL,
  `PRA` varchar(12) NOT NULL,

```

```

    `Police_District_ID` int NOT NULL,
    PRIMARY KEY (`Police_Locations_ID`),
    KEY `fk_Police_Addresses_Police_idx` (`Police_District_ID`),
    CONSTRAINT `fk_Police_Addresses_Police` FOREIGN KEY (`Police_District_ID`)
REFERENCES `police_district` (`Police_District_ID`)
) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8mb3;
/*!40101 SET character_set_client = @saved_cs_client */;

```

```

--
-- Dumping data for table `police_locations`
--

```

```

LOCK TABLES `police_locations` WRITE;
/*!40000 ALTER TABLE `police_locations` DISABLE KEYS */;
INSERT INTO `police_locations` VALUES (1,'D','2D2','33',3),
(2,'E','2.00E+01','63',3),(3,'D','2D1','6',3),(4,'A','1A1','258',2),
(5,'I','3I1','148',4),(6,'R','6R1','505',5),(7,'N','5N1','702',7);
/*!40000 ALTER TABLE `police_locations` ENABLE KEYS */;
UNLOCK TABLES;

```

```

--
-- Final view structure for view `bethesda_police_locations`
--

```

```

/*!50001 DROP VIEW IF EXISTS `bethesda_police_locations`*/;
/*!50001 SET @saved_cs_client      = @@character_set_client */;
/*!50001 SET @saved_cs_results    = @@character_set_results */;
/*!50001 SET @saved_col_connection = @@collation_connection */;
/*!50001 SET character_set_client  = utf8mb4 */;
/*!50001 SET character_set_results = utf8mb4 */;
/*!50001 SET collation_connection  = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `bethesda_police_locations` AS select
`police_district`.`Police_District_ID` AS
`Police_District_ID`,`police_district`.`Police_District_Name` AS
`Police_District_Name`,`police_locations`.`Sector` AS
`Sector`,`police_locations`.`Beat` AS `Beat`,`police_locations`.`PRA` AS `PRA` from
(`police_district` join `police_locations`
on((`police_district`.`Police_District_ID` =
`police_locations`.`Police_District_ID`))) where
(`police_locations`.`Police_District_ID` = 3) */;
/*!50001 SET character_set_client  = @saved_cs_client */;
/*!50001 SET character_set_results = @saved_cs_results */;
/*!50001 SET collation_connection  = @saved_col_connection */;

```

```

--
-- Final view structure for view `frequency_of_coordinates_in_location_addresses`
--

```

```

/*!50001 DROP VIEW IF EXISTS `frequency_of_coordinates_in_location_addresses`*/;
/*!50001 SET @saved_cs_client      = @@character_set_client */;
/*!50001 SET @saved_cs_results    = @@character_set_results */;
/*!50001 SET @saved_col_connection = @@collation_connection */;
/*!50001 SET character_set_client  = utf8mb4 */;
/*!50001 SET character_set_results = utf8mb4 */;
/*!50001 SET collation_connection  = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */

```

```

/*!50001 VIEW `frequency_of_coordinates_in_location_addresses` AS select
`coordinates`.`Coordinates_ID` AS `Coordinates ID`,`coordinates`.`Latitude` AS
`Latitude`,`coordinates`.`Longitude` AS
`Longitude`,count(`location_addresses`.`Coordinates_ID`) AS `Frequency of
Coordinates in Location Addresses` from (`coordinates` join `location_addresses`
on((`coordinates`.`Coordinates_ID` = `location_addresses`.`Coordinates_ID`))) group
by `location_addresses`.`Coordinates_ID` */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

```

```

--
-- Final view structure for view
`incidents_with_less_than_the_average_number_of_victims`
--

```

```

/*!50001 DROP VIEW IF EXISTS
`incidents_with_less_than_the_average_number_of_victims`*/;
/*!50001 SET @saved_cs_client      = @@character_set_client */;
/*!50001 SET @saved_cs_results     = @@character_set_results */;
/*!50001 SET @saved_col_connection = @@collation_connection */;
/*!50001 SET character_set_client   = utf8mb4 */;
/*!50001 SET character_set_results  = utf8mb4 */;
/*!50001 SET collation_connection   = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `incidents_with_less_than_the_average_number_of_victims` AS select
`incidents`.`Incidents_ID` AS `Incident ID`,`incidents`.`Incidents_Number` AS
`Incidents Number With Less Than the Average Number of Victims` from (`incidents`
join `location_addresses` on((`incidents`.`Incidents_ID` =
`location_addresses`.`Incidents_ID`))) where (`incidents`.`Victims` <= (select
avg(`incidents`.`Victims`) from `incidents`)) */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

```

```

--
-- Final view structure for view `number_of_abduction_incidents`
--

```

```

/*!50001 DROP VIEW IF EXISTS `number_of_abduction_incidents`*/;
/*!50001 SET @saved_cs_client      = @@character_set_client */;
/*!50001 SET @saved_cs_results     = @@character_set_results */;
/*!50001 SET @saved_col_connection = @@collation_connection */;
/*!50001 SET character_set_client   = utf8mb4 */;
/*!50001 SET character_set_results  = utf8mb4 */;
/*!50001 SET collation_connection   = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `number_of_abduction_incidents` AS select
count(`incidents`.`Incidents_ID`) AS `Number of Abduction Incidents After May 23,
2018` from ((`incidents` join `crime_incidents` on((`incidents`.`Incidents_ID` =
`crime_incidents`.`Incidents_ID`))) join `crimes` on((`crime_incidents`.`Crimes_ID`
= `crimes`.`Crimes_ID`))) where ((`crimes`.`Crimes_ID` = 16) and
(`incidents`.`Dispatch_Date_Time` > '2018-05-23 15:25:36')) */;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection     = @saved_col_connection */;

```



```
--
-- Final view structure for view `number_of_total_incidents_per_police_district`
--

/*!50001 DROP VIEW IF EXISTS `number_of_total_incidents_per_police_district`*/;
/*!50001 SET @saved_cs_client          = @@character_set_client */;
/*!50001 SET @saved_cs_results         = @@character_set_results */;
/*!50001 SET @saved_col_connection     = @@collation_connection */;
/*!50001 SET character_set_client      = utf8mb4 */;
/*!50001 SET character_set_results     = utf8mb4 */;
/*!50001 SET collation_connection      = utf8mb4_0900_ai_ci */;
/*!50001 CREATE ALGORITHM=UNDEFINED */
/*!50013 DEFINER=`root`@`localhost` SQL SECURITY DEFINER */
/*!50001 VIEW `number_of_total_incidents_per_police_district` AS select
`police_district`.`Police_District_Name` AS `Police
District`,`police_district`.`Police_District_Number` AS `Police District
Number`,count(`police_district`.`Police_District_Name`) AS `Incident Count` from
(`police_district` join `incidents` on((`police_district`.`Police_District_ID` =
`incidents`.`Police_District_ID`))) group by
`police_district`.`Police_District_Name`,`police_district`.`Police_District_Number`
*/;
/*!50001 SET character_set_client      = @saved_cs_client */;
/*!50001 SET character_set_results     = @saved_cs_results */;
/*!50001 SET collation_connection      = @saved_col_connection */;
/*!40103 SET TIME_ZONE=@OLD_TIME_ZONE */;

/*!40101 SET SQL_MODE=@OLD_SQL_MODE */;
/*!40014 SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS */;
/*!40014 SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS */;
/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
/*!40111 SET SQL_NOTES=@OLD_SQL_NOTES */;

-- Dump completed on 2023-05-15 17:51:04
```