

Salzgitter- Diebesstieg



Landfill Leachate Treatment Plant

Ozonia —leading the way
to a better world

[illegible]

Leachate Treatment Plant

Landfill Diebesstieg / Disposal Centre Salzgitter GmbH



Fig. 1: Oxidation tanks; 2 contact tanks with Ozonia Radial Diffusers, 1 post-reaction

Since June 1994, the Salzgitter-Diebesstieg landfill has been operated by the "Disposal Centre Salzgitter GmbH" as a municipal waste landfill for the urban area of Salzgitter. The permit for this landfill stipulated that a plant be constructed for treating the accumulating leachate. Based on the water quality requirements for direct discharge into a waterway, from Appendix 51 of the "Rahmenabwasser - Verwaltungs-vorschrift" dated 1-1-90, it was decided to install a treatment plant using the most current technology. For technical and economic reasons the treatment method speci-

fied was a combination of two-stage biological treatment with denitrification and nitrification, followed by chemical oxidation with ozone. The main contractor, Preussag-Noell Was-sertechnik, Bremen Branch, was responsible for dimensioning this treatment plant to the quality targets for direct discharges.

In 1993 Ozonia Ltd, Switzerland, received the order for the supply of the chemical oxidation treatment. In order to achieve both optimum reaction control and ozone use it was decided to dose the ozone into two contact tanks

using Ozonia radial diffusers (figs. 1 and 2). During normal operation these contact tanks are connected in series, whereby both tanks are supplied with fresh ozone. In addition, one tank can operate with gas recuperation. The residual ozone concentration, measured on-line just before the vent ozone destructor, is used to control the ozone production (fig. 5). The process requires 7.5 kgO₃/h, which is produced from one Ozonia "Advanced Technology" (AT) ozone generator (fig. 3). This latest generator technology enables ozone concentrations of up to 15 wt% to be produced with only moderate energy consumption. At the design concentration of 10 wt% (148 g/m³ STP) very good mass transfer rates are generally attained. As a result, the consumption of oxygen is reduced by 30 % compared with conventional technology. Both the reaction system and the production of ozone with 'AT' have wide operating parameters which open up numerous possibilities for cost and process optimisation.

This technology concept emphasises Ozonia's constant efforts to enhance environmentally friendly treatment processes, such as chemical oxidation with ozone, by enabling the user to make




Fig. 2: Diagram of the chemical oxidation process



Fig. 3: Ozone generator

Ozonia's Scope of Supply

- Ozone generation equipment
- Ozone contact tanks for COD and AOX removal
- Process automation
- Vent ozone destruction
- Piping, fittings, measurement and control equipment
- Refrigeration plant for chilling cooling water


Plant Statistics

Leachate water flow rate:	3 m ³ /h
Ozone production:	7.5 kg/h; Phase I 15.0 kg/h; Phase II
Ozone concentration:	10 wt % (148 g/m ³ STP)
Ozone contacting system:	2 stage with Ozonia Radial Diffusers
Vent ozone destruction:	thermal system with heat recovery
Treatment standard:	for direct discharge to a waterway



Fig. 4: Process control and power supply (PSU)

Fig. 5: Vent ozone destructor



Site

Salzgitter-Diebesstieg, Germany

Operator

Entsorgungszentrum Salzgitter GmbH

Commissioning

June 1995



OzonIA around the world



OzonIA Ltd
Stettbachstrasse 1
CH-8600 Duebendorf
Switzerland

Tel. +41 (1) 801 85 11
Fax +41 (1) 801 85 01
E-mail info@ozonia.ch



OzonIA North America
491 Edward H. Ross Drive
Elmwood Park, New Jersey 07407
USA

Tel. +1 (201) 794 31 00
Fax +1 (201) 794 33 58
E-mail info@ozonia.com



OzonIA Triogen Ltd
Triogen House
117 Barfillan Drive, Craigton
Glasgow G52 1BD, Scotland

Tel. +44 (141) 810 48 61
Fax +44 (141) 810 55 61
E-mail info@ozoniatriogen.com



OzonIA OOO
Dobrolubova st., 7
Nizhny Novgorod, 603109
Russia

Tel. +7 (8312) 33 44 84
Fax +7 (8312) 34 25 89
E-mail ozonia@kis.ru



OzonIA Korea Co., Ltd.
2F, Jae-il Bldg, # 94-412
7 Ga Youngdeungpo-Dong
Youngdeungpo-Gu, Seoul, Korea

Tel. +82 (2) 2633 69 63
Fax +82 (2) 678 65 94
E-mail champ02@unitel.co.kr



OzonIA Bern
Stauffacherstrasse 130a
CH-3014 Bern
Switzerland

Tel. +41 (31) 333 10 41
Fax +41 (31) 332 72 75
E-mail Rjenny@compuserve.com



OzonIA Japan
Komahara Bldg. 4F, 5-17-2 Shinbashi
Minato-ku, Tokyo 105-0004
Japan

Tel. +81 (3) 34 37 54 52
Fax +81 (3) 34 37 54 57
E-mail jeanmarc_morange@csi.com



Homepage
<http://www.ozonia.ch>
<http://www.ozonia.com>
<http://www.ozonia.ru>

**OzonIA products are available in all countries over the world.
Please contact us to find out details of your representative.**