





Management and Curation of EarthPortal Resources

A quick reference table for the Metadata guideline

Student

Emmanuel Nyandu Kagarabi

Internship Supervisor

Christelle Pierkot

20 September 2026

1 Introduction

The following is a short report presenting a quick reference table, that I suggest to accompany the ongoing *Metadata guideline* document, which is currently under review. Its purpose is to give a submitter a single page that answers three questions at a glance: *what must be filled in, what the field is called, and which FAIR sub-principles it supports.*

2 Development

The table covers all 99 attribute entries of the draft, in the document's own order and under its own twelve section headings. I have corrected a few property names for spelling as I went, and I made one small choice worth mentioning: *Categories* and *Subjects* currently declare the same property, so I kept `omv:hasDomain` for *Categories*, which is the portal's own controlled list, and used `dcterms:subject` for *Subjects*, as the MOD 3.0 column of the crosswalk [2] indicates. Before reading the table, a word on the columns.

Usage The level in the guideline. **M**: Mandatory, **R**: Recommended, **O**: Optional.

FsF The level in the FAIRsFAIR minimum metadata profile for semantic artefacts, as recorded in our *Metadata attributes* crosswalk [2]. A dash means the crosswalk records no level for that attribute.

FAIR The FAIR sub-principles the attribute supports, as annotated in the guideline. A dash means the guideline gives none. Values in **green** are sub-principles I would suggest adding, because the O'FAIRe tool [1] reads the attribute when it scores that sub-principle, according to its own property configuration [3].

Property The primary property, as a prefixed name.

Table 1: Quick reference table for the *Metadata guideline* (under review), covering 99 entries.

#	Attribute	U	FsF	FAIR	Primary property
1. General					
1.1	Acronym	M	M	F2	`mod:acronym`
1.2	Name	M	M	**F2**	`omv:name`
1.3	Representation language	M	M	I1, I3	`omv:hasOntologyLanguage`
1.4	Categories	M	–	**F2**	`omv:hasDomain`
1.5	Groups	O	–	R1.3	`bpm:group`
1.6	Administrators	M	–	–	`bpm:administeredBy`
1.7	Status	M	R	A2	`omv:status`
1.8	URI	M	O	F1, **A1**	`omv:URI`
1.9	Version IRI	R	M	F1	`omv:versionIRI`
1.10	Formality level	R	R	I1, I3	`omv:hasFormalityLevel`
1.11	Syntax	R	M	I1, I3	`omv:hasOntologySyntax`
1.12	Natural language	R	R	F2	`omv:naturalLanguage`
1.13	Generic type	R	M	F2	`omv:isOfType`
1.14	Other identifier	O	M	A1, F1	`dct:identifier`
2. Description					
2.1	Abstract	R	–	F2	`dct:abstract`
2.2	Description	M	M	F2	`omv:description`
2.3	Notes	R	R	F2	`omv:notes`
2.4	Homepage	R	–	F2	`foaf:homepage`
2.5	Documentation	R	M	**F2**	`omv:documentation`
2.6	Keywords	R	M	**F2**	`dcat:keyword`
2.7	Subjects	R	M	–	`dct:subject`
2.8	Hidden label	R	–	**F2**	`skos:hiddenLabel`
2.9	Alternative name	R	–	F2	`dct:alternative`
2.10	Bibliographic reference	R	O	F2	`bpm:publication`

continued on the next page

Table 1 continued from the previous page

#	Attribute	U	FsF	FAIR	Primary property
3. Dates					
3.1	Creation date	M	M	**F2**	`bpm:released`
3.2	Modification date	M	M	F2	`dct:modified`
3.3	Validity date	R	–	F2	`dct:valid`
3.4	Curation date	R	–	F2	`pav:curatedOn`
3.5	Submission date	M	–	**F2**	`dct:dateSubmitted`
4. Licensing					
4.1	Visibility	M	M	R1.1, **R1.3**	`bpm:viewingRestriction`
4.2	License	M	M	I3, R1.1	`omv:hasLicense`
4.3	Use guidelines	R	–	R1.1	`cc:useGuidelines`
4.4	More permissions	O	–	R1.1	`cc:morePermissions`
4.5	Rights holder	R	–	R1.1	`schema:copyrightHolder`
5. Persons and Organisations					
5.1	Contacts	M	M	R1.1	`bpm:contact`
5.2	Creator	M	M	R1.2	`dct:creator`
5.3	Contributor	R	R	R1.2	`dct:contributor`
5.4	Curator	R	–	R1.2	`pav:curatedBy`
5.5	Publisher	R	R	F2	`dct:publisher`
5.6	Funded or sponsored by	R	–	R1.2	`foaf:fundedBy`
5.7	Endorsed by	R	–	R1.3	`mod:endorsedBy`
5.8	Translator	R	–	R1.2	`schema:translator`
6. Links					
6.1	Location	M	M	**F2**	`bpm:pullLocation`
6.2	Is format of	R	–	I1, I3	`dct:isFormatOf`
6.3	Has format	R	–	I1, I3	`dct:hasFormat`
6.4	Download URL	M	R	F2	`void:dataDump`
6.5	CSV dump	M	–	–	`bpm:csvDump`
6.6	URI lookup Endpoint	M	–	F2	`void:uriLookupEndpoint`
6.7	Free-text search endpoint	M	–	**F2**	`void:openSearchDescription`
6.8	SPARQL endpoint	R	–	A1	`sd:endpoint`
6.9	Source	R	–	R1.2	`dct:source`
6.10	Indexed or Included in catalog or repository	R	O	F4	`schema:includedInDataCatalog`
7. Media					
7.1	The URL of a media associated to the ontology	O	–	F2	`schema:associatedMedia`
7.2	Depiction	O	–	F2	`foaf:depiction`
7.3	Logo	O	–	F2	`foaf:logo`
8. Community					
8.1	Bug database	R	–	F2	`doap:bug-database`
8.2	Audience	R	–	F2	`dct:audience`
8.3	Repository	R	–	F2	`doap:repository`
8.4	Mailing list	R	–	F2	`doap:mailing-list`
8.5	To do list	R	–	F2	`mod:toDoList`
8.6	Award	R	–	F2	`schema:award`
9. Usage					
9.1	Known usage	R	–	F2	`omv:knownUsage`
9.2	Design for task	R	–	R1.2	`mod:designedForTask`
9.3	Coverage	R	O	F2	`dct:coverage`
9.4	Example of use	R	–	**F2**	`vann:example`
10. Relations					

continued on the next page

Table 1 continued from the previous page

#	Attribute	U	FsF	FAIR	Primary property
10.1	This ontology is a view of	R	–	–	dct:isPartOf
10.2	Prior version	R	–	I3, R1.2	omv:hasPriorVersion
10.3	Has part (has views)	R	–	F2, I3	dct:hasPart
10.4	Similar to	R	–	I2, I3	mod:similar
10.5	Generally related to	O	–	I2, **I3**	mod: semanticArtefactRelation
10.6	Comes from the same domain	O	–	F2, I3	mod:comesFromTheSameDomain
10.7	Has equivalences with	R	–	I2, I3	mod:hasEquivalencesWith
10.8	Backward compatible	O	–	F2, I3	owl:backwardCompatibleWith
10.9	Incompatible	O	–	F2, I3	owl:incompatibleWith
10.10	Disparate modelling with	R	–	F2, I3	mod:hasDisparateModelling
10.11	Has disjunctions with	O	–	**F2**, **I3**	mod:hasDisjunctionsWith
10.12	Generalization of	O	–	I2, I3	mod:generalizes
10.13	Specialization of	O	–	I2, **I3**	mod:specializes
10.14	Imports	R	–	I2, I3	owl:imports
10.15	Used by	R	–	F2, I3	mod:usedBy
10.16	Translation	R	–	F2, I3	schema:workTranslation
10.17	Translation of	R	–	I2, I3	schema:translationOfWork
11. Content					
11.1	Root of obsolete branch	O	–	**R1**	bpm:obsoleteParent
11.2	URI Regex Pattern	O	–	F2	void:uriRegexPattern
11.3	Preferred namespace URI	R	–	F2	vann:preferredNamespaceUri
11.4	Preferred namespace prefix	R	–	F2	vann: preferredNamespacePrefix
11.5	Example of resource	O	–	F2	idot:exampleIdentifier
11.6	Key classes	O	–	F2	omv:keyClasses
11.7	Metadata vocabulary used	R	–	I2	voaf:metadataVoc
12. Methodology					
12.1	Knowledge representation paradigm	O	R	R1.2	omv:conformsToKnowledgeRepresentationParadigm
12.2	Engineering methodology	O	R	R1.2	omv:usedOntologyEngineeringMethodology
12.3	Created With	R	O	R1.2	omv: usedOntologyEngineeringTool
12.4	Accrual method	R	O	R1.2	dct:accrualMethod
12.5	Accrual periodicity	R	O	R1.2	dct:accrualPeriodicity
12.6	Accrual policy	R	O	R1.2	dct:accrualPolicy
12.7	Competency question	R	O	R1.2	mod:competencyQuestion
12.8	Sample Queries	R	–	F2	mod:sampleQueries
12.9	Was generated by	O	O	R1.2	prov:wasGeneratedBy
12.10	Was invalidated by	O	–	R1.2	prov:wasInvalidatedBy

3 Conclusion

The O'FAIRe tool [1] follows MOD 1.4, while our guideline follows MOD 3.0. As a result, some fields are required by O'FAIRe when it computes the FAIRness score, while our guideline does not explicitly mention them. For instance, in the following table, I have listed a few cases among others.

Property read by O'FAIRe, absent from our guideline	**Question**	**Credits**	**What our guideline has for the same question**
`mod:prefLabelProperty`, `mod:synonymProperty`, `mod:definitionProperty`, `mod:authorProperty`, `mod:obsoleteProperty`	R1Q1	5	nothing: the question rests entirely on these five
`mod:ontologyInUse`	R1.3Q1	5	*Endorsed by* (5.7), the other half of the question
`owl:deprecated`	A2Q4	2	*Status* (1.7), the other half of the question
`owl:versionInfo`	R1.2Q4	2	*Prior version* (10.2), which few artefacts fill
`mod:hierarchyProperty`	R1Q2	1	*Root of obsolete branch* (11.1); the third property of the question, `mod:maxDepth`, is computed by the portal

In the light of the previous illustration, I think we definitely need to discuss with Clement's team and make sure we all agree on how to align the current metric with the guideline.

References

[1] Emna Amdouni, Syphax Bouazzouni, and Clement Jonquet. O'FAIRe makes you an offer: metadata-based automatic FAIRness assessment for ontologies and semantic resources. *International Journal of Metadata, Semantics and Ontologies*, 16(1):16–46, 2022.

[2] Metadata attributes: crosswalk of the AgroPortal, MOD and FAIRsFAIR metadata properties. Shared spreadsheet of the team, sheet *Metadata curation*, `https://docs.google.com/spreadsheets/d/1z5-mR1LNvztkItc8SBjgu0TDl5rO8iaB2Um1JaIGNrA/edit?gid=1135453521`. Accessible to the members of the team only.

[3] O'FAIRe configuration files: metadata properties and assessment questions. `https://github.com/agroportal/fairness/tree/master/src/main/resources/config/common`. Files `properties.config.json` and `questions.config.json`, at commit `24def6b` of 4 June 2026.