## GeoWS Well Structured Text Format

Version: 1.0 (2015-04-08)

**Purpose**: Specify a common system of annotations and rules for data in structured text formats. An important factor is readability for both humans and machines. Simplicity is considered key for adoption and use. Data compliant with this specification is primarily targeted at delivery as data streams from a GeoWS web services. Ideally, existing structured text data would need very minimal modification, perhaps just additional headers, to be compliant.

# Requirements and Assumptions:

- 1. **Readability** by both humans and computers is very important.
- 2. **UTF-8** is the text encoding.
- 3. A "**line**" in a dataset is a string of text ending with one or more newline or carriage return characters.
  - **a.** Lines starting with # are treated as comments, unless a **keyword** is present.
  - **b.** Lines starting with # can occur anywhere in the data stream.
  - **c.** Lines without leading # are treated as delimited data.
- 4. A header line with a **keyword** takes the following form:

# keyword : value
or as a list of values:

# keyword : value1, value2, value3

A line beginning with a '#', followed by zero or more whitespace characters, followed by the keyword itself, followed by zero or more whitespace characters, followed by a ':', followed by the keyword value.

A POSIX extended regular expression to identify a keyword and value:

'^#\s\*(keyword)\s\*:(value)[\r\n]+'

5. **Padding keyword values** with spaces. Keyword values that are singular or in a list may be padded with white space that is not considered part of the value, all whitespace before and after a value should be trimmed by a reader. These pairs of headers are equivalent:

# keyword : value \n #keyword:value\n

or

# keyword : value1 , value2 of apples , value3
# keyword:value1,value2 of apples,value3

- 6. Known keywords are:
  - a. fields: names for each column of data (required, no empty values allowed)
  - b. field unit: units for each column of data
  - **c. field\_type**: types for each column, one of 'string','integer','float','datetime'
  - d. field\_long\_name: long descriptive field names, ala CF
  - e. field standard name: long descriptive field names from a vocabulary, ala CF
  - f. field\_missing: values used to denote missing values in the data

- g. delimiter: single character delimiter for data values
- h. attribution: identify attribution information, probably a URL
- i. standard\_name\_cv: identify controlled vocabulary for field\_standard\_name
- j. from CF: title, history, institution, source, comment, references
- 7. The only required header keyword is **fields** and it should be the first header and logically starts a data set. When multiple datasets occur in a stream the #fields header denotes the start of each set.
- 8. There are no global fields. Each dataset must be self contained, meaning that it must have all appropriate headers.
- 9. Values for field names and attributes (all field\_\* keywords) should use CF attribute names and definitions whenever appropriate and possible.
- 10. Keyword values for all field attributes (all field\_\* keywords) are optional and should be left empty if unknown.
- 11. The delimiter used for lists of keyword values is a comma.
- 12. The default delimiter for data is a comma. Other delimiters must be defined using the **delimiter** keyword. Non-obvious delimiters such as space and horizontal tab should be specified using the escape sequences prefixed with backslash. Common escape sequences:
  - **a.** \s space character (ASCII 0x20)
  - **b.** \t horizontal tab (ASCII 0x09)
  - c. \\ backslash (ASCII 0x5C)
- 13. Fields of type 'datetime' must be in an ISO 8601 format. The form of 'YYYY-MM-DDThh:mm:ss.sss[Z]' is strongly recommended, with the time portion optional for date-only specification and optional time zone designation per ISO 8601.
- 14. As a minor extension to CF field names for latitude and longitude, the producer and consumer should recognize any field names that begin with "lat" or "lon" (case-insensitive) respectively as latitude and longitude. In addition " lat" or " lon" anywhere in the field name, e.g. Geodetic Longitude, will also be recognized. Example field names: lon, long, longitude, Longitude, LON, LONG, LONGITUDE, Geodetic Longitude, lonnad27, lonnad83 are all accepted as longitude. Latitude has the same rules respectively.
- 15. Delimiters within delimiters, aka using commas within header value lists
  - **a.** If a comma is needed within a comma-delimited header value, use the hex version of \x2C for comma.

# **Examples**

Long lines have been wrapped for readability, but are not wrapped in the real data. Also, keywords have been bolded for illustration and does not represent real data set formatting.

#### **UNAVCO Example:**

```
# fields: ID, station_name, latitude, longitude, ellip_height, session_start_time, session_stop_time
# field_unit: UTF-8, UTF-8, degrees_north, degrees_east, meters, UTC, UTC
# field_type: string, string, float, float, float, datetime, datetime
# attribution: http://www.unavco.org/community/policies_forms/attribution/attribution.html
# GeodeticDatum: ITRF2008 epsg:7019
# Ellipsoid: GRS 1980 epsg:7019
# Ellipsoidal Coordinate System: EllipsoidalCS epsg:6423
# Axes: Geodetic longitude, Geodetic latitude, Ellipsoidal height. Orientations: east, north, up.
# Units of Measure: decimal degrees, decimal degrees, meters
ASBU,Astronaut Butte,43.8206,-121.3685,1234,2011-08-18T00:00:00,2015-02-16T23:59:45
CIHL,Cinder Hill,43.7509,-121.1487,4567,2011-09-13T16:04:30,2015-02-16T23:59:45
CPCO,Central Pumice Cone,43.7221,-121.2332,4321,2011-08-18T00:00:00,2012-03-05T12:02:30
CPCO,Central Pumice Cone,43.7221,-121.2332,222,2012-06-14T00:00:00,2012-09-25T23:59:45
CPCO,Central Pumice Cone,43.7221,-121.2332,999,2012-09-26T19:28:45,2013-06-10T22:11:15
```

## **IRIS Examples:**

#### Seismic station metadata example:

```
# fields: Network, Station, Latitude, Longitude, Elevation, SiteName, StartTime, EndTime
# field_unit: ASCII, ASCII, degrees_north, degrees_east, meters, UTC, UTC
# field_type: string, string, float, float, float, string, datetime, datetime
# delimiter: |
IU|ANMO|34.9459|-106.4572|1850.0|Albuquerque, New Mexico, USA|1989-08-29T00:00:00|1995-07-14T00:00:00
IU|ANMO|34.9459|-106.4572|1850.0|Albuquerque, New Mexico, USA|1995-07-14T00:00:00|2000-10-19T16:00:00
```

## Minimal IRIS Station example: # fields: Network, Station, Latitude, Longitude, Elevation, SiteName, StartTime, EndTime # delimiter: | IU|ANMO|34.9459|-106.4572|1850.0|Albuquerque, New Mexico, USA|1989-08-29T00:00:00|1995-07-14T00:00:00 IU|ANMO|34.9459|-106.4572|1850.0|Albuquerque, New Mexico, USA|1995-07-14T00:00:00|2000-10-19T16:00:00 Event (earthquake) parameter example: # fields: EventID, Time, Latitude, Longitude, Depth/km, Author, Catalog, Contributor, ContributorID, MagType, Magnitude, MagAuthor, EventLocationName # delimiter: | 3954686|2010-03-01T06:27:32|38.251|69.4919|12.0|ISC|ISC|ISC|00301439|mb|4.3|NNC|TAJIKISTAN 3954685|2010-03-01T06:25:56|37.26|138.91|9.0|JMA|ISC|ISC|15237974|mb|0.5|JMA|NEAR WEST COAST OF HONSHU, JAPAN R2R Example: Shiptrack navigation and geophysical profiles for research cruises from the US academic fleet: #fields: iso time, ship longitude, ship latitude, raw magnetics, magnetic anomaly, igrf, device longitude, device latitude, dp flag #names: iso time,ship longitude,ship latitude,raw magnetics,magnetic anomaly,igrf,device longitude,device latitude,dp flag #field unit: ISO 8601,degrees east,degrees north,nT,nT,nT,degrees east,degrees north,unitless #field type: datetime,float,float,float,float,float,integer #field long name: date and time, longitude of vessel, latitude of vessel, total magnetics field, residual magnetics field, theoretical magnetics, longitude at device (layback), latitude at device, (layback), data status flag #attribution: http://www.rvdata.us/about/products #delimiter: , #source: http://www.rvdata.us/ #title: Processed Magnetics Data from Research Cruise MGL1307 #cruise id: MGL1307 #device information: magnetometer (make: Geometrics model: G-882) #creation date: 2015-01-18T19:38:55+00:00 #input data: doi:10.7284/111029 #names NVSP02: DTUT8601,ALONGP01,ALATGP01,MAGNFLDX,MMANZZ01 2013-06-07T07:35:10.0997Z,-12.5669084,42.0360754,44984.68,-118.501,45103.28,-12.5657654,42.0363823,0

2013-06-07T07:36:10.1073Z,-12.5684555,42.0360966,44981.17,-122.736,45103.274,-12.5672536,42.0360089,0 2013-06-07T07:37:10.1950Z,-12.5699536,42.0361235,44982.41,-120.76,45103.271,-12.568746,42.0361294,0