# Physics Problem Solving

Dara Daneshvar Eason Shao Lev Shabalin

Physics Problem Solving Society St Paul's School

13.05.2024

#### Table of Contents

Water Tank

2 Springs

3 BPhO Question

### Table of Contents

Water Tank

2 Springs

BPhO Question

I hope everyone remembers this question from last time.

I hope everyone remembers this question from last time.

Question. A tank contains water to a depth of 1.0m. Water emerges from a small hole in the vertical side of the tank at 20cm below the surface. Determine:

- 1 the speed at which the water emerges from the hole
- 2 the distance from the base of the tank at which the water strikes the floor on which the tank is standing.

We also had a follow-up question on the envelope of the trajectory of the water (i.e. the boundary of the set of points that the water trajectory can hit).

We also had a follow-up question on the envelope of the trajectory of the water (i.e. the boundary of the set of points that the water trajectory can hit).

Question. A tank contains water to a depth of H. Water emerges from a small hole in the vertical side of the tank at h above ground. Determine the envelope formed by the trajectories of the water.

#### Ideas

It might be a good idea to have a think/guess of what the envelope looks like before we look at the solution.

#### Ideas

It might be a good idea to have a think/guess of what the envelope looks like before we look at the solution.

- ① A circle, bending outwards (convex).
- 2 A circle, bending inwards (concave).
- A parabola.
- A straight line.
- A hyperbola.

#### Ideas

It might be a good idea to have a think/guess of what the envelope looks like before we look at the solution.

- ① A circle, bending outwards (convex).
- 2 A circle, bending inwards (concave).
- A parabola.
- A straight line.
- A hyperbola.

▶ Desmos Demo

But why is it a straight line?

But why is it a straight line?

First, it is not difficult to see that the trajectory of the water satisfies the parametric equation

$$(x,y)=\left(\sqrt{2g(H-h)}t,h-\frac{gt^2}{2}\right).$$

But why is it a straight line?

First, it is not difficult to see that the trajectory of the water satisfies the parametric equation

$$(x,y) = \left(\sqrt{2g(H-h)}t, h - \frac{gt^2}{2}\right).$$

If we re-arrange the equation to find t in terms of x, we have

$$t=\frac{x}{\sqrt{2g(H-h)}},$$

and plugging this back for y gives us the explicit Cartesian equation

$$y=h-\frac{x^2}{4(H-h)}.$$

$$y = h - \frac{x^2}{4(H-h)},$$
  
 $4(H-h)y = 4(H-h)h - x^2.$ 

$$y = h - \frac{x^2}{4(H-h)},$$
  
 $4(H-h)y = 4(H-h)h - x^2.$ 

Rearranging gives us a quardratic equation in terms of h:

$$4h^2 - 4hy - 4hH + 4Hy + x^2 = 0.$$

$$y = h - \frac{x^2}{4(H-h)},$$
  
 $4(H-h)y = 4(H-h)h - x^2.$ 

Rearranging gives us a quardratic equation in terms of h:

$$4h^2 - 4hy - 4hH + 4Hy + x^2 = 0.$$

If the point (x, y) is covered by a certain trajectory, then this equation must have a solution for h in the interval (0, H).

$$y = h - \frac{x^2}{4(H-h)},$$
  
 $4(H-h)y = 4(H-h)h - x^2.$ 

Rearranging gives us a quardratic equation in terms of h:

$$4h^2 - 4hy - 4hH + 4Hy + x^2 = 0.$$

If the point (x, y) is covered by a certain trajectory, then this equation must have a solution for h in the interval (0, H).

$$\Delta = (4y + 4H)^2 - 4 \cdot 4 \cdot (4Hy + x^2) \ge 0.$$

$$\Delta = (4y + 4H)^2 - 4 \cdot 4 \cdot (4Hy + x^2) \ge 0.$$

$$\Delta = (4y + 4H)^2 - 4 \cdot 4 \cdot (4Hy + x^2) \ge 0.$$

We can reduce this inequality to

$$(y+H)^2 \ge 4Hy + x^2,$$

which can be further simplified to

$$(y-H)^2 \ge x^2.$$

$$\Delta = (4y + 4H)^2 - 4 \cdot 4 \cdot (4Hy + x^2) \ge 0.$$

We can reduce this inequality to

$$(y+H)^2 \ge 4Hy + x^2,$$

which can be further simplified to

$$(y-H)^2 \ge x^2.$$

At the boundary case, the equal sign is to be taken, and therefore the equation for the envelope will be (taking the branch in the first quadrant)

$$x + y = H$$
.



$$\Delta = (4y + 4H)^2 - 4 \cdot 4 \cdot (4Hy + x^2) \ge 0.$$

We can reduce this inequality to

$$(y+H)^2 \ge 4Hy + x^2,$$

which can be further simplified to

$$(y-H)^2 \ge x^2.$$

At the boundary case, the equal sign is to be taken, and therefore the equation for the envelope will be (taking the branch in the first quadrant)

$$x + y = H$$
.





# Alternative Approach

We reach the parametric equation

$$(x,y) = \left(\sqrt{2g(H-h)}t, h - \frac{gt^2}{2}\right).$$

# Alternative Approach

We reach the parametric equation

$$(x,y) = \left(\sqrt{2g(H-h)}t, h - \frac{gt^2}{2}\right).$$

We notice that

$$x + y = -\frac{gt^2}{2} + \sqrt{2g(H - h)}t + h$$

$$\leq \frac{-2gh - 2g(H - h)}{-2g}$$

$$= H$$

from basic propertiy of a quadratic curve.

## Important Maths

Quadratic Curve. For a quadratic curve with equation

$$y = ax^2 + bx + c, a \neq 0$$

its vertex will be the point with coordinate

$$\left(-\frac{b}{2a}, \frac{4ac-b^2}{4a}\right)$$
.

### Table of Contents

Water Tank

2 Springs

BPhO Question

We have learnt in class that the formula for the resultant spring constant k and resultant initial length I of springs with spring constants  $k_1, k_2, \ldots, k_n$  and initial lengths  $I_1, I_2, \ldots, I_n$  being in series satisfies that

We have learnt in class that the formula for the resultant spring constant k and resultant initial length l of springs with spring constants  $k_1, k_2, \ldots, k_n$  and initial lengths  $l_1, l_2, \ldots, l_n$  being in series satisfies that

$$\frac{1}{k} = \sum_{i=1}^{n} \frac{1}{k_i}, l = \sum_{i=1}^{n} l_i.$$

*Proof.* If a load F is applied to the strings, it will be passed along to every single spring.

*Proof.* If a load F is applied to the strings, it will be passed along to every single spring.

Therefore the extension of each spring will satisfy that

$$x_i = \frac{F}{k_i}$$
.

*Proof.* If a load F is applied to the strings, it will be passed along to every single spring.

Therefore the extension of each spring will satisfy that

$$x_i = \frac{F}{k_i}.$$

Therefore, the total extension will satisfy

$$x = \sum_{i=1}^{n} x_i = F \sum_{i=1}^{n} \frac{1}{k_i},$$

*Proof.* If a load F is applied to the strings, it will be passed along to every single spring.

Therefore the extension of each spring will satisfy that

$$x_i = \frac{F}{k_i}$$
.

Therefore, the total extension will satisfy

$$x = \sum_{i=1}^{n} x_i = F \sum_{i=1}^{n} \frac{1}{k_i},$$

and therefore the resultant spring constant satisfies

$$\frac{1}{k} = \frac{x}{F} = \sum_{i=1}^{n} \frac{1}{k_i}.$$

We have learnt in class that the formula for the resultant spring constant k of springs with spring constants  $k_1, k_2, \ldots, k_n$  and same initial lengths l being in parallel satisfies that

We have learnt in class that the formula for the resultant spring constant k of springs with spring constants  $k_1, k_2, \ldots, k_n$  and same initial lengths l being in parallel satisfies that

$$k=\sum_{i=1}^n k_i.$$

*Proof.* Due to the fact that the springs are connected in parallel, they must have the same extension (since they always have the same length), say x.

*Proof.* Due to the fact that the springs are connected in parallel, they must have the same extension (since they always have the same length), say x. Therefore, to cause this deformation, each tension in the spring  $F_i$  should satisfy that

$$F_i = k_i x$$
.

*Proof.* Due to the fact that the springs are connected in parallel, they must have the same extension (since they always have the same length), say x. Therefore, to cause this deformation, each tension in the spring  $F_i$  should satisfy that

$$F_i = k_i x$$
.

Therefore, the total force F satisfies

$$F = \sum_{i=1}^{n} F_i = x \sum_{i=1}^{n} k_i$$

# Parallel Springs

*Proof.* Due to the fact that the springs are connected in parallel, they must have the same extension (since they always have the same length), say x. Therefore, to cause this deformation, each tension in the spring  $F_i$  should satisfy that

$$F_i = k_i x$$
.

Therefore, the total force F satisfies

$$F = \sum_{i=1}^{n} F_i = x \sum_{i=1}^{n} k_i,$$

and therefore

$$k = \frac{F}{x} = \sum_{i=1}^{n} k_i.$$

### Table of Contents

Water Tank

2 Springs

3 BPhO Question

The pulley system in the figure consists of two pulleys of radii a and b rigidly fixed together, but free to rotate about a common horizontal axis. The weight W hangs from the axle of a freely suspended pulley P, which can rotate about its axle. If section A of a rough rope is pulled down with velocity V:

The pulley system in the figure consists of two pulleys of radii a and b rigidly fixed together, but free to rotate about a common horizontal axis. The weight W hangs from the axle of a freely suspended pulley P, which can rotate about its axle. If section A of a rough rope is pulled down with velocity V:

**1** Explain which way W will move.

The pulley system in the figure consists of two pulleys of radii a and b rigidly fixed together, but free to rotate about a common horizontal axis. The weight W hangs from the axle of a freely suspended pulley P, which can rotate about its axle. If section A of a rough rope is pulled down with velocity V:

- **1** Explain which way W will move.
- With what speed will it move?

The pulley system in the figure consists of two pulleys of radii a and b rigidly fixed together, but free to rotate about a common horizontal axis. The weight W hangs from the axle of a freely suspended pulley P, which can rotate about its axle. If section A of a rough rope is pulled down with velocity V:

- Explain which way W will move.
- With what speed will it move?




Figure: Pulley System

W will move upwards because the force pulling section A of rope downwards, must act upwards on section D of the rope.

W will move upwards because the force pulling section A of rope downwards, must act upwards on section D of the rope.

Rope D moves upwards with speed V because we assume that the rope is inextensible and ropes A and D are attached.

W will move upwards because the force pulling section A of rope downwards, must act upwards on section D of the rope.

Rope D moves upwards with speed V because we assume that the rope is inextensible and ropes A and D are attached.

However, we cannot say that rope B moves downwards with speed V. Since the two pulleys of radii a and b are rigidly fixed together, they must rotate with the same angular velocity,  $\omega_a = \omega_b$ .

$$V = \omega_a a \Rightarrow \omega_a = \frac{V}{a}$$
 and  $V_B = \omega_b b$ .

W will move upwards because the force pulling section A of rope downwards, must act upwards on section D of the rope.

Rope D moves upwards with speed V because we assume that the rope is inextensible and ropes A and D are attached.

However, we cannot say that rope B moves downwards with speed V. Since the two pulleys of radii a and b are rigidly fixed together, they must rotate with the same angular velocity,  $\omega_a = \omega_b$ .

$$V = \omega_a a \Rightarrow \omega_a = \frac{V}{a}$$
 and  $V_B = \omega_b b$ .

Substituting  $\omega_a = \frac{V}{a}$  into the expression for  $V_B$  using  $\omega_a = \omega_b$ ,

$$V_B = \omega_b b = \omega_a b = \frac{V}{a} b.$$

W rises as a result of the difference in speeds of ropes D and B since a greater length of rope D is pulled than length of rope B is pushed in a given time.

Therefore, the centre of P and W rise with speed  $V_W$ ,

$$V_W = \frac{1}{2} \left( V - \frac{b}{a} V \right)$$

$$V_W = \frac{V}{2} \left( 1 - \frac{b}{a} \right)$$

$$V_W = V\left(\frac{a-b}{2a}\right)$$
.

W rises as a result of the difference in speeds of ropes D and B since a greater length of rope D is pulled than length of rope B is pushed in a given time.

Therefore, the centre of P and W rise with speed  $V_W$ ,

$$V_{W} = \frac{1}{2} \left( V - \frac{b}{a} V \right)$$

$$V_{W} = \frac{V}{2} \left( 1 - \frac{b}{a} \right)$$

$$V_{W} = V \left( \frac{a - b}{2a} \right).$$

The factor of a half is required because length of rope on both sides of W must decrease by a length I for W to rise a length W.