SettingPageViewModel

```
+ LanguageChanged: EventHandler<EventArgs>?
+ LanguageChoice: CultureInfo
- languagePath: string

+ KmoniSettingsHelper: IKmoniSettingsHelper
+ SensorTypeChoices: IEnumerable<SensorType>
+ MeasurementTypeChoices: IEnumerable<MeasurementType>

+ WebSocketButtonText: string
+ WebSocketConnections
 : ObservableCollection<IWebSocketConnectionTemplate>
- _webSocketClient: _webSocketClient
- _startPost: WebSocketStartPost

+ OAuthButtonText: string
+ OAuthConnected: bool
+ ApiKeyConfirmed: bool
+ ApiKeyButtonEnabled: bool
+ ApiKeyText: string
+ AuthenticationStatus: AuthenticationStatus

- _logger: ILogger<SettingPageViewModel>
```
```
- OnLanguageChoiceChanged(CultureInfo): None
- SetResourcesCultureInfo(CultureInfo): None
- GetCultureInfo(): CultureInfo
- LanguageChangedWriteToFileEventHandler(
    object? EventArgs): None

+ WebSocketButtonCommand(): Task
+ WebSocketRefreshCommand(): Task
- WebSocketStatusChangedEventHandler(
    object?, EventArgs): None
- GetTotalWebSocketSlots(): Task<int>

+ OAuthButtonCommand(): Task
+ ApiKeyButtonCommand(): Task
- OnApiKeyTextChanged(string): None
- AuthenticationStatusChangedEventHandler(
    object?, AuthenticationStatusChangedEventArgs)
    : None

+ SettingPageViewModel(
    IOptions<WebSocketStartPost>,
    IKmoniSettingsHelper,
    IWebSocketClient,
    IAuthenticationHelper,
    IApiCaller,
    ITelegramRetriever,
    ITelegramParser,
    ITimeProvider,
    ILogger<SettingPageViewModel>): None
```

<<Interface>> IKmoniSettingsHelper

<<Interface>> IAuthenticatonHelper

<<Interface>> IWebSocketClient

<<Interface>> IApiCaller

<<Interface>> IWebSocketConnectionTemplate

```
+ WebSocketId: int
+ ApplicationName: string?
+ StartTime: DateTimeOffset
+ IsEnabled: bool
+ DisconnectCommand: IAsyncRelayCommand
```

EmptyWebSocketConnectionTemplate

```
+ WebSocketId: int
+ ApplicationName: string?
+ StartTime: DateTimeOffset
+ IsEnabled: bool
+ DisconnectCommand: IAsyncRelayCommand
+ Instance
    : EmptyWebSocketConenctionTemplate
```
```
- EmptyWebSocketConnectionTemplate()
    : None
```

<<Abstract>> ObservableObject

WebSocketConnectionTemplate

```
+ WebSocketId: int
+ ApplicationName: string?
+ StartTime: DateTimeOffset
+ IsEnabled: bool
+ DisconnectCommand: IAsyncRelayCommand
```
```
+  WebSocketConnectionTemplate(
    WebSocketDetails, Func<Task<bool>>: bool
```