Welcome to the Corero Management System

Search for help topics using the search panel above, or click the arrowhead at the left to explore the help using the table of contents and index.
Alternatively, click a link below to get started.

Basic CMS Information

This is a list of basic topics to get you started. Use the search panel, table of contents, or index to find more topics.

- Using the CMS dashboard
- Interpreting security events
- Configuring policies
- Adding a DDP to manage with the CMS
- Basic CMS setup and configuration
- Corero Management System overview

About Corero Network Security

- Go to www.corero.com, the Corero Network Security homepage
- Corero Product Overview: The First Line of Defense
- Contact Corero Customer Support
- Version and Legal Information For This CMS

Other Resources

- See these CMS help topics as a book in Adobe PDF

Corero Product Overview: The First Line of Defense

Corero Network Security provides the solution to a common problem that often impairs the performance and effectiveness of many organizations' IT infrastructures.

Recognizing a Common IT Infrastructure Problem

Today, an organization's network can be overwhelmed by unwanted traffic from the Internet. This can comprise a number of hazards, from undesired users and services on your network to distributed denial of service (DDoS) attacks and advanced evasions that target your servers. Unfortunately, today's security infrastructure is not sufficient to stop these encroachments on your network. Specifically:

- The state tables of current generation firewalls get saturated with large numbers of connections from unwanted traffic.
- Next generation firewalls don't have adequate DDoS protection, and therefore cannot discriminate good traffic from bad traffic.
- IT infrastructure and servers sitting downstream from the firewall end up processing unnecessary traffic and therefore are less responsive to good traffic.

This not only exposes you to threats, but costs service degradation, site downtime, brand damage, and most importantly, lost business.

The Solution: Corero's First Line of Defense

The solution to this problem, Corero's First Line of Defense®, stops DDoS attacks, protects infrastructure, and eliminates downtime from its position in front of your firewall. The First Line of Defense stops all types of DDoS attacks, targeted server attacks, advanced evasions and a host of other attack vectors including removal of all unwanted traffic before it even enters your network. As a result, it makes your IT infrastructure more efficient and effective, improving performance of applications and servers, and ultimately eliminating downtime. More importantly, the assumption you had in the beginning, that your customer traffic flows through unabated, now actually holds true. You have satisfied customers and foiled attackers.

Corero's First Line of Defense eliminates unwanted traffic with a systematic approach comprising five steps:

Allow expected traffic while restricting known attackers. Examples of known attackers are IP addresses known to be malicious and geographies that you don't do business with. Corero's ReputationWatch® filters them out ahead of time so that no traffic from these sources comes in.

Thwart attackers based on their behavior. Examples include an attacker who throws large volumes of traffic at your website, or who opens an excessive number of connections, tying up your server resources. Corero's dynamic threat assessment and

DDoS rejection capabilities mitigate these hazards by evaluating their behavior and limiting their rate, or blocking them altogether.

Enforce correct traffic behavior by checking whether traffic conforms to RFC specifications or de facto standards. For example, normal behavior does not send payload traffic in tiny fragments. Corero's protocol validation modules (PVMs) stop such protocol abuse and advanced evasion techniques (AETs).


Analyze traffic integrity by looking at whether it contains any known intrusions. Corerouses signatures to inspect traffic and block any buffer overflows, code injections, and exploits before they compromise your servers. With Protection Packs, key components of Corero's threat update service, Corero keeps its customers up to date with the latest security protection by delivering malware signatures and vulnerability protection on a weekly basis.

Provide you with insight into what is happening on your network. This includes the ability to collate data from SYSLOG events, SNMP gets & traps, and proprietary APIs into a meaningful stream of information. With that, you can reassess the threat landscape to see if your security policies are effective or need modifications. Corero's SecureWatch®, a maintenance and monitoring service, provides infrastructure and expertise to keep Corero deployments up to date and assure sustained availability.

Corero supports this approach with a product that acts as the First Line of Defense for your network: the Distributed Defense Point, or DDP. This device is managed using the Corero Management System, an application designed expressly for configuring, managing, and monitoring the DDPs that protect your network from harm.

Overview of the Distributed Defense Point (DDP)

The Corero DDP is a network security appliance that protects network infrastructure against distributed denial of service (DDoS) attacks. It is the core of Corero's First Line of Defense solution.
The DDP is available either as a purpose-built hardware unit (informally called a "brick") dedicated to running the Distributed Defense Point software, or as a software-only virtual appliance, known as a vDDP.
The DDP can stand alone as an individual appliance, or it can be combined with one or more other DDPs in a high-availability configuration, or in a networked series of DDPs, each of which inspects and handles different aspects of the traffic entering your network.



The DDP provides the following protection:

- sophisticated protection against DDoS attacks
-

Contacting Corero Customer Support

Corero Network Security offers two options for contacting Customer Services and Support.

• Contact the Customer Services Center by phone at + 1 978-212-1500

• Support is available for all customers with a Hardware or Software Warranty from 8:00 AM to 5:00 PM
(Eastern US Time).

• If you have purchased the Software Subscription Service, you can obtain service 7x24 by calling the support
phone number and pressing Option 2. If the issue is critical, press Option 2 then Option 7.

N O T E

If, for any reason, the primary support phone number does not work, call Corero's answering service at +1.888.324.1246 (US) or +1.603.645.4145 (International) and a support representative will return your call.

• On the web through the Customer Support Portal: https://support.corero.com.
The Web Portal is the most effective way to log and track support issues.
This Portal provides:

• Web-based incident management and customer support tracking system

• Service request communications

• Access to downloadable files including software and product documentation

• An extensive knowledge base. Glossary - list of terms used w/in the portal, customer feedback,
customer-specific history, profile, and service requests track customer contact and support history.

When you contact Customer Services and Support for assistance, have the following information ready:

• The case number, if you are calling about a previous problem

• Your name, and if someone else will be the contact person for the problem, the contact person's name.

• Your company name and location (city, state or province, and country)

• The telephone number (including area code) at which you or the contact person can be reached.

• The email address at which you or the contact person can be reached.

• The product name, model number, and serial number.

• A list of system hardware and software, including revision levels.

• A detailed problem description:
Describe the symptom and the activities that preceded it.
Include details about any recent configuration changes, if applicable.
Be as specific as possible.
Briefly describe your trouble-shooting steps and observations.

Commenting on This Help Set

At Corero Network Security, our goal is to provide the highest quality products and services to our customers. We value customer feedback and encourage users of Corero's systems to send their comments on the product, service, and documentation to our Customer Service Department, so that we can continue to improve our products.
Please send your comments and suggestions to Corero customer service at this Email address: customer.service@corero.com

Version and Legal Information

Corero Management System Version Information

Version 7.00 **DEVELOPMENT IN PROGRESS**.
This help set was built on Thursday, June 27, 2013 at 5:53 PM.

Corero Licensing Information

For Corero product licensing and warranty information, see http://www.-corero.com/en/support/end_user_agreements

Corero Copyright Information

Corero Network Security, Inc. (Corero) reserves the right to revise this documentation and to make changes in content from time to time without obligation on the part of Corero to provide notification of such revision or change. Coreroprovides this documentation without warranty, term, or condition of any kind, either implied or expressed, including, but not limited to, the implied warranties, terms or conditions of merchantability, satisfactory quality, and fitness for a particular purpose. Corero may make improvements or changes in the product(s) and/or the program(s) described in this documentation at any time.
If you are a United States government agency, this documentation and the software described herein are provided to you subject to the following:
This paragraph applies to all acquisitions of the software by or for the United States Government, or by any prime contractor or subcontractor (at any tier) under any contract, grant, cooperative agreement or other activity with the United States Government (collectively, the “Government”). All technical data and computer software are commercial in nature and developed solely at private expense. The software and documentation respectively are “commercial computer software” and “commercial computer software documentation” as defined in DFARS 252.227-7014 (June 1995) and “commercial items” as defined in FAR 2.101(a) and, to the maximum extent permitted by law, are provided with only such rights as are provided in Corero’s standard commercial license for the software and documentation and this notice. Technical data is provided with limited rights only as provided in DFAR 252.227-7015 (November 1995) or FAR 52.227-14 (June 1987), whichever is applicable. Corero’s standard commercial license for the software and documentation and this notice shall govern the Government’s use of the software, documentation, and technical data, and shall supersede any conflicting contractual terms or conditions. If these terms and conditions fail to meet the Government’s needs or is inconsistent in any respect with Federal law, the Government must return the software and the documentation unused to Corero. The following additional statement applies only to acquisitions governed by DFARS Subpart 227.4 (October 1988): “Restricted Rights – Use, duplication and disclosure by the Government is

subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 (OCT. 1988).” The Contractor is Corero Network Security, Inc.
You agree not to remove or deface any portion of any legend provided on any licensed program or documentation contained in, or delivered to you in conjunction with, this document.
No part of this documentation may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from Corero.
If there is any software on removable media described in this documentation, it is furnished under a license agreement which is located on the Corero web site.
For warranty, licensing and maintenance agreement information, visit http://www.-corero.com/agreements.jsp.
First Line of Defense, ReputationWatch, SecureCommand. and SecureWatch are registered trademarks of Corero Network Security, Inc. Agile Inspection Engine and AppSwitch are trademarks of Corero Network Security, Inc.
All other trademarks and registered trademarks are the property of their respective holders.
Copyright © 2013, Corero Network Security, Inc.

Universal Configuration

Delete this text and replace it with your own content.

Adding a DDP to Manage

A DDP has to be added to the CMS configuration in order for the CMS to be able to manage that DDP.
Add a DDP to the CMS configuration from the CMS Home page.
Click **Add** in the DDP pane to display the Device screen.
Type the name of the DDP that you are adding to the CMS configuration.
Click **Create** to execute the addition.

Configuring DDP Redundancy (HA)

Delete this text and replace it with your own content.

Configuring Service Groups

Create a new service group by clicking **Add** in the Service Groups pane. Type a name for the new service group and click **Create** to add it to the configuration.
Add an existing DDP cluster to the service group.

Configuring Security Policies

Click **Config** > **Firewall & IPS Policies** in the CMS tool bar to display the Firewall & IPS Policies screen for defining and managing security policies for your network.
Display the existing policies by first choosing a service group from the pulldown menu at the upper right of the Firewall & IPS Policies screen. Policies are configured per service group.
Two policies are built in to the software: blacklist and Catch-All. These can be edited, but cannot be deleted.
Disabled policies are dimmed in the list.

- *Create a new policy* by clicking **Add new policy line** and typing a descriptive name for it.
- *Delete one or more existing policies* by selecting them in the list and clicking **Delete policy lines**.
- *Edit an existing policy* by clicking on it in the list. This expands the policy's entry in the screen and exposes the controls that define it. You can expand multiple policies to compare their definitions.
- *Configure a policy* by specifying a traffic source (From), its destination (To), and the set of actions the DDP will execute on the traffic between the source and the destination.

See Security Policies for a detailed explanation of policy behavior.

Upgrading DDP Software

Click **Network** in the CMS tool bar and choose **Sw** from the pulldown menu to display the Local File Upload screen.
Upload, Install, Activate.
Specify the file to be uploaded to the DDP file library.
Select from the file library the file that you want to use to upgrade the DDP software.
Select the DDP cluster for which you want to upgrade the software.

Traffic Monitoring and Analysis

Delete this text and replace it with your own content.

Threat Mitigation

Delete this text and replace it with your own content.

Reference Topics

Delete this text and replace it with your own content.

Concepts and Models

Delete this text and replace it with your own content.

Rule Overview

Rules are a primary building block of security policies. They are constructed to identify traffic that may be suspicious in origin, malicious in intent, and harmful in its results. Some rules define very strict conditions that you may not want to apply to every host, while other rules address definite known issues that should be applied universally. You can create a named set of rules, modify the treatment applied to individual rules within the set, and then use the named rule set as a building block when creating Firewall + IPS rule policies.

Changing rule settings can affect system operation adversely. Consult with Corero Network Security before changing these settings.

There are several basic types of rules: packet-based rules, rate-based rules, IPS rules, and reputation-based rules:

- Packet-based rules are applied based on layer 2 network traffic. The settings for these rules have been optimized by Corero, and they should not generally be changed under normal system operation.
- Rate-based rules are applied based on the rate at which requests, connections, or network communications are sent to the DDP. You may choose to disable some of these rate-based rules which are applied system-wide.
- IPS rules are applied based on the protocol characteristics exhibited by incoming packets, as well as on other attack signatures and patterns.
- Reputation-based rules are applied according to user-configured criteria for IP addresses that Corero characterizes by their level of trustworthiness.

You can view detailed information about each rule including its identifier (which starts with "tln-") and a description of the rule's purpose.

Security Event Category

Every rule begins with a six character security event category prefix that allows for sorting by rule prefix anywhere a list of rules appears. Rule prefixes and their descriptions follow:

- AAUPV: Acceptable application usage policy violation or condition match
- DDOSA: Rate-based attack
- EXPLT: Attempt to exploit a known vulnerability
- FWALL: Firewall policy violation or condition match
- NETWK: Network behavior issue - an IP, UDP, or TCP issue
- OTHER: Another issue or interest
- PROTO: Protocol anomaly or violation
- RATEV: Rate-based policy usage violation concerning connection limits or client rate limits
- RECON: Reconnaissance in the form of port scans or sweeps
- RRBDx: Request response behavior - DNS
- RRBHx: Request response behavior - HTTP

- SPYWR: Spyware was found in the inspected body
- TROJN: Trojan or backdoor program
- VIRUS: Virus and/or worm in executable file

Confidence Levels

In addition to a security event category, each event has a predefined confidence level, from one to three stars, that designates how likely it is that the rule will yield false positives. A false positive is an instance in which traffic matches a rule, but is misidentified as troublesome or malicious when it is not. Rules are organized into default rule sets based on their confidence level.
Rules and rule sets each have a predefined confidence level. The confidence level reflects how likely the rule is to trigger a false positive, which might misidentify traffic as malicious or troublesome when it is not. Confidence levels and their descriptions follow:

- Three Stars: Rules with three stars are considered safe. These rules should never cause a false positive. Three star rules that trigger events should always be considered malicious.
- Two Stars: Rules with two stars are recommended. These rules seldom trigger false positives. Two star rules that trigger events should always be considered suspect and probably malicious.
- One Star: Rules with one star should be used for strict enforcement. One star rules may provide false positives, but they are extremely useful in situations where you are leery of a particular host group.
- No Stars: Rules with no stars are extremely targeted. They are to be used in special cases, under certain conditions, or for specific, restricted situations. When used indiscriminately, these rules can easily trigger false positives.

User-Modifiable Rule Settings

In addition to the specific issue it is designed to detect, every rule has user-modifiable treatment settings that affect whether or how that rule is used by a security policy to detect malicious traffic. Rules are designed to be very granular in their detection abilities. For example, not all rules identify known bad traffic. Some identify when too much traffic is coming in, whether good or bad. And, in some cases, what might be bad traffic from one client is acceptable traffic from another client.

N O T E

Some rules cannot be modified by the user. For both the default rule sets and the rule sets you create, you can modify the following characteristics on a rule-by-rule basis:

• Status: Whether the rule is enabled or disabled.
• Actions: The action that the DDP should take if the rule is triggered.
• Logging options: Including whether the traffic that triggered the rule should be copied to the discard port.

N O T E

Your treatment modifications apply only to the instance of that rule in the named rule set in which you edited it.

Status

Every rule set always contains every rule. The way to control which rules are applied in a specified rule set and which are not is by modifying the status of the rule for that particular rule set. You can either enable the rule, which means it will be applied for that policy, or you can disable it.

Actions

An action is a response by the DDP when traffic triggers a security rule. It is part of the treatment portion of a security policy. When traffic through the device triggers a rule, the device can take one of the following actions:

• Allow: Pass the traffic.
• Drop: Passively block the traffic by dropping the traffic with no indication to the offending client.
• Reject: Actively block the traffic by dropping the traffic and taking specific action, for example, by resetting the connection.

When you create the IPS portion of a Firewall + IPS policy, you apply a rule set to the IPS part of the policy. Each rule in the rule set has an action associated with it, which you can modify.

In the case of the firewall portion of the Firewall + IPS policy, the same action applies to all of the firewall rules.

Logging Options

Logging options are also part of the treatment portion of a security policy. They specify the reporting actions the DDP should take when traffic triggers a rule. Logging options include sending information to a log file based on its severity rating, and copying the associated traffic to the discard port.

You can specify logging options for all traffic that triggers an IPS or rate-based rule, even if the action you choose for that rule is “allow.” Discovering when traffic triggers a rule enables to you record usage information about applications you allow as well as those you block.

Limit Profiles for Rate-Based Policies

Rate based security policies contain host groups and rules, but each policy also contains limit profiles. The following types of rate limit profiles are part of the policy:

• Connection Limits: This feature limits the number of simultaneous connections allowed for a host group, and for individual members of the group.

• Client Request Limits: This feature limits the traffic the system will accept from each client in the group. Client request limiting is performed based on the client, server, and service associated with a particular packet.

• SYN Flood Limits

Provides limits for the number of incomplete SYN requests for servers and for various categories of clients (trusted, suspicious, malicious, and so forth).

Rule Set Overview

A rule set is a named collection of rules that is configured to identify and handle traffic for a particular purpose. For example, the DDP includes built-in rule sets with names like “Recommended Client Protection,” “Recommended Server Protection,” “Strict Client Protection,” and “Strict Server Protection,” each of which furnishes a collection of rules that have been enabled and configured to support the purpose for which the rule set is named. Every DDP comes with a number of these pre-defined rule sets built in. Every rule is included in every rule set; however, each rule can be enabled or disabled explicitly for a particular rule set, so that even though each rule is present in every rule set, it isn’t necessarily used. In addition, every other aspect of how an enabled rule is handled can be configured explicitly for a rule set; this includes the action to be taken when the rule is met, and any logging that is performed at that time.

There are two types of rule sets:

- IPS rule sets: IPS rule sets describe behaviors for identifying and addressing traffic based on the nature of the traffic itself, such as its packet formation or its content.
- Reputation rule sets: Reputation rule sets describe behaviors for identifying and addressing traffic based on the trustworthiness of its originating host.

Although the DDP contains default rules sets, you can modify those rule sets. Or, if you prefer, you can copy a rule set and use the copy to create a custom rule set to use in your IPS policies.

Service Groups

A service group is a collection of DDPs that you configure to have the same security settings. A service group typically comprises DDPs that share a common role or location at your site. The purpose of a service group is to allow you to create and modify policies and environmental configuration items and apply them as a group of settings to one or more DDPs. You can also modify the settings within a service group by automatically updating certain environmental configuration items using Threat Update Service Defense Packs.

A service group is a collection of DDPs that should have the same security settings. A service group can contain one or more individual devices and/or one or more DDP clusters. Each service group contains all of the settings required to make security decisions as the devices examine traffic flows. By collecting all of these settings into a service group, you can easily manage the common settings you want to apply to specific sets of DDPs. Each policy group contains all of the settings required by DDPs to make traffic security decisions as they examine traffic flows.

By collecting devices into a service group, you can easily manage the settings that you apply to specific sets of DDPs.

A policy group enables you to specify the following types of settings across all policy group members:

• Firewall and intrusion protection policies, including shunning
• Rate-based policies
• Traffic rate limits
• Security environment configuration items, including:
• Address groups
• Services (a service is a combination of a network protocol, a port number, and a server group)
• IPS rule sets (rules used by DDPs to classify traffic as good or bad)
• IPS rule details (specific settings that apply to certain rules)
• IPS signatures (specific data patterns that identify problem traffic)

Shunning Overview

DDPs have an effective protection capability called *shunning* that can quickly block traffic from IP addresses, temporarily or permanently, that are suspected of originating or participating in an attack. Shunning an attacker's IP address at an ingress point to the network reduces the possibility of the attack expanding to other targets within the environment protected by the DDP.

When shunning, you group IP addresses into collections called shun labels. You can assign IP addresses to a shun label based on any criteria you desire, including common features of the IP source system, by date, or by attack type.

The advanced protection capabilities provided by shunning are described below:

- Attack Source Identification: The Security Event Viewer enables users to identify a set of attacker IP addresses associated with blocked and detected attacks.
- Malicious IP Address Shunning: Isolate events of interest and automatically shun all IP addresses associated with a particular attack event. Users can set time periods for how long each address should be shunned. They can also manually unshun addresses that are later determined to be safe.
- Attack Defense Dashboards: The user interface allows Security Operations Center personnel to switch between daily monitoring and under-siege incident response.
- Additional Router Protection: Administrators can export a list of IP addresses being shunned so that they can be imported into a router for blocking by the router.

Once you have identified one or more IP addresses associated with events of interest, you can shun one, some, or all of them. IP addresses you want shunned can also be entered manually. Shunning is a temporary activity, and various time periods can be specified for the addresses to be shunned.

Security Policies

Security policies are the logical constructions that guide a DDP's security decisions as it examines traffic flows for the device subsystems to meet the needs of your network. Security policies enable you to allow or block traffic depending on its characteristics. You can define policies that permit necessary traffic and block unnecessary traffic, not only to reduce traffic volume, but also to prevent attacks. You can block specific traffic types in different ways. For example, if you wanted to block Instant Messaging traffic, you could block the services associated with that type of traffic, you could block traffic of a particular type using a specific port, or you could block traffic based on a known host name from which the traffic originates.

Security policies are configured and managed using the Security Policies screen. Refer to Configuring Security Policies for additional information about the configuration process.

Blacklist Security Policy

The blacklist security policy is built in to the CMS and can be edited, but cannot be deleted. It describes a very narrow policy that pertains to traffic originating from specific sources. It is always first in the list of security policies for any service group.

Catch-All Security Policy

The Catch-All security policy is built in to the CMS and can be edited, but cannot be deleted. It describes a very broad policy that pertains to a wide variety of incoming traffic. It is always last in the list of security policies for any service group.

Screen Descriptions

Delete this text and replace it with your own content.

Device Screen

Click **Add** in the DDPs pane of the Home screen to display the Device screen for adding a new DDP to the CMS configuration so that the DDP can be managed.
Type a name for the device and click **Create** the finish adding it to the CMS configuration so it can be managed. The new device will be added to the list of devices managed by the CMS.

Device Group screen

Click **Add** in the DDP Cluster pane on the Home screen to display the Device Group screen for defining a new device group.
Type a name for the device group and click **Add** to complete its creation and add it to the list of device groups managed by the CMS.

Firewall & IPS Policies screen

Click **Config** > **Firewall & IPS Policies** in the CMS tool bar to display the Firewall & IPS Policies screen for defining and managing security policies for your network.
The Security Policies screen provides these controls:
For service group menu: Choose the service group for which you want to display security policies. Policies are configured per service group.
Add new policy line: Create a new security policy by typing its name and clicking **Create**. Use a descriptive name that will help you remember the policy's purpose.
Delete policy line: Remove one or more selected security policies.
List of security policy names: The security policies that have been defined for the current service group are listed in decreasing priority from most-important to least-important. Policies are processed in row order, with row 1 processed first, and so forth. You can move policies around in the list to change their priority, but the built-in blacklist policy will always be first, and the built-in Catch-All policy will always be last.
Click on a policy name to expand its definition and edit its configuration.
Click the **Enabled** checkbox to activate a policy. Disabled policies are dimmed in the list.
From: Specify the origin of the traffic to which the policy will apply. **Anywhere** means traffic from any source, regardless of its address, geography, or reputation. **Specific address groups** enables you to choose one or more existing address groups to which you want the policy to apply.
To: Specify the destination of the traffic to which the policy will apply. **Anywhere** means traffic destined for any host, regardless of its address or service. **Specific address groups** enables you to choose one or more existing address groups to which you want the policy to apply.
Bi-directional: Select this if you want the policy to have the same effect on traffic returning to the original source.
Ports: Specify the destination ports to which the policy will apply. **Anywhere** means traffic destined for any port, regardless of its ID or service. **Specific service ports** enables you to choose one or more well-known port/service to which you want the policy to apply.
Firewall Action: Choose one of **Allow**, **Drop**, or **Reject**.
Logging: Select **Log this action** if you want the Allow/Drop/Reject action to be logged when it occurs. Choose a corresponding Log/Event Severity, one of **Low**, **Moderate**, or **Critical**.
Rate Limiting: Choose one or more existing rate-limiting rule sets to apply to the traffic.
IPS Rule Set: Choose one or more existing IPS rule sets to apply to the traffic.
Reputation Rule Set: Choose one or more existing reputation rule sets to apply to the traffic.

See Security Policies for a detailed explanation of policy behavior.

Security Event Viewer

The Security Event Viewer is a security monitoring and management tool that enables you to easily examine and react to the traffic that triggers security rules. The viewer includes features that enable you to filter and focus on event details, then take security management steps immediately.

Service Group screen

Click **Add** in the Service Group pane on the Home screen to display the Service Group screen for defining a new service group.
Type a name for the new service group and click **Create** to complete its creation. The new service group is added list in the Service Groups pane on the Home screen.

Glossary

Delete this text and replace it with your own content.

DDP

The Corero DDP is a network security appliance that protects network infrastructure against distributed denial of service (DDoS) attacks. It is the core of Corero's First Line of Defense solution.

Device

A device is any purpose-built security appliance provided by Corero Network Security. A device can be a physical hardware unit, such as a DDP (a "brick"), or it can be a software-only virtual appliance, such as a vDDP. Functionally, the two forms are similar, and each qualifies as a device for the management purposes of the CMS.

Device Group

A device group is a set of devices that have been configured to work together for a common function. A device group may provide redundant high-availability, or it may provide multiple network security functions performed in a configured sequence.

Rule

Rules are building blocks of security policies; they identify traffic that may be suspicious in origin, malicious in intent, and harmful in its results.

Rule Set

A rule set is a named collection of rules that is configured to identify and address traffic for a particular purpose.

Security Policy

A *security policy* specifies a set of actions to be performed on incoming traffic that exhibits certain specific characteristics. Security policies are the logical constructions that inform the DDP's security decisions as it examines traffic flows to protect your network. See Security Policies for a complete explanation.
The Security Policies screen provides the controls you need for configuring security policies.

Service Group

A service group is a collection of DDPs that you would like to have the same security settings. A service group typically comprises DDPs that share a common role or location at your site. The purpose of a service group is to allow you to create and modify policies and environmental configuration items and apply them as a group of settings to one or more DDPs. You can also modify the settings within a service group by automatically updating certain environmental configuration items using Threat Update Service Defense Packs.
Service groups were known as "policy groups" in previous releases.

Shun Label

When shunning, you group IP addresses into collections called shun labels. You can assign IP addresses to a shun label based on any criteria you desire, including common features of the IP source system, by date, or by attack type.

Shunning

DDPs have an effective protection capability called shunning that can quickly block traffic from IP addresses, temporarily or permanently, that are suspected of originating or participating in an attack.