DECK OVER SYSTEMS



UPDATED DESIGN

- New 26’ length offering
- 16K GVW models now available
- Lower trailer weight = Higher payload capacity
  - Up to 520 lbs. more payload capacity vs. previous model
- Updated 50/50 ramp design (same as our gooseneck trailers)
- New coupler/jack design
  - Hydaulic jack option now possible

NEW 50/50 RAMP DESIGN



STANDARD SPECIFICATIONS	1420 DO	1426 DO	1620 DO	1626 DO
GVW	14,000 lbs.	14,000 lbs.	16,000 lbs.	16,000 lbs.
Usable Deck Size	20’ x 98.25”	25’-4” x 98.25”	20’ x 98.25”	25’-4” x 98.25”
Empty Weight	Est. 2,680 lbs.	Est. 3,000 lbs.	Est. 3,060 lbs.	Est. 3,380 lbs.
Overall Width	102”	102”	102”	102”
Overall Length	25’-8”	31’-8”	25’-8”	31’-8”
Payload Capacity	11,320 lbs.	11,000 lbs.	12,940 lbs.	12,620 lbs.
Ramp Length	Approx. 4’	Approx. 4’	Approx. 4’	Approx. 4’
Tongue Length	68”	68”	68”	68”
Deck Height	35”	35”	35”	35”
Loading Angle	14˚	14˚	14˚	14˚
Overall Deck Length	20’	25’-4”	20’	25’-4”
Dovetail Length	60”	60”	60”	60”
Wheel Size	16”	16”	16”	16”
Tires	ST235/80R16E - 10 ply	ST235/80R16E - 10 ply	ST235/80R16G - 14 ply	ST235/80R16G - 14 ply
Number of Lug Bolts	8 per wheel (32)	8 per wheel (32)	8 per wheel (32)	8 per wheel (32)
Axle/Suspension	7K Rubber Torsion	7K Rubber Torsion	8K Rubber Torsion	8K Rubber Torsion
Brakes	Electric Self-Adjusting	Electric Self-Adjusting	Electric Self-Adjusting	Electric Self-Adjusting
Coupler	2-5/16” Ball	2-5/16” Ball	2-5/16” Ball	2-5/16” Ball
Coupler Position	Adjustable	Adjustable	Adjustable	Adjustable
Jack Style	Side Crank	Side Crank	Side Crank	Side Crank
Jack Rating	12,000 lbs.	12,000 lbs.	12,000 lbs.	12,000 lbs.
Stake Pockets	12 per side (24 total)	14 per side (28 total)	12 per side (24 total)	14 per side (28 total)
Lighting	LED	LED	LED	LED