Graphiti / UI / API / Adapters

Graphiti = readonly. UI = display only. API = bridge only. Adapters = output only. Ce support isole les surfaces qui ne doivent pas devenir autorite.

Graphiti readonly - 21 lignes

#2 — Brody seulement

CANON_GUARDIAN

Core:NON | V1:NON | Enr:OK | K:NON | G:OK | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody; ne pas brancher domaine sans g[illegible]vision. Phase: 2_BRODY_STABILIZATION

#3 — Brody seulement

GRAPH_BUILDER

Core:NON | V1:NON | Enr:OK | K:NON | G:OK | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody; ne pas brancher domaine sans g[illegible]vision. Phase: 2_BRODY_STABILIZATION

#40 — Brody seulement

CALIBRATION_PROCEDURALE

Core:NON | V1:NON | Enr:OK | K:NON | G:OK | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody; ne pas brancher domaine sans g[illegible]vision. Phase: 2_BRODY_STABILIZATION

#5 — Brody seulement

PROOF_SENTINEL

Core:NON | V1:NON | Enr:OK | K:NON | G:OK | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody; ne pas brancher domaine sans g[illegible]vision. Phase: 2_BRODY_STABILIZATION

READONLY_CONTEXT_ONLY — Brody seulement

READONLY_CONTEXT_ONLY

Core:OK | V1:NON | Enr:OK | K:NON | G:OK | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody; ne pas brancher domaine sans g[illegible]ecision. Phase: 2_BRODY_STABILIZATION

READONLY_CONTEXT_PROVIDER

Brody seulement

READONLY_CONTEXT_PROVIDER

Core:NON V1:NON Enr:OK K:NON G:OK Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans graphe/provision. Phase: 2_BRODY_STABILIZATION

readonly_evidence

Brody seulement

readonly_evidence

Core:NON V1:NON Enr:OK K:NON G:OK Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans graphe/provision. Phase: 2_BRODY_STABILIZATION

BALANCE

OK Brody + domaine

BALANCE

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, comparer au kernel seulement. Phase: 1_KERNEL_MINIMUM

Balance exponentielle

OK Brody + domaine

Balance exponentielle

Core:OK V1:NON Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 3_DOMAIN_GATES

FROZEN_READONLY

OK Brody + domaine

FROZEN_READONLY

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 3_DOMAIN_GATES

GUARDIAN_010

OK Brody + domaine

Merkle Verifier

Core:OK V1:NON Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

READONLY_CONTEXT — OK Brody + domaine

READONLY_CONTEXT

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 3_DOMAIN_GATES

ROLE_005 — OK Brody + domaine

Human Operator

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_006 — OK Brody + domaine

Governance Layer

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_007 — OK Brody + domaine

OS3 Audit Layer

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_014 — OK Brody + domaine

Adapter MCP

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

graphiti — OK Brody + domaine

graphiti

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 7_GRAPHITI_READONLY_CONTEXT

readonly

OK Brody + domaine

readonly

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kerr… seulement. Phase: 8_UI_COCKPIT_RSSI

readonly=True

OK Brody + domaine

readonly=True

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kerr… seulement. Phase: 8_UI_COCKPIT_RSSI

"name": "Balance exponentielle",

Partiel runtime

"name": "Balance exponentielle",

Core:NON V1:NON Enr:NON K:NON G:OK Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: …_RESEARCH_SANDBOX_LATER

"summary": "CANON_GUARDIAN verifies name collisions for Balance expon

Partiel runtime

"summary": "CANON_GUARDIAN verifies name collisions for Balance exponentielle."

Core:NON V1:NON Enr:NON K:NON G:OK Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: …_RESEARCH_SANDBOX_LATER

UI / Cockpit - 41 lignes

/api/audit/events

Brody seulement

/api/audit/events

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/blockchain/status

Brody seulement

/api/blockchain/status

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/gencoin

Brody seulement

/api/gencoin

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/ir/candidate

Brody seulement

/api/ir/candidate

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/memory

Brody seulement

/api/memory

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/memory/

Brody seulement

/api/memory/

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/memory/candidates

Brody seulement

/api/memory/candidates

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/os-reverse/project

Brody seulement

/api/os-reverse/project

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/os-trad/translate

Brody seulement

/api/os-trad/translate

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/os3/

Brody seulement

/api/os3/

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/os3/tickets

Brody seulement

/api/os3/tickets

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/periphery/cognitive/trees

Brody seulement

/api/periphery/cognitive/trees

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/runtime-wiring/os-map/query

Brody seulement

/api/runtime-wiring/os-map/query

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/runtime-wiring/preview

Brody seulement

/api/runtime-wiring/preview

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/runtime-wiring/source-runtime/preview

Brody seulement

/api/runtime-wiring/source-runtime/preview

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/worldcalls

Brody seulement

/api/worldcalls

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/worldcalls/sovereign-tickets

Brody seulement

/api/worldcalls/sovereign-tickets

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/x108/

Brody seulement

/api/x108/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/x108/status

Brody seulement

/api/x108/status

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

A11

Brody seulement

Resonance / Reconstruction totale

Core:NON V1:NON Enr:OK K:OK G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 1_KERNEL_MINIMUM

ROLE_013

Brody seulement

Orchestrator

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

selected_routes

Brody seulement

selected_routes

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

support_routes

Brody seulement

support_routes

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/brody/chat

OK Brody + domaine

/api/brody/chat

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

GUARDIAN_009

OK Brody + domaine

Sigma Verifier

Core:OK V1:OK Enr:OK K:OK G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

GUARDIAN_010

OK Brody + domaine

Merkle Verifier

Core:OK V1:NON Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

GUARDIAN_011

OK Brody + domaine

RFC3161 Verifier

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_PSSI

KX108_ONLY

OK Brody + domaine

KX108_ONLY

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_PSSI

ROLE_005

OK Brody + domaine

Human Operator

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_006

OK Brody + domaine

Governance Layer

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_007

OK Brody + domaine

OS3 Audit Layer

Core:OK V1:OK Enr:OK K:OK G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

ROLE_014

OK Brody + domaine

Adapter MCP

Core:OK V1:OK Enr:OK K:NON G:OK Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

canonical

OK Brody + domaine

canonical

Core:OK V1:OK Enr:OK K:OK G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 1_KERNEL_MINIMUM

decision_authority

OK Brody + domaine

decision_authority

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

decision_authority=KX108_ONLY

OK Brody + domaine

decision_authority=KX108_ONLY

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

domain_raccord

OK Brody + domaine

domain_raccord

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

domains

OK Brody + domaine

domains

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

graphiti — OK Brody + domaine

graphiti

Core:OK | V1:OK | Enr:OK | K:NON | G:OK | Bnk:OK | Trd:OK | GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 7_GRAPHITI_READONLY_CONTEXT

graphiti readonly — OK Brody + domaine

graphiti readonly

Core:OK | V1:NON | Enr:OK | K:NON | G:NON | Bnk:OK | Trd:OK | GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

readonly — OK Brody + domaine

readonly

Core:OK | V1:OK | Enr:OK | K:NON | G:OK | Bnk:OK | Trd:OK | GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

readonly=True — OK Brody + domaine

readonly=True

Core:OK | V1:OK | Enr:OK | K:NON | G:OK | Bnk:OK | Trd:OK | GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 8_UI_COCKPIT_RSSI

API / routes / adapters detectes - 400 lignes

Check: are V1 Brody routes (F33/F36/F38) using _BOUNDARY or their mo — Brody seulement

Check: are V1 Brody routes (F33/F36/F38) using _BOUNDARY or their module BOUNDARY?

Core:NON | V1:OK | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

#11

Brody seulement

FORMAL_BRIDGE

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/balance')` ? `periphery_balance`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `periphery/brody/brody_language_router.py`

Brody seulement

- `periphery/brody/brody_language_router.py`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/agents/status

Brody seulement

/api/blockchain/agents/status

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/classifiers/fraud-check

Brody seulement

/api/blockchain/classifiers/fraud-check

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/gencoin/compute

Brody seulement

/api/blockchain/gencoin/compute

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/blockchain/policy/evaluate

Brody seulement

/api/blockchain/policy/evaluate

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/sandbox/simulate

Brody seulement

/api/blockchain/sandbox/simulate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/sandbox/truth-gate

Brody seulement

/api/blockchain/sandbox/truth-gate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/signature/check

Brody seulement

/api/blockchain/signature/check

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/wallet/gate

Brody seulement

/api/blockchain/wallet/gate

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/world/bus-dispatch

Brody seulement

/api/blockchain/world/bus-dispatch

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/world/dry-run

Brody seulement

/api/blockchain/world/dry-run

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/world/gateway

Brody seulement

/api/blockchain/world/gateway

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/blockchain/world/ticket-status

Brody seulement

/api/blockchain/world/ticket-status

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/brody/chat.

Brody seulement

/api/brody/chat.

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/bus/bus/signal

Brody seulement

/api/bus/bus/signal

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/context/from-message

Brody seulement

/api/context/from-message

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/graphiti/

Brody seulement

/api/graphiti/

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/health

Brody seulement

/api/health

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/memory/candidate-ledger

Brody seulement

/api/memory/candidate-ledger

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/memory/candidate/from-message

Brody seulement

/api/memory/candidate/from-message

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/memory/promotion-policy

Brody seulement

/api/memory/promotion-policy

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/memory/sources

Brody seulement

/api/memory/sources

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/memory/status

Brody seulement

/api/memory/status

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/operator/governed-runtime

Brody seulement

/api/operator/governed-runtime

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/os3/replay/

Brody seulement

/api/os3/replay/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/os3/replay/{ticket_id}

Brody seulement

/api/os3/replay/{ticket_id}

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody-runtime/f33/integration-packet

Brody seulement

/api/periphery/brody-runtime/f33/integration-packet

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody-runtime/f36/user-scenario

Brody seulement

/api/periphery/brody-runtime/f36/user-scenario

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody-runtime/f38/multi-domain-scenarios

Brody seulement

/api/periphery/brody-runtime/f38/multi-domain-scenarios

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody-runtime/f38/multi-domain-scenarios

Brody seulement

/api/periphery/brody-runtime/f38/multi-domain-scenarios

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody/context-query

Brody seulement

/api/periphery/brody/context-query

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody/diffusion-mix

Brody seulement

/api/periphery/brody/diffusion-mix

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody/double-brain-route

Brody seulement

/api/periphery/brody/double-brain-route

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/brody/language-route

Brody seulement

/api/periphery/brody/language-route

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/memory-world-map

Brody seulement

/api/periphery/cognitive/memory-world-map

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/tree-signal

Brody seulement

/api/periphery/cognitive/tree-signal

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/trees/

Brody seulement

/api/periphery/cognitive/trees/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/trees/domain/

Brody seulement

/api/periphery/cognitive/trees/domain/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/trees/domain/{domain}

Brody seulement

/api/periphery/cognitive/trees/domain/{domain}

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/trees/domain/{domain}

Brody seulement

/api/periphery/cognitive/trees/domain/{domain}

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/cognitive/trees/{tree_id}

Brody seulement

/api/periphery/cognitive/trees/{tree_id}

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/context/build

Brody seulement

/api/periphery/context/build

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/context/export

Brody seulement

/api/periphery/context/export

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/context/ingress

Brody seulement

/api/periphery/context/ingress

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/context/sanitize

Brody seulement

/api/periphery/context/sanitize

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/context/validate

Brody seulement

/api/periphery/context/validate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/demo/runtime-readiness

Brody seulement

/api/periphery/demo/runtime-readiness

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/education/audience

Brody seulement

/api/periphery/education/audience

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/education/format

Brody seulement

/api/periphery/education/format

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/education/score

Brody seulement

/api/periphery/education/score

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/feedback/bridge-candidate

Brody seulement

/api/periphery/feedback/bridge-candidate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/feedback/candidate

Brody seulement

/api/periphery/feedback/candidate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/gencoin/avdr-phase

Brody seulement

/api/periphery/gencoin/avdr-phase

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/balance

Brody seulement

/api/periphery/gencoin/balance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/balance

Brody seulement

/api/periphery/gencoin/balance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/collective-summary

Brody seulement

/api/periphery/gencoin/collective-summary

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/consciousness-regime

Brody seulement

/api/periphery/gencoin/consciousness-regime

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/passfail

Brody seulement

/api/periphery/gencoin/passfail

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/regime-state

Brody seulement

/api/periphery/gencoin/regime-state

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/governance/

Brody seulement

/api/periphery/governance/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/agent-run

Brody seulement

/api/periphery/governance/agent-run

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/agent-spec-check

Brody seulement

/api/periphery/governance/agent-spec-check

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/agents

Brody seulement

/api/periphery/governance/agents

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/benchmarks

Brody seulement

/api/periphery/governance/benchmarks

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/failure-classify

Brody seulement

/api/periphery/governance/failure-classify

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/failure-codes

Brody seulement

/api/periphery/governance/failure-codes

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/lifecycle

Brody seulement

/api/periphery/governance/lifecycle

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/partition-gate

Brody seulement

/api/periphery/governance/partition-gate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/sequence-govern

Brody seulement

/api/periphery/governance/sequence-govern

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/governance/workflow-guard

Brody seulement

/api/periphery/governance/workflow-guard

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/graphiti/context-adapt

Brody seulement

/api/periphery/graphiti/context-adapt

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/graphiti/freeze-snapshot/

Brody seulement

/api/periphery/graphiti/freeze-snapshot/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/graphiti/freeze-snapshot/{snapshot_id}

Brody seulement

/api/periphery/graphiti/freeze-snapshot/{snapshot_id}

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/ingestion/classify-source

Brody seulement

/api/periphery/ingestion/classify-source

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/ingestion/document

Brody seulement

/api/periphery/ingestion/document

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/ingestion/hash

Brody seulement

/api/periphery/ingestion/hash

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/ingestion/memory-sources

Brody seulement

/api/periphery/ingestion/memory-sources

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/bias-gate

Brody seulement

/api/periphery/interface/bias-gate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/bias-trace

Brody seulement

/api/periphery/interface/bias-trace

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/log-event

Brody seulement

/api/periphery/interface/log-event

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/mcp-access

Brody seulement

/api/periphery/interface/mcp-access

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/state-packet

Brody seulement

/api/periphery/interface/state-packet

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/view-contracts

Brody seulement

/api/periphery/interface/view-contracts

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/interface/workbench-check

Brody seulement

/api/periphery/interface/workbench-check

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/operator/governed-runtime

Brody seulement

/api/periphery/operator/governed-runtime

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/operator/runtime-panel

Brody seulement

/api/periphery/operator/runtime-panel

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/operator/runtime-panel.html

Brody seulement

/api/periphery/operator/runtime-panel.html

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/os3/manifest

Brody seulement

/api/periphery/os3/manifest

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/os3/replay-compare

Brody seulement

/api/periphery/os3/replay-compare

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/os3/replay-run

Brody seulement

/api/periphery/os3/replay-run

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/os3/ticket

Brody seulement

/api/periphery/os3/ticket

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/os3/world-action-readiness

Brody seulement

/api/periphery/os3/world-action-readiness

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/constants

Brody seulement

/api/periphery/pipeline/constants

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/data-gate

Brody seulement

/api/periphery/pipeline/data-gate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/eml-compression

Brody seulement

/api/periphery/pipeline/eml-compression

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/energy-thermo

Brody seulement

/api/periphery/pipeline/energy-thermo

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/memory-governor

Brody seulement

/api/periphery/pipeline/memory-governor

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/merge

Brody seulement

/api/periphery/pipeline/merge

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/ocs-generation

Brody seulement

/api/periphery/pipeline/ocs-generation

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/operational-constance

Brody seulement

/api/periphery/pipeline/operational-constance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/permission-economic

Brody seulement

/api/periphery/pipeline/permission-economic

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/provenance-gate

Brody seulement

/api/periphery/pipeline/provenance-gate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/run

Brody seulement

/api/periphery/pipeline/run

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/pipeline/validate-candidate

Brody seulement

/api/periphery/pipeline/validate-candidate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/sigma/evaluate

Brody seulement

/api/periphery/sigma/evaluate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/workbench/runtime-connector

Brody seulement

/api/periphery/workbench/runtime-connector

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/periphery/workflow-governance/packet

Brody seulement

/api/periphery/workflow-governance/packet

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/query

Brody seulement

/api/query

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/readiness

Brody seulement

/api/readiness

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/runtime-wiring/os-trad/api/ir/candidate

Brody seulement

/api/runtime-wiring/os-trad/api/ir/candidate

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/runtime-wiring/os-trad/api/os-reverse/project

Brody seulement

/api/runtime-wiring/os-trad/api/os-reverse/project

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/runtime-wiring/os-trad/api/os-trad/translate

Brody seulement

/api/runtime-wiring/os-trad/api/os-trad/translate

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/runtime-wiring/source-runtime/status

Brody seulement

/api/runtime-wiring/source-runtime/status

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/bank

Brody seulement

/api/sigma/bank

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/bank

Brody seulement

/api/sigma/bank

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/domains

Brody seulement

/api/sigma/domains

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/domains

Brody seulement

/api/sigma/domains

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/ecom

Brody seulement

/api/sigma/ecom

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/evaluate

Brody seulement

/api/sigma/evaluate

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/gps-defense-aviation

Brody seulement

/api/sigma/gps-defense-aviation

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/gps-defense-aviation

Brody seulement

/api/sigma/gps-defense-aviation

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/trading

Brody seulement

/api/sigma/trading

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/sigma/trading

Brody seulement

/api/sigma/trading

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/status

Brody seulement

/api/status

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_brody_

Brody seulement

/api/test_brody_

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_brody_authority_escalation_no_act.py

Brody seulement

/api/test_brody_authority_escalation_no_act.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_brody_chat_readonly.py

Brody seulement

/api/test_brody_chat_readonly.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_f63_

Brody seulement

/api/test_f63_

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_f65_

Brody seulement

/api/test_f65_

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/test_f72_os_trad_ir_reverse_pipeline_audit.py

Brody seulement

/api/test_f72_os_trad_ir_reverse_pipeline_audit.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/test_no_memory_write_api.py

Brody seulement

/api/test_no_memory_write_api.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/translation/trace

Brody seulement

/api/translation/trace

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/worldcalls/gateway-status

Brody seulement

/api/worldcalls/gateway-status

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/cognitive/

Brody seulement

/api/x108/cognitive/

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/cognitive/dominant-trees

Brody seulement

/api/x108/cognitive/dominant-trees

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/cognitive/regime-classify

Brody seulement

/api/x108/cognitive/regime-classify

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/cognitive/shazam

Brody seulement

/api/x108/cognitive/shazam

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/math/lyapunov

Brody seulement

/api/x108/math/lyapunov

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/math/pog

Brody seulement

/api/x108/math/pog

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/math/trust-path

Brody seulement

/api/x108/math/trust-path

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/memory/candidates/append

Brody seulement

/api/x108/memory/candidates/append

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/memory/candidates/read

Brody seulement

/api/x108/memory/candidates/read

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/memory/logs/sealed

Brody seulement

/api/x108/memory/logs/sealed

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/memory/replay/coherence

Brody seulement

/api/x108/memory/replay/coherence

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/memory/replay/session

Brody seulement

/api/x108/memory/replay/session

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/oracle/freshness

Brody seulement

/api/x108/oracle/freshness

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/readonly-ingress

Brody seulement

/api/x108/readonly-ingress

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

/api/x108/timeverse/sync

Brody seulement

/api/x108/timeverse/sync

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

By reading the route handler implementations, F33/F36/F38 call safe_ba

Brody seulement

By reading the route handler implementations, F33/F36/F38 call safe_backend_response(result)

Core:NON V1:OK Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Brody seulement

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\obsidia_ir.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Brody seulement

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\obsidia_ir.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 7_GRAPHITI_READONLY_CONTEXT

CAPABILITY_ROUTER

Brody seulement

CAPABILITY_ROUTER

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

CAPABILITY_ROUTER_RESOLVED

Brody seulement

CAPABILITY_ROUTER_RESOLVED

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

CONNECTED_ROUTE_HANDLER

Brody seulement

CONNECTED_ROUTE_HANDLER

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

CONNECTORS_DO_NOT_RUN: aviation_robo.py, bank_normal_flow.py, trading_

Brody seulement

CONNECTORS_DO_NOT_RUN: aviation_robo.py, bank_normal_flow.py, trading_live.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

Check: are V1 Brody routes (F33/F36/F38) using _BOUNDARY or their modu

Brody seulement

Check: are V1 Brody routes (F33/F36/F38) using _BOUNDARY or their module BOUNDARY?

Core:NON V1:OK Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

OS_TRAD_ROUTE_CONTEXT

Brody seulement

OS_TRAD_ROUTE_CONTEXT

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

P36 — Global Capability Path Router.

Brody seulement

P36 — Global Capability Path Router.

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

P45_ROUTE_CAPABILITY_MAP

Brody seulement

P45_ROUTE_CAPABILITY_MAP

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

_BOUNDARY is used only by legacy pipeline/governance routes.

Brody seulement

_BOUNDARY is used only by legacy pipeline/governance routes.

Core:NON V1:OK Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

_ok(f"F1: CONFIRMED_LEGACY_ONLY — _BOUNDARY is truncated ({len(ops_key

Brody seulement

_ok(f"F1: CONFIRMED_LEGACY_ONLY — _BOUNDARY is truncated ({len(ops_keys)} flags vs {len(f32_keys)} in V1 modules), but V1 Brody routes (F33/F36/F38) use full module-level BOUNDARY. Only legacy pipeline/governance routes are affected.")

Core:NON V1:OK Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

_warn("F4: CONFIRMED_ARCHITECTURAL — base.update(data) merges correctl

Brody seulement

_warn("F4: CONFIRMED_ARCHITECTURAL — base.update(data) merges correctly for current V1 modules (all module dicts carry correct BOUNDARY). But merge direction is unsafe by design: a future module returning {allowed_to_decide: True} would propagate without resistance. V1 runtime not exploitable via current routes.")

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

alpha_beta_router.py

Brody seulement

alpha_beta_router.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/brody_domain_raccord_adapter.py

Brody seulement

apps/obsidia_api/brody_domain_raccord_adapter.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/brody_semantic_query_router.py

Brody seulement

apps/obsidia_api/brody_semantic_query_router.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/

Brody seulement

apps/obsidia_api/routes/

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/__init__.py

Brody seulement

apps/obsidia_api/routes/__init__.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/audit.py

Brody seulement

apps/obsidia_api/routes/audit.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/blockchain.py

Brody seulement

apps/obsidia_api/routes/blockchain.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/brody.py

Brody seulement

apps/obsidia_api/routes/brody.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/brody.py::brody_chat

Brody seulement

apps/obsidia_api/routes/brody.py::brody_chat

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/brody_monitoring.py

Brody seulement

apps/obsidia_api/routes/brody_monitoring.py

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/bus.py

Brody seulement

apps/obsidia_api/routes/bus.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/context.py

Brody seulement

apps/obsidia_api/routes/context.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/gencoin.py

Brody seulement

apps/obsidia_api/routes/gencoin.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

apps/obsidia_api/routes/graphiti.py

Brody seulement

apps/obsidia_api/routes/graphiti.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/memory.py

Brody seulement

apps/obsidia_api/routes/memory.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/os3.py

Brody seulement

apps/obsidia_api/routes/os3.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/os_map.py

Brody seulement

apps/obsidia_api/routes/os_map.py

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/os_map.py::os_map_query

Brody seulement

apps/obsidia_api/routes/os_map.py::os_map_query

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/os_map.py::os_map_status

Brody seulement

apps/obsidia_api/routes/os_map.py::os_map_status

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/os_trad_ir_reverse.py

Brody seulement

apps/obsidia_api/routes/os_trad_ir_reverse.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/periphery_ops.py

Brody seulement

apps/obsidia_api/routes/periphery_ops.py

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/runtime_freeze.py

Brody seulement

apps/obsidia_api/routes/runtime_freeze.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/runtime_wiring_preview.py

Brody seulement

apps/obsidia_api/routes/runtime_wiring_preview.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/sigma_monitoring.py

Brody seulement

apps/obsidia_api/routes/sigma_monitoring.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/source_runtime_status.py

Brody seulement

apps/obsidia_api/routes/source_runtime_status.py

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/status.py

Brody seulement

apps/obsidia_api/routes/status.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/translation.py

Brody seulement

apps/obsidia_api/routes/translation.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/worldcalls.py

Brody seulement

apps/obsidia_api/routes/worldcalls.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

apps/obsidia_api/routes/x108.py

Brody seulement

apps/obsidia_api/routes/x108.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

capability_path_router

Brody seulement

capability_path_router

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

docs/runtime/F34B_LIVE_UVICORN_ROUTE_PROOF_20260529_044331.json

Brody seulement

docs/runtime/F34B_LIVE_UVICORN_ROUTE_PROOF_20260529_044331.json

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

dry_run_packet_router

Brody seulement

dry_run_packet_router

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

from apps.obsidia_api.brody_balance_engine import BrodyBalanceEngine

Brody seulement

from apps.obsidia_api.brody_balance_engine import BrodyBalanceEngine

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

os-trad route

Brody seulement

os-trad route

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

os-trad route translate endpoint

Brody seulement

os-trad route translate endpoint

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

periphery_brody_language_route

Brody seulement

periphery_brody_language_route

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

periphery_double_brain_route

Brody seulement

periphery_double_brain_route

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

route_capability_map

Brody seulement

route_capability_map

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

route_count

Brody seulement

route_count

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

route_coverage_classifier

Brody seulement

route_coverage_classifier

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

route_entry_to_context_packet

Brody seulement

route_entry_to_context_packet

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

route_map

Brody seulement

route_map

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

routes_modified

Brody seulement

routes_modified

Core:NON V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/dry_run_packet_router.py

Brody seulement

runtime_wiring/dry_run_packet_router.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/source_runtime/capability_path_router.py Brody seulement

runtime_wiring/source_runtime/capability_path_router.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/source_runtime/capability_path_router.py::route_capabil Brody seulement

runtime_wiring/source_runtime/capability_path_router.py::route_capability_path

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/source_runtime/route_capability_map.py Brody seulement

runtime_wiring/source_runtime/route_capability_map.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/source_runtime/route_capability_map.py::build_route_cap Brody seulement

runtime_wiring/source_runtime/route_capability_map.py::build_route_capability_map

Core:OK V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

runtime_wiring/source_runtime/route_coverage_classifier.py Brody seulement

runtime_wiring/source_runtime/route_coverage_classifier.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

total_routes Brody seulement

total_routes

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

unclassified_routes

Brody seulement

unclassified_routes

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 2_BRODY_STABILIZATION

"MMONDE_REVERSE_OS_34ARBRES","MCP_BRIDGE_OBSIDIA_IR","periphery/OBSIDI

Non branche strict

"MMONDE_REVERSE_OS_34ARBRES","MCP_BRIDGE_OBSIDIA_IR","periphery/OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1/09_MCP_BRIDGE_OBSIDIA_IR/* ; specs/07_AGENTS_CONNECTORS_MCP/*","19","BRIDGE","MCP_IR","tool_gate","agents","SOURCE_CANON_CANDIDATE","REGROUP_CANON"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"evidence_location": "apps/obsidia_api/brody_cognitive_modules_adapter

Non branche strict

"evidence_location": "apps/obsidia_api/brody_cognitive_modules_adapter.py:29 covered_by=brody_true_voice_adapter.py; brody_semantic_query_router.py:149; brody_true_voice_adapter.py:739",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"notes": "Orchestrator module exists. Not imported by main.py or activ

Non branche strict

"notes": "Orchestrator module exists. Not imported by main.py or active routes.",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"operationId": "periphery_balance_api_periphery_gencoin_balance_post",

Non branche strict

"operationId": "periphery_balance_api_periphery_gencoin_balance_post",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

"path": ".\\apps\\obsidia_api\\brody_balance_engine.py",

Non branche strict

"path": ".\\apps\\obsidia_api\\brody_balance_engine.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"path": "C:\\Users\\User\\Desktop\\obsidia-engine-proof-core\\obsidia-

Non branche strict

"path": "C:\\Users\\User\\Desktop\\obsidia-engine-proof-core\\obsidia-engine-candidate\\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\\07_BDF_DOUBLE_CERVEAU\\alpha_beta_router.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"text": "- brody_double_brain: path=/api/periphery/brody/double-brain

Non branche strict

"text": "- brody_double_brain: path=/api/periphery/brody/double-brain-route status=OK code=200 length=386 preview={\"readonly\":true,\"advisory_only\":true,\"emits_act\":false,\"emits_verdict\":false,\"decision_authority\":\"KX108_ONLY\",\"memory_write\":false,\"kernel_mutation\":false,\"real_action\":false,\"source\":\"REAL_BACKEND\",\"timestamp\":\"2026-05-27T05:53:33.050391+00:00\",\"route_id\":\"phase9b0ter_bdf\",\"mode\":\"BALANCED\",\"syst"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

"text": "POST /api/periphery/gencoin/balance ok=True status=200 summa

Non branche strict

"text": "POST /api/periphery/gencoin/balance ok=True status=200 summary={\u0027decision_authority\u0027: \u0027KX108_ONLY\u0027, \u0027readonly\u0027: True, \u0027emits_act\u0027: False, \u0027source\u0027: \u0027REAL_BACKEND\u0027, \u0027status\u0027: \u0027orbite\u0027, \u0027total\u0027: None, \u0027count\u0027: None, \u0027reason\u0027: None, \u0027no_wallet\u0027: None, \u0027no_mint\u0027: None, \u0027is_real_token\u0027: None}"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- "GPS connector = DRY_RUN local — pas défense production"

Non branche strict

- "GPS connector = DRY_RUN local — pas défense production"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- "Le connector aviation POST en local (127.0.0.1) — DRY_RUN"

Non branche strict

- "Le connector aviation POST en local (127.0.0.1) — DRY_RUN"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- "X108 est évalué après SIGMA_ROUTED et avant OS3_TICKETED"

Non branche strict

- "X108 est évalué après SIGMA_ROUTED et avant OS3_TICKETED"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- "aviation connector = défense réelle"

Non branche strict

- "aviation connector = défense réelle"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **10 états** : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_S

Non branche strict

- **10 états** : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_SCORED → SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED → GENCOIN_EVALUATED → WORLD_ACTION_DRY_RUN_READY → FEEDBACK_CAPTURED → MEMORY_CANDIDATE_BUILT → CLOSED

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **BDF Double Cerveau** : `periphery/bdf/double_brain_router.py` — `e

Non branche strict

- **BDF Double Cerveau** : `periphery/bdf/double_brain_router.py` — `emits_act=False`, `emits_verdict=False`

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **Dry-run pipeline** : connecter GPS connector au pipeline X108 comp

Non branche strict

- **Dry-run pipeline** : connecter GPS connector au pipeline X108 complet

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **GPS / Aviation** : stack complet — adapter + connector + sigma dom

Non branche strict

- **GPS / Aviation** : stack complet — adapter + connector + sigma domain

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Genco

Non branche strict

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Gencoin Ledger/Debt/Distribution, Gencoin Sandbox, World Call Gateway, Math Core, Lyapunov, PoG, Language Router, Education Score, Bias Gate, Document Ingestion, Context Packet/X108 Ingress, MCP Permission Matrix, GitHub Workflow Guard, Benchmark, JSON Schemas, Integration Tests, Non-sovereignty Tests, Periphery Tests, Demo Connectors, Documentation, Validation 194 tests)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Genco

Non branche strict

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Gencoin Ledger/Debt/Distribution, Gencoin Sandbox, World Call Gateway, Math Core, Lyapunov, PoG, Language Router, Education Score, Bias Gate, Document Ingestion, Context Packet/X108 Ingress, MCP Permission Matrix, GitHub Workflow Guard, Benchmark, JSON Schemas, Integration Tests, Non-sovereignty Tests, Periphery Tests, Demo Connectors, Documentation, Validation 194 tests)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **current binding status**: EXISTS in periphery; NOT imported by aut

Non branche strict

- **current binding status**: EXISTS in periphery; NOT imported by automation_orchestrator or routes/brody.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **recommended action: Expose in /api/brody/chat payload if detaile**

Non branche strict

- **recommended action**: Expose in /api/brody/chat payload if detailed taxonomy needed

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- **recommended action: Verify if still imported in routes/brody.py;**

Non branche strict

- **recommended action**: Verify if still imported in routes/brody.py; if not, STALE

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- 10 états définis : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHE

Non branche strict

- 10 états définis : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_SCORED → SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED → GENCOIN_EVALUATED → WORLD_ACTION_DRY_RUN_READY → FEEDBACK_CAPTURED → MEMORY_CANDIDATE_BUILT → CLOSED

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- DoubleBrainRoute: emits_act=False, emits_verdict=False\n- Route Syst

Non branche strict

- DoubleBrainRoute: emits_act=False, emits_verdict=False\n- Route System1 vs System2

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- Education, bias, language_router — récepteurs prêts à être étendus

Non branche strict

- Education, bias, language_router — récepteurs prêts à être étendus

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED (ordre strict)

Non branche strict

- SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED (ordre strict)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- X108_EVALUATED est l'étape centrale — avant OS3_TICKETED et après SI

Non branche strict

- X108_EVALUATED est l'étape centrale — avant OS3_TICKETED et après SIGMA_ROUTED

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `connectors/aviation_robo.py` (DEFAULT_API_BASE = http://127.0.0.1:8

Non branche strict

- `connectors/aviation_robo.py` (DEFAULT_API_BASE = http://127.0.0.1:8000)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `connectors/aviation_robo.py` — RUNTIME_CODE

Non branche strict

- `connectors/aviation_robo.py` — RUNTIME_CODE

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `docs/periphery/GPS_ADAPTER_MAPPING_V0.md` — DOC_ONLY

Non branche strict

- `docs/periphery/GPS_ADAPTER_MAPPING_V0.md` — DOC_ONLY

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `language_router.py` → language_encoding_score

Non branche strict

- `language_router.py` → language_encoding_score

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `memory_write=False` dans BrodyLanguageRoute

Non branche strict

- `memory_write=False` dans BrodyLanguageRoute

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `patches/periphery_ops_world_atlas_routes_SNIPPET_NOT_APPLIED.py`

Non branche strict

- `patches/periphery_ops_world_atlas_routes_SNIPPET_NOT_APPLIED.py`

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `patches/periphery_ops_world_atlas_routes_SNIPPET_NOT_APPLIED.py` :

Non branche strict

- `patches/periphery_ops_world_atlas_routes_SNIPPET_NOT_APPLIED.py` : DO_NOT_IMPORT (SNIPPET_NOT_APPLIED)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `periphery/adapters/gps_adapter.py` — RUNTIME_CODE

Non branche strict

- `periphery/adapters/gps_adapter.py` — RUNTIME_CODE

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- `tests/api/test_brody_chat_readonly.py` (existant)

Non branche strict

- `tests/api/test_brody_chat_readonly.py` (existant)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- connectors/aviation_robo.py\n- periphery/adapters/gps_adapter.py

Non branche strict

- connectors/aviation_robo.py\n- periphery/adapters/gps_adapter.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- periphery/bdf/double_brain_router.py

Non branche strict

- periphery/bdf/double_brain_router.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

- periphery/language/language_router.py + apps/obsidia-workbench/OS_TR

Non branche strict

- periphery/language/language_router.py + apps/obsidia-workbench/OS_TRAD_REVERSE_IR_DISCOVERY_REPORT.md — IR candidate readonly

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

. J'ai repris le "Grimoire d'Exécution : Plan Commando P2+" présent da

Non branche strict

. J'ai repris le "Grimoire d'Exécution : Plan Commando P2+" présent dans vos sources 1, 2 et je l'ai massivement enrichi avec l'ensemble des protocoles, algorithmes (AVDR, Continuum, HexaFlux), architectures (23 Agents, 13 Domaines), et pipelines de Data Science (I/O, API) issus de vos documents 3-6.

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

/api/

Non branche strict

/api/

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

105376043786_CURRENT_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_LEAN_

Non branche strict

105376043786_CURRENT_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_LEAN_SKELETON_V1.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

3. Aucun agent, arbre, cortex, Shazam, Reverse OS, BDF, HexaFlux ou MC

Non branche strict

3. Aucun agent, arbre, cortex, Shazam, Reverse OS, BDF, HexaFlux ou MCP Bridge ne peut ouvrir un chemin `ACT`.

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

55513BA21298_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_LEAN_OBLIGATI

Non branche strict

55513BA21298_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_LEAN_OBLIGATIONS_V1.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

5DA4EEE4D184_CURRENT_ZIP1_SANDBOX_READONLY_MEMORY_READ_API_CLEAN.txt

Non branche strict

5DA4EEE4D184_CURRENT_ZIP1_SANDBOX_READONLY_MEMORY_READ_API_CLEAN.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

87F1572B5843_OBSIDIA_REVERSE_OS_AUDIENCE_ADAPTER_PROOF_OBLIGATIONS_V1.

Non branche strict

87F1572B5843_OBSIDIA_REVERSE_OS_AUDIENCE_ADAPTER_PROOF_OBLIGATIONS_V1.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

919906206304_CURRENT_OBSIDIA_CONTEXT_ACTIVATION_ROUTER_V1_1_REPAIR.txt

Non branche strict

919906206304_CURRENT_OBSIDIA_CONTEXT_ACTIVATION_ROUTER_V1_1_REPAIR.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

919906206304_CURRENT_OBSIDIA_CONTEXT_ACTIVATION_ROUTER_V1_1_REPAIR.txt

Non branche strict

919906206304_CURRENT_OBSIDIA_CONTEXT_ACTIVATION_ROUTER_V1_1_REPAIR.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

93D0169F13CE_ZIP1_SANDBOX_READONLY_MEMORY_READ_API_CLEAN_STATUS.txt — Non branche strict

93D0169F13CE_ZIP1_SANDBOX_READONLY_MEMORY_READ_API_CLEAN_STATUS.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

?? apps/obsidia_api/brody_balance_engine.py — Non branche strict

?? apps/obsidia_api/brody_balance_engine.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

A7A4BFCE2328_routers.getRecentTransactions.summary.txt — Non branche strict

A7A4BFCE2328_routers.getRecentTransactions.summary.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

A7A4BFCE2328_routers.getRecentTransactions.summary.txt — Non branche strict

A7A4BFCE2328_routers.getRecentTransactions.summary.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida — Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\07_BDF_DOUBLE_CERVEAU\alpha_beta_router.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\07_BDF_DOUBLE_CERVEAU\alpha_beta_router.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\07_BDF_DOUBLE_CERVEAU\alpha_beta_router.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\MCPBridge.schema.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\MCPBridge.schema.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\ObsidiaIR.schema.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\ObsidiaIR.schema.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\README.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\README.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\mcp_bridge.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\mcp_bridge.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\policy_scope_guard.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\09_MCP_BRIDGE_OBSIDIA_IR\policy_scope_guard.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\10_AGENTS_52\01_CODE_REPO_CI\FORMAL_BRIDGE.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candida

Non branche strict

C:\Users\User\Desktop\obsidia-engine-proof-core\obsidia-engine-candidate\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1_FREEZE_CANDIDATE\OBSIDIA_MMONDE_REVERSE_OS_34ARBRES_AGENTS_P2PLUS_V1\17_TESTS\test_mcp_bridge.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 7_GRAPHITI_READONLY_CONTEXT

CCAE37FB92E1_CURRENT_AUDIT_BRODY_CONNECTOR_SOURCE_SCAN_BEFORE_WORLD_IN

Non branche strict

CCAE37FB92E1_CURRENT_AUDIT_BRODY_CONNECTOR_SOURCE_SCAN_BEFORE_WORLD_INTAKE.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

Ceci est la feuille de route exhaustive, le "Blueprint de Déploiement"

Non branche strict

Ceci est la feuille de route exhaustive, le "Blueprint de Déploiement", pour coder et mettre en service l'AGI Obsidia X-108.

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

D173BEA2115A_route.md

Non branche strict

D173BEA2115A_route.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

DBB21AC6214C_context_activation_router_config_v1.json

Non branche strict

DBB21AC6214C_context_activation_router_config_v1.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

DBB21AC6214C_context_activation_router_config_v1.json

Non branche strict

DBB21AC6214C_context_activation_router_config_v1.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

DC1415DA98A0_BRIDGE_SERVER_BANK_DIAG_20260428_135743.txt

Non branche strict

DC1415DA98A0_BRIDGE_SERVER_BANK_DIAG_20260428_135743.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

DomainAdapterPeriphery,bank,local_audit,.local_audits\BRODY_COGNITIVE_

Non branche strict

DomainAdapterPeriphery,bank,local_audit,.local_audits\BRODY_COGNITIVE_ACCELERATION_KERNEL_PATCH_PLAN_V3_20260613_130000\V3_balance_engine_matrix.json,94,"""couche_à_éviter"": [""domain_layer:bank"", ""domain_layer:trading"", ""graphiti_topk_layer""],"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

DomainAdapterPeriphery,trading,local_audit,.local_audits\BRODY_COGNITI

Non branche strict

DomainAdapterPeriphery,trading,local_audit,.local_audits\BRODY_COGNITIVE_ACCELERATION_KERNEL_PATCH_PLAN_V3_20260613_130000\V3_balance_engine_matrix.json,94,"""couche_à_éviter"": [""domain_layer:bank"", ""domain_layer:trading"", ""graphiti_topk_layer""],"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

Graphiti proxy API routes (/api/graphiti/*) — readonly only

Non branche strict

Graphiti proxy API routes (/api/graphiti/*) — readonly only

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

Memory API routes (/api/memory/*) — candidate_only, no auto-promotion

Non branche strict

Memory API routes (/api/memory/*) — candidate_only, no auto-promotion

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

Une fois le sens traduit, le Reverse OS route cette information vers l

Non branche strict

Une fois le sens traduit, le Reverse OS route cette information vers le canal adéquat : du texte, de l'audio (synthèse vocale), ou une interface visuelle (UI) 4, 9. Pour les 34 Arbres, par exemple, il ne calcule pas leur état ; il lit leurs coordonnées vectorielles et applique une "Réduction Cognitive Active" pour n'allumer visuellement que les 3 à 5 arbres dominants, évitant ainsi le chaos visuel 10, 11.

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

apps/obsidia_api/runtime_loader.py,API_RUNTIME,runtime_loader.py,Dynam

Non branche strict

apps/obsidia_api/runtime_loader.py,API_RUNTIME,runtime_loader.py,Dynamic module loader,API,runtime,RUNTIME_ACTIVE,routes/brody.py,no,no,no,no,no,no,false,false,false,false,load_runtime_components()

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

periphery_balance_api_periphery_gencoin_balance_post

Non branche strict

periphery_balance_api_periphery_gencoin_balance_post

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

route

Non branche strict

route

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

router

Non branche strict

router

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

routes

Non branche strict

routes

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

| /api/periphery/gencoin/balance | post |

Non branche strict

| /api/periphery/gencoin/balance | post |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| Language encoding | Tree10 + language_router | `ARBRE_10__Arbre_du_L

Non branche strict

| Language encoding | Tree10 + language_router | `ARBRE_10__Arbre_du_Langage/` + `periphery/language/language_router.py` | DOC_ONLY + RUNTIME_CODE | authority_claim_detected → BLOCK |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

| Language encoding | Tree10 Langage + `language_router.py` | `.../ARB

Non branche strict

| Language encoding | Tree10 Langage + `language_router.py` | `.../ARBRE_10__Arbre_du_Langage/` + `periphery/language/language_router.py` | DOC_ONLY + RUNTIME_CODE |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

| `specs/npl/CULTURAL_MATRIX_SPEC.md` | `periphery/OBSIDIA_MMONDE.../A

Non branche strict

| `specs/npl/CULTURAL_MATRIX_SPEC.md` | `periphery/OBSIDIA_MMONDE.../ARBRE_19__Arbre_de_la_Culture/activation_rules.md`, `periphery/language/language_router.py` | OUI | SPEC_CANDIDATE | `cultural_matrix_density ∈ [0,1]`; `language_encoding_score ∈ [0,1]`; non_decision_contract respecté (Tree34 ↛ ACT) | jamais hiérarchiser cultures; jamais "culture X est supérieure"; jamais verdict culturel | test_cultural_matrix_no_verdict | Tree19 = récepteur déjà présent |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

→ adapters/gps_adapter.py, sigma/domains/gps_defense_aviation_agents.p

Non branche strict

→ adapters/gps_adapter.py, sigma/domains/gps_defense_aviation_agents.py, connectors/aviation_robo.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

→ apps/obsidia_api/routes/periphery_ops.py

Non branche strict

→ apps/obsidia_api/routes/periphery_ops.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

→ language_router.py: détection fr/en, authority markers détectés et b

Non branche strict

→ language_router.py: détection fr/en, authority markers détectés et bloqués

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

→ periphery/cognitive_trees/shazam_cognitif.py, bdf/double_brain_route

Non branche strict

→ periphery/cognitive_trees/shazam_cognitif.py, bdf/double_brain_router.py, hexaflux/ltcu_plus.py, mcp_bridge.py, jarvis_projection.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 10_RESEARCH_SANDBOX_LATER

brody_domain_raccord_adapter

OK Brody + domaine

brody_domain_raccord_adapter

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 9_DOWNLOAD_GATED

brody_semantic_query_router

OK Brody + domaine

brody_semantic_query_router

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:OK Trd:OK GPS:OK

DEJA OK domaine - conserver, tester, receipt/kernel seulement. Phase: 9_DOWNLOAD_GATED

"/api/periphery/gencoin/balance": {

Partiel runtime

"/api/periphery/gencoin/balance": {

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"/api/periphery/gencoin/balance": {

Partiel runtime

"/api/periphery/gencoin/balance": {

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"module": "apps/obsidia_api/routes/memory.py",

Partiel runtime

"module": "apps/obsidia_api/routes/memory.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/brody_domain_raccord_adapter.py",

Partiel runtime

"module_path": "apps/obsidia_api/brody_domain_raccord_adapter.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/brody_semantic_query_router.py",

Partiel runtime

"module_path": "apps/obsidia_api/brody_semantic_query_router.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/__init__.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/__init__.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/audit.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/audit.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/blockchain.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/blockchain.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/brody.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/brody.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/brody_monitoring.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/brody_monitoring.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/bus.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/bus.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/context.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/context.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/gencoin.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/gencoin.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"module_path": "apps/obsidia_api/routes/graphiti.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/graphiti.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/memory.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/memory.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/os3.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/os3.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/os_map.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/os_map.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/os_trad_ir_reverse.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/os_trad_ir_reverse.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/periphery_ops.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/periphery_ops.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/runtime_freeze.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/runtime_freeze.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/runtime_wiring_preview.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/runtime_wiring_preview.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/sigma_monitoring.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/sigma_monitoring.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/source_runtime_status.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/source_runtime_status.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/status.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/status.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/translation.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/translation.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/worldcalls.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/worldcalls.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "apps/obsidia_api/routes/x108.py", Partiel runtime

"module_path": "apps/obsidia_api/routes/x108.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "runtime_wiring/dry_run_packet_router.py",

Partiel runtime

"module_path": "runtime_wiring/dry_run_packet_router.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "runtime_wiring/source_runtime/capability_path_router.p

Partiel runtime

"module_path": "runtime_wiring/source_runtime/capability_path_router.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "runtime_wiring/source_runtime/route_capability_map.py"

Partiel runtime

"module_path": "runtime_wiring/source_runtime/route_capability_map.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"module_path": "runtime_wiring/source_runtime/route_coverage_classifie

Partiel runtime

"module_path": "runtime_wiring/source_runtime/route_coverage_classifier.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

"path": "/api/periphery/gencoin/balance",

Partiel runtime

"path": "/api/periphery/gencoin/balance",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"path": "/api/periphery/gencoin/balance",

Partiel runtime

"path": "/api/periphery/gencoin/balance",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"reason": "Memory routes operational, REAL_MODULE confirmed"

Partiel runtime

"reason": "Memory routes operational, REAL_MODULE confirmed"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

- Port 8000 : UP fraîche HEAD 84cc0d0 — /api/runtime-wiring/preview →

Partiel runtime

- Port 8000 : UP fraîche HEAD 84cc0d0 — /api/runtime-wiring/preview → 200 ✓

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

- Port 8012 : UP fraîche HEAD 84cc0d0 — /api/runtime-wiring/preview →

Partiel runtime

- Port 8012 : UP fraîche HEAD 84cc0d0 — /api/runtime-wiring/preview → 200 ✓

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/bank

Partiel runtime

/api/adapters/bank

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/bank

Partiel runtime

/api/adapters/bank

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/gps

Partiel runtime

/api/adapters/gps

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/gps

Partiel runtime

/api/adapters/gps

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/trading

Partiel runtime

/api/adapters/trading

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/adapters/trading

Partiel runtime

/api/adapters/trading

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/brody-cli-registry

Partiel runtime

/api/brody-cli-registry

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/brody-historical-convergence

Partiel runtime

/api/brody-historical-convergence

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/brody-trace-analyze

Partiel runtime

/api/brody-trace-analyze

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/bus/bus/bridge

Partiel runtime

/api/bus/bus/bridge

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/bus/bus/stats

Partiel runtime

/api/bus/bus/stats

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/hexaflux/ltcu-plus

Partiel runtime

/api/hexaflux/ltcu-plus

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/hexaflux/transition-map

Partiel runtime

/api/hexaflux/transition-map

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/memory/* (6 routes)

Partiel runtime

/api/memory/* (6 routes)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/os3/* (7 routes)

Partiel runtime

/api/os3/* (7 routes)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/periphery/governance/* (10 routes)

Partiel runtime

/api/periphery/governance/* (10 routes)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

/api/x108/* (14 routes)

Partiel runtime

/api/x108/* (14 routes)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

147 routes 100% classified; os-map/status and os-map/query emit no ACT

Partiel runtime

147 routes 100% classified; os-map/status and os-map/query emit no ACT

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Add MEMORY_CANDIDATE capability for /api/memory/* routes

Partiel runtime

Add MEMORY_CANDIDATE capability for /api/memory/* routes

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Add OS3_AUDIT capability for /api/os3/* routes

Partiel runtime

Add OS3_AUDIT capability for /api/os3/* routes

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Add X108_COGNITIVE capability for /api/x108/cognitive/* routes

Partiel runtime

Add X108_COGNITIVE capability for /api/x108/cognitive/* routes

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Bind brody_semantic_query_router to SEMANTIC_ROUTING capability

Partiel runtime

Bind brody_semantic_query_router to SEMANTIC_ROUTING capability

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Brody chat + context bridge fully classified P47/P48; all routes CONNE

Partiel runtime

Brody chat + context bridge fully classified P47/P48; all routes CONNECTED_READONLY

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Capability path router (P36/P37, readonly routing)

Partiel runtime

Capability path router (P36/P37, readonly routing)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Dispatcher: routes SourceFileRegistryEntry to correct adapter via _ADA

Partiel runtime

Dispatcher: routes SourceFileRegistryEntry to correct adapter via _ADAPTER_DISPATCH table. Never reads zip content. Raises ValueError on FORBIDDEN entries.

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

KEY_CAPABILITY_MODULE = "runtime_wiring/source_runtime/capability_path

Partiel runtime

KEY_CAPABILITY_MODULE = "runtime_wiring/source_runtime/capability_path_router.py"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Memory routes operational, REAL_MODULE confirmed

Partiel runtime

Memory routes operational, REAL_MODULE confirmed

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

OS_MAP_MODULE = "apps/obsidia_api/routes/os_map.py"

Partiel runtime

OS_MAP_MODULE = "apps/obsidia_api/routes/os_map.py"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

P45_FULL_ROUTE_COVERAGE_MAP

Partiel runtime

P45_FULL_ROUTE_COVERAGE_MAP

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Route status / readiness / metrics endpoints

Partiel runtime

Route status / readiness / metrics endpoints

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Routes already wired to graphiti_v20_readonly_client

Partiel runtime

Routes already wired to graphiti_v20_readonly_client

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Routes classified CONNECTED_READONLY allow dry-run invocation for test

Partiel runtime

Routes classified CONNECTED_READONLY allow dry-run invocation for testing

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

STATUS_ONLY (21) + CONNECTED_READONLY (101) routes: no ACT pathway — Partiel runtime

STATUS_ONLY (21) + CONNECTED_READONLY (101) routes: no ACT pathway

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

Simulation / preview routes (dry path evaluation) — Partiel runtime

Simulation / preview routes (dry path evaluation)

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

assert classify_module(m) == "CONNECTED_ROUTE_HANDLER" — Partiel runtime

assert classify_module(m) == "CONNECTED_ROUTE_HANDLER"

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

brody_chat_route — Partiel runtime

brody_chat_route

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

capability_path_router_readonly — Partiel runtime

capability_path_router_readonly

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

def test_capability_path_router_module_classification(coverage_map): — Partiel runtime

def test_capability_path_router_module_classification(coverage_map):

Core:NON | V1:NON | Enr:NON | K:NON | G:NON | Bnk:NON | Trd:NON | GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

def test_os_map_module_is_route_handler(coverage_map):

Partiel runtime

def test_os_map_module_is_route_handler(coverage_map):

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

f"{OS_MAP_MODULE} must be CONNECTED_ROUTE_HANDLER, got '{status}'"

Partiel runtime

f"{OS_MAP_MODULE} must be CONNECTED_ROUTE_HANDLER, got '{status}'"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

m = {"module_path": "apps/obsidia_api/routes/blockchain.py", "risk_fla

Partiel runtime

m = {"module_path": "apps/obsidia_api/routes/blockchain.py", "risk_flags": []}

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

m = {"module_path": "apps/obsidia_api/routes/os_map.py", "risk_flags":

Partiel runtime

m = {"module_path": "apps/obsidia_api/routes/os_map.py", "risk_flags": []}

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

m = {"module_path": "runtime_wiring/source_runtime/capability_path_rou

Partiel runtime

m = {"module_path": "runtime_wiring/source_runtime/capability_path_router.py", "risk_flags": []}

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

route_capability_path + link_capabilities_to_inventory: no side effect

Partiel runtime

route_capability_path + link_capabilities_to_inventory: no side effects

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

route_status_endpoints

Partiel runtime

route_status_endpoints

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

router_templates

Partiel runtime

router_templates

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

router_templates_total

Partiel runtime

router_templates_total

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

routes_in_templates

Partiel runtime

routes_in_templates

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

routes_total

Partiel runtime

routes_total

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

simulation_routes

Partiel runtime

simulation_routes

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

still_unconnected_routes_count — Partiel runtime

still_unconnected_routes_count

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

still_unconnected_routes_notable — Partiel runtime

still_unconnected_routes_notable

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

— Test 10 : os_map.py est CONNECTED_ROUTE_HANDLER ———————— — Partiel runtime

— Test 10 : os_map.py est CONNECTED_ROUTE_HANDLER ————————————

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

— Test 11 : route handlers P45 sont classés ———————————— — Partiel runtime

— Test 11 : route handlers P45 sont classés ————————————————

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

— Test 8 : capability_path_router est CONNECTED_CAPABILITY ———— — Partiel runtime

— Test 8 : capability_path_router est CONNECTED_CAPABILITY ————————

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

— Test 9 : route_capability_path est CONNECTED_CAPABILITY ———— — Partiel runtime

— Test 9 : route_capability_path est CONNECTED_CAPABILITY ————————

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 10_RESEARCH_SANDBOX_LATER

DO_NOT_CONNECT / sandbox / hold - 83 lignes

*** **Description :** Gencoin, la balance universelle, la calibration én**

Brody seulement

* **Description :** Gencoin, la balance universelle, la calibration énergétique.

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/avdr-phase')` ? `periphery_avdr_phase`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/balance')` ? `periphery_balance`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/balance')` ? `periphery_balance`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/collective-summary')` ? `periphery_collective_summary`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/consciousness-regime')` ? `periphery_consciousness_regime`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/passfail')` ? `periphery_passfail`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/

Brody seulement

- `apps/obsidia_api/routes/periphery_ops.py` ? `router.post('/gencoin/regime-state')` ? `periphery_regime_state`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

- `periphery/gencoin_sandbox/balance_operator.py`

Brody seulement

- `periphery/gencoin_sandbox/balance_operator.py`

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/blockchain/gencoin/compute

Brody seulement

/api/blockchain/gencoin/compute

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/gencoin

Brody seulement

/api/gencoin

Core:OK V1:OK Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 8_UI_COCKPIT_RSSI

/api/periphery/gencoin/avdr-phase

Brody seulement

/api/periphery/gencoin/avdr-phase

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/balance

Brody seulement

/api/periphery/gencoin/balance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/balance

Brody seulement

/api/periphery/gencoin/balance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/collective-summary

Brody seulement

/api/periphery/gencoin/collective-summary

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/consciousness-regime

Brody seulement

/api/periphery/gencoin/consciousness-regime

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody: ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/passfail

Brody seulement

/api/periphery/gencoin/passfail

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/periphery/gencoin/regime-state

Brody seulement

/api/periphery/gencoin/regime-state

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/test_f72_os_trad_ir_reverse_pipeline_audit.py

Brody seulement

/api/test_f72_os_trad_ir_reverse_pipeline_audit.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

/api/x108/timeverse/sync

Brody seulement

/api/x108/timeverse/sync

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

apps/obsidia_api/routes/gencoin.py

Brody seulement

apps/obsidia_api/routes/gencoin.py

Core:OK V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

from periphery.gencoin_sandbox.balance_operator import compute_balance

Brody seulement

from periphery.gencoin_sandbox.balance_operator import compute_balance

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

periphery/gencoin_sandbox/balance_operator.py

Brody seulement

periphery/gencoin_sandbox/balance_operator.py

Core:NON V1:NON Enr:OK K:NON G:NON Bnk:NON Trd:NON GPS:NON

Garder couche Brody; ne pas brancher domaine sans gate/decision. Phase: 11_DO_NOT_CONNECT_HOLD

"COGNITIVE", "EXTERNAL_SIGNALS", "BALANCE", "GENCOIN",

Non branche strict

"COGNITIVE", "EXTERNAL_SIGNALS", "BALANCE", "GENCOIN",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

"operationId": "periphery_balance_api_periphery_gencoin_balance_post",

Non branche strict

"operationId": "periphery_balance_api_periphery_gencoin_balance_post",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

"specs\05_BALANCE_BUV_GEOMETRIES\HIGH_GEOMETRIES_CANONICAL_INDEX.md","

Non branche strict

"specs\05_BALANCE_BUV_GEOMETRIES\HIGH_GEOMETRIES_CANONICAL_INDEX.md","740","75219340F70962C4154B3D9BF52314D025BE32A262D626DB703BA2B72FC8E1A2"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

"text": "POST /api/periphery/gencoin/balance ok=True status=200 summa

Non branche strict

"text": "POST /api/periphery/gencoin/balance ok=True status=200 summary={\u0027decision_authority\u0027: \u0027KX108_ONLY\u0027, \u0027readonly\u0027: True, \u0027emits_act\u0027: False, \u0027source\u0027: \u0027REAL_BACKEND\u0027, \u0027status\u0027: \u0027orbite\u0027, \u0027total\u0027: None, \u0027count\u0027: None, \u0027reason\u0027: None, \u0027no_wallet\u0027: None, \u0027no_mint\u0027: None, \u0027is_real_token\u0027: None}"

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

6. Grep Gencoin / Jcoin / BUV / Balance

Non branche strict

6. Grep Gencoin / Jcoin / BUV / Balance

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **10 états : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_S**

Non branche strict

- **10 états** : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_SCORED → SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED → GENCOIN_EVALUATED → WORLD_ACTION_DRY_RUN_READY → FEEDBACK_CAPTURED → MEMORY_CANDIDATE_BUILT → CLOSED

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **Source alternative : `docs/gencoin/sandbox_pre_freeze/BALANCE_CA**

Non branche strict

- **Source alternative** : `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md`, `periphery/gencoin_sandbox/balance_operator.py`

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **Statut : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Genco**

Non branche strict

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Gencoin Ledger/Debt/Distribution, Gencoin Sandbox, World Call Gateway, Math Core, Lyapunov, PoG, Language Router, Education Score, Bias Gate, Document Ingestion, Context Packet/X108 Ingress, MCP Permission Matrix, GitHub Workflow Guard, Benchmark, JSON Schemas, Integration Tests, Non-sovereignty Tests, Periphery Tests, Demo Connectors, Documentation, Validation 194 tests)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- **Statut : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Genco**

Non branche strict

- **Statut** : 22 domaines COMPLETE (Agent Registry, OS3 Replay, Gencoin Ledger/Debt/Distribution, Gencoin Sandbox, World Call Gateway, Math Core, Lyapunov, PoG, Language Router, Education Score, Bias Gate, Document Ingestion, Context Packet/X108 Ingress, MCP Permission Matrix, GitHub Workflow Guard, Benchmark, JSON Schemas, Integration Tests, Non-sovereignty Tests, Periphery Tests, Demo Connectors, Documentation, Validation 194 tests)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- 10 états définis : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHE

Non branche strict

- 10 états définis : INPUT_CAPTURED → ACTION_CANDIDATE_BUILT → PERIPHERY_SCORED → SIGMA_ROUTED → X108_EVALUATED → OS3_TICKETED → GENCOIN_EVALUATED → WORLD_ACTION_DRY_RUN_READY → FEEDBACK_CAPTURED → MEMORY_CANDIDATE_BUILT → CLOSED

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- 22 domaines COMPLETE : Agent Registry (14 agents), OS3 Replay, Genco

Non branche strict

- 22 domaines COMPLETE : Agent Registry (14 agents), OS3 Replay, Gencoin Ledger/Debt/Distribution, Gencoin Sandbox, World Call Gateway (12 modules), Math Core / Lyapunov / PoG, Language Router, Education Score, Bias Gate, Document Ingestion, Context Packet / X108 Ingress, MCP Permission Matrix, GitHub Workflow Guard, Benchmark Case Schema, JSON Schemas (3), Integration Tests (V3+V4), Non-sovereignty Tests, Periphery Tests, Demo Connectors, Documentation, Validation (194 tests pass), Zip Artifact

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- SANDBOX — `balance_operator.py` est dans `gencoin_sandbox/`

Non branche strict

- SANDBOX — `balance_operator.py` est dans `gencoin_sandbox/`

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- Tout agent, LLM, Brody, Graphiti, Tree34, NPL, Balance, Gencoin, GPS

Non branche strict

- Tout agent, LLM, Brody, Graphiti, Tree34, NPL, Balance, Gencoin, GPS ne décide

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- Tout agent, LLM, Brody, Graphiti, Tree34, NPL, Balance, Gencoin, GPS

Non branche strict

- Tout agent, LLM, Brody, Graphiti, Tree34, NPL, Balance, Gencoin, GPS ne décide

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md` — Non branche strict

- `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md`

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md` — DOC_ONLY — Non branche strict

- `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md` — DOC_ONLY

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- `periphery/gencoin_sandbox/balance_operator.py` — RUNTIME_CODE + SAN — Non branche strict

- `periphery/gencoin_sandbox/balance_operator.py` — RUNTIME_CODE + SANDBOX

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md — Non branche strict

- docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- periphery/gencoin_sandbox/balance_operator.py — Non branche strict

- periphery/gencoin_sandbox/balance_operator.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- periphery/gencoin_sandbox/balance_operator.py\n- periphery/gencoin_s — Non branche strict

- periphery/gencoin_sandbox/balance_operator.py\n- periphery/gencoin_sandbox/regime_truth_gate.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

- periphery/gencoin_sandbox/balance_operator.py\n- periphery/x108_ingr

Non branche strict

- periphery/gencoin_sandbox/balance_operator.py\n- periphery/x108_ingress/readonly_context_ingress.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

.local_audits/CIC_METRICS_V0_VERIFY_AND_TEST_20260613_020125/zip_extra

Non branche strict

.local_audits/CIC_METRICS_V0_VERIFY_AND_TEST_20260613_020125/zip_extracted/docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

.local_exports/CIC_PACK_STAGE_20260613_015520/docs/gencoin/sandbox_pre

Non branche strict

.local_exports/CIC_PACK_STAGE_20260613_015520/docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

5D31F72C8871_activation_rules.md

Non branche strict

5D31F72C8871_activation_rules.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

6. Grep Gencoin / Jcoin / BUV / Balance

Non branche strict

6. Grep Gencoin / Jcoin / BUV / Balance

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

717F72699F46_response_trading.json — Non branche strict

717F72699F46_response_trading.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

86F73F080BAC_bank_payload.json — Non branche strict

86F73F080BAC_bank_payload.json

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

9D1F69D233EE_metrics_full_bank.csv — Non branche strict

9D1F69D233EE_metrics_full_bank.csv

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

A docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md — Non branche strict

A docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

A periphery/gencoin_sandbox/balance_operator.py — Non branche strict

A periphery/gencoin_sandbox/balance_operator.py

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

CA613D29EF3A_CURRENT_OBSIDIA_LLMOBSIDIEN_LOCAL_CHAT_STACK_CANDIDATE_RE — Non branche strict

CA613D29EF3A_CURRENT_OBSIDIA_LLMOBSIDIEN_LOCAL_CHAT_STACK_CANDIDATE_READONLY_V0_CLOSE.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON
Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

CB30216D2321_OBSIDIA_LLMOBSIDIEN_PROVIDER_ADAPTER_STUB_READONLY_V0_SMO

Non branche strict

CB30216D2321_OBSIDIA_LLMOBSIDIEN_PROVIDER_ADAPTER_STUB_READONLY_V0_SMOKE_OBLIGATIONS.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

D163F708AD84_ARTIFACT_HASH_MANIFEST.csv

Non branche strict

D163F708AD84_ARTIFACT_HASH_MANIFEST.csv

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

E891CCAD237B_CURRENT_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_BOUND

Non branche strict

E891CCAD237B_CURRENT_OBSIDIA_REVERSE_OS_READONLY_RUNTIME_ADAPTER_BOUNDARY_BINDING_V1.txt

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

F701EB8E5069_Obsidia - Souverainete Cognitive et Protocole MCP.docx

Non branche strict

F701EB8E5069_Obsidia - Souverainete Cognitive et Protocole MCP.docx

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Non branche strict

docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

grep -rl "Gencoin|Jcoin|BUV|Balance|mint_allowed|gencoin_candidate|gro

Non branche strict

grep -rl "Gencoin|Jcoin|BUV|Balance|mint_allowed|gencoin_candidate|gross_value|net_value" periphery/ sigma/

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

periphery_balance_api_periphery_gencoin_balance_post

Non branche strict

periphery_balance_api_periphery_gencoin_balance_post

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| "prototype fonctionnel actif" (BUV balance_operator.py) | Prototype

Non branche strict

| "prototype fonctionnel actif" (BUV balance_operator.py) | Prototype sandbox uniquement | Non branché production | periphery/gencoin_sandbox/ |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| **Balance/BUV | Balance pèse, Balance ↛ ALLOW/HOLD/BLOCK | `periph**

Non branche strict

| **Balance/BUV** | Balance pèse, Balance ↛ ALLOW/HOLD/BLOCK | `periphery/gencoin_sandbox/balance_operator.py` | PYTHON_SPEC | FORMAL_PROOF_PENDING |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| /api/periphery/gencoin/balance | post |

Non branche strict

| /api/periphery/gencoin/balance | post |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| BALANCE_SOURCE.md | periphery/gencoin_sandbox/balance_operator.py +

Non branche strict

| BALANCE_SOURCE.md | periphery/gencoin_sandbox/balance_operator.py + BALANCE_CANON.md |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| Balance / BUV | `balance_operator.py`, `BALANCE_CANON.md` | REMOTE_A

Non branche strict

| Balance / BUV | `balance_operator.py`, `BALANCE_CANON.md` | REMOTE_A5F21C6B | `periphery/gencoin_sandbox/balance_operator.py`, `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md` | RUNTIME_CODE + DOC_ONLY | RUNTIME_CODE | `specs/BALANCE_BUV_MASTER_SPEC_V1.md` | P1 | BUV est l'alias conceptuel — la source réelle est BALANCE_CANON.md |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| Balance operator / BUV | `periphery/gencoin_sandbox/balance_operator

Non branche strict

| Balance operator / BUV | `periphery/gencoin_sandbox/balance_operator.py` | Prototype Python | Spec formelle, Lean proof | PARTIAL — sandbox uniquement | MOYEN — ne pas clamer "opérationnel" |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| Balance | `periphery/gencoin_sandbox/balance_operator.py` | RUNTIME_

Non branche strict

| Balance | `periphery/gencoin_sandbox/balance_operator.py` | RUNTIME_CODE (sandbox) | "Score balance sandbox" | "Balance décide / BUV = token" |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| Balance | periphery/gencoin_sandbox/balance_operator.py, docs/gencoi

Non branche strict

| Balance | periphery/gencoin_sandbox/balance_operator.py, docs/gencoin/sandbox_pre_freeze/ |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `BALANCE_BUV_MASTER_SPEC_V1.md` | `periphery/gencoin_sandbox/balance

Non branche strict

| `BALANCE_BUV_MASTER_SPEC_V1.md` | `periphery/gencoin_sandbox/balance_operator.py`, `docs/gencoin/sandbox_pre_freeze/BALANCE_CANON.md`, `docs/gencoin/sandbox_pre_freeze/LIMITS_AND_STATUS.md` | RUNTIME_CODE + DOC_ONLY | Sandbox uniquement — ne pas exposer balance_operator en production sans gate | Tests balance dans sandbox | Python test uniquement | "Balance Obsidienne" ≠ décision finale — résultat d'une évaluation multi-facteur |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `BUV` | `BALANCE_CANON.md` + `balance_operator.py` | `docs/gencoin/s

Non branche strict

| `BUV` | `BALANCE_CANON.md` + `balance_operator.py` | `docs/gencoin/sandbox_pre_freeze/`, `periphery/gencoin_sandbox/` | BUV = concept audio/Gemini — terme réel = Balance Obsidienne |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `BUV` | `balance_operator.py`, `BALANCE_CANON.md` | `periphery/genco

Non branche strict

| `BUV` | `balance_operator.py`, `BALANCE_CANON.md` | `periphery/gencoin_sandbox/`, `docs/gencoin/sandbox_pre_freeze/` | SOURCE_FOUND_UNDER_DIFFERENT_NAME |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `module_type` | enum | — | `KERNEL`, `SIGMA`, `GRAPHITI`, `BRODY`, `

Non branche strict

| `module_type` | enum | — | `KERNEL`, `SIGMA`, `GRAPHITI`, `BRODY`, `NPL`, `ATLAS`, `COGNITIVE`, `EXTERNAL_SIGNALS`, `BALANCE`, `GENCOIN`, `GPS`, `AGENT`, `LLM`, `UNKNOWN` |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `periphery/gencoin_sandbox/balance_operator.py` | DO_NOT_PROMOTE_TO_

Non branche strict

| `periphery/gencoin_sandbox/balance_operator.py` | DO_NOT_PROMOTE_TO_RUNTIME | Sandbox uniquement |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

| `specs/npl/CULTURAL_MATRIX_SPEC.md` | `periphery/OBSIDIA_MMONDE.../A

Non branche strict

| `specs/npl/CULTURAL_MATRIX_SPEC.md` | `periphery/OBSIDIA_MMONDE.../ARBRE_19__Arbre_de_la_Culture/activation_rules.md`, `periphery/language/language_router.py` | OUI | SPEC_CANDIDATE | `cultural_matrix_density ∈ [0,1]`; `language_encoding_score ∈ [0,1]`; non_decision_contract respecté (Tree34 ↛ ACT) | jamais hiérarchiser cultures; jamais "culture X est supérieure"; jamais verdict culturel | test_cultural_matrix_no_verdict | Tree19 = récepteur déjà présent |

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

├──→ No ACT Sigma / Brody / Tree34 / Agents / Balance / Gencoin / GPS

Non branche strict

├──→ No ACT Sigma / Brody / Tree34 / Agents / Balance / Gencoin / GPS

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

├──→ No ACT Sigma / Brody / Tree34 / Agents / Balance / Gencoin / GPS

Non branche strict

├──→ No ACT Sigma / Brody / Tree34 / Agents / Balance / Gencoin / GPS

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Non branche: ne pas connecter maintenant; garder sandbox/source-gap. Phase: 11_DO_NOT_CONNECT_HOLD

"/api/periphery/gencoin/balance": {

Partiel runtime

"/api/periphery/gencoin/balance": {

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"/api/periphery/gencoin/balance": {

Partiel runtime

"/api/periphery/gencoin/balance": {

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"module_path": "apps/obsidia_api/routes/gencoin.py",

Partiel runtime

"module_path": "apps/obsidia_api/routes/gencoin.py",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"path": "/api/periphery/gencoin/balance",

Partiel runtime

"path": "/api/periphery/gencoin/balance",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

"path": "/api/periphery/gencoin/balance",

Partiel runtime

"path": "/api/periphery/gencoin/balance",

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD

NPL context packet (readonly)

Partiel runtime

NPL context packet (readonly)

Core:NON V1:NON Enr:NON K:NON G:NON Bnk:NON Trd:NON GPS:NON

Partiel: creer gates/registry/runtime puis re-scan. Phase: 11_DO_NOT_CONNECT_HOLD