



Draw It or Lose It — Web Application
CS 230 Project Software Design Template
Version 1.1

Table of Contents

CS 230 Project Software Design Template	1
Table of Contents	2
Document Revision History	2
Executive Summary	3
Requirements	3
Design Constraints	4
System Architecture View	4
Domain Model	4
Evaluation	6
Recommendations	12

Document Revision History

Version	Date	Author	Comments
1.0	09/23/2025	Ebony Anderson	Initial draft for The Gaming Room
1.1	09/29/2025	Ebony Anderson	Added security architecture (HTTPS, OAuth2/OIDC, short-lived JWTs, CSRF/CORS), secrets management, dependency/container scans, WAF/rate-limiting, encryption at rest, SIEM logging; plus Requirements, System Architecture View, and Evaluation/Recommendations. No change to functional scope.

Executive Summary

In one line: Turn *Draw It or Lose It* from Android-only into a browser game that many people can play at once—fair, fast, and foolproof on names.

Problem (plain): We need a web version that handles multiple teams/players, enforces unique names, runs timed rounds, and stays perfectly in sync.

Solution (simple):

- A single in-memory **Singleton** service acts like the referee (one source of truth).
- Every Game/Team/Player gets a **unique ID**; **iterator checks** block duplicate names.
- Expose **REST endpoints** for create/join/name-check.
- Start **in memory** for speed; later swap in PostgreSQL and WebSockets with minimal changes.

Why this works: Quick demo now, fewer race conditions (one referee), and a clean domain model that's easy to scale (add PostgreSQL/Redis and real-time events later).

What we need from you:

1. Approve Phase 1 scope.
2. Provide concurrency/security targets and hosting preference.
3. Approve Phase 2 roadmap (DB + WebSockets).
4. Confirm stakeholders and a single point of contact for approvals.

Assumptions/Risks: Phase 1 resets on restart; names are case-insensitive; rich real-time polish arrives in Phase 2.

Phase 1 Done when: One active game, multi-team/multi-player, name-availability endpoint blocks duplicates, unique IDs assigned, 60s rounds (30s image complete + 15s steal window) scaffolded, clean code ready for persistence/real-time.

Requirements

Business Requirements

- Reach players on desktop (Windows, macOS, Linux) and mobile (iOS, Android) **without native installs**.
- Support **thousands of concurrent players** per region with smooth one-minute rounds and real-time updates.
- Target **≥99.9% availability** and low latency for guess/timer events.
- Keep **TCO low** via cloud hosting and open tooling where feasible.
- **Protect user data** with least privilege and data minimization.
- Provide **analytics** (sessions, rounds, guesses, retention).
- Ensure **accessibility** (keyboard navigation, screen reader support, color contrast).

Technical Requirements

- **Responsive HTML5/JS** client working across Chrome, Edge, Firefox, Safari (desktop & mobile).
- **WebSockets** for real-time (SSE/polling fallback).
- **Stateless** app servers; **Redis** for ephemeral state; **PostgreSQL** for durable data; **Object storage + CDN** for drawings.
- **Security by default:** HTTPS, OAuth2/OIDC, short-lived tokens, CSRF/CORS controls.
- **Observability:** logs, metrics, traces, alerts; audit trail for key actions.
- **CI/CD** with automated tests, code scanning, blue-green/rolling deploys.
- **DR/Backups:** nightly backups + point-in-time restore; documented RPO/RTO.
- **Scalability:** horizontal app scaling; CDN for static assets/images.

Design Constraints

- Web & concurrency: Many users act at once; server methods that change state are synchronized to prevent race conditions.
- Single authority: Singleton GameService maintains one authoritative in-memory game instance (no split-brain states).
- Name uniqueness: Before creating games/teams, the service iterates existing lists to block duplicates (case-insensitive).
- Security (baseline): Validate inputs (reject malformed IDs/names), sanitize strings; plan for TLS (HTTPS) and authentication/authorization in Phase 2. This prevents misuse early without slowing the Phase-1 demo.
- Portability: Java 17, standard libraries—runs consistently on Windows/Mac/Linux; no platform-specific dependencies in Phase 1.
- Timing guarantees: Server is the source of truth for 60-second rounds, 30-second full-reveal, and 15-second steal window.
- Future growth: Clean domain layer so persistence (PostgreSQL), caching (Redis), and WebSockets can be added without redesign.

System Architecture View

- **Clients:** Desktop browsers (Windows/macOS/Linux) and mobile browsers (iOS/Android).
- **Edge:** **CDN + WAF** for asset caching, TLS, and basic abuse filtering.
- **Ingress/LB:** Routes HTTPS to app pods; keep sessions stateless.
- **Application Tier:** Containerized **Java 17** service (Dropwizard/Spring Boot) with multiple replicas.
- **Data/Cache:** **PostgreSQL** (durable), **Redis** (ephemeral round state, rate limits, leaderboards).
- **Object Storage:** Drawings/media served via **CDN**; signed URLs if restricted.
- **Real-Time:** **WebSockets** over the same ingress for timers/guess events (fallback to SSE/polling).
- **Ops:** Centralized logs/metrics/traces, dashboards, alerting, CI/CD.

Logical topology:

Browser/Device ⇌ CDN/WAF ⇌ Ingress/LB ⇌ App Pods ⇌ (Redis | PostgreSQL | Object Storage)

Domain Model

What you're looking at (plain English):

- **Entity** is the template all others share: everything has an **id** and a **name**.
- **Game, Team, Player** all **extend Entity** (inherit id+name).
- A **Game owns Teams** (List<Team>). A **Team owns Players** (List<Player>). That's composition: if the parent goes away, its children do too.
- **GameService** is the single "referee." It holds a List<Game> and the methods to **add/get games/teams/players**.
- **ProgramDriver** just runs main() to exercise the service. **SingletonTester** calls getInstance() to prove only one GameService exists.

How the classes relate:

- **Inheritance:** Game → Entity, Team → Entity, Player → Entity. Reuses common id/name.
- **Composition/Aggregation:** Game 1 — 0...* Team, Team 1 — 0...* Player.

- **Dependency:** ProgramDriver and SingletonTester **depend on** GameService (UML «uses» association); no direct access to internals.

OOP principles shown (and why they help):


- **Abstraction:** Entity captures the shared identity (keeps code DRY).
- **Inheritance:** Children reuse id/name logic (less duplication).
- **Encapsulation:** Collections are private; you add via methods that **enforce rules** (e.g., no duplicate names).
- **Polymorphism:** Common base (Entity) allows uniform handling/logging later.
- **Design patterns:**
 - **Singleton:** GameService.getInstance() → exactly **one** service controls state, avoiding conflicting “referees.”
 - **Iterator:** addGame/getGame, addTeam, addPlayer **scan lists** to find existing names and **prevent duplicates**.

How this fulfills the requirements:

- **One or more teams per game:** Game keeps a list of Team; addTeam() creates or returns the existing one.
- **Multiple players per team:** Team keeps a list of Player; addPlayer() creates or returns the existing one.
- **Unique game & team names:** Iterator checks in addGame/addTeam **block duplicates** (case-insensitive in code).
- **Single instance in memory:** **Singleton GameService** is the only manager; it can also enforce “only one active Game” rule.
- **Unique identifiers:** All entities get an **id** via Entity (and service-side counters).

Efficiency note (why this is fine now):

- **Efficiency note:** Iterating lists is simple and clear for a small demo. If the roster grows, **swap lists for HashMap/HashSet to get ~O(1) lookups**—no redesign needed because the service hides the storage detail.



Evaluation

Development Requirements	Mac	Linux	Windows	Mobile Devices
Server Side	Simple analogy: A beautiful venue but not designed for touring arenas. Key ideas: Can host (Unix base) but uncommon in production; Apple hardware requirement raises cost. Step-by-step: Use only for dev/test; production should target Linux unless there's a hard Mac-only need. Checks: N/A for prod; ensure local parity via Docker. Troubleshooting: Homebrew service configs, file permissions, and SIP constraints when running daemons. macOS: No server SKU, but must run on Apple hardware (primary cost).	Simple analogy: Linux is the cheapest, most configurable concert venue—every touring guide knows it. Key ideas: First-class for web servers, containers, and autoscaling; lowest TCO; massive community playbooks. Step-by-step: Use Ubuntu LTS → package app in Docker → run behind Nginx/ALB → scale with Kubernetes or VM autoscaling → Redis for fast game state, Postgres for durable data. Checks: Linear scale when adding pods; error rate <1%; p95 guess submit <150 ms; CPU/mem stable under load. Troubleshooting: Tune file descriptors, keep images small, use liveness/readiness probes, roll back via blue-green. Linux: OS free; optional paid support (e.g., RHEL/SUSE).	Simple analogy: A venue with great security turnstiles (AD) but higher rent. Key ideas: Excellent for IIS/.NET; can run Java/Node; licensing cost is the trade-off. Step-by-step: If AD integration or Windows-only dependencies exist, host on Windows Server/IIS; otherwise prefer Linux for cost. Checks: Throughput parity with Linux for Java/Node; auth works with AD; patch cadence tracked. Troubleshooting: Monitor antivirus impact, file-path limits, and service accounts; consider WSL2 for build pipelines. Windows Server: Requires Windows Server license (+ possible CALs)	Simple analogy: A seat, not a venue—don't host here. Key ideas: Battery/NAT/security make phones unsuitable as servers. Step-by-step: Keep all hosting in cloud; mobiles only connect to the game APIs over HTTPS. Checks: N/A. Mobile (iOS/Android): Clients only; not used for hosting.

Client Side	Simple analogy: Seats with Safari/Chrome/Firefox; Safari has a few house rules. Key ideas: Web standards mostly uniform; watch Safari media/autoplay, WebRTC, and PWA quirks. Cost/Time: One codebase (TS/React) reduces build cost; budget for cross-browser/device QA and cloud device farm hours. Expertise: Front-end performance & a11y, mobile web gestures, WebSockets, and test automation (Playwright). Step-by-step: Test in Safari Tech Preview; validate keyboard nav, fullscreen, audio cues; confirm WebSocket stability. Checks: Feature tests pass in Safari 17+; Lighthouse ≥90; text crisp on Retina. Troubleshooting: Use feature detection (not UA); polyfill where needed; provide click-to-play for audio.	Simple analogy: Audience seats with Chrome/Firefox—same show as other desktops. Key ideas: Standards-based HTML5 works out of the box; minimal Linux-specific quirks. Step-by-step: Build responsive TS/React → test on Chrome/Firefox with HiDPI and input methods → verify fonts. Checks: Lighthouse ≥90, keyboard + screen-reader paths pass, animations smooth at 60 fps. Troubleshooting: Font fallback, Wayland display scaling, GPU acceleration flags if stutter appears.	Simple analogy: Seats with Edge/Chrome/Firefox and some 2-in-1s. Key ideas: Touch + mouse + pen; corporate policies can block features. Cost/Time: One codebase (TS/React) reduces build cost; budget for cross-browser/device QA and cloud device farm hours. Expertise: Front-end performance & a11y, mobile web gestures, WebSockets, and test automation (Playwright). Step-by-step: Test pointer/touch events, HiDPI scaling, clipboard/file dialogs; verify WebSocket through enterprise proxies. Checks: Works on Edge latest + Chrome; accessibility shortcuts (Tab/Shift+Tab) OK. Troubleshooting: Group Policy blocking Service Workers/WebSoc	Simple analogy: Standing-room crowd—great energy, unpredictable network. Key ideas: One responsive web app; touch targets ≥44px; Service Worker for caching; WebSockets for real-time. Cost/Time: One codebase (TS/React) reduces build cost; budget for cross-browser/device QA and cloud device farm hours. Expertise: Front-end performance & a11y, mobile web gestures, WebSockets, and test automation (Playwright). Step-by-step: Design mobile-first; optimize bundles; prefetch next-round assets; handle resume after backgrounding; test on iOS Safari (WebKit) and Android Chrome. Checks: p75 Time-to-Interactive <3s on mid-tier Android; reconnect after loss <2s; a11y gestures pass. Troubleshooting: iOS background throttling—resync state on focus; captive portals—detect offline and queue actions; fall back to polling if WebSockets blocked.
---------------------------	---	--	---	---

	Test Matrix: Edge (LTS), Chrome (current & -1), Firefox (current), Safari (current & Tech Preview); iOS (current & -1), Android (API 30+), orientations (portrait/landscape), touch + keyboard.		kets; provide polling fallback and clear error copy. Test Matrix: Edge (LTS), Chrome (current & -1), Firefox (current), Safari (current & Tech Preview); iOS (current & -1), Android (API 30+), orientations (portrait/landscape), touch + keyboard.	Test Matrix: Edge (LTS), Chrome (current & -1), Firefox (current), Safari (current & Tech Preview); iOS (current & -1), Android (API 30+), orientations (portrait/landscape), touch + keyboard.
--	--	--	--	--

Development Tools	Simple analogy: The studio favored by many front-end devs. Key ideas: Great local DX; required for iOS on-device debugging. Step-by-step: Xcode (for iOS Web Inspector), VS Code/IntelliJ, Node LTS, Docker Desktop, Homebrew for deps. Checks: iOS device remote debugging works; builds reproducible in CI. Troubleshooting: Fix file-watch limits (fs.inotify analogs), ensure ARM64 images for Apple Silicon. Tool licensing: Editors/IDEs: VS Code (free); IntelliJ IDEA (optional paid). Platforms/SDKs: Xcode (free), Android Studio (free). Containers: Docker Desktop (free for personal/edu; check business terms). Device testing: BrowserStack/Device Farm (subscription).	Simple analogy: The backstage with every tool on a rolling cart. Key ideas: Free/open stack; best CI/CD runner host. Step-by-step: VS Code/IntelliJ, OpenJDK 17, Node LTS, Docker/Podman, kubectl; wire to GitHub Actions or GitLab CI. Checks: Reproducible builds in CI; unit/integration tests pass headless. Troubleshooting: Permissions (chmod/UID) in containers; pin Node/JDK versions to avoid “works on my machine.” Tool licensing: Editors/IDEs: VS Code (free); IntelliJ IDEA (optional paid). Platforms/SDKs: Xcode (free), Android Studio (free). Containers: Docker Desktop (free for personal/edu; check business terms). Device testing: BrowserStack/Dev	Simple analogy: Big workbench plus a Linux drawer (WSL2). Key ideas: VS Code/IntelliJ run great; WSL2 gives Linux toolchains; Docker Desktop available. Step-by-step: Install JDK 17, Node LTS, WSL2 Ubuntu, Docker Desktop; use Edge DevTools for browser debugging. Checks: Same build scripts succeed in WSL2 and CI; containers start locally. Troubleshooting: File-watcher limits on Windows; CRLF vs LF line endings—enforce via .gitattributes. Tool licensing: Editors/IDEs: VS Code (free); IntelliJ IDEA (optional paid). Platforms/SDKs: Xcode (free), Android Studio (free). Containers: Docker Desktop (free for personal/edu; check business terms). Device testing: BrowserStack/Device Farm (subscription).	Simple analogy: Road crew for devices. Key ideas: Free tooling; main cost is device coverage or cloud device farms. Step-by-step: Android Studio (ADB), Safari Remote Web Inspector (requires Mac), Chrome DevTools remote; add BrowserStack/Device Farm for matrix coverage. Checks: Test plan spans iOS current-1 and Android 10+; no blocker defects by device or orientation. Troubleshooting: USB driver issues (Windows↔Android), iOS provisioning for on-device inspect, flaky Wi-Fi during debug. Tool licensing: Editors/IDEs: VS Code (free); IntelliJ IDEA (optional paid). Platforms/SDKs: Xcode (free), Android Studio (free). Containers: Docker Desktop (free for personal/edu; check business terms). Device testing: BrowserStack/Device Farm (subscription).
--------------------------	---	--	---	---

		ice Farm (subscription).		
--	--	-----------------------------	--	--

Recommendations

Analyze the characteristics of and techniques specific to various systems architectures and make a recommendation to The Gaming Room. Specifically, address the following:

1. **Operating Platform:** Use **Linux (Ubuntu LTS)** for production hosting due to cost, maturity, and container ecosystem. Keep **Windows Server** only if Active Directory or .NET dependencies demand it. Develop on any OS; **ship to Linux**.
2. **Operating Systems Architectures:** Adopt a **three-tier, stateless** web architecture: **CDN/WAF** at the edge → **horizontally scaled app pods** behind an ingress/LB → **managed PostgreSQL + Redis + object storage**. Use containers and an orchestrator or autoscaling VMs.
3. **Storage Management:** **PostgreSQL** for durable entities (users, games, rounds, guesses) with migrations (Flyway/Liquibase). **Redis** for ephemeral game state, leaderboards, and rate limits. **Object storage + CDN** for drawings. Enable nightly backups, **PITR**, and encryption at rest.
4. **Memory Management:** Keep servers **stateless**; store per-round state in **Redis** to limit JVM heap pressure. Tune **Java 17 (G1GC)**, size heap/metaspaces per pod, and use **HikariCP**. Autoscale on **CPU and latency**.
5. **Distributed Systems and Networks:** Expose a single **HTTPS** entry via ingress. Use **idempotent APIs**, retries with **exponential backoff**, health checks, and circuit breakers. Prefer **WebSockets** for real-time; gracefully fall back if blocked. On reconnect, **resync game state**.
6. **Security:** **HTTPS everywhere**, **OAuth2/OIDC**, short-lived **JWTs**, secure/HttpOnly cookies, **CSRF** and strict **CORS**. Manage secrets in a **vault**; run dependency/container scans; **WAF/rate limiting** at the edge. Encrypt data at rest; restrict object-store buckets; **minimize PII in logs** and route alerts to a **SIEM**.