

VISHNU D1.0 - General specifications

COLLABORATORS

	<i>TITLE :</i> VISHNU D1.0 - General specifications		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Benjamin Isnard, Daouda Traoré, Eugène Pamba Capo-Chichi, Kevin Coulomb, and Ibrahima Cissé	December 24, 2010	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
01	07/12/2010	Formatting example	B.Isnard
02	13/12/2010	Pre-delivrable	B.Isnard

Contents

1	Document presentation	1
1.1	Document objectives	1
1.2	Document structure	1
1.3	References	1
1.4	Glossary	1
2	Use cases for User Management System (UMS)	2
2.1	Use case descriptions	2
2.1.1	U1 - Session with manual closure	2
2.1.2	U1.1 - Open session	2
2.1.3	U1.2 - Close session	3
2.1.4	U1.3 - Execute synchronous user request	4
2.1.5	U1.3.1 - Configure Option	4
2.1.6	U1.3.2 - Display options	4
2.1.7	U1.3.3 - Change password	5
2.1.8	U1.3.4 - Display session command history	5
2.1.9	U1.3.5 - Display sessions log	5
2.1.10	U1.4 - Execute asynchronous user request	6
2.1.11	U1.5 - Reconnect to session	6
2.1.12	U2 - Session with automatic closure on timeout	7
2.1.13	U2.1 - Close session auto	7
2.1.14	U3 - Session with automatic closure on disconnect	8
2.1.15	U4 - Create new local user config	8
2.1.16	U4.1 - Update local user config	9
2.1.17	U4.2 - Delete local user config	9
2.1.18	U4.3 - Display local user configs	9
2.1.19	UA1 - Create new user account	10
2.1.20	UA1.1 - Update user account	10
2.1.21	UA1.2 - Delete user account	10
2.1.22	UA2 - Reset user password	11

2.1.23	UA3 - Save configuration	11
2.1.24	UA4 - Restore configuration	11
2.1.25	UA5.1 - Display sessions	12
2.1.26	UA5.2 - Display users	12
2.1.27	UA5.3 - Display local users configs	13
2.1.28	UA6.1 Add a machine	13
2.1.29	UA6.2 Remove a machine	13
2.1.30	UA6.3 Display machines	14
2.2	Use case diagrams	14
2.2.1	UC UMS Admin	14
2.2.2	UC UMS Admin Machines	14
2.2.3	UC UMS User Auto	15
2.2.4	UC UMS User Manual	16
2.2.5	UC UMS User account	16
2.3	Data dictionary	17
3	Use cases for Tasks Management System (TMS)	18
3.1	Use case descriptions	18
3.1.1	T1 - AsyncCommandOnMachine	18
3.1.2	T1.1 - SubmitJob	18
3.1.3	T1.2 - AsynGetJobOutPut	19
3.1.4	T2 - SyncCommandOnMachine	19
3.1.5	T2.1 - GetJob	20
3.1.6	T2.2 - CancelJob	21
3.1.7	T2.3 - ListQueue	21
3.1.8	T2.4 - ListJobs	21
3.1.9	T2.5 - JobProgress	22
3.1.10	T2.6 - GetJobOutPut	22
3.1.11	TA1 - SetMachineRefreshPeriod	22
3.1.12	TA2 - SetMachineEnv	23
3.1.13	TA3 - LaunchTmsServer	23
3.2	Use case diagrams	24
3.2.1	UC TMS Overview	24
3.3	Data dictionary	24

4	Use cases for Information Management System (IMS)	25
4.1	Use case descriptions	25
4.1.1	I1. Get the update frequency	25
4.1.2	I2 Get metric data	25
4.1.3	I3. Export and replay commands	26
4.1.4	I4. Get data on the infrastructure	26
4.1.5	IA1. Get the running processes	27
4.1.6	IA10. Update machine description	27
4.1.7	IA2. Define a system load treshold	28
4.1.8	IA2.1 Get a system load treshold	28
4.1.9	IA3. Define the identifiers	28
4.1.10	IA4. Hard delestage	29
4.1.11	IA5. Soft delestage	29
4.1.12	IA6. Set the update frequency	30
4.1.13	IA7. Notification of limit overflow	30
4.1.14	IA8. Restart the System	30
4.1.15	IA9. Automatic restart	31
4.1.16	U1.3 Execute synchronous request	31
4.2	Use case diagrams	32
4.2.1	Consult	32
4.2.2	Fonctionnalités Global	33
4.2.3	PlatformManagement	34
4.2.4	Replay	34
4.2.5	Stop_Restart	35
4.3	Data dictionary	35
5	Use cases for File Management System (FMS)	36
5.1	Use case descriptions	36
5.1.1	Execute a synchronous tranfer file	36
5.1.2	Execute an asynchronous copy of files	36
5.1.3	Execute an asynchronous tranfer file	36
5.1.4	F1- Execute simple command on one remote machine	37
5.1.5	F1.1- Change acces modes of files	37
5.1.6	F1.10- Display tail of files	38
5.1.7	F1.2- Change group owner of files	38
5.1.8	F1.3- Create new directories	39
5.1.9	F1.4- Create new files	39
5.1.10	F1.5- Delete directories	39
5.1.11	F1.6- Delete files	40

5.1.12	F1.7- Display contents of directories	40
5.1.13	F1.8- Display contents of files	41
5.1.14	F1.9- Display Head of files	41
5.1.15	F2- Transfer a file between two remote hosts	42
5.1.16	F2.1- Execute a synchronous copy of files	42
5.1.17	F2.1.1- Execute a synchronous move of files	43
5.1.18	F2.2- Execute an asynchronous copy of files	43
5.1.19	F2.2.1- Execute an asynchronous move of files	44
5.1.20	F2.3- Suspend a file tranfer	44
5.1.21	F2.3.1- Suspend all files transfer	44
5.1.22	F2.4- List files transfer status	44
5.1.23	F2.4.1- List all files transfer status	45
5.1.24	F2.5- Display the file transfer history list	45
5.1.25	F2.5.1-Display all file transfer history list	45
5.1.26	F2.6- re-submit a suspended file transfer	45
5.1.27	F2.6.1- re-submit all suspended file transfer	45
5.2	Use case diagrams	46
5.2.1	Change acces modes of files	46
5.2.2	Create new directories	46
5.2.3	Create new files	46
5.2.4	Delete directories	46
5.2.5	Delete files	46
5.2.6	Display Head of files	46
5.2.7	Display contents of directories	47
5.2.8	Display contents of files	47
5.2.9	Display tail of files	47
5.2.10	Execute a synchronous copy of files	47
5.2.11	Execute a synchronous tranfer file	47
5.2.12	Execute an asynchronous copy of files	47
5.2.13	Execute an asynchronous tranfer file	47
5.2.14	Execute command on one machine	48
5.2.15	FMS Transfert command use cases	48
5.2.16	FMS simple command use cases	48
5.2.17	Transfer a file between two machines	48
5.2.18	UseCase Diagram	48
5.3	Data dictionary	48

List of Figures

2.1	UC UMS Admin	14
2.2	UC UMS Admin Machines	14
2.3	UC UMS User Auto	15
2.4	UC UMS User Manual	16
2.5	UC UMS User account	16
3.1	UC TMS Overview	24
4.1	Consult	32
4.2	Fonctionnalités Global	33
4.3	PlatformManagement	34
4.4	Replay	34
4.5	Stop_Restart	35
5.1	Change acces modes of files	46
5.2	Create new directories	46
5.3	Create new files	46
5.4	Delete directories	46
5.5	Delete files	46
5.6	Display Head of files	46
5.7	Display contents of directories	47
5.8	Display contents of files	47
5.9	Display tail of files	47
5.10	Execute a synchronous copy of files	47
5.11	Execute a synchronous tranfer file	47
5.12	Execute an asynchronous copy of files	47
5.13	Execute an asynchronous tranfer file	47
5.14	Execute command on one machine	48
5.15	FMS Transfert command use cases	48
5.16	FMS simple command use cases	48
5.17	Transfer a file between two machines	48
5.18	UseCase Diagram	48

Chapter 1

Document presentation

1.1 Document objectives

This document presents the external specifications of the Vishnu system at a general level. At this level, we describe the interaction of a user with the system without providing implementation details. The different steps that constitute the scenario are detailed as well as the content of the messages exchanged. The main objective is to describe the system from the user point of view.

These general specifications are a prerequisite for the detailed specifications step in the software development process.

1.2 Document structure

The document is divided into 4 parts corresponding to the 4 modules that compose the Vishnu system:

- UMS: Users Management System
- TMS: Tasks Management System
- FMS: Files Management System
- IMS: Information Management System

Each module corresponds to a chapter in the document, and each chapter contains two sections:

- A first section containing "Use case descriptions" that follow the standard UML description of a use case
- A second section containing the "Use case diagrams" that describe the organization of the different use cases. These diagrams follow the UML2.0 standard.

1.3 References

1.4 Glossary

Chapter 2

Use cases for User Management System (UMS)

2.1 Use case descriptions

2.1.1 U1 - Session with manual closure

Title	U1 - Session with manual closure
Summary	The user opens a new session and closes it manually by using the API command for closure
Actors	User
Precondition	<ul style="list-style-type: none"> - The user is authenticated - VISHNU is installed and running on the client System
Postcondition	<ul style="list-style-type: none"> - The session state is closed - A session log has been created - All user requests submitted within the session are completed
Base sequence	<ol style="list-style-type: none"> 1. Include::U1.1 Open session 2. System is ready to process user commands 3. Include::U1.2 Close session (before the maximum inactivity delay if option CLOSE_POLICY is equal to CLOSE_ON_TIMEOUT)
Branch sequence	<ol style="list-style-type: none"> 2a. U1.3 Execute synchronous user request 2b. U1.4 Execute asynchronous user request 2c. U1.5 Reconnect to session
Exception sequence	<ol style="list-style-type: none"> 1a. Include::U1.1 exceptions 3a. If session cannot be closed due to running commands, user must wait until all commands are completed before trying step 3 again
Extensions	<ul style="list-style-type: none"> U1.3 - Execute synchronous user request U1.5 - Reconnect to session U1.4 - Execute asynchronous user request

2.1.2 U1.1 - Open session

Title	U1.1 - Open session
Summary	The user opens a session
Actors	User
Precondition	<ul style="list-style-type: none"> - The user is connected on a client System in which VISHNU is installed and that can be connected to the VISHNU infrastructure

Postcondition	<ul style="list-style-type: none"> - A session is active - The user's environment contains a session certificate
Base sequence	<ol style="list-style-type: none"> 1. User provides login, password and optionnally the way of closing the session automatically on disconnect or on timeout to the "connect" command (when the default option is not set the the SESSION_CLOSE_POLICY is CLOSE ON TIMEOUT) 2. System validates login, password (User is authenticated) and optionnally, the name of the closing mode (CLOSE_ON_DISCONNECT or CLOSE ON TIMEOUT) if the SESSION_CLOSE_POLICY is set. 3. System creates the session and activates it 4. System provides the session certificate to the user
Branch sequence	<ol style="list-style-type: none"> 2a. If the password is a temporary password (after reset by the administrator) the System asks the user to enter a new password, then asks for a confirmation, and registers the new password if both steps are ok. If non-interactive request then this is an exception (a change password request is required).
Exception sequence	<ol style="list-style-type: none"> 2a. The user login is unknown 2a1. The System returns an error message 2b. The user password is invalid 2b1. The System returns an error message 2c. The SESSION_CLOSE_POLICY option is unknown 2c1. The System returns an error message 2d. VISHNU infrastructure is unreachable or unavailable 2d1. The System returns an error message 2e. The user password is temporary and request is non-interactive: the System returns an error message

2.1.3 U1.2 - Close session

Title	U1.2 - Close session
Summary	The user closes the session manually
Actors	User
Precondition	<ul style="list-style-type: none"> - The user is connected on the client System - The user has an open session on the client System
Postcondition	<ul style="list-style-type: none"> - The session is closed - A session log has been created - All user requests submitted during the session are completed
Base sequence	<ol style="list-style-type: none"> 1. The user sends a request to close a session by giving the session identifier 2. The System checks that the session identifier is valid and the corresponding session is open 3. The System checks that there are no running commands within the session 4. The System closes the session 5. The System informs the user that the session has been closed
Branch sequence	

Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable 2a. The session identifier is invalid 2b. The session is already closed 2c. The session identifier is incompatible with the authenticated user (that means that the session identifier is not for the user who sends the requests). 2a. If there are running commands within the session, the System informs the user that the session can not be closed
--------------------	--

2.1.4 U1.3 - Execute synchronous user request

Title	U1.3 - Execute synchronous user request
Summary	The user submits a synchronous request to the System
Actors	User
Precondition	- A session (for the current user and client host) is active
Postcondition	- The request is completed - A request log is created
Base sequence	1. The user sends the request to the System 2. The System returns the results to the user
Branch sequence	
Exception sequence	1.a Invalid session (bad session certificate or unavailable session) 1.b Invalid request 1.c Permission denied (admin request issued by normal user) 1.d Ressource not available 1.e VISHNU System crashed
Extension of	U1 - Session with manual closure U3 - Session with automatic closure on disconnect U2 - Session with automatic closure on timeout

2.1.5 U1.3.1 - Configure Option

Title	U1.3.1 - Configure Option
Summary	The user wants to modify the value of an option attached to his/her VISHNU account
Actors	User
Precondition	
Postcondition	
Base sequence	1. The user sends a request for modifying the value of an option to the System 2. System registers the new value for the option 3. System returns an acknowledgment to the user
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable 2a. Invalid option name 2b. Invalid option value

2.1.6 U1.3.2 - Display options

Title	U1.3.2 - Display options
Summary	The user displays all options concerning his/her VISHNU account

Actors	User
Precondition	
Postcondition	
Base sequence	1. The user sends a request to list all his/her options 2. The System returns all options of the user
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.1.7 U1.3.3 - Change password

Title	U1.3.3 - Change password
Summary	The user wants to change his/her password
Actors	User
Precondition	
Postcondition	- The password is changed
Base sequence	- The user sends a request containing a new password - The System registers the new user's password - The System returns an acknowledgment to the user
Branch sequence	
Exception sequence	

2.1.8 U1.3.4 - Display session command history

Title	U1.3.4 - Display session command history
Summary	The user displays all the commands sent during one session
Actors	User
Precondition	
Postcondition	
Base sequence	1. The user sends a request containing the session ID 2. The System returns the list of all commands issued by the user during the session which id corresponds to the provided session id. Each command has exactly the same format and parameters as the original submission and can be resubmitted as-is to the System.
Branch sequence	
Exception sequence	1a. Invalid session ID (unknown / belonging to another user, if the current user is not an administrator) 1b. VISHNU infrastructure is unreachable or unavailable

2.1.9 U1.3.5 - Display sessions log

Title	U1.3.5 - Display sessions log
Summary	The user displays his/her sessions (active or closed)
Actors	User
Precondition	
Postcondition	
Base sequence	1. The user sends a request to list all his/her sessions (active and/or closed) that have an open timestamp within an interval provided by the user (start and finish date) 2. The System returns all (or only active, or only closed) sessions of the user matching the search criteria with the following information for each session: id, date of opening, client host name, closure policy (timeout or disconnect), time before automatic closure (if applicable)

Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.1.10 U1.4 - Execute asynchronous user request

Title	U1.4 - Execute asynchronous user request
Summary	The user submits an asynchronous request to the system
Actors	User
Precondition	- A session (for the current user and client host) is active
Postcondition	- The request is completed - A request log is created
Base sequence	1. The user sends the request to the system 2. The System returns an acknowledgment to the user 3. The System runs the request in the background 4. When the request is completed the system updates the status of the request
Branch sequence	
Exception sequence	1.a Invalid session (bad session certificate or session unavailable) 1.b Invalid request 1.c Permission denied 1.d Resource not available 1.e VISHNU System crashed
Extension of	U1 - Session with manual closure U2 - Session with automatic closure on timeout U3 - Session with automatic closure on disconnect

2.1.11 U1.5 - Reconnect to session

Title	U1.5 - Reconnect to session
Summary	The user wants to use a session in which he/she was disconnected previously without closing it
Actors	User
Precondition	- The user is connected on a client host in which VISHNU is installed and that can be connected to the VISHNU infrastructure
Postcondition	- A session is active - The user's environment contains a session certificate
Base sequence	1. User provides its login, password and the short identifier of the session (in fact, for each session, a short identifier is assigned) to the System 2. The System validates the user's login, password and the identifier of the session 3. The System provides the chosen session certificate to the user
Branch sequence	1a. If the user is already within an active session then go to step 3 directly. The current session will be automatically closed according to the UC U2 or U3 depending on the close policy for that session.

Exception sequence	cf U1.1 (Open session) 2.f The identifier of the session is nonexistent 2f1. The System returns an error message 2.g The identifier relates to a session belonging to another user 2g1. The System returns an error message 2.h The identifier is for a session closed 2h1. The System returns an error message
Extension of	U1 - Session with manual closure U2 - Session with automatic closure on timeout U3 - Session with automatic closure on disconnect

2.1.12 U2 - Session with automatic closure on timeout

Title	U2 - Session with automatic closure on timeout
Summary	The user opens a new session that is closed by the System after the inactivity delay has expired
Actors	User
Precondition	- VISHNU is installed and running on the client system - The client system can be connected to VISHNU - The option SESSION_CLOSE_POLICY is CLOSE_ON_TIMEOUT (either user option is defined or this is the default policy)
Postcondition	- A session log has been created - The session state is closed - All user requests submitted during the session are complete
Base sequence	1. U1.1 Open session 2. The System is ready to process user commands 3. After inactivity delay has expired: U1.3 Close session auto
Branch sequence	2a. U1.3 Execute synchronous user request 2b. U1.4 Execute asynchronous user request 2c. U1.5 Reconnect to session 2d. If the user disconnects from the client terminal or the client system crashes or is shutdown, the session remains open and all asynchronous commands that were not completed are kept running
Exception sequence	see U1
Extensions	U1.5 - Reconnect to session U1.4 - Execute asynchronous user request U1.3 - Execute synchronous user request

2.1.13 U2.1 - Close session auto

Title	U2.1 - Close session auto
Summary	The session is closed by the system
Actors	
Precondition	- The user is connected on the client system - The user has an open session on the client system either the inactivity timeout for the session has expired or the user disconnected from its shell session
Postcondition	- The session is closed - The session close event is stored in the system's log

Base sequence	1. The system checks if the user has got no running commands (file transfers or tasks) 2. The system registers session closure
Branch sequence	1a. If the user has got some running commands, the system does not close the session and reset the inactivity timeout. After this delay is expired, back to step 1.
Exception sequence	

2.1.14 U3 - Session with automatic closure on disconnect

Title	U3 - Session with automatic closure on disconnect
Summary	The user opens a new session that will be closed by the system after the user disconnects from the client terminal
Actors	User
Precondition	<ul style="list-style-type: none"> - VISHNU is installed and running on the client system - The client system can be connected to VISHNU - The option SESSION_CLOSE_POLICY is CLOSE_ON_DISCONNECT (either user option is defined or this is the default policy)
Postcondition	<ul style="list-style-type: none"> - A session log has been created - The session state is closed - All user requests submitted during the session are complete
Base sequence	<ol style="list-style-type: none"> 1. U1.1 Open session 2. System is ready to process user commands 3. The user disconnects from the terminal (either by typing an exit command, by closing the window, or by remote disconnection) 4. U1.3 Close session auto
Branch sequence	<ol style="list-style-type: none"> 2a. U1.4 Execute synchronous user request 2b. U1.5 Execute asynchronous user request 3a. if the client system crashes or is shutdown, go to step 4
Exception sequence	see U1
Extensions	U1.3 - Execute synchronous user request U1.5 - Reconnect to session U1.4 - Execute asynchronous user request

2.1.15 U4 - Create new local user config

Title	U4 - Create new local user config
Summary	The user creates a new local user config for a given user on a given machine
Actors	User
Precondition	<ul style="list-style-type: none"> - The user has an account on VISHNU - The user has no local user config defined for the machine
Postcondition	<ul style="list-style-type: none"> - Local user config is registered - An email is sent to the user with a message containing a SSH public key

Base sequence	<ol style="list-style-type: none"> 1. The user provides local user config information for a given machine: user login (unix), home directory 2. The System checks the user login and the machine Id 3. The System generates a ssh private/public key pair 4. The System sends an email to the user containing the public key and asking the user to add this key to the authorized_keys on the machine 5. The user updates his/her authorized_keys file on the machine by adding the public key
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 2a. Invalid login 2b. unknown machine 4a. Invalid email address

2.1.16 U4.1 - Update local user config

Title	U4.1 - Update local user config
Summary	The user updates his/her local user config for a given machine
Actors	User
Precondition	<ul style="list-style-type: none"> - The user has an account on VISHNU - The user has a local user config defined for the machine
Postcondition	- local user config is updated
Base sequence	<ol style="list-style-type: none"> 1. The user provides the identifier of his/her local config and information to be updated 2. The System updates the local user account information 3. The System returns an acknowledgment to the user
Branch sequence	
Exception sequence	1a. Invalid account (unknown or inactive)

2.1.17 U4.2 - Delete local user config

Title	U4.2 - Delete local user config
Summary	The user deletes his/her local user config on a given machine
Actors	User
Precondition	<ul style="list-style-type: none"> - The local user config exists for the given machine - There is no job or file transfer running on the given machine
Postcondition	- The local user config for the given machine is deleted
Base sequence	<ol style="list-style-type: none"> 1. The user provides the identifier of the local user config 2. The System deletes the local user config identified 3. The System returns an acknowledgment to the user
Branch sequence	
Exception sequence	1a. Invalid login (unknown or inactive)

2.1.18 U4.3 - Display local user configs

Title	U4.3 - Display local user configs
Summary	The user displays all of his/her local configs
Actors	User
Precondition	
Postcondition	

Base sequence	1. The user sends a request to list all his/her local configs 2. The System returns all local configs
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.1.19 UA1 - Create new user account

Title	UA1 - Create new user account
Summary	The administrator creates a new user account in the System (database)
Actors	Admin
Precondition	- The user has not an account on VISHNU
Postcondition	- The user account is created and in an active state - The account's password must be changed at the first connection
Base sequence	1. The administrator provides the new user's last name, first name, email address and specifies whether the user has standard or admin rights 2. The System creates the new user account and initializes the password with a random-generated string (temporary password) 3. The System sends an email to the user containing the temporary password 4. The System returns an acknowledgment to the administrator
Branch sequence	
Exception sequence	2a. Login already used by another active user 3a. Invalid email address

2.1.20 UA1.1 - Update user account

Title	UA1.1 - Update user account
Summary	The administrator updates the user account (database)
Actors	Admin
Precondition	- The user has an account on VISHNU
Postcondition	- The user account is updated
Base sequence	1. The administrator provides the user's information changes 2. The System updates user account (database) 3. The System returns an acknowledgment to the administrator
Branch sequence	
Exception sequence	1.a Invalid login or login unknown 1.b The user information set are invalid 1.c The user information set are not consistent with the System

2.1.21 UA1.2 - Delete user account

Title	UA1.2 - Delete user account
Summary	The administrator deletes a user account
Actors	Admin
Precondition	- The user has an account on VISHNU - There is no job or file transfer running for the user

Postcondition	- The user account is no longer in the System - System does not contain any information related to the user
Base sequence	1. The administrator provides a user's login 2. The System deletes the user account together with all the information (configuration, history) related to it. 3. The System returns an acknowledgment to the administrator
Branch sequence	
Exception sequence	1a. Invalid login (unknown or inactive)

2.1.22 UA2 - Reset user password

Title	UA2 - Reset user password
Summary	The administrator resets a user password
Actors	Admin
Precondition	
Postcondition	- The password of the user is temporary and must be changed at the first connection by the user
Base sequence	1. The administrator provides a user's login 2. The System resets the user's password using a random-generated string 3. The System sends an email to the user containing the new temporary password 4. The System returns an acknowledgment to the administrator
Branch sequence	
Exception sequence	1a. Invalid login (unknown or inactive) 3a. Invalid email address

2.1.23 UA3 - Save configuration

Title	UA3 - Save configuration
Summary	The administrator saves the configuration of the system
Actors	Admin
Precondition	
Postcondition	- The configuration is saved on a file - A log information is created
Base sequence	1. The administrator requests to save the configuration in a file 2. The System creates a configuration file containing: the list of users, the list of local users configs and the list of machines according to the local users configs 3. The Systems saves the file on the client host
Branch sequence	
Exception sequence	2a. File creation problems 2b. VISHNU System crashed

2.1.24 UA4 - Restore configuration

Title	UA4 - Restore configuration
-------	-----------------------------

Summary	The administrator restores a saved configuration
Actors	Admin
Precondition	- All users are disconnected from VISHNU - The configuration file was saved using the "save configuration" feature.
Postcondition	- The System is operational on all the machines that are both properly configured in the saved configuration and where the VISHNU processes are running.
Base sequence	1. The administrator opens a session as the Root user 2. The administrator checks that there is no other user/admin connected to VISHNU 3. The administrator loads the configuration file 4. The System replaces the current configuration with the loaded configuration.
Branch sequence	
Exception sequence	1a. If the Root user already has an open session, the System cannot open a second session with the Root user 3a. If the configuration file cannot be loaded, the System provides an error message. The System configuration is reset to a basic configuration with only the Root user configured.

2.1.25 UA5.1 - Display sessions

Title	UA5.1 - Display sessions
Summary	The administrator displays all past and present sessions stored in the database.
Actors	Admin
Precondition	
Postcondition	
Base sequence	1. The administrator sends a request to list all sessions (active and/or closed) that have an open timestamp within an interval provided by the user (start and finish date) 2. The System returns the list of sessions that match the search criteria and provides detailed information about these sessions (user id, open and close timestamp, client machine id)
Branch sequence	
Exception sequence	

2.1.26 UA5.2 - Display users

Title	UA5.2 - Display users
Summary	The administrator displays the description of all users registered in the database
Actors	Admin
Precondition	
Postcondition	
Base sequence	1. The administrator sends a request to list all users 2. The System returns all users with the following information for each user: id, firstname, lasname, login, status, email and password state.
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.1.27 UA5.3 - Display local users configs

Title	UA5.3 - Display local users configs
Summary	The administrator displays the local user configs for all users registered in the database
Actors	Admin
Precondition	
Postcondition	
Base sequence	<ol style="list-style-type: none"> 1. The administrator sends a request to list all local users configs 2. The System returns all the local users configs for all users
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.1.28 UA6.1 Add a machine

Title	UA6.1 Add a machine
Summary	The administrator registers a new machine in VISHNU
Actors	Admin
Precondition	
Postcondition	The infrastructure has one more machine // A new machine is added in VISHNU System
Base sequence	<ol style="list-style-type: none"> 1. The administrator adds a new machine on VISHNU by giving : <ul style="list-style-type: none"> - The machine name - The machine state (private or accessible to users) - The public address (IP) - A structure describing the machine state - A structure describing the network 2. The machine is added on VISHNU and the System returns the machine ID.
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 1a. A machine with the same name exists, the ALREADY_MACHINE_REGISTERED exception is raised. 1b. A machine with the same public address already exists, the ALREADY_MACHINE_REGISTERED exception is raised

2.1.29 UA6.2 Remove a machine

Title	UA6.2 Remove a machine
Summary	The administrator unsubscribed a machine
Actors	Admin
Precondition	- The machine is registered in the System
Postcondition	The Machine is unsubscribed
Base sequence	<ol style="list-style-type: none"> 1. The administrator removes a machine from VISHNU by giving the machine ID 2. The System returns an acknowledgment to the administrator
Branch sequence	
Exception sequence	1a. The public address is unknown, the UNKNOWNMACHINE exception is raised.

2.1.30 UA6.3 Display machines

Title	UA6.3 Display machines
Summary	The administrator displays the machines registered in the database
Actors	Admin
Precondition	
Postcondition	
Base sequence	1. The administrator sends a request to list all machines in the database 2. The System returns all machines in the database
Branch sequence	
Exception sequence	1a. VISHNU infrastructure is unreachable or unavailable

2.2 Use case diagrams

2.2.1 UC UMS Admin




Figure 2.1: UC UMS Admin

2.2.2 UC UMS Admin Machines

UMS Admin Machines.png UMS Admin Machines.png

Figure 2.2: UC UMS Admin Machines

2.2.4 UC UMS User Manual




Figure 2.4: UC UMS User Manual

2.2.5 UC UMS User account




Figure 2.5: UC UMS User account

2.3 Data dictionary

- **CLOSE ON DISCONNECT** : CLOSE ON DISCONNECT is a value which means that the only one way for closing the session is when the user closes her/his terminal
 - **CLOSE ON TIMEOUT** : CLOSE ON TIMEOUT is a value which means that the way for closing a session is after a session inactivity delay. This value is given by the client or registered by default by the administrator
 - **Client System** : Client System or Client Host is a program which uses VISHNU API commands and that can be connected to VISHNU Infrastructure
 - **Configuration** : The configuration contains all information about the users and machines registered in the database. It does not contain chronological information about the users or the infrastructure (logs, metrics values)
 - **Local user config** : The local user config is the description of the given user on a specific machine described in the database
 - **Manual closure** : The Manual closure means that the user uses the API command for closing the session
 - **Option** : The option is a parameter of the user account that is not mandatory. Default value for each option is defined by the administrator. This features can be used by all VISHNU modules (not only UMS).
 - **Password state** : Records the current state of the password of a user: either 'temporary' if the password must be changed next time the user connects to the System, or 'valid' if the password is in a normal state.
 - **Root user** : Special user that is pre-configured in the VISHNU system and that has administrator privileges. This user cannot be deleted from the system.
 - **SESSION_CLOSE_POLICY** : SESSION_CLOSE_POLICY is an option represents the way to close the session (on timeout or on disconnect)
 - **Session** : A session is the context in which VISHNU commands are executed (ex: job submission, file transfers). It is created following authentication of a user and lasts until it is closed either manually or automatically.
 - **Session inactivity delay** : The session inactivity delay is the delay in which no api commands are launched
 - **User account** : The user account is the description in the database of a VISHNU user
-

Chapter 3

Use cases for Tasks Management System (TMS)

3.1 Use case descriptions

3.1.1 T1 - AsyncCommandOnMachine

Title	T1 - AsyncCommandOnMachine
Summary	User starts an asynchronous command on a given machine
Actors	User
Precondition	- User has an active open session
Postcondition	- The command is in active state until completed - The system log has been updated and contains the request parameters
Base sequence	1. User sends the request with parameters including session id and machine id 2. System checks that the machine id is valid and machine is available 3. System checks that the session id is valid 4. If command parameters contain a file the System verifies that the file is available and readable 5. System returns information to the user about the request status 6. System records request information (time, user, machine, request parameters) in the system log
Branch sequence	5a. T1.1 SubmitJob
Exception sequence	1a. The TMS server is unavailable - The system returns an error message that informs the user. 2a. The name of the given machine is unknown -The system returns an error message that informs the user. 3a. The session id is not valid - The system returns an error message that informs the user. 4a. The path to a file parameter is invalid - The system returns an error message that informs user.
Extensions	T1.1 - SubmitJob T1.2 - AsynGetJobOutPut

3.1.2 T1.1 - SubmitJob

Title	T1.1 - SubmitJob
-------	------------------

Summary	User submits a job on a given machine
Actors	User
Precondition	
Postcondition	<ul style="list-style-type: none"> - The job is submitted on the specified machine - The job state and id are recorded on the system's log - The job id is sent to the user
Base sequence	<ol style="list-style-type: none"> 1. The System checks that request parameters contain: <ul style="list-style-type: none"> - job script path - job options 2. The TMS server on the given machine is contacted 3. The job is submitted by the TMS server to the batch scheduler 4. The id of the submitted job is returned to the user
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 1a. Invalid options or script 4a. The batch scheduler server is unavailable 4b. The batch scheduler server rejects the request
Extension of	T1 - AsyncCommandOnMachine

3.1.3 T1.2 - AsyncGetJobOutPut

Title	T1.2 - AsyncGetJobOutPut
Summary	User gets the job results dynamically on a given machine
Actors	
Precondition	
Postcondition	<ul style="list-style-type: none"> - The System sends online the completed jobs
Base sequence	<ol style="list-style-type: none"> 1. The TMS server is contacted at each interval refresh period 2. The TMS server checks each submitted job state 3. The TMS server sends completed job results
Branch sequence	
Exception sequence	<ul style="list-style-type: none"> -2a The TMS server is unavailable -2b The underlying batch scheduler is unavailable
Extension of	T1 - AsyncCommandOnMachine

3.1.4 T2 - SyncCommandOnMachine

Title	T2 - SyncCommandOnMachine
Summary	User executes a synchronous command on a given machine
Actors	User
Precondition	<ul style="list-style-type: none"> - User has an active open session
Postcondition	<ul style="list-style-type: none"> - Request is in completed state - The system log has been updated and contains the request parameters

Base sequence	<ol style="list-style-type: none"> 1. User sends the request with parameters including session id and machine id 2. System checks that the machine id is valid and machine is available 3. System checks that the session id is valid 4. If command parameters contain a file the System verifies that the file is available and readable 5. System returns information containing the results of the request 6. System records request information (time, user, machine, request parameters) in the system log
Branch sequence	<ol style="list-style-type: none"> 5a. T2.1-GetJobs 5b. T2.2-CancelJob 5c. T2.3-ListQueue 5d. T2.4-ListJobs 5e. T2.5-JobProgress 5f. TA1-SetMachineRefreshRate 5g. TA2-SetMachineEnv
Exception sequence	<ol style="list-style-type: none"> 1a. The TMS server is unavailable - The system returns an error message that informs the user. 2a. The name of the given machine is unknown -The system returns an error message that informs the user. 3a. The session id is not valid - The system returns an error message that informs the user. 4a. The path to a file parameter is invalid - The system returns an error message that informs user. - The user revises the path
Extensions	<ol style="list-style-type: none"> T2.1 - GetJob T2.2 - CancelJob T2.3 - ListQueue T2.4 - ListJobs TA1 - SetMachineRefreshPeriod TA2 - SetMachineEnv T2.5 - JobProgress T2.6 - GetJobOutPut

3.1.5 T2.1 - GetJob

Title	T2.1 - GetJob
Summary	User requests the TMS server to get information about a job
Actors	User
Precondition	
Postcondition	
Base sequence	<ol style="list-style-type: none"> 1. The Systems checks the job id 2. The TMS server on the given machine is contacted 3. The TMS server asks job information to the batch scheduler server 4. The user receives job information
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 1a. The job id is invalid 3a. The batch scheduler server is unavailable 3b. The batch scheduler server rejects the request
Extension of	T2 - SyncCommandOnMachine

3.1.6 T2.2 - CancelJob

Title	T2.2 - CancelJob
Summary	The user cancels a job
Actors	User
Precondition	
Postcondition	<ul style="list-style-type: none"> - The job is canceled on the specified machine - The job state and id are removed to the system's log - An information is sent to the user
Base sequence	<ol style="list-style-type: none"> 1. The systems checks the job id 2. The TMS server on the given machine is contacted 3. The TMS server cancels the job 4. The user receives a message
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 1a. The job id is invalid 3a. The batch scheduler server is unavailable 3b. The batch scheduler server rejects the request
Extension of	T2 - SyncCommandOnMachine

3.1.7 T2.3 - ListQueue

Title	T2.3 - ListQueue
Summary	User lists all queues or classes of a specific batch scheduler
Actors	User
Precondition	
Postcondition	<ul style="list-style-type: none"> - The system collects the informations on each queue or classes - The system records request parameters in system's log - The system send the list contained the information on all queues to the user.
Base sequence	<ol style="list-style-type: none"> 1. The TMS server on the given machine is contacted 2. The TMS server asks queues or classes information to the batch scheduler server 3. The System sends all queues list to the user
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 2a. The batch scheduler server is unavailable 2b. The batch scheduler server rejects the request
Extension of	T2 - SyncCommandOnMachine

3.1.8 T2.4 - ListJobs

Title	T2.4 - ListJobs
Summary	User lists all jobs submitted
Actors	User
Precondition	-User has an active open session
Postcondition	<ul style="list-style-type: none"> - The System sends information on all jobs to the user - The System records request parameters in the system's log
Base sequence	<ol style="list-style-type: none"> 1. The TMS server on the given machine is contacted 2. The TMS server asks job information to the batch scheduler server 3. The System sends full information on all jobs to the user

Branch sequence	
Exception sequence	2a. The batch scheduler server is unavailable 2b. The batch scheduler server rejects the request
Extension of	T2 - SyncCommandOnMachine

3.1.9 T2.5 - JobProgress

Title	T2.5 - JobProgress
Summary	User gets jobs progression (execution percent) status on a machine
Actors	
Precondition	- User has an active open session
Postcondition	- The System sends jobs information progression - The System records request parameters in the system's log
Base sequence	1. The TMS server on the given machine is contacted 2. The TMS server computes each job progression 3. The System sends all jobs progression to the user
Branch sequence	
Exception sequence	2a. The TMS server is unavailable - The system returns an error message that informs the user.
Extension of	T2 - SyncCommandOnMachine

3.1.10 T2.6 - GetJobOutPut

Title	T2.6 - GetJobOutPut
Summary	
Actors	
Precondition	
Postcondition	-User gets the job results on a given machine
Base sequence	1. The TMS server is contacted. 2. The TMS server check the job state. 3. The TMS server sends job results if the job is completed
Branch sequence	
Exception sequence	-2a The TMS server is unavailable -2b The underlying batch scheduler is unavailable
Extension of	T2 - SyncCommandOnMachine

3.1.11 TA1 - SetMachineRefreshPeriod

Title	TA1 - SetMachineRefreshPeriod
Summary	The admin sets the refresh period of output and error file content
Actors	Admin
Precondition	
Postcondition	- The refresh period value is stored by the system
Base sequence	1. System saves the refresh period for the given machine. 2. System applies the refresh period to all current jobs and future requests
Branch sequence	
Exception sequence	1a. Refresh period value is too short (minimum value : see technical requirements) - System returns an error message

Extension of	T2 - SyncCommandOnMachine
--------------	---------------------------

3.1.12 TA2 - SetMachineEnv

Title	TA2 - SetMachineEnv
Summary	The admin sets an environment variable
Actors	Admin
Precondition	
Postcondition	- Environment variable is set
Base sequence	<ol style="list-style-type: none"> 1. System saves the environment variable for the given machine. 2. System applies the environment variable to all current jobs and future requests
Branch sequence	
Exception sequence	
Extension of	T2 - SyncCommandOnMachine

3.1.13 TA3 - LaunchTmsServer

Title	TA3 - LaunchTmsServer
Summary	The administrator launches the VISHNU TMS server on a given machine
Actors	Admin
Precondition	<ul style="list-style-type: none"> - The Vishnu server software (TMS Module and dependencies) is installed on the machine - The machine is configured in the Vishnu system database - The batch scheduler processes are up and running on the same machine - The network connection between the machine and the Vishnu database server is up and running
Postcondition	<ul style="list-style-type: none"> - The TMS server is up and running - A server log has been created
Base sequence	<ol style="list-style-type: none"> 1. Admin connects to the machine as vishnu user 2. Admin updates the Vishnu configuration if necessary (database server hostname and credentials, DIET configuration, Batch scheduler configuration) 3. Admin launches the Vishnu TMS Server executable 4. System checks the connections to its peers within the Vishnu platform 5. System retrieves the list of active jobs (not completed jobs) that were launched on the same machine 6. System checks that all the active jobs (from previous step) are still running on the batch scheduler, and eventually updates the job status (for ex. from waiting to running, or from running to finished) 7. System returns a status message to the administrator
Branch sequence	
Exception sequence	<ol style="list-style-type: none"> 4a. A connection to a Vishnu peer is down. System returns an error message and stops 6a. The batch scheduler does not recognize some job ids. In this case the System updates the job status to completed.

3.2 Use case diagrams

3.2.1 UC TMS Overview




Figure 3.1: UC TMS Overview

3.3 Data dictionary

- **Batch Scheduler** : A batch scheduler is a distributed resource manager that enables to allocate at best the resources to the jobs on a machine according to user needs (the needs are specified by the user by batch directives (batch options) in file or command line).
- **Job** : A job is a sequence of instructions (included batch scheduler directives) written to launch and to perform by a specified batch scheduler.
- **Job id** : A job id allows to identify the job in the batch scheduler system.
- **JobPath** : A jobPath is the path to the file (script) containing the instructions (batch directives or job characteristics, job execution command) of the job.
- **Queue ou Classe** : A queue or class allows to associate the resource limits (CPU wallclock time, CPU memory) and execution priorities of the jobs.
- **TMS** : Task Management System

Chapter 4

Use cases for Information Management System (IMS)

4.1 Use case descriptions

4.1.1 I1. Get the update frequency

Title	I1. Get the update frequency
Summary	The user gets how often the IMS database tables are updated
Actors	User
Precondition	
Postcondition	
Base sequence	1) The user calls the function to know how often the IMS database tables are automatically updated 2) The System returns the value in second
Branch sequence	
Exception sequence	2 -> There is a problem with the database, the system returns a DATABASEERROR

4.1.2 I2 Get metric data

Title	I2 Get metric data
Summary	The user gets data concerning the metrics on a machine
Actors	User
Precondition	
Postcondition	
Base sequence	1) The user calls to get the metrics data. on a machine identified by a machine id, for a metric type, from start time up to end time. The metrics are within {number of cpu, percentage of cpu used, total diskSpace, free diskSpace, total RAM, free RAM, number of processes running} 2) The System returns the results by groups (metric,value, time).
Branch sequence	

Exception sequence	<p>1 -> The machine id is invalid, an INVALIDPARAMETER error is returned</p> <p>2 -> There is a problem with the database, the system returns a DATABASEERROR</p>
--------------------	---

4.1.3 I3. Export and replay commands

Title	I3. Export and replay commands
Summary	The user exports and replays a sequence of commands made during a session.
Actors	User
Precondition	
Postcondition	All the System commands submitted during a session have been re-executed keeping the same order they were originally launched.
Base sequence	<p>1) The user calls to export the history of a session identified by an id in python format</p> <p>2) The System provides a python script containing all the commands of the session with the same parameters as provided initially by the user (including file paths, numbers, strings, options)</p> <p>3) The user executes the python script in VISHNU</p>
Branch sequence	<p>1a) The user calls to export the history of a session identified by an id in shell format.</p> <p>2a) The System provides a shell script containing all the commands of the session with the same parameters as provided initially by the user (including file paths, numbers, strings, options)</p> <p>3a) The user executes the shell script in a shell</p>
Exception sequence	<p>1 -> The session id is invalid, an INVALIDPARAMETER exception is raised.</p> <p>3 -> A command in the execution fails, the error of the command is returned</p>

4.1.4 I4. Get data on the infrastructure

Title	I4. Get data on the infrastructure
Summary	The user gets System information about the machines
Actors	User
Precondition	
Postcondition	
Base sequence	<p>B1 * The user calls to get the use of the CPUs on a machine identified by an ID.</p> <p>* The System returns him the use of the CPUs on the machine in percentage.</p>

Branch sequence	<p>B2 * The user calls to get the number of CPUs on a machine identified by an ID. * The System returns him the number of CPUs on the machine.</p> <p>---</p> <p>B3 * The user calls to get the total diskSpace. * The System returns him the value.</p> <p>---</p> <p>B4 * The user calls to get the free diskSpace. * The System returns him the value.</p> <p>---</p> <p>B5 * The user calls to get the total RAM on a machine identified by an id. * The System returns him an id.</p> <p>---</p> <p>B6 * The user calls to get the free RAM on a machine identified by an id. * The System returns him the value</p>
Exception sequence	The machine id is invalid, an INVALIDPARAMETER exception is raised

4.1.5 IA1. Get the running processes

Title	IA1. Get the running processes
Summary	The admin gets the list of the running processes on a machine
Actors	Admin
Precondition	
Postcondition	
Base sequence	<p>1) The admin calls to get the list of the processes on a machine referenced by a machine id</p> <p>2) The System returns a list of processes</p>
Branch sequence	
Exception sequence	1 -> machineId is invalid, an INVALIDPARAMETER is return.

4.1.6 IA10. Update machine description

Title	IA10. Update machine description
Summary	Updates the data concerning a machine (if the machine has some memory diskSpace added, some memory added, a new description)
Actors	
Precondition	
Postcondition	The description of the machine in the database is updated
Base sequence	<p>1) An admin calls to update the data concerning a machine identified by an id giving a new diskSpace size, a new memory size, a new machine description</p> <p>2) The System updates the database</p>
Branch sequence	
Exception sequence	<p>1 -> The machine id is invalid, an INVALIDPARAMETER error is returned</p> <p>2 -> There is an error with the database, a DATABASEERROR error is returned</p>

4.1.7 IA2. Define a system load threshold

Title	IA2. Define a system load threshold
Summary	The administrator defines a system load threshold for a machine
Actors	Admin
Precondition	
Postcondition	The system load threshold is added to the System database
Base sequence	<p>1a) The administrator calls to define the limit size of the diskSpace to use with a machine id, a threshold value and an admin id</p> <p>2a) The System updates the database</p> <p>OR-----</p> <p>1b) The administrator calls to define the limit of RAM available to the user with a machine id, a threshold value and an admin id</p> <p>2b) The System updates the database</p> <p>OR-----</p> <p>1c) The administrator calls to define the number of processes threshold on a machine with a machine id, a threshold value and an admin id</p> <p>2c) The System updates the database</p>
Branch sequence	
Exception sequence	<p>1* -> The admin ID is invalid, the database is not updated and an INVALIDPARAMETER error is returned</p> <p>2* -> The modification of the database fails, a DATABASEERROR is returned.</p>

4.1.8 IA2.1 Get a system load threshold

Title	IA2.1 Get a system load threshold
Summary	The user wants to get the thresholds on a machine
Actors	Admin
Precondition	
Postcondition	
Base sequence	<p>1) The user calls to get the defined limit on a machine identified by an id. These limits are within {free diskSpace, free RAM, number of processes running}</p> <p>2) The System returns the value.</p>
Branch sequence	
Exception sequence	<p>1 -> The machine id is invalid, the user gets an INVALIDPARAMETER error returned</p> <p>2 -> There is a problem with the database request, a DATABASEERROR is returned</p>

4.1.9 IA3. Define the identifiers

Title	IA3. Define the identifiers
Summary	The administrator defines the format of the automatic identifiers defined for the System objects.
Actors	Admin
Precondition	
Postcondition	A new format will be used to create the new identifiers

Base sequence	<p>1) The administrator has a list of variables to define the identifiers shape. He has a method by kind of object (an object is either a user or a machine or a task or a file transfer).</p> <p>Available variables are :</p> <p>YEAR : the last two digits, (e.g. 10 for 2010)</p> <p>MONTH : Numerical value of the month (from 1 to 12)</p> <p>DAY : Day number, from 1 to 31</p> <p>TYPE : The object kind</p> <p>SITE : The place for machine/users</p> <p>NAME : Username or machine name</p> <p>CPT : A counter automatically increased (each kind of object has its counter).</p> <p>2) He calls the function to redefine the format with some of the previous parameters in a string. For example, "\$TYPE\$DAY\$MONTH\$YEAR\$CPT"</p> <p>3) The System database is updated, the System does not check if the given format creates unique identifiers. If the same identifier is created, it will degenerate the database (the key will not be unique)</p>
Branch sequence	<p>2 -> An invalid variable is given, an INVALIDPARAMETER is returned and the old format is still used</p> <p>3 -> The update fails, a DATABASEERROR is returned</p>
Exception sequence	

4.1.10 IA4. Hard delestage

Title	IA4. Hard delestage
Summary	Abruptly stop the processes running on a machine (the waiting actions are cancelled and the running ones are cut).
Actors	Admin
Precondition	
Postcondition	The whole machine is flushed and no job is running on it
Base sequence	<p>1) The admin launches the hard delestage function on a machine identified by an id.</p> <p>2) The System flushes all the waiting action.</p> <p>3) The System stops all the running processes on this machine.</p>
Branch sequence	
Exception sequence	1 -> The id of the machine is invalid, an INVALIDPARAMETER is returned

4.1.11 IA5. Soft delestage

Title	IA5. Soft delestage
Summary	The admin purges all the waiting actions and stops the running ones
Actors	Admin
Precondition	
Postcondition	No jobs are waiting to run or running
Base sequence	<p>1) The admin calls the soft delestage function on the machine identified by an id.</p> <p>2) The System flushes the waiting jobs and stops the running ones. They are stored and can be restarted later</p>

Branch sequence	
Exception sequence	1 -> The machine id is invalid, an INVALIDPARAMETER error is returned

4.1.12 IA6. Set the update frequency

Title	IA6. Set the update frequency
Summary	The administrator sets the update frequency
Actors	Admin
Precondition	
Postcondition	The System updates the IMS database at the new frequency
Base sequence	1) The administrator calls to set the update frequency in seconds 2) The System updates its database update frequency value
Branch sequence	
Exception sequence	The database is is not reachable. A DATABASEERROR is returned.

4.1.13 IA7. Notification of limit overflow

Title	IA7. Notification of limit overflow
Summary	The admin is informed of a limit overflow
Actors	Admin
Precondition	A machine on the System has a limit overflow
Postcondition	
Base sequence	1) The System gets the email adress of the admin to contact 2) The System sends a mail to the admin concerning the overflow. The mail contains the name of the machine and the treshold concerned.
Branch sequence	
Exception sequence	1 -> The system fails getting the admin e-mail, a DATABASEERROR error is returned 2 -> Sending the mail fails, a MAILERROR error is returned.

4.1.14 IA8. Restart the System

Title	IA8. Restart the System
Summary	Restart all the servers, agents, and daemons of the System. The started actions are restarted again.
Actors	Admin
Precondition	The System platforms needs to be restarted
Postcondition	The System is running with the same server, agents and daemons that were running before the crash. The interrupted actions are restarted from the beginning.
Base sequence	1) An admin detects a problem 2) An admin calls to restart the System 3) The System saves the current actions 4) The System restarts components and restarts the stopped action from the beginning
Branch sequence	

Exception sequence	4-> Fail to relaunch a component (SeD, daemon, agent), an UNREACHABLECOMPONENT error is returned.
--------------------	---

4.1.15 IA9. Automatic restart

Title	IA9. Automatic restart
Summary	A component is restarted
Actors	Admin
Precondition	A component of the platform is down
Postcondition	The component is up and running again
Base sequence	1) An admin detects a component has stopped for unknown reasons (a component = server, daemon, agent) 2) The admin calls the System to relaunch the component with its name 3) The System relauches the component
Branch sequence	
Exception sequence	3-> Fail to restart the component, an UNREACHABLECOMPONENT error is returned.

4.1.16 U1.3 Execute synchronous request

Title	U1.3 Execute synchronous request
Summary	The user submits a synchronous request to the System. c.f. the UMS use case description (U1.3)
Actors	User, Admin, Admin
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	

4.2 Use case diagrams

4.2.1 Consult




Figure 4.1: Consult

4.2.2 Fonctionnalités Global




Figure 4.2: Fonctionnalités Global

4.2.3 PlatformManagement




Figure 4.3: PlatformManagement

4.2.4 Replay




Figure 4.4: Replay

4.2.5 Stop_Restart




Figure 4.5: Stop_Restart

4.3 Data dictionary

- **Actions** : A generic naming to design both jobs and file transfers
- **Agent** : A component of the VISHNU hierarchy
- **CPU** : Central Processing Unit
- **Daemon** : Daemon running on the machines.
- **DiskSpace** : File system memory (not volatile)
- **IMS** : Information Management System
- **Infrastructure** : Contains all the machine directly under the System supervision
- **Live measure** : Measure regularly updated
- **Memory** : RAM (volatile)
- **Objects** : An object is an abstraction of what can be manipulated by the System (user, machine, task, file transfer)
- **Process** : Process of the system
- **SeD** : A component of the VISHNU hierarchy doing jobs for the clients
- **Task** : Job submitted via the TMS module

Chapter 5

Use cases for File Management System (FMS)

5.1 Use case descriptions

5.1.1 Execute a synchronous tranfer file

Title	Execute a synchronous tranfer file
Summary	
Actors	
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	

5.1.2 Execute an asynchronous copy of files

Title	Execute an asynchronous copy of files
Summary	
Actors	
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	

5.1.3 Execute an asynchronous tranfer file

Title	Execute an asynchronous tranfer file
Summary	
Actors	
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	

5.1.4 F1- Execute simple command on one remote machine

Title	F1- Execute simple command on one remote machine
Summary	This use case allows User to execute a command on one remote host.
Actors	User
Precondition	-User has an active open session.
Postcondition	-The command is performed successfully and the potential results are sent back to User. - The System log has been updated and contains a request parameters.
Base sequence	1. User enters the command by specifying the parameters, the session id and the involved host id. 2. The System checks that the host id is valid and the machine is available. 3. The System checks that the session id is valid. 4.The System returns information to User about the request status. 5.The System performs the command and send back the results to User . 6. The System records request information (time, User, machine, request parameters).
Branch sequence	
Exception sequence	1a. The given parameters are invalid for this command. 1.b The 1b. The specified host is unknown. 2a. The command fails and a error message is printed on the standard output of client System.
Extensions	F1.2- Change group owner of files F1.2- Change group owner of files F1.1- Change acces modes of files F1.3- Create new directories F1.4- Create new files F1.5- Delete directories F1.6- Delete files F1.6- Delete files F1.8- Display contents of files F1.9- Display Head of files F1.7- Display contents of directories F1.10- Display tail of files F2.1- Execute a synchronous copy of files F2.2- Execute an asynchronous copy of files

5.1.5 F1.1- Change acces modes of files

Title	F1.1- Change acces modes of files
Summary	This use case allows User to change acces rights of a given file.
Actors	
Precondition	
Postcondition	The new access permissions of the specified file is set.
Base sequence	1. User submits the change acces rights command with the file, the new acces rights to set and the involved machine. 2.The client System sets the new access rights to the file.
Branch sequence	

Exception sequence	1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System. 1b. if the file is unknown, a message is also printed on the standard output of the client System.
Extension of	F1- Execute simple command on one remote machine

5.1.6 F1.10- Display tail of files

Title	F1.10- Display tail of files
Summary	This command allows User to print the last few lines of a given file located on a remote host.
Actors	
Precondition	
Postcondition	The first lines of the specified file are printed on the standard output of the client System.
Base sequence	1. User submits the display command with the path of the file to display and the involved host. 2.The client System displays the first line of the specified file on the its standard output.
Branch sequence	
Exception sequence	1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System. 1.b if the file is unknown, a message is printed on the standard output of the client System. 1.c if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System
Extension of	F1- Execute simple command on one remote machine

5.1.7 F1.2- Change group owner of files

Title	F1.2- Change group owner of files
Summary	
Actors	Admin
Precondition	
Postcondition	The new access permissions of the specified file is set.
Base sequence	1. Administrator submits the change group owner command with the file , the new group to set and the involved host. 2.The The client System sets the new group owner to the file.
Branch sequence	
Exception sequence	1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System. 1b if the file is unknown, a message is also printed on the standard output of the client System.
Extension of	F1- Execute simple command on one remote machine F1- Execute simple command on one remote machine

5.1.8 F1.3- Create new directories

Title	F1.3- Create new directories
Summary	This use case allows User to create a new directory in a named host.
Actors	
Precondition	
Postcondition	The new directory is created on the specified host.
Base sequence	1. User submits the create directory command with the path of directory to create and the involved host. 2.The client System creates a new directory with the specified path.
Branch sequence	
Exception sequence	1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System. 1b. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.
Extension of	F1- Execute simple command on one remote machine

5.1.9 F1.4- Create new files

Title	F1.4- Create new files
Summary	This use case allows User to create a new file in a named host.
Actors	
Precondition	
Postcondition	The new file is created on the specified host.
Base sequence	1. User submits the create file command with the path of file to create and the involved host. 2.The FMS Server creates a new file with the specified path.
Branch sequence	
Exception sequence	1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System. 1b if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.
Extension of	F1- Execute simple command on one remote machine

5.1.10 F1.5- Delete directories

Title	F1.5- Delete directories
Summary	This use case allows User to removes a given directory (and its contents) located on a remote host.
Actors	
Precondition	
Postcondition	The specified directory is removed from the given host.
Base sequence	1. User submits the delete directory command with the path of directory to delete and the involved host. 2.The client System deletes the specified directory from the host.

Branch sequence	
Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the file is unknown, a message is printed on the standard output of the client System.</p> <p>1.c if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	F1- Execute simple command on one remote machine

5.1.11 F1.6- Delete files

Title	F1.6- Delete files
Summary	This use case allows User to removes a given file located on a remote host.
Actors	
Precondition	
Postcondition	
Base sequence	<p>1. User submits the delete file command with the path of file to delete and the involved host.</p> <p>2.The client System deletes the specified file from the host.</p>
Branch sequence	
Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the file is unknown, a message is printed on the standard output of the client System.</p> <p>1.c if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	<p>F1- Execute simple command on one remote machine</p> <p>F1- Execute simple command on one remote machine</p>

5.1.12 F1.7- Display contents of directories

Title	F1.7- Display contents of directories
Summary	This use case allows User to list the files contained in the given directory located on a remote host.
Actors	
Precondition	
Postcondition	The contents of the specified directory is printed on the standard output of the client System.
Base sequence	<p>1. User submits the display command with the path of directory to list and the involved host.</p> <p>2.The client System displays the contents of the specified directory on its standard output.</p>
Branch sequence	

Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the file is unknown, a message is printed on the standard output of the client System.</p> <p>1c. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	F1- Execute simple command on one remote machine

5.1.13 F1.8- Display contents of files

Title	F1.8- Display contents of files
Summary	This use case allows User to print the contents of a given file located on a remote host.
Actors	
Precondition	
Postcondition	The named file is printed on the standard output of the client System.
Base sequence	<p>1. User submits the display command with the path of the file to display and the involved host.</p> <p>2.The client System deletes the specified file from the machine</p>
Branch sequence	
Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the file is unknown, a message is printed on the standard output of the client System.</p> <p>1c. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	F1- Execute simple command on one remote machine

5.1.14 F1.9- Display Head of files

Title	F1.9- Display Head of files
Summary	This command allows User to print the first few lines of a given file located on a remote host.
Actors	
Precondition	
Postcondition	The first lines of the specified file are printed on the standard output of the client System.
Base sequence	<p>1. User submits the display command with the path of the file to display and the involved host.</p> <p>2.The client System displays the first lines of the specified file on its standard output.</p>
Branch sequence	

Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the file is unknown, a message is printed on the standard output of the client System.</p> <p>1c. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	F1- Execute simple command on one remote machine

5.1.15 F2- Transfer a file between two remote hosts

Title	F2- Transfer a file between two remote hosts
Summary	This use case allows User to execute a transfer file command from a remote host A to another remote host B.
Actors	User
Precondition	<p>-User is logged in the client System.</p> <p>-FMS server is installed and running on A and B .</p>
Postcondition	<p>-The transfer file is done successfully and a copy of the file is in the remote host B.</p> <p>- The System log has been updated and contains the request parameters.</p>
Base sequence	<p>1. User submits the transfer file command with the path of the file to copy and the involved two hosts.</p> <p>2.The client System copy the given source file to the specified destination.</p>
Branch sequence	
Exception sequence	<p>1a. The given parameters are invalid for this command.</p> <p>1b. The specified hosts are unknown.</p> <p>2a. The command fails and a error message is printed on the standard output of client System.</p>

5.1.16 F2.1- Execute a synchronous copy of files

Title	F2.1- Execute a synchronous copy of files
Summary	<p>This use case allows User to copy a file between two hosts. The three cases of transfer are covered this use case :</p> <ul style="list-style-type: none"> - inside the same host which can be local or remote, - from local host to remote host, - from remote host to local host, - from remote host to another remote host.
Actors	User
Precondition	
Postcondition	-The file transfer is full accomplished.
Base sequence	<p>1. User submits the transfer file command with the path of the source file to copy and the path of destination.</p> <p>2.The client System copy the given source file to the specified destination.</p>
Branch sequence	

Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the source file is unknown, a message is printed on the standard output of the client System.</p> <p>1c. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>
Extension of	F1- Execute simple command on one remote machine F2.1.1- Execute a synchronous move of files
Extensions	F2.1.1- Execute a synchronous move of files

5.1.17 F2.1.1- Execute a synchronous move of files

Title	F2.1.1- Execute a synchronous move of files
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.1- Execute a synchronous copy of files
Extensions	F2.1- Execute a synchronous copy of files

5.1.18 F2.2- Execute an asynchronous copy of files

Title	F2.2- Execute an asynchronous copy of files
Summary	<p>This use case gives the possibility to User to copy a file located on a local machine towards a remote machine and submit another command without waiting the end of transfer file.</p> <p>The three cases of transfer are covered this use case :</p> <ul style="list-style-type: none"> - inside the same host which can be local or remote - from local host to remote host - from remote host to local host
Actors	User
Precondition	
Postcondition	<p>-The file transfer may be on-going or completed.</p> <p>-User gets an transfer id in order to check the file tranfert status.</p>
Base sequence	<p>1. User submits the tranfer file command with the path of the file to copy , the path of destination file, and the destination host.</p> <p>2.The The client System copy the given source file to the specified destination.</p>
Branch sequence	
Exception sequence	<p>1a. If there are missing parameters, a message that contains the way to use the command, is displayed on the standard output of the client System.</p> <p>1b. if the source file is unknown, a message is printed on the standard output of the client System.</p> <p>1c. if User does not have write permission in the parent directory, a message is also printed on the standard output of the client System.</p>

Extension of	F1- Execute simple command on one remote machine
Extensions	F2.2.1- Execute an asynchronous move of files

5.1.19 F2.2.1- Execute an asynchronous move of files

Title	F2.2.1- Execute an asynchronous move of files
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.2- Execute an asynchronous copy of files

5.1.20 F2.3- Suspend a file tranfer

Title	F2.3- Suspend a file tranfer
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extensions	F2.3.1- Suspend all files transfer

5.1.21 F2.3.1- Suspend all files transfer

Title	F2.3.1- Suspend all files transfer
Summary	
Actors	Admin
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.3- Suspend a file tranfer

5.1.22 F2.4- List files transfer status

Title	F2.4- List files transfer status
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extensions	F2.4.1- List all files transfer status

5.1.23 F2.4.1- List all files transfer status

Title	F2.4.1- List all files transfer status
Summary	
Actors	Admin
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.4- List files transfer status

5.1.24 F2.5- Display the file transfer history list

Title	F2.5- Display the file transfer history list
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extensions	F2.5.1-Display all file transfer history list

5.1.25 F2.5.1-Display all file transfer history list

Title	F2.5.1-Display all file transfer history list
Summary	
Actors	Admin
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.5- Display the file transfer history list

5.1.26 F2.6- re-submit a suspended file transfer

Title	F2.6- re-submit a suspended file transfer
Summary	
Actors	User
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extensions	F2.6.1- re-submit all suspended file transfer

5.1.27 F2.6.1- re-submit all suspended file transfer

Title	F2.6.1- re-submit all suspended file transfer
-------	---

Summary	
Actors	Admin
Precondition	
Postcondition	
Base sequence	
Branch sequence	
Exception sequence	
Extension of	F2.6- re-submit a suspended file transfer

5.2 Use case diagrams

5.2.1 Change acces modes of files

acces modes of files.png acces modes of files.png

Figure 5.1: Change acces modes of files

5.2.2 Create new directories

new directories.png new directories.png

Figure 5.2: Create new directories

5.2.3 Create new files

new files.png new files.png

Figure 5.3: Create new files

5.2.4 Delete directories

directories.png directories.png

Figure 5.4: Delete directories

5.2.5 Delete files

files.png files.png

Figure 5.5: Delete files

5.2.6 Display Head of files

Head of files.png Head of files.png

Figure 5.6: Display Head of files

5.2.7 Display contents of directories

contents of directories.png contents of directories.png

Figure 5.7: Display contents of directories

5.2.8 Display contents of files

contents of files.png contents of files.png

Figure 5.8: Display contents of files

5.2.9 Display tail of files

tail of files.png tail of files.png

Figure 5.9: Display tail of files

5.2.10 Execute a synchronous copy of files

a synchronous copy of files.png a synchronous copy of files.png

Figure 5.10: Execute a synchronous copy of files

5.2.11 Execute a synchronous tranfer file

a synchronous tranfer file.png a synchronous tranfer file.png

Figure 5.11: Execute a synchronous tranfer file

5.2.12 Execute an asynchronous copy of files

an asynchronous copy of files.png an asynchronous copy of files.png

Figure 5.12: Execute an asynchronous copy of files

5.2.13 Execute an asynchronous tranfer file

an asynchronous tranfer file.png an asynchronous tranfer file.png

Figure 5.13: Execute an asynchronous tranfer file

5.2.14 Execute command on one machine

command on one machine.png command on one machine.png

Figure 5.14: Execute command on one machine

5.2.15 FMS Transfert command use cases

Transfert command use cases.png Transfert command use cases.png

Figure 5.15: FMS Transfert command use cases

5.2.16 FMS simple command use cases

simple command use cases.png simple command use cases.png

Figure 5.16: FMS simple command use cases

5.2.17 Transfer a file between two machines

a file between two machines.png a file between two machines.png

Figure 5.17: Transfer a file between two machines

5.2.18 UseCase Diagram

Diagram.png Diagram.png

Figure 5.18: UseCase Diagram

5.3 Data dictionary

- FMS: File Management System