

# **VISHNU D1.0 - Command line interface specifications**

---

<b>COLLABORATORS</b>
----------------------

	<i>TITLE :</i>  VISHNU D1.0 - Command line interface specifications		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Benjamin Isnard, Daouda Traoré, Eugène Pamba Capo-Chichi, Kevin Coulomb, and Ibrahima Cissé	January 12, 2011	

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME
0	05/01/2011	Formatting example	B.Isnard

# Contents

<b>1</b>	<b>Document presentation</b>	<b>1</b>
1.1	Document objectives . . . . .	1
1.2	Document structure . . . . .	1
1.3	References . . . . .	1
1.4	Glossary . . . . .	1
1.5	Generic command definition format . . . . .	1
<b>2</b>	<b>Commands specification for User Management System (UMS)</b>	<b>3</b>
2.1	Command definitions . . . . .	3
2.1.1	UMS connect . . . . .	3
2.1.2	UMS reconnect . . . . .	3
2.1.3	UMS addVishnuUser . . . . .	4
2.1.4	UMS updateUser . . . . .	4
2.1.5	UMS deleteUser . . . . .	5
2.1.6	UMS close . . . . .	5
2.1.7	UMS changePassword . . . . .	6
2.1.8	UMS resetPassword . . . . .	6
2.1.9	UMS addLocalAccount . . . . .	7
2.1.10	UMS updateLocalAccount . . . . .	7
2.1.11	UMS deleteLocalAccount . . . . .	8
2.1.12	UMS saveConfiguration . . . . .	9
2.1.13	UMS restoreConfiguration . . . . .	9
2.1.14	UMS addMachine . . . . .	9
2.1.15	UMS updateMachine . . . . .	10
2.1.16	UMS deleteMachine . . . . .	11
2.1.17	UMS listLocalAccount . . . . .	11
2.1.18	UMS listMachine . . . . .	12
2.1.19	UMS listHistoryCmd . . . . .	12
2.1.20	UMS listOptions . . . . .	13
2.1.21	UMS listUsers . . . . .	13

---

2.1.22	UMS listSessions . . . . .	14
2.1.23	UMS configureOption . . . . .	15
2.1.24	UMS configureDefaultOption . . . . .	15
2.2	Parameters definitions . . . . .	15
<b>3</b>	<b>Commands specification for Tasks Management System (TMS)</b>	<b>17</b>
3.1	Command definitions . . . . .	17
3.1.1	TMS submitJob . . . . .	17
3.1.2	TMS listJobs . . . . .	18
3.1.3	TMS getJobInfo . . . . .	18
3.1.4	TMS cancelJob . . . . .	19
3.1.5	TMS getJobOutPut . . . . .	19
3.1.6	TMS getAllJobsOutPut . . . . .	20
3.1.7	TMS listQueues . . . . .	20
3.1.8	TMS setMachineEnv . . . . .	21
3.1.9	TMS setMachineRefreshPeriod . . . . .	21
3.1.10	TMS getJobProgress . . . . .	22
3.2	Parameters definitions . . . . .	22
<b>4</b>	<b>Commands specification for Information Management System (IMS)</b>	<b>24</b>
4.1	Command definitions . . . . .	24
4.1.1	IMS exportCommands . . . . .	24
4.1.2	IMS getMetricCurrentValue . . . . .	24
4.1.3	IMS getMetricHistory . . . . .	25
4.1.4	IMS getProcesses . . . . .	25
4.1.5	IMS setSystemInfo . . . . .	26
4.1.6	IMS setSystemThreshold . . . . .	26
4.1.7	IMS getSystemThreshold . . . . .	27
4.1.8	IMS defineUserIdentifier . . . . .	27
4.1.9	IMS defineMachineIdentifier . . . . .	28
4.1.10	IMS defineJobIdentifier . . . . .	28
4.1.11	IMS defineTransferIdentifier . . . . .	29
4.1.12	IMS loadShed . . . . .	29
4.1.13	IMS setUpdateFrequency . . . . .	30
4.1.14	IMS getUpdateFrequency . . . . .	30
4.1.15	IMS restart . . . . .	31
4.2	Parameters definitions . . . . .	31

---

<b>5</b>	<b>API specification for File Management System (FMS)</b>	<b>32</b>
5.1	Command definitions . . . . .	32
5.1.1	FMS createFile . . . . .	32
5.1.2	FMS createDir . . . . .	32
5.1.3	FMS removeFile . . . . .	33
5.1.4	FMS removeDir . . . . .	33
5.1.5	FMS chGrpOfFile . . . . .	34
5.1.6	FMS chModOfFile . . . . .	34
5.1.7	FMS headOfFile . . . . .	35
5.1.8	FMS tailOfFile . . . . .	35
5.1.9	FMS contentOfFile . . . . .	35
5.1.10	FMS listDir . . . . .	36
5.1.11	FMS copyFile . . . . .	36
5.1.12	FMS copyAsyncFile . . . . .	37
5.1.13	FMS moveFile . . . . .	37
5.1.14	FMS moveAsyncFile . . . . .	38
5.1.15	FMS stopFileTransfer . . . . .	38
5.1.16	FMS listFilesTransferStatus . . . . .	39
5.1.17	FMS listFilesTransfer . . . . .	39
5.2	Parameters definitions . . . . .	40

# Chapter 1

## Document presentation

### 1.1 Document objectives

This document presents the detailed specifications of the Vishnu command line user interface.

These specifications include the definition of all commands. ###FIXME###

### 1.2 Document structure

The document is divided into 4 parts corresponding to the 4 modules that compose the Vishnu system:

- UMS: Users Management System
- TMS: Tasks Management System
- FMS: Files Management System
- IMS: Information Management System

Each module corresponds to a chapter in the document, and each chapter contains the following sections:

- A first section describing the definition of all commands provided by the package
- A second section describing the definition of all data types used ###FIXME###

### 1.3 References

TODO - ajouter ref. vers les specs générales

### 1.4 Glossary

### 1.5 Generic command definition format

This section presents the generic format used in the following chapters to describe the commands. It also details the environment variables required and the user options.

---

A commands is defined as follows:

### Access

Here is detailed the access level of the command line (i.e. the privilege required to use this command)

### Description

Here is detailed the purpose of the command line.

### Example of use

Here is detailed an example of the use of the command line which start by optional arguments preceded by a short letter and the required arguments at the end.

myCommand **-l** acLogin **-s** sshKeyPath userId

### Parameters

The following table contains all the input arguments of the command with their type and description, their short letter for options and a required flag.

Parameter	Type	Option	Description	Required
userId	string		This is an example of a required argument	YES
acLogin	string	l	This is an example of an optional argument	NO
sshKeyPath	string	s	This is an example of an optional argument	NO

The following table contains the list of environment variables information, a required flag and a user option flag. The user option flag means that this parameter is a user option that can be define as an environment variable.

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	This is an example of an environment variable	YES	NO

### Note:

For each command line the -h option can be used for help.

## Chapter 2

# Commands specification for User Management System (UMS)

### 2.1 Command definitions

#### 2.1.1 UMS connect

##### Access

This command line can be used by any VISHNU user

##### Description

The connect command line opens a session

##### Example of use

connect **-p** closePolicy **-d** sessionInactivityDelay **-s** substituteUserId userId

##### Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier	YES
password	string		password represents the password of the user, it is an interactive parameter	YES
closePolicy	SessionCloseType	p	is an option for closing session automatically	NO
sessionInactivityDelay	int	d	The sessionInactivityDelay is the maximum delay in seconds between two API commands when the CLOSE_ON_TIMEOUT option is set	NO
substituteUserId	string	s	is an option which allows an admin to open a session as he/she was a specific user identified by his/her userId	NO

##### Environment variables

This command defines no environment variables.

#### 2.1.2 UMS reconnect

##### Access

This command line can be used by any VISHNU user



## Description

The reconnect command line returns the sessionKey of a session in which the user was disconnected previously without closing it

## Example of use

reconnect userId sessionId

## Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier	YES
password	string		password represents the password of the user, it is an interactive parameter	YES
sessionId	string		sessionId is the identifier of the session defined in the database	YES

## Environment variables

This command defines no environment variables.

## 2.1.3 UMS addVishnuUser

### Access

This command line can be used by ADMIN users only

### Description

The addVishnuUser command line adds a new VISHNU user

### Example of use

addVishnuUser -w password -f firstname -l lastname -p privilege -m email userId

### Parameters

Parameter	Type	Option	Description	Required
userId	string		represents the VISHNU user identifier	YES
password	string	w	is the password of the user. At the beginning, an admin can give a temporary password or it is automatically generated by the System.	NO
firstname	string	f	is the firstname of the user	NO
lastname	string	l	is the lastname of the user	NO
privilege	int	p	is the privilege of the user (admin or simple user)	NO
email	string	m	is the email of the user	NO

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.1.4 UMS updateUser

### Access

This command line can be used by ADMIN users only

### Description

The updateUser command line updates the user information except the userId and the password

### Example of use

updateUser **-f** firstname **-l** lastname **-p** privilege **-m** email userId

### Parameters

Parameter	Type	Option	Description	Required
userId	string		represents the VISHNU user identifier of the user whose information will be updated	YES
firstname	string	f	represents the updated firstname of the user	NO
lastname	string	l	represents the updated lastname of the user	NO
privilege	string	p	represents the updated privilege of the user	NO
email	string	m	represents the updated email adress of the user	NO

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.1.5 UMS deleteUser

### Access

This command line can be used by ADMIN users only

### Description

The deleteUser command line removes a user from VISHNU

### Example of use

deleteUser userId

### Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier of the user who will be deleted from VISHNU	YES

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.1.6 UMS close

### Access

This command line can be used by any VISHNU user

#### Description

The close command line closes the session identified by the session key

#### Example of use

close

#### Parameters

This command defines no arguments.

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.7 UMS changePassword

#### Access

This command line can be used by any VISHNU user

#### Description

The changePassword command line changes the password

#### Example of use

changePassword userId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier	YES
password	string		password represents the password of the user, it is an interactive parameter	YES
passwordNew	string		passwordNew represents the new password of the user, it is an interactive parameter	YES

#### Environment variables

This command defines no environment variables.

### 2.1.8 UMS resetPassword

#### Access

This command line can be used by ADMIN users only

#### Description

The resetPassword command line resets the password of a user

#### Example of use

resetPassword userId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier of the user whose password will be reset	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.9 UMS addLocalAccount

#### Access

This command line can be used by any VISHNU user

#### Description

The addLocalAccount command line adds a new local user configuration

#### Example of use

addLocalAccount -l acLogin -s sshKeyPath -d HomeDirectory userId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string		The userId represents the VISHNU user identifier of the user of the local user configuration	YES
machineId	string		The MachineId represents the identifier of the machine associated to the local user configuration	YES
acLogin	string	l	accLogin represents the login of the user on the associated machine	NO
sshKeyPath	string	s	sshKeyPath is the path of the ssh key of the user on the associated machine	NO
HomeDirectory	string	d	HomeDirectory is the path of the home directory of the user on the associated machine	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.10 UMS updateLocalAccount

#### Access

This command line can be used by any VISHNU user

#### Description

The updateLocalAccount command line updates a local user configuration

#### Example of use

updateLocalAccount **-l** acLogin **-s** sshKeyPath **-d** HomeDirectory userId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string		The userId represents the VISHNU user identifier of the user of the local user configuration	YES
machineId	string		The MachineId represents the identifier of the machine associated to the local user configuration	YES
acLogin	string	l	accLogin represents the login of the user on the associated machine	NO
sshKeyPath	string	s	sshKeyPath is the path of the ssh key of the user on the associated machine	NO
HomeDirectory	string	d	HomeDirectory is the path of the home directory of the user on the associated machine	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.11 UMS deleteLocalAccount

#### Access

This command line can be used by any VISHNU user

#### Description

The deleteLocalAccount command line removes a local user configuration (for a given user on a given machine) from VISHNU

#### Example of use

deleteLocalAccount userId machineId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string		userId represents the VISHNU user identifier of the user whose local configuration will be deleted for the given machine	YES
machineId	string		machineId represents the identifier of the machine whose local configuration will be deleted for the given user	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.12 UMS saveConfiguration

#### Access

This command line can be used by ADMIN users only

#### Description

The saveConfiguration command line saves the configuration of VISHNU

#### Example of use

saveConfiguration filePath

#### Parameters

Parameter	Type	Option	Description	Required
filePath	string		The filePath is the path of the file in which the VISHNU configuration will be saved	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.13 UMS restoreConfiguration

#### Access

This command line can be used by ADMIN users only

#### Description

The restoreConfiguration command line restores the configuration of VISHNU

#### Example of use

restoreConfiguration filePath

#### Parameters

Parameter	Type	Option	Description	Required
filePath	string		The filePath is the path of the VISHNU configuration file	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.14 UMS addMachine

#### Access

This command line can be used by ADMIN users only

**Description**

The addMachine command line adds a new machine in VISHNU

**Example of use**

addMachine -n name -s site -t machineDescription -l language machineId

**Parameters**

Parameter	Type	Option	Description	Required
machineId	string		represents the identifier of the machine	YES
name	string	n	represents the name of the machine	NO
site	string	s	represents the location of the machine	NO
machineDescription	string	t	represents the description of the machine	NO
language	string	l	represents the language in which the description of the machine has been done	NO

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

**2.1.15 UMS updateMachine****Access**

This command line can be used by ADMIN users only

**Description**

The updateMachine command line updates machine description

**Example of use**

updateMachine -n name -s site -t machineDescription -l language machineId

**Parameters**

Parameter	Type	Option	Description	Required
machineId	string		represents the identifier of the machine	YES
name	string	n	represents the name of the machine	NO
site	string	s	represents the location of the machine	NO
machineDescription	string	t	represents the description of the machine	NO
language	string	l	represents the language in which the description of the machine has been done	NO

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.1.16 UMS deleteMachine

### Access

This command line can be used by ADMIN users only

### Description

The deleteMachine command line removes a machine from VISHNU

### Example of use

deleteMachine machineId

### Parameters

Parameter	Type	Option	Description	Required
machineId	string		machineId represents the identifier of the machine	YES

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.1.17 UMS listLocalAccount

### Access

This command line can be used by any VISHNU user

### Description

The listLocalAccount command line lists the local user configurations

### Example of use

listLocalAccount -a -u userId -i machineId

### Parameters

Parameter	Type	Option	Description	Required
AdminListOption	boolean	a	is an admin option for listing all local configurations of all users	NO
userId	string	u	is an admin option for listing the local configurations of a specific user	NO
machineId	string	i	is an option for listing local user configurations on a specific machine	NO

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO



### 2.1.18 UMS listMachine

#### Access

This command line can be used by any VISHNU user

#### Description

The listMachine command line lists the machines in which the local user configurations are defined for the given user

#### Example of use

listMachine **-u** userId **-a -m** machineId

#### Parameters

Parameter	Type	Option	Description	Required
userId	string	u	is an admin option for listing machines in which a specific user has a local configuration	NO
listAllmachine	boolean	a	is an option for listing all VISHNU machines	NO
machineId	string	m	is an option for listing information about a specific machine	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.19 UMS listHistoryCmd

#### Access

This command line can be used by any VISHNU user

#### Description

The listHistoryCmd command line lists the commands

#### Example of use

listHistoryCmd **-a -u** userId **-i** sessionId **-s** startDateOption **-e** endDateOption

#### Parameters

Parameter	Type	Option	Description	Required
AdminListOption	boolean	a	is an admin option for listing all commands of all users	NO
userId	string	u	is an admin option for listing commands launched by a specific user identified by his/her userId	NO
sessionId	string	i	lists all commands launched within a specific session	NO
startDateOption	long	s	allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used)	NO
endDateOption	long	e	allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day	NO

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.20 UMS listOptions

#### Access

This command line can be used by any VISHNU user

#### Description

The listOptions command line lists the options of the user

#### Example of use

listOptions **-a -u** userId **-n** optionName

#### Parameters

Parameter	Type	Option	Description	Required
AdminListOption	boolean	a	is an admin option for listing all user options defined in VISHNU	NO
userId	string	u	is an admin option for listing the options of a specific user	NO
optionName	string	n	allows the user to get the value of a specific option identified by its name	NO

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.21 UMS listUsers

#### Access

This command line can be used by ADMIN users only

#### Description

The listUsers command line lists VISHNU users

#### Example of use

listUsers **-i** userIdOption

#### Parameters

Parameter	Type	Option	Description	Required
userIdOption	string	i	allows an admin to get information about a specific user identified by his/her userId	NO

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

**2.1.22 UMS listSessions****Access**

This command line can be used by any VISHNU user

**Description**

The listSessions command line lists all sessions of the user

**Example of use**

listSessions **-t** sessionListOption **-p** sessionClosePolicy **-d** sessionInactivityDelay **-m** machineId **-a -u** userId **-i** sessionId **-s** startDateOption **-e** endDateOption

**Parameters**

Parameter	Type	Option	Description	Required
sessionListOption	SessionStateType	t	specifies the type of the sessions which will be listed (INACTIVE or ACTIVE)	NO
sessionClosePolicy	SessionCloseType	p	specifies the closure mode of the sessions which will be listed (CLOSE_ON_TIMEOUT or CLOSE_ON_DISCONNECT)	NO
sessionInactivityDelay	int	d	specifies the inactivity delay in seconds of the sessions which will be listed	NO
machineId	string	m	allows the user to list sessions opened on a specific machine	NO
AdminListOption	boolean	a	is an admin option for listing all sessions of all users	NO
userId	string	u	is an admin option for listing sessions opened by a specific user	NO
sessionId	string	i	allows the user to list all commands launched within a specific session	NO
startDateOption	long	s	allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used)	NO
endDateOption	long	e	allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day	NO

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.23 UMS configureOption

#### Access

This command line can be used by any VISHNU user

#### Description

The configureOption command line configures an option of the user

#### Example of use

configureOption optionName value

#### Parameters

Parameter	Type	Option	Description	Required
optionName	string		represents the name of an option	YES
value	string		represents the value of an option	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 2.1.24 UMS configureDefaultOption

#### Access

This command line can be used by ADMIN users only

#### Description

The configureDefaultOption command line configures a default option value

#### Example of use

configureDefaultOption optionName value

#### Parameters

Parameter	Type	Option	Description	Required
optionName	string		represents the name of an option	YES
value	string		represents the value of an option	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 2.2 Parameters definitions

Enumeration UMS::SessionCloseType Type

---

Name	Value
CLOSE_ON_TIMEOUT	0
CLOSE_ON_DISCONNECT	1

**Enumeration UMS::SessionStateType Type**

Name	Value
INACTIVE	0
ACTIVE	1

## Chapter 3

# Commands specification for Tasks Management System (TMS)

### 3.1 Command definitions

#### 3.1.1 TMS submitJob

##### Access

This command line can be used by any VISHNU user

##### Description

The submitJob command line submits job on a machine through the use of a script (scriptFilePath). The script is a shell script which will be executed by a command shell such as sh or csh

##### Example of use

submitJob **-n** name **-p** priority **-q** queue **-t** wallTime **-m** memory **-P** nbCpu **-N** nbNodesAndCpuPerNode **-o** OutPutPath **-e** ErrorPath machineId scriptFilePath

##### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Is the id of the machine where the job must be submitted	YES
scriptFilePath	string		The path to the file containing the characteristics (job command, and batch scheduler directive required or optional) of the job to submit.	YES
name	string	n	Assigns a job name. The default is the name of job path.	NO
priority	JobPriority	p	Assigns priority of the job.	NO
queue	string	q	Assigns the queue or class of the job.	NO
wallTime	int	t	The maximum wall-clock time during which the job can run.	NO
memory	int	m	The size of memory that the job will use.	NO
nbCpu	int	P	The number of cpu that the job will use.	NO
nbNodesAndCpuPerNode	string	N	The number of nodes and processors per node.	NO
OutPutPath	string	o	Assigns the path and file for job output.	NO
ErrorPath	string	e	Assigns the path and file for job error.	NO

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.2 TMS listJobs

#### Access

This command line can be used by any VISHNU user

#### Description

The listJobs command line gets a list of all submitted jobs

#### Example of use

listJobs **-i** JobId **-P** nbCpu **-d** fromSubmitDate **-D** toSubmitDate **-u** owner **-s** status **-p** priority **-o** OutPutPath **-e** ErrorPath **-q** queue machineId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES
JobId	string	i	To list job which has this id.	NO
nbCpu	int	P	To list jobs which have this number of cpu.	NO
fromSubmitDate	long	d	List jobs submitted after this date (unix timestamp).	NO
toSubmitDate	long	D	List jobs submitted before this date (unix timestamp)	NO
owner	string	u	To list all jobs submitted by this owner.	NO
status	JobStatus	s	To list jobs which have this status.	NO
priority	JobPriority	p	To list jobs which have this priority	NO
OutPutPath	string	o	Gets the path and file for each job output.	NO
ErrorPath	string	e	Gets the path and file for each job error.	NO
queue	string	q	To list jobs which have this queue name.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.3 TMS getJobInfo

#### Access

This command line can be used by any VISHNU user

#### Description

The getJobInfo command line gets information on a job from it Id

#### Example of use

getJobInfo machineId jobId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES
jobId	string		The id of the job	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.4 TMS cancelJob

#### Access

This command line can be used by any VISHNU user

#### Description

The cancelJob command line cancels a job from its Id

#### Example of use

cancelJob machineId jobId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES
jobId	string		The Id of the job	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.5 TMS getJobOutPut

#### Access

This command line can be used by any VISHNU user

#### Description

The getJobOutPut command line gets outputPath and errorPath of a job from it Id

#### Example of use

getJobOutPut machineId jobId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES
jobId	string		The Id of the job	YES



## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.6 TMS getAllJobsOutPut

#### Access

This command line can be used by any VISHNU user

#### Description

The getAllJobsOutPut command line gets outputPath and errorPath of completed jobs dynamically

#### Example of use

getAllJobsOutPut machineId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.7 TMS listQueues

#### Access

This command line can be used by any VISHNU user

#### Description

The listQueues command line gets queues information

#### Example of use

listQueues machineId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Machine hash key	YES

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.8 TMS setMachineEnv

#### Access

This command line can be used by ADMIN users only

#### Description

The setMachineEnv command line sets environment variables on a remote machine

#### Example of use

```
setMachineEnv machineId listEnv
```

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Represents the machine id	YES
listEnv	string		Represents the list environnement variables	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.9 TMS setMachineRefreshPeriod

#### Access

This command line can be used by ADMIN users only

#### Description

The setMachineRefreshPeriod command line sets the refresh period of output and error file content

#### Example of use

```
setMachineRefreshPeriod machineId value
```

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine	YES
value	int		Is the refresh interval value (in seconds)	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

### 3.1.10 TMS getJobProgress

#### Access

This command line can be used by any VISHNU user

#### Description

The getJobProgress command line get the progression status of jobs

#### Example of use

getJobProgress **-i** jobId **-u** jobOwner machineId

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		Is the id of the machine to get the jobs progression.	YES
jobId	string	i	Represents the id of the job that the user wants to see its progression.	NO
jobOwner	string	u	Represents the owner of the job.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	YES	NO

## 3.2 Parameters definitions

#### Enumeration TMS::JobPriority Type

Name	Value
VERY_LOW	100
LOW	200
NORMAL	300
HIGH	400
VERY_HIGH	500

#### Enumeration TMS::JobStatus Type

Name	Value
RUNNING	0
WAITING	1
COMPLETED	2
CANCELED	3
HELD	4

Name	Value
QUEUED	5
FAILED	6
NOT_SUBMITTED	7

**Enumeration TMS::QueuePriority Type**

Name	Value
VERY_LOW	0
LOW	1
NORMAL	2
HIGH	3
VERY_HIGH	4

**Enumeration TMS::QueueStatus Type**

Name	Value
STARTED	0
RUNNING	1
NOT_STARTED	2
NOT_AVAILABLE	3

## Chapter 4

# Commands specification for Information Management System (IMS)

### 4.1 Command definitions

#### 4.1.1 IMS exportCommands

##### Access

This command line can be used by any VISHNU user

##### Description

The exportCommands command line exports all the commands made by a user during a session

##### Example of use

```
exportCommands oldSessionKey
```

##### Parameters

Parameter	Type	Option	Description	Required
oldSessionKey	string		The key of the session to export (session has ended)	YES

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command (current session key)	YES	NO

#### 4.1.2 IMS getMetricCurrentValue

##### Access

This command line can be used by any VISHNU user

##### Description

The getMetricCurrentValue command line retrieve the current value of a metric on a machine

### Example of use

getMetricCurrentValue machineId metricType

### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine	YES
metricType	MetricType		Type of metric	YES

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

## 4.1.3 IMS getMetricHistory

### Access

This command line can be used by any VISHNU user

### Description

The getMetricHistory command line retrieve the history of values of a metric on a machine

### Example of use

getMetricHistory machineId startTime endTime metricType

### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine	YES
startTime	long		Start time of metric history	YES
endTime	long		End time of metric history	YES
metricType	MetricType		Type of metric	YES

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

## 4.1.4 IMS getProcesses

### Access

This command line can be used by ADMIN users only

### Description

The getProcesses command line gets the list of the processes running over a front machine

### Example of use

getProcesses machineId

## Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine the user wants the running processes	YES

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.5 IMS setSystemInfo

#### Access

This command line can be used by ADMIN users only

#### Description

The setSystemInfo command line updates the system information of a machine

#### Example of use

setSystemInfo machineId **-m** memory **-d** diskSpace

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine	YES
memory	long	m	Amount of RAM memory available on the machine (in Bytes)	NO
diskSpace	long	d	Amount of disk space available on the machine (in KBytes)	NO

## Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.6 IMS setSystemThreshold

#### Access

This command line can be used by ADMIN users only

#### Description

The setSystemThreshold command line sets a threshold on a machine of a system

#### Example of use

setSystemThreshold machineId tresholdType value

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine the user wants to set the treshold over	YES
tresholdType	MetricType		The type of the metric to set	YES
value	double		The treshold value	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.7 IMS getSystemThreshold

#### Access

This command line can be used by ADMIN users only

#### Description

The getSystemThreshold command line gets a System threshold on a machine

#### Example of use

getSystemThreshold machineId type

#### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine the user wants to get the treshold over	YES
type	MetricType		The treshold type desired	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.8 IMS defineUserIdentifier

#### Access

This command line can be used by ADMIN users only

#### Description

The defineUserIdentifier command line defines the shape of the identifiers automatically generated for the users

#### Example of use

defineUserIdentifier format

#### Parameters



Parameter	Type	Option	Description	Required
format	string		The new format to use	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.9 IMS defineMachineIdentifier

#### Access

This command line can be used by ADMIN users only

#### Description

The defineMachineIdentifier command line defines the shape of the identifiers automatically generated for the machines

#### Example of use

defineMachineIdentifier format

#### Parameters

Parameter	Type	Option	Description	Required
format	string		The new format to use	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.10 IMS defineJobIdentifier

#### Access

This command line can be used by ADMIN users only

#### Description

The defineJobIdentifier command line defines the shape of the identifiers automatically generated for the jobs

#### Example of use

defineJobIdentifier format

#### Parameters

Parameter	Type	Option	Description	Required
format	string		The new format to use	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

#### 4.1.11 IMS defineTransferIdentifier

##### Access

This command line can be used by ADMIN users only

##### Description

The defineTransferIdentifier command line defines the shape of the identifiers automatically generated for the file transfers

##### Example of use

defineTransferIdentifier format

##### Parameters

Parameter	Type	Option	Description	Required
format	string		The new format to use	YES

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

#### 4.1.12 IMS loadShed

##### Access

This command line can be used by ADMIN users only

##### Description

The loadShed command line load sheds a machine

##### Example of use

loadShed machineId loadShedType

##### Parameters

Parameter	Type	Option	Description	Required
machineId	string		The id of the machine to stop	YES
loadShedType	LoadShedType		Selects a load shedding mode (SOFT: flushes all services, HARD: stops all services)	YES

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

#### 4.1.13 IMS setUpdateFrequency

##### Access

This command line can be used by ADMIN users only

##### Description

The setUpdateFrequency command line sets the update frequency of the IMS tables

##### Example of use

setUpdateFrequency freq

##### Parameters

Parameter	Type	Option	Description	Required
freq	int		Frequency the data are updated, in second	YES

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

#### 4.1.14 IMS getUpdateFrequency

##### Access

This command line can be used by any VISHNU user

##### Description

The getUpdateFrequency command line gets the update frequency of the IMS database

##### Example of use

getUpdateFrequency

##### Parameters

This command defines no arguments.

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

### 4.1.15 IMS restart

#### Access

This command line can be used by ADMIN users only

#### Description

The restart command line restarts the whole VISHNU infrastructure. Actions are saved and restarted from the beginning once the infrastructure has been restarted

#### Example of use

restart **-n** componentName type

#### Parameters

Parameter	Type	Option	Description	Required
type	RestartType	t	The type of restart desired	YES
componentName	string	n	If not restarting all, the name of the component to restart	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The key of the session of the user that submits the command	YES	NO

## 4.2 Parameters definitions

#### Enumeration IMS::LoadShedType Type

Name	Value
SOFT	0
HARD	1

#### Enumeration IMS::MetricType Type

Name	Value
CPUNBR	0
CPUUSE	1
DISKSPACE	2
FREEDISKSPACE	3
MEMORY	4
FREEMEMORY	5

#### Enumeration IMS::RestartType Type

Name	Value
ALL	0
SED	1
AGENT	2
DAEMON	3
MACHINE	4

## Chapter 5

# API specification for File Management System (FMS)

### 5.1 Command definitions

#### 5.1.1 FMS createFile

##### Access

This command line can be used by any VISHNU user

##### Description

The createFile command line creates files on remote machines.

##### Example of use

createFile **-m** mode path

##### Parameters

Parameter	Type	Option	Description	Required
path	string		The file to create following the pattern [host:]file path.	YES
mode	long	m	the file access permissions in octal system.	NO

##### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

#### 5.1.2 FMS createDir

##### Access

This command line can be used by any VISHNU user

##### Description

The createDir command line creates directories on remote machines.

##### Example of use

createDir **-m** mode path

#### Parameters

Parameter	Type	Option	Description	Required
path	string		The directory to create following the pattern [host:]directory path.	YES
mode	long	m	the new directories permission access in octal system.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.3 FMS removeFile

#### Access

This command line can be used by any VISHNU user

#### Description

The removeFile command line removes files from remote hosts.

#### Example of use

removeFile path

#### Parameters

Parameter	Type	Option	Description	Required
path	string		The file to remove following the pattern [host:]file path.	YES

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.4 FMS removeDir

#### Access

This command line can be used by any VISHNU user

#### Description

The removeDir command line removes directories (and subdirectories ) from remote machines.

#### Example of use

removeDir path

#### Parameters

Parameter	Type	Option	Description	Required
path	string		The directory to remove following the pattern [host:]directory path.	YES

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

**5.1.5 FMS chGrpOfFile****Access**

This command line can be used by any VISHNU user

**Description**

The chGrpOfFile command line changes group owner of remote files.

**Example of use**

chGrpOfFile path group

**Parameters**

Parameter	Type	Option	Description	Required
path	string		The file/directory following the pattern [host:]file path.	YES
group	string		the new group owner of file/directory.	YES

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

**5.1.6 FMS chModOfFile****Access**

This command line can be used by any VISHNU user

**Description**

The chModOfFile command line changes access rights of remote files.

**Example of use**

chModOfFile path mode

**Parameters**

Parameter	Type	Option	Description	Required
path	string		The file/directory following the pattern [host:]file path.	YES
mode	long		the access rights of file/directory in octal system.	YES

**Environment variables**

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

---

### 5.1.7 FMS headOfFile

#### Access

This command line can be used by any VISHNU user

#### Description

The headOfFile command line displays a few first lines of files located on remote machines.

#### Example of use

headOfFile -n nLine path

#### Parameters

Parameter	Type	Option	Description	Required
path	string		The file following the pattern [host:]file path.	YES
nLine	int	n	number of lines to display	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.8 FMS tailOfFile

#### Access

This command line can be used by any VISHNU user

#### Description

The tailOfFile command line displays a few last lines of files located on remote machines

#### Example of use

tailOfFile -n nLine path

#### Parameters

Parameter	Type	Option	Description	Required
path	string		The file following the pattern [host:]file path.	YES
nLine	int	n	number of lines to display	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.9 FMS contentOfFile

#### Access

This command line can be used by any VISHNU user

#### Description

The contentOfFile command line displays content of files located on remote machines



### Example of use

contentOfFile path

### Parameters

Parameter	Type	Option	Description	Required
path	string		The file to display following the pattern [host:]file path.	YES

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

## 5.1.10 FMS listDir

### Access

This command line can be used by any VISHNU user

### Description

The listDir command line displays the contents of remote directory.

### Example of use

listDir **-l -a** path

### Parameters

Parameter	Type	Option	Description	Required
path	string		The directory to list following the pattern [host:]directory path.	YES
longFormat	boolean	l	It specifies the long display format (all available file informations)	NO
allFiles	boolean	a	Allows to display all files including hidden files	NO

### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

## 5.1.11 FMS copyFile

### Access

This command line can be used by any VISHNU user

### Description

The copyFile command line executes a synchronous copy of file.

### Example of use

copyFile **-r -c** transferCommand src dest

### Parameters

Parameter	Type	Option	Description	Required
src	string		The source file to copy following the pattern [host:]file path.	YES
dest	string		The path of the destination file	YES
isRecursive	boolean	r	It specifies when the copy is recursive (case of directory) or not.	NO
transferCommand	TransferCommand	c	the command to use to perform file transfer.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO
VISHNU_TRANSFER_CMD	transferCommand	TransferCommand	the command to use to perform file transfer.	NO	YES

### 5.1.12 FMS copyAsyncFile

#### Access

This command line can be used by any VISHNU user

#### Description

The copyAsyncFile command line executes an asynchronous copy of file.

#### Example of use

copyAsyncFile -r -c transferCommand src dest

#### Parameters

Parameter	Type	Option	Description	Required
src	string		The source file to copy following the pattern [host:]file path.	YES
dest	string		The path of the destination file	YES
isRecursive	boolean	r	It specifies when the copy is recursive (case of directory) or not.	NO
transferCommand	TransferCommand	c	the command to use to perform file transfer.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO
VISHNU_TRANSFER_CMD	transferCommand	TransferCommand	the command to use to perform file transfer.	NO	YES

### 5.1.13 FMS moveFile

#### Access

This command line can be used by any VISHNU user

#### Description

The moveFile command line executes a synchronous move of file.

#### Example of use

moveFile -c transferCommand src dest

#### Parameters

Parameter	Type	Option	Description	Required
src	string		The source file to move following the pattern [host:]file path.	YES
dest	string		The path of the destination file	YES
transferCommand	TransferCommand	c	the command to use to perform file transfer.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO
VISHNU_TRANSFER_CMD	transferCommand	TransferCommand	the command to use to perform file transfer.	NO	YES

### 5.1.14 FMS moveAsyncFile

#### Access

This command line can be used by any VISHNU user

#### Description

The moveAsyncFile command line executes an asynchronous move of file.

#### Example of use

moveAsyncFile -c transferCommand src dest

#### Parameters

Parameter	Type	Option	Description	Required
src	string		The source file to move following the pattern [host:]file path.	YES
dest	string		The path of the destination file	YES
transferCommand	TransferCommand	c	the command to use to perform file transfer.	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO
VISHNU_TRANSFER_CMD	transferCommand	TransferCommand	the command to use to perform file transfer.	NO	YES

### 5.1.15 FMS stopFileTransfer

#### Access

This command line can be used by any VISHNU user

#### Description

The stopFileTransfer command line stops an execution of an set of file transfer.

#### Example of use

stopFileTransfer **-i** transferId **-m** fromMachineId **-u** userId

#### Parameters

Parameter	Type	Option	Description	Required
transferId	string	i	a given transfer id	NO
fromMachineId	string	m	the machine that is the source of the file transfer	NO
userId	string	u	allows an admin to stop file transfers of a specific user	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.16 FMS listFilesTransferStatus

#### Access

This command line can be used by any VISHNU user

#### Description

The listFilesTransferStatus command line displays the status of all files transfer submitted by User.

#### Example of use

listFilesTransferStatus **-i** transferId **-m** fromMachineId **-u** userId

#### Parameters

Parameter	Type	Option	Description	Required
transferId	string	i	a given transfer id	NO
fromMachineId	string	m	the machine that is the source of the file transfer	NO
userId	string	u	allows the admin to list file transfers initiated by a specific user	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

### 5.1.17 FMS listFilesTransfer

#### Access

This command line can be used by any VISHNU user

#### Description

The listFilesTransfer command line displays the history of all files transfer submitted by User.

#### Example of use

listFilesTransfer **-m** fromMachineId **-u** userId **-s** status

#### Parameters

Parameter	Type	Option	Description	Required
fromMachineId	string	m	the machine that is the source of the file transfer	NO
userId	string	u	allows the admin to list file transfers initiated by a specific user	NO
status	Status	s	the file transfer status	NO

#### Environment variables

Name	Parameter	Type	Description	Required	User option
VISHNU_SESSION_KEY	sessionKey	string	The session identifier	YES	NO

## 5.2 Parameters definitions

#### Enumeration FMS::FileType Type

Name	Value
BLOCK	0
CHARACTER	1
DIRECTORY	2
SYMBOLICLINK	3
SCKT	4
FIFO	5
REGULAR	6

#### Enumeration FMS::Status Type

Name	Value
INPROGRESS	0
COMPLETED	1
CANCELLED	2
FAILED	3

#### Enumeration FMS::TransferCommand Type

Name	Value
SCP	0
RSYNC	1