

VISHNU D1.1 - APIs specifications



COLLABORATORS

	<i>TITLE :</i> VISHNU D1.1 - APIs specifications		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Benjamin Isnard, Daouda Traoré, Eugène Pamba Capo-Chichi, Kevin Coulomb, and Ibrahima Cissé	January 12, 2011	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
0	05/01/2011	Formatting example	B.Isnard

Contents

1	Document presentation	1
1.1	Document objectives	1
1.2	Document structure	1
1.3	Generic definition formats presentation	1
1.3.1	Methods definition format	2
1.3.1.1	Generic method definition format	2
1.3.1.2	C++ specific aspects	2
1.3.1.3	Python specific aspects	2
1.3.1.4	Web Services specific aspects	3
1.3.2	Data types definition format	3
1.3.2.1	Generic data definition format	3
1.3.2.2	C++ specific aspects	3
1.3.2.3	Python specific aspects	3
1.3.2.4	Web Services specific aspects	3
1.4	References	3
1.5	Glossary	4
2	API specification for User Management System (UMS)	5
2.1	Definition of the functions of the package	5
2.1.1	Function UMS::connect	5
2.1.2	Function UMS::addVishnuUser	6
2.1.3	Function UMS::updateUser	6
2.1.4	Function UMS::deleteUser	7
2.1.5	Function UMS::close	8
2.1.6	Function UMS::changePassword	8
2.1.7	Function UMS::resetPassword	9
2.1.8	Function UMS::addLocalAccount	9
2.1.9	Function UMS::updateLocalAccount	10
2.1.10	Function UMS::deleteLocalAccount	11
2.1.11	Function UMS::saveConfiguration	11

2.1.12	Function UMS::restoreConfiguration	12
2.1.13	Function UMS::addMachine	13
2.1.14	Function UMS::updateMachine	13
2.1.15	Function UMS::deleteMachine	14
2.1.16	Function UMS::listLocalAccount	14
2.1.17	Function UMS::listMachine	15
2.1.18	Function UMS::listHistoryCmd	16
2.1.19	Function UMS::listOptions	16
2.1.20	Function UMS::listUsers	17
2.1.21	Function UMS::listSessions	18
2.1.22	Function UMS::configureOption	18
2.1.23	Function UMS::configureDefaultOption	20
2.1.24	Function UMS::vishnuInitialize	21
2.1.25	Function UMS::vishnuFinalize	21
2.2	Data types definitions	21
3	API specification for Tasks Management System (TMS)	26
3.1	Definition of the functions of the package	26
3.1.1	Function TMS::submitJob	26
3.1.2	Function TMS::listJobs	27
3.1.3	Function TMS::getJobInfo	28
3.1.4	Function TMS::cancelJob	28
3.1.5	Function TMS::getJobOutPut	29
3.1.6	Function TMS::getAllJobsOutPut	30
3.1.7	Function TMS::listQueues	31
3.1.8	Function TMS::setMachineEnv	31
3.1.9	Function TMS::setMachineRefreshPeriod	32
3.1.10	Function TMS::getJobProgress	32
3.2	Data types definitions	33
4	API specification for Information Management System (IMS)	37
4.1	Definition of the functions of the package	37
4.1.1	Function IMS::exportCommands	37
4.1.2	Function IMS::getMetricCurrentValue	37
4.1.3	Function IMS::getMetricHistory	38
4.1.4	Function IMS::getProcesses	39
4.1.5	Function IMS::setSystemInfo	39
4.1.6	Function IMS::setSystemThreshold	40
4.1.7	Function IMS::getSystemThreshold	40

4.1.8	Function IMS::defineUserIdentifier	41
4.1.9	Function IMS::defineMachineIdentifier	41
4.1.10	Function IMS::defineJobIdentifier	42
4.1.11	Function IMS::defineTransferIdentifier	42
4.1.12	Function IMS::loadShed	43
4.1.13	Function IMS::setUpdateFrequency	43
4.1.14	Function IMS::getUpdateFrequency	44
4.2	Data types definitions	44

5 API specification for File Management System (FMS) 46

5.1	Definition of the functions of the package	46
5.1.1	Function FMS::createFile	46
5.1.2	Function FMS::createDir	47
5.1.3	Function FMS::removeFile	47
5.1.4	Function FMS::removeDir	48
5.1.5	Function FMS::chGrpOfFile	49
5.1.6	Function FMS::chModOfFile	49
5.1.7	Function FMS::headOfFile	50
5.1.8	Function FMS::tailOfFile	51
5.1.9	Function FMS::contentOfFile	51
5.1.10	Function FMS::listDir	52
5.1.11	Function FMS::copyFile	53
5.1.12	Function FMS::copyAsyncFile	53
5.1.13	Function FMS::moveFile	54
5.1.14	Function FMS::moveAsyncFile	55
5.1.15	Function FMS::stopFileTransfer	56
5.1.16	Function FMS::listFilesTransferStatus	56
5.1.17	Function FMS::listFilesTransfer	57
5.1.18	Function FMS::getFilesInfo	57
5.2	Data types definitions	58

Chapter 1

Document presentation

1.1 Document objectives

This document presents the detailed specifications of the Vishnu APIs (Application Programming Interfaces). The following APIs are included in the project:

- C++ API
- Python (v2.x) API
- Web services (WSDL 1.1) API

These specifications include the definition of all methods and all data types in a format that is common to all APIs. Therefore the description is not tied to a particular implementation and all implementations will follow the same logic and will differ only when the language that is used imposes some constraints.

Specific aspects of each implementation language are described in the section 1.3.

1.2 Document structure

The document is divided into 4 parts corresponding to the four modules that compose the Vishnu system:

- UMS: Users Management System
- TMS: Tasks Management System
- FMS: Files Management System
- IMS: Information Management System

Each module corresponds to a chapter in the document, and each chapter contains the following sections:

- A first section describing the definition of all the methods provided by the library
- A second section describing the definition of all the data types provided by the library

1.3 Generic definition formats presentation

This section presents the formats used in the following chapters to describe the methods and data types provided by the libraries. It also details the particular implementation constraints for each language.

1.3.1 Methods definition format

The following paragraphs show how all methods (or "operations" in the Web Services terminology) are specified in this document. First, the generic format used for each Vishnu module is explained, then the aspects that are specific to each implementation language are detailed.

1.3.1.1 Generic method definition format

Parameters

The following table contains all the input and output parameters of the method, along with their type and description, and their optional or required flag.

Parameter	Type	Description	Mode	Required
sessionKey	string	This is an example of a required input parameter	IN	yes
listOfJobs	ListJobs	This is an example of an output parameter	OUT	yes

Access

Here is detailed the access level of the method 'myMethod' (i.e. the privilege required to use this method)

Description

Here is detailed the purpose of the method 'myMethod'

Return Value

Here are detailed the different return codes provided by the method. Please note that these return codes may be implemented differently depending on the language, for example by using an exception mechanism. In all implementations the library will provide a way of mapping the code to a human-readable message that will contain detailed information about the context of the exception that happened.

Name	Description
VISHNU_OK	The service was performed successfully.
TMS_UNKNOWN_MACHINE	This is the human-readable generic message that will be available to the user of the API.

Signature

This shows the C++ signature of the method.

```
int myMethod(const string& sessionKey, ListJobs& listOfJobs);
```

1.3.1.2 C++ specific aspects

- The output parameters will be implemented as references in the method signature.
- The methods will always return an integer with a default value for success.
- The methods will throw exceptions for each error message specified. The exception will contain additional details provided by the server.

1.3.1.3 Python specific aspects

- The output parameters will be implemented as a Python tuple returned by the method.

1.3.1.4 Web Services specific aspects

- The input and output parameters will be implemented as Java Beans: a "Request" bean containing the input parameters and a "Response" bean containing the output parameters.
- The methods will throw exceptions for each error message specified. The exception will contain additional details provided by the server.
- Methods with restricted access (administration) will not be included in the WS API.

1.3.2 Data types definition format

The following paragraphs show how all data types are specified in this document. First, the generic format used for each Vishnu data type is explained, then the aspects that are specific to each implementation language are detailed.

1.3.2.1 Generic data definition format

Class Module::Class Content

Name	Type	Description
Class attribute name	Class attribute type	Description/usage of the attribute

1.3.2.2 C++ specific aspects

- All attributes of the class will be private.
- For each attribute of the class a couple of getter/setter methods will be implemented.
- The string type will be mapped to the C++ STL string type.

1.3.2.3 Python specific aspects

- For each attribute of the class a couple of getter/setter methods will be implemented.
- The string type will be mapped to standard Python strings.

1.3.2.4 Web Services specific aspects

- When a single instance of object is used as input or output parameter, the attributes of the object will be mapped respectively to attributes of the 'Request' or 'Response' Java Bean.
- When multiple instances of object are used as input or output parameter (for example list of machines or list of users) the 'Request' or 'Response' Java Bean will contain a 'data' subclass containing the instances. This follows the standard WSDL/Java mapping for Apache-CXF.

1.4 References

- **UMS.wsdl** : WSDL file for the UMS module
- **TMS.wsdl** : WSDL file for the TMS module
- **FMS.wsdl** : WSDL file for the FMS module
- **IMS.wsdl** : WSDL file for the IMS module

1.5 Glossary



Chapter 2

API specification for User Management System (UMS)

2.1 Definition of the functions of the package

2.1.1 Function UMS::connect

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
userId	string	userId represents the VISHNU user identifier	IN	yes
password	string	password represents the password of the user	IN	yes
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	OUT	yes
options	ConnectOptions	options is an object which encapsulates the options available for the connect method. It allows the user to choose the way for closing the session automatically on TIMEOUT or on DISCONNECT and the possibility for an admin to open a session as he/she was a specific user	IN	no

Description

The connect() function opens a session

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NOT_AUTHENTICATED	Unknown user
UNKNOWN_CLOSURE_MODE	The name of the closure mode is unknown
INCORRECT_TIMEOUT	The value of the timeout is incorrect (negative or higher than the TIMEOUT treshold)
UNKNOWN_USERID	The userId is unknown
NO_ADMIN	The user is not an administrator
INCORRECT_PASSWORD_SIZE	The size of the password is incorrect

Name	Description
INCORRECT_USERID_SIZE	The size of the userId is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int connect(const string& userId, const string& password, string& sessionKey, const ConnectOptions& options=ConnectOptions());
```

2.1.2 Function UMS::addVishnuUser**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
newUser	User	newUser is an object which encapsulates the new user information	IN	yes

Description

The addVishnuUser() function adds a new VISHNU user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
INCORRECT_USERID_SIZE	The size of the userId is incorrect
INCORRECT_PASSWORD_SIZE	The size of the password is incorrect
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
USERID_EXISTING	The userId already exists in the database
INVALID_MAIL_ADRESS	The mail adress is invalid
USERID_REQUIRED	The userId must to be defined
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int addVishnuUser(const string& sessionKey, const User& newUser);
```

2.1.3 Function UMS::updateUser**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
userId	string	represents the VISHNU user identifier of the user whose information will be updated	IN	yes
options	UpdateUserOptions	options is an object which encapsulates user information updated	IN	no

Description

The updateUser() function updates the user information except the userId and the password

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
UNKNOWN_USERID	The userId is unknown
INVALID_MAIL_ADRESS	The mail adress is invalid
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
INCORRECT_USERID_SIZE	The size of the userId is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int updateUser(const string& sessionKey, const string& userId, const UpdateUserOptions& options=UpdateUserOptions());
```

2.1.4 Function UMS::deleteUser

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
userId	string	userId represents the VISHNU user identifier of the user who will be deleted from VISHNU	IN	yes
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes

Description

The deleteUser() function removes a user from VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_USERID	The userId is unknown
NO_ADMIN	The user is not an administrator
INCORRECT_USERID_SIZE	The size of the userId is incorrect

Name	Description
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int deleteUser(const string& userId, const string& sessionKey);
```

2.1.5 Function UMS::close

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes

Description

The close() function closes the session identified by the session key

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
COMMAND_RUNNING	Command(s) is/are running
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int close(const string& sessionKey);
```

2.1.6 Function UMS::changePassword

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
userId	string	userId represents the VISHNU user identifier	IN	yes
password	string	password represents the password of the user	IN	yes
passwordNew	string	passwordNew represents the new password of the user	IN	yes

Description

The changePassword() function changes the password

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NOT_AUTHENTICATED	Unknown user
INCORRECT_USERID_SIZE	The size of the userId is incorrect
INCORRECT_PASSWORD_SIZE	The size of the password is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int changePassword(const string& userId, const string& password, const string& passwordNew);
```

2.1.7 Function UMS::resetPassword

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
userId	string	userId represents the VISHNU user identifier of the user whose password will be reset	IN	yes
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes

Description

The resetPassword() function resets the password of a user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
UNKNOWN_USERID	The userId is unknown
INCORRECT_USERID_SIZE	The size of the userId is incorrect
INCORRECT_PASSWORD_SIZE	The size of the password is incorrect
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int resetPassword(const string& userId, const string& sessionKey);
```

2.1.8 Function UMS::addLocalAccount

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
newAccount	LocalAccount	newAccount is the object which encapsulates the new local user configuration	IN	yes

Description

The addLocalAccount() function adds a new local user configuration

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
LOCAL_ACCOUNT_EXIST	The local account already exists for the given user on the given machine
USERID_REQUIRED	The userId must to be defined
MACHINEID_REQUIRED	The machineId must to be defined
UNKNOWN_USERID	The userId is unknown
UNKNOWN_MACHINE	The machineId is unknown
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int addLocalAccount(const string& sessionKey, const LocalAccount& newAccount);
```

2.1.9 Function UMS::updateLocalAccount**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
LocalAccUpd	LocalAccount	is an object which encapsulates the local user configuration changes except the machineId and the userId	IN	yes

Description

The updateLocalAccount() function updates a local user configuration

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
UNKNOWN_USERID	The userId is unknown
UNKNOWN_MACHINE	The machineId is unknown

Name	Description
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
UNKNOWN_LOCAL_ACCOUNT	The local configuration for the given user on the given machine is unknown
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int updateLocalAccount(const string& sessionKey, const LocalAccount& LocalAccUpd);
```

2.1.10 Function UMS::deleteLocalAccount**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
userId	string	userId represents the VISHNU user identifier of the user whose local configuration will be deleted for the given machine	IN	yes
machineId	string	machineId represents the identifier of the machine whose local configuration will be deleted for the given user	IN	yes
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes

Description

The deleteLocalAccount() function removes a local user configuration (for a given user on a given machine) from VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_LOCAL_ACCOUNT	The local configuration for the given user on the given machine is unknown
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int deleteLocalAccount(const string& userId, const string& machineId, const string& sessionKey);
```

2.1.11 Function UMS::saveConfiguration**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
filePath	string	The filePath is the path of the file in which the VISHNU configuration will be saved	IN	yes
configuration	Configuration	The configuration is an object which encapsulates the configuration description	OUT	yes

Description

The saveConfiguration() function saves the configuration of VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
SAVE_CONFIG_ERROR	A problem occurs during the configuration saving
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int saveConfiguration(const string& sessionKey, const string& filePath, Configuration& configuration);
```

2.1.12 Function UMS::restoreConfiguration

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
configuration	Configuration	The configuration is the object which encapsulates the configuration information	IN	yes

Description

The restoreConfiguration() function restores the configuration of VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
RESTORE_CONFIG_ERROR	A problem occurs during the configuration restoring
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int restoreConfiguration(const string& sessionKey, const Configuration& configuration );
```

2.1.13 Function UMS::addMachine

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
newMachine	Machine	new machine information	IN	yes

Description

The addMachine() function adds a new machine in VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
MACHINE_EXISTING	The machineId already exists in the database
MACHINEID_REQUIRED	The machineId must to be defined
NO_ADMIN	The user is not an administrator
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int addMachine(const string& sessionKey, const Machine& newMachine);
```

2.1.14 Function UMS::updateMachine

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machine	Machine	existing machine information	IN	yes

Description

The updateMachine() function updates machine description

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
MACHINEID_REQUIRED	The machineId must to be defined
UNKNOWN_MACHINE	The machineId is unknown
NO_ADMIN	The user is not an administrator
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int updateMachine(const string& sessionKey, const Machine& machine);
```

2.1.15 Function UMS::deleteMachine

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
machineId	string	machineId represents the identifier of the machine	IN	yes
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes

Description

The deleteMachine() function removes a machine from VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
UNKNOWN_MACHINE	The machineId is unknown
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int deleteMachine(const string& machineId, const string& sessionKey);
```

2.1.16 Function UMS::listLocalAccount

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listLocalAcct	ListLocalAccounts	listLocalAccount is the list of the local user configurations	OUT	yes
options	ListLocalAccOptions	allows an admin to list all local configurations of all users or a simple user to list his/her local user configurations on a specific machine	IN	no

Description

The listLocalAccount() function lists the local user configurations

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_USERID	The userId is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

int listLocalAccount(const string& sessionKey, ListLocalAccounts& listLocalAcct, const ListLocalAccOptions& options=ListLocalAccOptions())

2.1.17 Function UMS::listMachine

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listMachine	ListMachines	listLocalAccount is the list of the local configs	OUT	yes
options	ListMachineOptions	allows a user to list all VISHNU machines or information about a specific machine and an admin to list machines used by a specific user	IN	no

Description

The listMachine() function lists the machines in which the local user configurations are defined for the given user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_USERID	The userId is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.

Name	Description
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int listMachine(const string& sessionKey, ListMachines& listMachine, const ListMachineOptions& options=ListMachineOptions());
```

2.1.18 Function UMS::listHistoryCmd**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listCommands	ListCommands	listCommands is the list of commands	OUT	yes
options	ListCmdOptions	allows the user to list commands by using several optional criteria: a period, specific session and for admin to list all commands of all VISHNU users or commands from a specific user	IN	no

Description

The listHistoryCmd() function lists the commands

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_USERID	The userId is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int listHistoryCmd(const string& sessionKey, ListCommands& listCommands, const ListCmdOptions& options=ListCmdOptions());
```

2.1.19 Function UMS::listOptions**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listOptValues	ListOptionsValues	listOptValues is an object which encapsulates the list of options	OUT	yes
options	ListOptOptions	allows the user to list a specific option or an admin to list all options of the System or to list all options of a specific user	IN	no

Description

The listOptions() function lists the options of the user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
UNKNOWN_USERID	The userId is unknown
UNKNOWN_OPTION	the name of the option is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int listOptions(const string& sessionKey, ListOptionsValues& listOptValues=ListOptionsValues(), const ListOptOptions& options=ListOptOptions());
```

2.1.20 Function UMS::listUsers

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listuser	ListUsers	listuser is the list of users	OUT	yes
userIdOption	string	allows an admin to get information about a specific user identified by his/her userId	IN	no

Description

The listUsers() function lists VISHNU users

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
NO_ADMIN	The user is not an administrator

Name	Description
UNKNOWN_USERID	The userId is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int listUsers(const string& sessionKey, ListUsers& listuser, const string& userIdOption);
```

2.1.21 Function UMS::listSessions

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
listsession	ListSessions	listsession is the list of sessions	OUT	yes
options	ListSessionOptions	allows the user to list sessions using several optional criteria such as: the state of sessions (actives or inactives, by default, all sessions are listed), a period, a specific session or for admin to list all sessions of all users or sessions of a specific user.	IN	no

Description

The listSessions() function lists all sessions of the user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_USERID	The userId is unknown
UNKNOWN_SESSION_OPTION	The name of the session option is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
INCORRECT_DATE_OPTION	The date option is incorrect
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int listSessions(const string& sessionKey, ListSessions& listsession, const ListSessionOptions& options=ListSessionOptions());
```

2.1.22 Function UMS::configureOption

Access

This function can be used by any Vishnu user.

Parameters



Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
optionValue	OptionValue	The optionValue is an object which encapsulates the option information	IN	yes

Description

The configureOption() function configures an option of the user

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
UNKNOWN_OPTION	the name of the option is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int configureOption(const string& sessionKey, const OptionValue& optionValue);
```

2.1.23 Function UMS::configureDefaultOption

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
optionValue	OptionValue	The optionValue is an object which encapsulates the option information	IN	yes

Description

The configureDefaultOption() function configures a default option value

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
NO_ADMIN	The user is not an administrator
UNKNOWN_OPTION	the name of the option is unknown
SESSIONKEY_EXPIRED	The sessionKey is expired. The session is closed.
SESSIONKEY_NOT_FOUND	The sessionKey is unrecognized
DB_ERROR	A problem occurs with the database
UMS_SERVER_NOT_AVAILABLE	The server UMS is not available

Signature

```
int configureDefaultOption(const string& sessionKey, const OptionValue& optionValue);
```

2.1.24 Function UMS::vishnuInitialize

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
configPath	string	configPath is the path of VISHNU configuration file	IN	yes

Description

The vishnuInitialize() function initializes VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
INCORRECT_CFG_PATH	The configuration file path is incorrect

Signature

```
int vishnuInitialize(const string& configPath);
```

2.1.25 Function UMS::vishnuFinalize

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
-----------	------	-------------	------	----------

Description

The vishnuFinalize() function allows a user to go out properly from VISHNU

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully
VISHNU_FINALIZE_ERROR	An error occurs during vishnuFinalize

Signature

```
int vishnuFinalize();
```

2.2 Data types definitions

ConnectOptions Class Content

Name	Type	Description
closePolicy	SessionCloseType	is an option for closing session automatically
sessionInactivityDelay	int	The sessionInactivityDelay is the maximum delay in seconds between two API commands when the CLOSE_ON_TIMEOUT option is set
substituteUserId	string	is an option which allows an admin to open a session as he/she was a specific user identified by his/her userId

SessionCloseType Enumeration Type

Name	Value
CLOSE_ON_TIMEOUT	0
CLOSE_ON_DISCONNECT	1

User Class Content

Name	Type	Description
userId	string	represents the VISHNU user identifier
password	string	is the password of the user. At the beginning, an admin can give a temporary password or it is automatically generated by the System.
firstname	string	is the firstname of the user
lastname	string	is the lastname of the user
privilege	int	is the privilege of the user (admin or simple user)
email	string	is the email of the user

UpdateUserOptions Class Content

Name	Type	Description
firstname	string	represents the updated firstname of the user
lastname	string	represents the updated lastname of the user
privilege	string	represents the updated privilege of the user
email	string	represents the updated email adress of the user

LocalAccount Class Content

Name	Type	Description
userId	string	The userId represents the VISHNU user identifier of the user of the local user configuration
machineId	string	The MachineId represents the identifier of the machine associated to the local user configuration
acLogin	string	accLogin represents the login of the user on the associated machine
sshKeyPath	string	sshKeyPath is the path of the ssh key of the user on the associated machine
HomeDirectory	string	HomeDirectory is the path of the home directory of the user on the associated machine

Configuration Class Content

Name	Type	Description
filePath	string	The filePath is the path of the VISHNU configuration file
listConfUsers	List of User	is the list of users objects

Name	Type	Description
listConfMachines	List of Machine	is a list of machines objects
listConfLocalAccounts	List of LocalAccount	is the list of LocalAccount objects

Machine Class Content

Name	Type	Description
machineId	string	represents the identifier of the machine
name	string	represents the name of the machine
site	string	represents the location of the machine
machineDescription	string	represents the description of the machine
language	string	represents the language in which the description of the machine has been done

ListLocalAccounts Class Content

Name	Type	Description
accounts	List of LocalAccount	is a list of LocalAccount objects which encapsulates local user configurations

ListLocalAccOptions Class Content

Name	Type	Description
AdminListOption	boolean	is an admin option for listing all local configurations of all users
userId	string	is an admin option for listing the local configurations of a specific user
machineId	string	is an option for listing local user configurations on a specific machine

ListMachines Class Content

Name	Type	Description
machines	List of Machine	is a list of machines objects which encapsulates the machines information

ListMachineOptions Class Content

Name	Type	Description
userId	string	is an admin option for listing machines in which a specific user has a local configuration
listAllmachine	boolean	is an option for listing all VISHNU machines
machineId	string	is an option for listing information about a specific machine

ListCommands Class Content

Name	Type	Description
Commands	List of Command	is the list of commands objects

Command Class Content

Name	Type	Description
commandId	string	is the identifier of a command
sessionId	string	The sessionId is the identifier of the session define in the database
machineId	string	The machineId is the identifier of the machine used by the command
cmdDescription	string	cmdDescription is the description of the command
cmdStartTime	long	cmdStartTime is the date of the command beginning (the UNIX timestamps is used)
cmdEndTime	long	cmdEndTime is the date of the command end (the UNIX timestamps is used)

ListCmdOptions Class Content

Name	Type	Description
AdminListOption	boolean	is an admin option for listing all commands of all users
userId	string	is an admin option for listing commands launched by a specific user identified by his/her userId
sessionId	string	lists all commands launched within a specific session
startDateOption	long	allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used)
endDateOption	long	allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day

ListOptionsValues Class Content

Name	Type	Description
optionValues	List of OptionValue	is a list of optionValue objects which encapsulates the optionValue information

OptionValue Class Content

Name	Type	Description
optionName	string	represents the name of an option
value	string	represents the value of an option

ListOptOptions Class Content

Name	Type	Description
AdminListOption	boolean	is an admin option for listing all user options defined in VISHNU
userId	string	is an admin option for listing the options of a specific user
optionName	string	allows the user to get the value of a specific option identified by its name

ListUsers Class Content

Name	Type	Description
users	List of User	is the list of users objects

ListSessions Class Content

Name	Type	Description
sessions	List of Session	is the list of session objects

Session Class Content

Name	Type	Description
sessionId	string	represents the VISHNU session identifier of the session
userId	string	represents the VISHNU user identifier of the user who has opened the session
sessionKey	string	is the key of the session generated by VISHNU
dateLastConnect	long	is the date of the last connection to the session (the UNIX timestamps is used)
dateCreation	long	is the date of the first connection to the session (the UNIX timestamps is used)
dateClosure	long	is the date of the closure of the session (the UNIX timestamps is used)
state	SessionStateType	is the state of the session (ACTIVE OR INACTIVE)
closePolicy	SessionCloseType	is the way to close the session
timeout	long	is the inactivity delay in seconds associated to the CLOSE_ON_TIMEOUT option

SessionStateType Enumeration Type

Name	Value
INACTIVE	0
ACTIVE	1

ListSessionOptions Class Content

Name	Type	Description
sessionListOption	SessionStateType	specifies the type of the sessions which will be listed (INACTIVE or ACTIVE)
sessionClosePolicy	SessionCloseType	specifies the closure mode of the sessions which will be listed (CLOSE_ON_TIMEOUT or CLOSE_ON_DISCONNECT)
sessionInactivityDelay	int	specifies the inactivity delay in seconds of the sessions which will be listed
machineId	string	allows the user to list sessions opened on a specific machine
AdminListOption	boolean	is an admin option for listing all sessions of all users
userId	string	is an admin option for listing sessions opened by a specific user
sessionId	string	allows the user to list all commands launched within a specific session
startDateOption	long	allows the user to organize the commands listed by providing the start date (the UNIX timestamp of the start date is used)
endDateOption	long	allows the user to organize the commands listed by providing the end date (the timestamp of the end date is used). By default, the end date is the current day

Chapter 3

API specification for Tasks Management System (TMS)

3.1 Definition of the functions of the package

3.1.1 Function TMS::submitJob

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Is the id of the machine where the job must be submitted	IN	yes
scriptFilePath	string	The path to the file containing the characteristics (job command, and batch scheduler directive required or optional) of the job to submit.	IN	yes
jobId	string	Is the returned id of the submitted job	OUT	yes
jobPath	string	Is the path to the file containing job characteristics	OUT	yes
options	SubmitOptions	Is an instance of the class SubmitOptions. Each optionnal value is associated to a set operation (e.g: setNbCpu(...)) in the class SubmitOptions. If no set operation is not called on the instance object options, the job is submitted with the options defined in the scriptFilePath. Otherwise the job is submitted with the optionnal values set by the options object and optionnal values defined in the scriptFilePath, but optionnal values set by SubmitOptions object take precedence over those in scriptFilePath. With in the object options or within the scriptFilePath, the last occurrence of an optionnal value takes precedence over earlier occurrence.	IN	no

Description

The submitJob() function submits job on a machine through the use of a script (scriptFilePath). The script is a shell script which will be executed by a command shell such as sh or csh

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully.
TMS_UNKNOWN_MACHINE	The machine is not known.
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_PATH	The path to the file containing the characteristics of the job to submit is not a valid path
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_SUBMIT_SERVICE_NOT_AVAILABLE	Indicates that the service to perform the submit operation is not found.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_QUEUE	Indicates that the specified queue by the user is not known.

Signature

```
int submitJob(const string& sessionKey, const string& machineId, const string& scriptFilePath, string& jobId, string& jobPath,
const SubmitOptions& options=SubmitOptions());
```

3.1.2 Function TMS::listJobs

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
listOfJobs	ListJobs	The constructed object list of jobs	OUT	yes
options	ListJobsOptions	Additional options for jobs listing	IN	no

Description

The listJobs() function gets a list of all submitted jobs

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
VISHNU_OK	The service was performed successfully.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.

Name	Description
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int listJobs(const string& sessionKey, const string& machineId, ListJobs& listOfJobs, const ListJobsOptions& options=ListJobsOptions)
```

3.1.3 Function TMS::getJobInfo**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
jobId	string	The id of the job	IN	yes
jobInfos	Job	The resulting information on the job	OUT	yes

Description

The getJobInfo() function gets information on a job from its Id

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
VISHNU_OK	The service was performed successfully.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int getJobInfo(const string& sessionKey, const string& machineId, const string& jobId, Job& jobInfos);
```

3.1.4 Function TMS::cancelJob**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
jobId	string	The Id of the job	IN	yes
infoMsg	string	The information message	OUT	yes

Description

The cancelJob() function cancels a job from its Id

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
VISHNU_OK	The service was performed successfully.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int cancelJob(const string& sessionKey, const string& machineId, const string& jobId, string& infoMsg);
```

3.1.5 Function TMS::getJobOutPut

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
jobId	string	The Id of the job	IN	yes
outputPath	string	The path of the file containing the output result of the job	OUT	yes
errorPath	string	The path of the file containing the errors that has been occurred during the execution of the job	OUT	yes

Description

The getJobOutPut() function gets outputPath and errorPath of a job from it Id

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
VISHNU_OK	The service was performed successfully.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

int **getJobOutPut**(const string& sessionKey, const string& machineId, const string& jobId, string& outputPath, string& errorPath);

3.1.6 Function TMS::getAllJobsOutPut

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
listOfResults	ListJobResults	Is the list of jobs results	OUT	yes

Description

The getAllJobsOutPut() function gets outputPath and errorPath of completed jobs dynamically

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
VISHNU_OK	The service was performed successfully.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

int **getAllJobsOutPut**(const string& sessionKey, const string& machineId, ListJobResults& listOfResults);

3.1.7 Function TMS::listQueues

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Machine hash key	IN	yes
listofQueues	ListQueues	The list of queues	OUT	yes

Description

The listQueues() function gets queues information

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
TMS_BATCH_SCHEDULER_ERROR	Indicates an error caused by the underlying batch scheduler
TMS_INVALID_RESPONSE	Indicates that the implementation produced a response that does not match the criteria defined by the specification.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_PERMISSION_DENIED	Indicates the requested operation is not allowed for provided user.
VISHNU_OK	The service was performed successfully.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_UNKNOWN_BATCH_SCHEDULER_TYPE	Indicates that the batch scheduler type is not known.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int listQueues(const string& sessionKey, const string& machineId, ListQueues& listofQueues);
```

3.1.8 Function TMS::setMachineEnv

Access

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Represents the machine id	IN	yes
listEnv	string	Represents the list environnement variables	IN	yes

Description

The setMachineEnv() function sets environment variables on a remote machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int setMachineEnv(const string& sessionKey, const string& machineId, const string& listEnv);
```

3.1.9 Function TMS::setMachineRefreshPeriod**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	The id of the machine	IN	yes
value	int	Is the refresh interval value (in seconds)	IN	yes

Description

The setMachineRefreshPeriod() function sets the refresh period of output and error file content

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully.
TMS_UNKNOWN_MACHINE	The machine is not known.

Signature

```
int setMachineRefreshPeriod(const string& sessionKey, const string& machineId, const int& value);
```

3.1.10 Function TMS::getJobProgress**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The sessionKey is the identifier of the session generated by VISHNU	IN	yes
machineId	string	Is the id of the machine to get the jobs progression.	IN	yes
progress	Progression	Is the object containing jobs progression information	OUT	yes
options	ProgressOptions	Is an object containing the available options jobs for progression .	IN	no

Description

The getJobProgress() function get the progression status of jobs

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service was performed successfully.
TMS_INVALID_REQUEST	Indicates that the request is not valid.
TMS_UNKNOWN_MACHINE	The machine is not known.
TMS_INVALID_SESSION_KEY	The session key is not valid to perform the service.
TMS_SERVER_NOT_AVAILABLE	Indicates that the task management server is not available.
TMS_SUBMIT_SERVICE_NOT_AVAILABLE	Indicates that the service to perform the submit operation is not found.

Signature

```
int getJobProgress(const string& sessionKey, const string& machineId, Progression& progress, const ProgressOptions& options=ProgressOptions());
```

3.2 Data types definitions

SubmitOptions Class Content

Name	Type	Description
name	string	Assigns a job name. The default is the name of job path.
priority	JobPriority	Assigns priority of the job.
queue	string	Assigns the queue or class of the job.
wallTime	int	The maximum wall-clock time during which the job can run.
memory	int	The size of memory that the job will use.
nbCpu	int	The number of cpu that the job will use.
nbNodesAndCpuPerNode	string	The number of nodes and processors per node.
OutPutPath	string	Assigns the path and file for job output.
ErrorPath	string	Assigns the path and file for job error.

JobPriority Enumeration Type

Name	Value
VERY_LOW	100
LOW	200
NORMAL	300
HIGH	400
VERY_HIGH	500

ListJobs Class Content

Name	Type	Description
nbJobs	long	Represents the total number of jobs in the list.
nbRunningJobs	long	Represents of running jobs in the list.
nbWaitingJobs	long	Represents the total number of waiting jobs in the list.
jobs	List of Job	Is a list of job information (jobId, jobName, ...).

Job Class Content

Name	Type	Description
sessionId	string	Is the id of the session that contained the job submission command
submitMachineId	string	Is the id of the machine on which the job has been submitted.
submitMachineName	string	Is the name of the machine on which the job has been submitted.
jobId	string	Represents the id to job.
jobName	string	Represents the name assigned to the job.
jobPath	string	Is the path to the file containing job characteristics.
outputPath	string	Is the path to the job output results.
errorPath	string	Is the path to the file containing errors occurred during job's execution.
jobPrio	JobPriority	Represents the job priority.
nbCpus	int	Is the number of cpu used by the job.
jobWorkingDir	string	Indicates the directory where the job has been launched.
status	JobStatus	The current status of the job.
submitDate	long	Date and time when job was submitted (unix timestamp)
endDate	long	Represents the execution end date of the job (unix timestamp)
owner	string	Represents the job owner.
jobQueue	string	Is the name of the queue or class associated to the job.
wallClockLimit	long	Is the maximum wall-clock time during which the job can run (in seconds)
groupName	string	Represents the job owner group name.
jobDescription	string	Is the textual description of the job.
memLimit	int	Represents the memory size limit of the job.
nbNodes	int	Is the total number of nodes used by the job.
nbNodesAndCpuPerNode	string	Is the number of nodes and processors per node used by the job.

JobStatus Enumeration Type

Name	Value
RUNNING	0
WAITING	1
COMPLETED	2
CANCELED	3
HELD	4
QUEUED	5
FAILED	6
NOT_SUBMITTED	7

ListJobsOptions Class Content

Name	Type	Description
JobId	string	To list job which has this id.
nbCpu	int	To list jobs which have this number of cpu.
fromSubmitDate	long	List jobs submitted after this date (unix timestamp).
toSubmitDate	long	List jobs submitted before this date (unix timestamp)
owner	string	To list all jobs submitted by this owner.
status	JobStatus	To list jobs which have this status.
priority	JobPriority	To list jobs which have this priority
OutPutPath	string	Gets the path and file for each job output.
ErrorPath	string	Gets the path and file for each job error.

Name	Type	Description
queue	string	To list jobs which have this queue name.

ListJobResults Class Content

Name	Type	Description
nbJobs	string	Is the number of jobs.
Results	List of JobResult	Represents the list of completed jobs results.

JobResult Class Content

Name	Type	Description
jobId	string	Represents the id of the job.
outputPath	string	Is the path to the job output results.
errorPath	string	Is the path to the file containing errors occurred during job's execution.

ListQueues Class Content

Name	Type	Description
nbQueues	int	Represents the number of queues.
queues	List of Queue	Represents the list of queues.

Queue Class Content

Name	Type	Description
name	string	Is the queue name.
maxJobCpu	int	Is the maximum number of Cpus that a job can use.
maxProcCpu	int	Is the maximum number of Cpus of the queue.
memory	int	Represents the queue memory size.
wallTime	long	Is the total wallTime of the queue.
node	int	Is the maximum number of nodes of the queue.
nbRunningJobs	int	Is the total running jobs in the queue.
nbJobsInQueue	int	Is the total number of jobs in the queue.
state	QueueStatus	Is the status of the queue.
priority	QueuePriority	Represents the priority of the queue.
description	string	Is the queue description.

QueueStatus Enumeration Type

Name	Value
STARTED	0
RUNNING	1
NOT_STARTED	2
NOT_AVAILABLE	3

QueuePriority Enumeration Type

Name	Value
VERY_LOW	0
LOW	1
NORMAL	2
HIGH	3

Name	Value
VERY_HIGH	4

Progression Class Content

Name	Type	Description
jobId	string	Represents the job id.
jobName	string	Represents the job name.
wallTime	int	Represents the job wall time.
startTime	long	Start date and time of the job (unix timestamp)
endTime	long	End date and time of the job (unix timestamp)
percent	double	Represent the job progression.
status	JobStatus	Represents the job status.

ProgressOptions Class Content

Name	Type	Description
jobId	string	Represents the id of the job that the user wants to see its progression.
jobOwner	string	Represents the owner of the job.

Chapter 4

API specification for Information Management System (IMS)

4.1 Definition of the functions of the package

4.1.1 Function IMS::exportCommands

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command (current session key)	IN	yes
oldSessionKey	string	The key of the session to export (session has ended)	IN	yes
filename	string	The path of the output file containing the vishnu shell commands	OUT	yes

Description

The exportCommands() function exports all the commands made by a user during a session

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int exportCommands(const string& sessionKey, const string& oldSessionKey, string& filename);
```

4.1.2 Function IMS::getMetricCurrentValue

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine	IN	yes
metricType	MetricType	Type of metric	IN	yes
metricValue	Metric	Value of the metric	OUT	yes

Description

The `getMetricCurrentValue()` function retrieve the current value of a metric on a machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int getMetricCurrentValue(const string& sessionKey, const string& machineId, const MetricType& metricType, Metric& metricValue);
```

4.1.3 Function `IMS::getMetricHistory`

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine	IN	yes
startTime	long	Start time of metric history	IN	yes
endTime	long	End time of metric history	IN	yes
metricType	MetricType	Type of metric	IN	yes
metricValues	ListMetric	List of metric values	OUT	yes

Description

The `getMetricHistory()` function retrieve the history of values of a metric on a machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

int **getMetricHistory**(const string& sessionKey, const string& machineId, const long& startTime, const long& endTime, const MetricType& metricType, ListMetric& metricValues);

4.1.4 Function IMS::getProcesses**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine the user wants the running processes	IN	yes
process	ListProcesses	The list of the processes on the machine	OUT	yes

Description

The getProcesses() function gets the list of the processes running over a front machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
INVALID_PARAMETER	If a parameter is invalid

Signature

int **getProcesses**(const string& sessionKey, const string& machineId, ListProcesses& process);

4.1.5 Function IMS::setSystemInfo**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine	IN	yes
systemInfo	SystemInfo	Contains system information to store in Vishnu database	IN	yes

Description

The setSystemInfo() function updates the system information of a machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success

Name	Description
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int setSystemInfo(const string& sessionKey, const string& machineId, const SystemInfo& systemInfo);
```

4.1.6 Function IMS::setSystemThreshold**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine the user wants to set the threshold over	IN	yes
thresholdType	MetricType	The type of the metric to set	IN	yes
value	double	The threshold value	IN	yes

Description

The setSystemThreshold() function sets a threshold on a machine of a system

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int setSystemThreshold(const string& sessionKey, const string& machineId, const MetricType& thresholdType, const double& value);
```

4.1.7 Function IMS::getSystemThreshold**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine the user wants to get the threshold over	IN	yes
type	MetricType	The threshold type desired	IN	yes
value	double	The threshold value	OUT	yes

Description

The `getSystemThreshold()` function gets a System threshold on a machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int getSystemThreshold(const string& sessionKey, const string& machineId, const MetricType& type, double& value);
```

4.1.8 Function IMS::defineUserIdentifier**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
format	string	The new format to use	IN	yes

Description

The `defineUserIdentifier()` function defines the shape of the identifiers automatically generated for the users

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
INVALID_PARAMETER	If a parameter is invalid
DBERROR	The database generated an error

Signature

```
int defineUserIdentifier(const string& sessionKey, const string& format);
```

4.1.9 Function IMS::defineMachineIdentifier**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
format	string	The new format to use	IN	yes

Description

The `defineMachineIdentifier()` function defines the shape of the identifiers automatically generated for the machines

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int defineMachineIdentifier(const string& sessionKey, const string& format);
```

4.1.10 Function IMS::defineJobIdentifier**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
format	string	The new format to use	IN	yes

Description

The `defineJobIdentifier()` function defines the shape of the identifiers automatically generated for the jobs

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int defineJobIdentifier(const string& sessionKey, const string& format);
```

4.1.11 Function IMS::defineTransferIdentifier**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
format	string	The new format to use	IN	yes

Description

The `defineTransferIdentifier()` function defines the shape of the identifiers automatically generated for the file transfers

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int defineTransferIdentifier(const string& sessionKey, const string& format);
```

4.1.12 Function IMS::loadShed**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
machineId	string	The id of the machine to stop	IN	yes
loadShedType	LoadShedType	Selects a load shedding mode (SOFT: flushes all services, HARD: stops all services)	IN	yes

Description

The `loadShed()` function load sheds a machine

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
COMPONENT_ERROR	If a component is unavailable
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int loadShed(const string& sessionKey, const string& machineId, const LoadShedType& loadShedType);
```

4.1.13 Function IMS::setUpdateFrequency**Access**

This function can be used by ADMIN users only

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
freq	int	Frequency the data are updated, in second	IN	yes

Description

The setUpdateFrequency() function sets the update frequency of the IMS tables

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int setUpdateFrequency(const string& sessionKey, const int& freq);
```

4.1.14 Function IMS::getUpdateFrequency**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The key of the session of the user that submits the command	IN	yes
freq	int	Frequency the data are updated, in second	OUT	yes

Description

The getUpdateFrequency() function gets the update frequency of the IMS database

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	Error code returned if success
DBERROR	The database generated an error
INVALID_PARAMETER	If a parameter is invalid

Signature

```
int getUpdateFrequency(const string& sessionKey, int& freq);
```

4.2 Data types definitions**MetricType Enumeration Type**

Name	Value
CPUNBR	0
CPUUSE	1
DISKSPACE	2
FREEDISKSPACE	3
MEMORY	4
FREEMEMORY	5

Metric Class Content

Name	Type	Description
type	MetricType	The type of the metric
value	double	The value of the metric
time	int	The timestamp the metric had the value

ListMetric Class Content

Name	Type	Description
metric	List of Metric	The metrics of the list

ListProcesses Class Content

Name	Type	Description
processName	List of string	The processes of the list

SystemInfo Class Content

Name	Type	Description
memory	long	Amount of RAM memory available on the machine (in Bytes)
diskSpace	long	Amount of disk space available on the machine (in KBytes)

LoadShedType Enumeration Type

Name	Value
SOFT	0
HARD	1

Chapter 5

API specification for File Management System (FMS)

5.1 Definition of the functions of the package

5.1.1 Function FMS::createFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session identifier	IN	yes
pathList	StringList	The list of files to create, each path following the pattern [host:]file path.	IN	yes
mode	long	the file access permissions in octal system.	IN	no

Description

The createFile() function creates files on remote machines.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int createFile(const string& sessionKey, const StringList& pathList, const long& mode);
```

5.1.2 Function FMS::createDir

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session identifier	IN	yes
pathList	StringList	The list of directories to create, each path following the pattern [host:]file path.	IN	yes
mode	long	the new directories permission access in octal system.	IN	no

Description

The createDir() function creates directories on remote machines.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed successfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unknown error occurred.

Signature

```
int createDir(const string& sessionKey, const StringList& pathList, const long& mode);
```

5.1.3 Function FMS::removeFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of files to delete, each path following the pattern [host:]file path.	IN	yes

Description

The removeFile() function removes files from remote hosts.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int removeFile(const string& sessionKey, const StringList& pathList);
```

5.1.4 Function FMS::removeDir

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of directories to delete, each path following the pattern [host:]directory path.	IN	yes

Description

The removeDir() function removes directories (and subdirectories) from remote machines.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int removeDir(const string& sessionKey, const StringList& pathList);
```

5.1.5 Function FMS::chGrpOfFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of files , each path following the pattern [host:]file path.	IN	yes
group	string	the new group owner of files/directories.	IN	yes

Description

The chGrpOfFile() function changes group owner of remote files.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int chGrpOfFile(const string& sessionKey, const StringList& pathList, const string& group);
```

5.1.6 Function FMS::chModOfFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of files, each path following the pattern [host:]file path.	IN	yes
mode	long	the access righths of files/directories in octal system.	IN	yes

Description

The chModOfFile() function changes access rights of remote files.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int chModOfFile(const string& sessionKey, const StringList& pathList, const long& mode);
```

5.1.7 Function FMS::headOfFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of files , each path following the pattern [host:]file path.	IN	yes
nLine	int	number of lines to display	IN	no
fileContent	StringList	a buffer in which the first "nline" lines will be stored. The string fileContent[i] represents the firts "nline" of the file located in pathList[i] (0<=i<length(pathList)).	OUT	yes

Description

The headOfFile() function displays a few first lines of files located on remote machines.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed succesfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int headOfFile(const string& sessionKey, const StringList& pathList, const int& nLine, StringList& fileContent);
```

5.1.8 Function FMS::tailOfFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The paths of files, each path following the pattern [host:]file path ..	IN	yes
nLine	int	number of lines to display	IN	no
fileContent	StringList	a buffer in which the last "nLine" lines will be stored. The string fileContent[i] represents the last "nline" of the file located in pathList[i] (0<=i<length(pathList)).	OUT	yes

Description

The tailOfFile() function displays a few last lines of files located on remote machines

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed successfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unkown error occured.

Signature

```
int tailOfFile(const string& sessionKey, const StringList& pathList, const int& nLine, StringList& fileContent);
```

5.1.9 Function FMS::contentOfFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The paths of files to display, each path following the pattern [host:]file path .	IN	yes
fileContent	StringList	a buffer in which the contents of files will be stored. The string fileContent[i] represents the content of the file located in pathList[i] (0<=i<length(pathList)).	OUT	yes

Description

The contentOfFile() function displays content of files located on remote machines

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
VISHNU_OK	The service has been performed successfully.
INVALID_SESSION_KEY	Invalid provided session key.
INVALID_MACHINE_ID	Invalid provided machine identifier.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
FMS_PERMISSION_DENIED	User does not have permission access.
DB_ERROR	A problem occurs with the database.
UNKNOWN_ERROR	an unknown error occurred.

Signature

```
int contentOfFile(const string& sessionKey, const StringList& pathList, StringList& fileContent);
```

5.1.10 Function FMS::listDir

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	The list of directories, each path following the pattern [host:]directory path.	IN	yes
options	LsDirOptions	List of options for the listDir command	IN	no
dirContent	StringList	a buffer in which the contents of the directories will be stored (only file names with short format, all file informations with long format)	OUT	yes

Description

The listDir() function displays the contents of remote directory.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int listDir(const string& sessionKey, const StringList& pathList, const LsDirOptions& options=LsDirOptions(), StringList& dirContent);
```

5.1.11 Function FMS::copyFile**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
machineId	string	The machine identifier	IN	yes
sessionKey	string	The session identifier	IN	yes
src	StringList	The list of source files to copy, each path following the pattern [host:]file path.	IN	yes
dest	string	The path of the destination file	IN	yes
options	CopyFileOptions	the copy options.	IN	no

Description

The copyFile() function executes a synchronous copy of file.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int copyFile(const string& machineId, const string& sessionKey, const StringList& src, const string& dest, const CopyFileOptions& options=CopyFileOptions());
```

5.1.12 Function FMS::copyAsyncFile**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
machineId	string	The machine identifier	IN	yes
sessionKey	string	The session identifier	IN	yes
src	StringList	The list of source files to copy, each path following the pattern [host:]file path.	IN	yes

Parameter	Type	Description	Mode	Required
dest	string	The path of the destination file	IN	yes
options	CopyFileOptions	the copy options.	IN	no
thrRef	LongList	a list of file transfer identifiers	OUT	yes

Description

The copyAsyncFile() function executes an asynchronous copy of file.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

int copyAsyncFile(const string& machineId, const string& sessionKey, const StringList& src, const string& dest, const CopyFileOptions& options=CopyFileOptions(), LongList& thrRef);

5.1.13 Function FMS::moveFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
machineId	string	The machine identifier	IN	yes
sessionKey	string	The session identifier	IN	yes
src	StringList	The list of source files to move, each path following the pattern [host:]file path.	IN	yes
dest	string	The path of the destination file	IN	yes
options	MvFileOptions	the move command options.	IN	no

Description

The moveFile() function executes a synchronous move of file.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.

Name	Description
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int moveFile(const string& machineId, const string& sessionKey, const StringList& src, const string& dest, const MvFileOptions& options=MvFileOptions());
```

5.1.14 Function FMS::moveAsyncFile

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
machineId	string	The machine identifier	IN	yes
sessionKey	string	The session identifier	IN	yes
src	StringList	The list of source files to move, each path following the pattern [host:]file path.	IN	yes
dest	string	The path of the destination file	IN	yes
thrRef	LongList	a list of file transfer identifiers	OUT	yes
options	MvFileOptions	the mv command options.	IN	no

Description

The moveAsyncFile() function executes an asynchronous move of file.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int moveAsyncFile(const string& machineId, const string& sessionKey, const StringList& src, const string& dest, LongList& thrRef, const MvFileOptions& options=MvFileOptions());
```

5.1.15 Function FMS::stopFileTransfer

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session identifier	IN	yes
options	StopFileTransferOptions	the file transfer command options	IN	no

Description

The stopFileTransfer() function stops an execution of an set of file transfer.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unkown error occured.
VISHNU_OK	The service has been performed succesfully.

Signature

```
int stopFileTransfer(const string& sessionKey, const StopFileTransferOptions& options=StopFileTransferOptions());
```

5.1.16 Function FMS::listFilesTransferStatus

Access

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
options	LsFileTransferStatusOptions		IN	no

Description

The listFilesTransferStatus() function displays the status of all files transfer submitted by User.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.

Name	Description
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int listFilesTransferStatus(const LsFileTransferStatusOptions& options=LsFileTransferStatusOptions());
```

5.1.17 Function FMS::listFilesTransfer**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
options	LsFileTransferOptions		IN	no

Description

The listFilesTransfer() function displays the history of all files transfer submitted by User.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int listFilesTransfer(const LsFileTransferOptions& options=LsFileTransferOptions());
```

5.1.18 Function FMS::getFilesInfo**Access**

This function can be used by any Vishnu user.

Parameters

Parameter	Type	Description	Mode	Required
sessionKey	string	The session id	IN	yes
pathList	StringList	the list of file whose inode information will be displayed.	IN	yes
filesinfo	FileStatList	the list of inode.	OUT	yes

Description

The `getFilesInfo()` function displays the information of files.

Return Value

An error code is returned when an error occurs during the execution of the function.

Name	Description
DB_ERROR	A problem occurs with the database.
FMS_INVALID_CFG_FILE	Option unknown in the config file.
FMS_INVALID_OPTION	The option provided is invalid for this service.
FMS_INVALID_PATH	The path provided is invalid.
FMS_PERMISSION_DENIED	User does not have permission access.
FMS_SERVER_UNAVAILABLE	The FMS server is unavailable.
INVALID_MACHINE_ID	Invalid provided machine identifier.
INVALID_SESSION_KEY	Invalid provided session key.
UNKNOWN_ERROR	an unknown error occurred.
VISHNU_OK	The service has been performed successfully.

Signature

```
int getFilesInfo(const string& sessionKey, const StringList& pathList, FileStatList& filesinfo);
```

5.2 Data types definitions**StringList Class Content**

Name	Type	Description
Error	Error	TO DO
listOfStrings	List of string	the dynamic list of strings.

LsDirOptions Class Content

Name	Type	Description
Error	Error	TO DO
longFormat	boolean	TO DO
allFiles	boolean	TO DO

CopyFileOptions Class Content

Name	Type	Description
Error	Error	TO DO
isRecursive	boolean	TO DO
transferCommand	TransferCommand	the command to use to perform file transfer.

TransferCommand Enumeration Type

Name	Value
SCP	0
RSYNC	1

LongList Class Content

Name	Type	Description
Error	Error	TO DO
listOfLongs	List of long	TO DO

MvFileOptions Class Content

Name	Type	Description
Error	Error	TO DO
transferCommand	TransferCommand	the command to use to perform file transfer.

StopFileTransferOptions Class Content

Name	Type	Description
Error	Error	TO DO
transferId	string	a given transfer id
fromMachineId	string	the machine that is the source of the file transfer
userId	string	allows an admin to stop file transfers of a specific user

LsFileTransferStatusOptions Class Content

Name	Type	Description
Error	Error	TO DO
transferId	string	a given transfer id
fromMachineId	string	the machine that is the source of the file transfer
userId	string	allows the admin to list file transfers initiated by a specific user

LsFileTransferOptions Class Content

Name	Type	Description
Error	Error	TO DO
fromMachineId	string	the machine that is the source of the file transfer
userId	string	allows the admin to list file transfers initiated by a specific user
status	Status	the file transfer status

Status Enumeration Type

Name	Value
INPROGRESS	0
COMPLETED	1
CANCELLED	2
FAILED	3

FileStatList Class Content

Name	Type	Description
listOfFileStat	List of FileStat	list of inodes.

FileStat Class Content

Name	Type	Description
Error	Error	TO DO
path	string	TO DO
owner	string	TO DO
group	string	TO DO
uid	long	TO DO
gid	long	TO DO
size	long	TO DO
atime	long	TO DO
mtime	long	TO DO
ctime	long	TO DO
type	FileType	TO DO

FileType Enumeration Type

Name	Value
BLOCK	0
CHARACTER	1
DIRECTORY	2
SYMBOLICLINK	3
SCKT	4
FIFO	5
REGULAR	6