Matched Pairs Analysis

Riley Smith

14 November 2016

$$McNemar's\chi^2 = rac{(n_{21}-n_{12})^2}{n_{21}+n_{12}}$$

Data: data/dep.sav



```
cnt <- array( ## What we want to generate directly from the data ## c(146, 155, 47, 303), \frac{\text{dim} = c(2, 2)}{\text{dimnames} = list(w1dep = c("not", "depressed"), w2dep = } c("not", "depressed")))
cnt
```

 not
 depressed

 not
 146
 47

 depressed
 155
 303

What the results of the McNemar's Test should be:
mcnemar.test(cnt, correct = FALSE)

Table 2: McNemar's Chi-squared test: cnt

Test statistic	df	P value
57.74	1	2.988e-14 * * *

dat <- read.spss("data/dep.sav", to.data.frame = T)
sapply(dat, R.isna) ## THANK YOU!!!! (no NAs to deal with) ##</pre>

w1dep	w2dep	w3dep
0	0	0

```
# ## ... except the factor labels are kind of obnoxious for output... ##
dat <- within(dat, {
    levels(wldep) <- c("not", "depressed")</pre>
```

```
levels(w2dep) <- c("not", "depressed")</pre>
})
names(dat) <- c("T1", "T2", "T3")</pre>
ft <- with(dat, {
    ftable(dat, row.vars = 1, col.vars = 2)
})
ft
```

	"T2"	"not"	"depressed"
"T1"			
"not"		146	155
"depressed"	•	47	303

```
ftc <- matrix(ft, nrow = 2, byrow = T)</pre>
ftc
```

```
ftc.a <- array(ftc, \underline{\text{dim}} = c(2, 2), \underline{\text{dimnames}} = \text{list}(
       \underline{\mathsf{T1}} = \mathbf{c}("\mathsf{not}", "\mathsf{depressed}"),
       \underline{T2} = \mathbf{c}("not", "depressed")))
ftc.a
```


	not	depressed
not	146	47
depressed	155	303

mcnemar.test(ftc.a, correct = FALSE)

Table 7: McNemar's Chi-squared test: ftc.a

Test statistic	df	P value
57.74	1	2.988e-14 * * *

mosaicplot(ftc.a, type = "deviance", las = 2, color = mypal.a75[c(5, 16)])



References1

Allaire, JJ, Joe Cheng, Yihui Xie, Jonathan McPherson, Winston Chang, Jeff Allen, Hadley Wickham, Aron Atkins, and Rob Hyndman. rmarkdown: Dynamic Documents for R, 2016. https://CRAN. R-project.org/package=rmarkdown.

Arnold, Jeffrey B. Ggthemes: Extra Themes, Scales and Geoms for *Ggplot2*, 2016. https://CRAN.R-project.org/package=ggthemes.

Aust, Frederik, and Marius Barth. Papaja: Create APA Manuscripts with RMarkdown, 2015. https://github.com/crsh/papaja.

Boettiger, Carl. knitcitations: Citations for Knitr Markdown Files, 2015. https://CRAN.R-project.org/package=knitcitations.

Chang, Winston. Extrafont: Tools for Using Fonts, 2014. https: //CRAN.R-project.org/package=extrafont.

Daroczi, Gergely, and Roman Tsegelskyi. Pander: An R Pandoc Writer, 2015. https://CRAN.R-project.org/package=pander.

Fox, John, and Sanford Weisberg. An R Companion to Applied Regression. Second. Thousand Oaks CA: Sage, 2011. http://socserv. socsci.mcmaster.ca/jfox/Books/Companion.

Francois, Romain. Bibtex: Bibtex Parser, 2014. https://CRAN. R-project.org/package=bibtex.

Highlight: Syntax Highlighter, 2015. https://CRAN.R-project. org/package=highlight.

Qiu, Yixuan. Showtext: Using Fonts More Easily in RGraphs, 2015. https://CRAN.R-project.org/package=showtext.

Qiu, Yixuan, and others. Sysfonts: Loading System Fonts into R, 2015. https://CRAN.R-project.org/package=sysfonts.

R Core Team. R: A Language and Environment for Statistical Computing. Vienna, Austria: R Foundation for Statistical Computing, 2016. https://www.R-project.org/.

Wickham, Hadley. Ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York, 2009. http://ggplot2.org.

- —. Gtable: Arrange Grobs in Tables, 2016. https://CRAN. R-project.org/package=gtable.
- ——. Scales: Scale Functions for Visualization, 2016. https://CRAN. R-project.org/package=scales.
- -. "The Split-Apply-Combine Strategy for Data Analysis." Journal of Statistical Software 40, no. 1 (2011): 1–29. http://www. istatsoft.org/v40/i01/.
- Tidyr: Easily Tidy Data with Spread() and Gather() Functions, 2016. https://CRAN.R-project.org/package=tidyr.

Wickham, Hadley, and Winston Chang. Devtools: Tools to Make Developing RPackages Easier, 2016. https://CRAN.R-project.org/

¹ Note: This document was created using R-v3.3.2 R Core Team, R, and the following R-packages: base-v3.3. R Core Team, R, bibtex-vo.4. Francois, Bibtex, car-v2.1. Fox and Weisberg, An R Companion to Applied Regression, dplyr-vo.5. Wickham and Francois, Dplyr, DT-vo.2. Xie, DT, extrafontvo.17. Chang, Extrafont, ggplot2-v2.1. Wickham, Ggplot2, knitcitations-v1.o. Boettiger, knitcitations, knitr-v1.14. Xie, Dynamic Documents with R and Knitr, pander-vo.6. Daroczi and Tsegelskyi, Pander, papaja-vo.1. Aust and Barth, Papaja, plyr-v1.8. Wickham, "The Split-Apply-Combine Strategy for Data Analysis.", rmarkdown-v1.1. Allaire et al., rmarkdown, scales-vo.4. Wickham, Scales, tidyr-vo.6. Wickham, Tidyr, ggthemes-v3.2. Arnold, Ggthemes, gtablevo.2. Wickham, Gtable, kableExtra-vo.o. Zhu, KableExtra, tufte-vo.2. Xie and Allaire, Tufte, devtools-v1.12. Wickham and Chang, Devtools, highlight-vo.4. Francois, Highlight, sysfonts-vo.5. Qiu and others, Sysfonts, and showtext-vo.4. Oiu. Showtext

package=devtools.

Wickham, Hadley, and Romain Francois. Dplyr: A Grammar of Data Manipulation, 2015. https://CRAN.R-project.org/package=dplyr. Xie, Yihui. DT: A Wrapper of the Javascript Library Datatables, 2015. https://CRAN.R-project.org/package=DT.

-. Dynamic Documents with R and Knitr. 2nd ed. Boca Raton, Florida: Chapman; Hall/CRC, 2015. http://yihui.name/knitr/. Xie, Yihui, and JJ Allaire. Tufte: Tufte's Styles for Rmarkdown Documents, 2016. https://CRAN.R-project.org/package=tufte. Zhu, Hao. KableExtra: Decorate Kable Output Using Pipe Syntax,

2016. https://github.com/haozhu233/kableExtra.