Maximum Likelihood Estimation (MLE)

Riley Smith

14 Nov 2016

Binomial Probability Estimation

$$P(Y = k; n, \pi) = \binom{n}{k} \pi^k (1 - \pi)^{n-k}$$

For MLE, the first term on the right side of the *binomial coefficient*[$^{\t}$] is ignored, as it does not inform the estimation of π , which is what MLE is interested in finding. The rest of the right side of the *binomial estimation* is the "*kernel*" in MLE^1 .



```
par(family = "ETBembo")
eq.pbn <- expression(paste("P(", Y == k, "; n,", pi, ") = ",
                              bgroup("(", atop(n, x), ")"), pi^k,
                              " (", 1 - pi^{n - k}, ")"))
x5 < - for (n in 0:5) choose(n, k = 0:n) ## n = 10 ##
\times 10 < - seq(1:10) \# n = 10 \#
\times 100 < - seq(1:100) \# n = 100 \#
ppi <- 0.5
nk < -c(5, 10, 100)
x1 \leftarrow matrix(c(0:5, dbinom(0:5, 5, 0.5)), ncol = 2,
              dimnames = list(NULL, c("n", "P")))
h.bn \leftarrow function(n, p, ...) {
         k < -0:n
         p \leftarrow dbinom(k, n, p)
         names(p) <- as.character(0:n)</pre>
}
h.bn(5, 0.5)
```


See Newsom 2016-CDA Handout-4


¹ Agresti, Catagorical Data Analysis; Eliason, Maximum Likelihood Estimation; Fisher, "Contributions to Mathematical Statistics."; Myung, "Tutorial on Maximum Likelihood Estimation." R-Code Source

eq.pbn(): Binomial Probability Equation

h.bn(): Plot a relative frequency histogram of the binomial distribution

```
R? -
 clinton <- c(22, 40, 11, 33, 27, 30, 25, 25, 20, 19, 44, 27,
               28, 30, 34, 24, 28, 29, 31, 19, 24, 29, 33, 32, 25)
 k <- clinton
 n <- 50
 p < - k/n
   0.44, 0.8, 0.22, 0.66, 0.54, 0.6, 0.5, 0.5, 0.4, 0.38, 0.88, 0.54, 0.56, 0.6,
 0.68, 0.48, 0.56, 0.58, 0.62, 0.38, 0.48, 0.58, 0.66, 0.64 and 0.5
 ll <- function(p) sum(dbinom(k, n, p, log = TRUE))</pre>
 p.sq <- seq(0.01, 0.99, 0.01)
 p.sql <- sapply(p.sq,ll)</pre>
 par(family = "ETBembo", pch = 20);
 plot(p.sq, p.sql, type = "l", xlab = "x", ylab = "y",
     main = "CDF - Hillary Clinton")
 hist(p, freq = TRUE, xlab = "x", ylab = "y", col = mypal[16])
```





References²

Agresti, Alan. Catagorical Data Analysis. Third Edition. New York, NY: Wiley & Sons, 2013.

Allaire, JJ, Joe Cheng, Yihui Xie, Jonathan McPherson, Winston Chang, Jeff Allen, Hadley Wickham, Aron Atkins, and Rob Hyndman. rmarkdown: Dynamic Documents for R, 2016. https://CRAN. R-project.org/package=rmarkdown.

Arnold, Jeffrey B. Ggthemes: Extra Themes, Scales and Geoms for *Ggplot2*, 2016. https://CRAN.R-project.org/package=ggthemes.

Aust, Frederik, and Marius Barth. Papaja: Create APA Manuscripts with RMarkdown, 2015. https://github.com/crsh/papaja.

Boettiger, Carl. knitcitations: Citations for Knitr Markdown Files, 2015. https://CRAN.R-project.org/package=knitcitations.

Chang, Winston. Extrafont: Tools for Using Fonts, 2014. https: //CRAN.R-project.org/package=extrafont.

Daroczi, Gergely, and Roman Tsegelskyi. Pander: An R Pandoc Writer, 2015. https://CRAN.R-project.org/package=pander.

Eliason, Scott R. Maximum Likelihood Estimation: Logic and Practice. Vol. 96. Thousand Oaks, CA: SAGE Publications, 1993.

Fisher, Ronald Aylmer. "Contributions to Mathematical Statistics." 1950.

François, Romain. *Bibtex: Bibtex Parser*, 2014. https://CRAN. R-project.org/package=bibtex.

Highlight: Syntax Highlighter, 2015. https://CRAN.R-project. org/package=highlight.

Myung, In Jae. "Tutorial on Maximum Likelihood Estimation." Journal of Mathematical Psychology 47, no. 1 (2003): 90–100.

Qiu, Yixuan. Showtext: Using Fonts More Easily in RGraphs, 2015. https://CRAN.R-project.org/package=showtext.

Qiu, Yixuan, and others. Sysfonts: Loading System Fonts into R, 2015. https://CRAN.R-project.org/package=sysfonts.

R Core Team. R: A Language and Environment for Statistical Computing. Vienna, Austria: R Foundation for Statistical Computing, 2016. https://www.R-project.org/.

Wickham, Hadley. Ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York, 2009. http://ggplot2.org.

——. Gtable: Arrange Grobs in Tables, 2016. https://CRAN. R-project.org/package=gtable.

———. Scales: Scale Functions for Visualization, 2016. https://CRAN. R-project.org/package=scales.

——. "The Split-Apply-Combine Strategy for Data Analysis." *Journal of Statistical Software* 40, no. 1 (2011): 1–29. http://www.

² Note: This document was created using R-v3.3.2 R Core Team, R, and the following R-packages: base-v3.3. R Core Team, R, bibtex-vo.4. Francois, Bibtex, dplyr-vo.5. Wickham and Francois, Dplyr, DT-vo.2. Xie, DT, extrafontvo.17. Chang, Extrafont, ggplot2-v2.1. Wickham, Ggplot2, knitcitations-v1.o. Boettiger, knitcitations, knitr-v1.14. Xie, Dynamic Documents with R and Knitr, pander-vo.6. Daroczi and Tsegelskyi, Pander, papaja-vo.1. Aust and Barth, Papaja, plyr-v1.8. Wickham, "The Split-Apply-Combine Strategy for Data Analysis.", rmarkdown-v1.1. Allaire et al., rmarkdown, scales-vo.4. Wickham, Scales, tidyr-vo.6. Wickham, Tidyr, ggthemes-v3.2. Arnold, Ggthemes, gtablevo.2. Wickham, Gtable, kableExtra-vo.o. Zhu, KableExtra, tufte-vo.2. Xie and Allaire, Tufte, devtools-v1.12. Wickham and Chang, Devtools, highlight-vo.4. Francois, Highlight, sysfonts-vo.5. Qiu and others, Sysfonts, and showtext-vo.4. Qiu, Showtext

jstatsoft.org/v40/i01/.

———. Tidyr: Easily Tidy Data with Spread() and Gather() Functions, 2016. https://CRAN.R-project.org/package=tidyr.

Wickham, Hadley, and Winston Chang. Devtools: Tools to Make Developing RPackages Easier, 2016. https://CRAN.R-project.org/ package=devtools.

Wickham, Hadley, and Romain Francois. Dplyr: A Grammar of Data Manipulation, 2015. https://CRAN.R-project.org/package=dplyr.

Xie, Yihui. DT: A Wrapper of the Javascript Library Datatables, 2015. https://CRAN.R-project.org/package=DT.

——. Dynamic Documents with R and Knitr. 2nd ed. Boca Raton, Florida: Chapman; Hall/CRC, 2015. http://yihui.name/knitr/. Xie, Yihui, and JJ Allaire. Tufte: Tufte's Styles for Rmarkdown Documents, 2016. https://CRAN.R-project.org/package=tufte.

Zhu, Hao. KableExtra: Decorate Kable Output Using Pipe Syntax, 2016. https://github.com/haozhu233/kableExtra.