

Bộ môn: Kỹ Thuật Phần Mềm

---

# Lập trình WWW *Java*




# Spring DI (Dependency Injection)



## The dependency inversion principle

The client delegates to call to another object the responsibility of providing its dependencies.

# Coding Scenario




# Coding Scenario



Primary functions of Spring Container:

- » **Create** and **manage** objects (IoC)
- » **Inject** object's **dependencies** (DI)



Can we use IoC to create dependence object?

There are many types of injections with Spring. We will cover two most common:

- » **Constructor Injection**
- » **Setter Injection**

- » **Define** the **dependency interface** and **Class**
- » **Create** a **constructor** in **your class** for injection
- » **Configure** the **dependency** injection in Spring config file

# Step 1: Define the dependency Interface and Class



File: *FortuneService.java*

```
public interface FortuneService  
    public String getFortune();  
}
```

File: *HappyFortuneService.java*

```
public class HappyFortuneService implements FortuneService {  
    @Override  
    public String getFortune() {  
        return "Today is your lucky day!";  
    }  
}
```



## Step 2: Create a constructor in your class for injection



File: *BaseballCoach.java*

```
public class BaseballCoach implements Coach{  
    //define a private field for dependency  
    private FortuneService fortuneSevice;  
    //define a constructor for denpendency injection  
    public BaseballCoach(FortuneService theFortuneService ) {  
        fortuneSevice= theFortuneService;  
    }  
    ...  
}
```

**Define  
field**

**Define  
constructor**

## Step 3: Configure the dependency injection in Spring config file



File: *ApplicationContext.xml*

```
<bean id="myFortune"  
      class="com.se.springdemo.libs.HappyFortuneService">  
</bean>  
<bean id="myCoach"  
      class="com.se.springdemo.libs.BaseballCoach">  
  <constructor-arg ref = "myFortune" />  
</bean>
```

**Define  
dependency/helper**

**inject the  
dependency/helper using  
constructor injection**

**Inject dependencies** by calling  
**setter methods** on your class

- » **Create setter method(s)** in your class for **injection**
- » **Configure** the **dependency** injection in Spring config file

# Step 1: Create setter method(s) in your class for injection



File: *CricketCoach.java*

```
public class CricketCoach implements Coach {  
    private FortuneService fortuneService;  
    public void setFortuneService(FortuneService fortuneSevice) {  
        this.fortuneService = fortuneSevice; }  
}
```


called by Spring  
during setter  
injection

## Step 2: Configure the dependency injection in Spring config file




File: *applicationContext.xml*

```
<bean id="myFortune"
      class="com.se.springdemo.libs.HappyFortuneService">
</bean>
<bean id="myCricketCoach"
      class="com.se.springdemo.libs.CricketCoach" >
  <property name="fortuneService" ref="myFortune" />
</bean>
```


A diagram illustrating the configuration of dependency injection in an XML file. A red arrow originates from the 'myFortune' bean definition and points to the 'ref="myFortune"' attribute within the 'myCricketCoach' bean's property definition. A blue arrow originates from the 'fortuneService' attribute within the 'myCricketCoach' bean's property definition and points to the 'fortuneService' field in the Java code block below.

File: *CricketCoach.java*

```
public class CricketCoach implements Coach {
  private FortuneService fortuneService;
  public void setFortuneService(FortuneService fortuneSevice) {
    this.fortuneService = fortuneSevice; }
}
```

A diagram illustrating the implementation of dependency injection in a Java class. A blue arrow originates from the 'fortuneService' field in the 'CricketCoach' class and points to the 'fortuneService' attribute within the 'myCricketCoach' bean's property definition in the XML block above. A red arrow originates from the 'setFortuneService' method in the 'CricketCoach' class and points to the 'fortuneService' field in the same class.

# Injecting Literal Values



- » **Create setter method(s)** in your class for **injection**
- » **Configure** the **dependency** injection in Spring config file



# Step 1: Create setter method(s) in your class for injection



File: *CricketCoach.java*

```
public class CricketCoach implements Coach {  
    private String emailAddress;  
    private String team;  
    public void setEmailAddress(String mailAddress) { ...4 lines }  
    public void setTeam(String team) { ...4 lines }
```

Create private  
fields

Create setter  
methods

## Step 2: Configure the dependency injection in Spring config file



File: *applicationContext.xml*

```
<bean id="myFortune"
      class="com.se.springdemo.libs.HappyFortuneService">
</bean>
<bean id="myCricketCoach"
      class="com.se.springdemo.libs.CricketCoach" >
  <property name="fortuneService" ref="myFortune" />
  <property name="emailAddress" value="ThegoodCoach@se.com " />
  <property name="team" value="India National" />
</bean>
```

File: *CricketCoach.java*

```
public class CricketCoach implements Coach {
  private String emailAddress;
  private String team;
  public void setEmailAddress(String mailAddress) { ...4 lines }
  public void setTeam(String team) { ...4 lines }
```

# Injecting Literal Values from Properties File



Email:  
Team:



Properties file

FortuneSevice

CricketCoach

```
public class CricketCoach implements Coach {  
    private String emailAddress;  
    private String team;  
    private FortuneService fortuneService;  
}
```

- » **Create properties file**
- » **Load Properties File in Spring config file**
- » **Reference values from Properties File**

# Step 1: Create Properties File



File: *sport.properties*

```
foo.email=TheCricketCoach@se.com  
foo.team=West Indies cricket team
```

**Name**

**Value**

## Step 2: Load Properties File in Spring config file



**File name**

File: *applicationContext.xml*

```
<context:property-placeholder location="classpath:sport.properties" />
```

## Step 3: Reference values from Properties File



File: *applicationContext.xml*

```
<bean id= "myCricketCoach"  class="com.se.spring.soc.libs.CricketCoach"
    <property name="fortuneService" ref="myFortune" />
    <property name="emailAddress" value="${foo.email}" />
    <property name="team" value="${foo.team}" />
    <!-- <property name="emailAddress" value="ThegoodCoach@se.com " />
        <property name="team" value="India National" />-->
</bean>
```

**`${property  
name}`**

`foo.email=TheCricketCoach@se.com`  
`foo.team=West Indies cricket team`



# QUESTIONS