

Bộ môn: Kỹ Thuật Phần Mềm

Lập trình WWW *Java*




Spring IoC (Inversion of Control)



Outsource to an object factory

The approach of outsourcing the construction and management of Objects


IoC – Coding Scenario




- » Easily change the **coach** for other sport **Hockey, Cricket, Tennis** etc.
- » The app should be **configurable**




- » The app should be **configurable** (I don't want to edit code in **MyApp** class)
- » **Ideal solution**






Primary functions:

- » **Create** and **manage** objects (IoC)
- » **Inject** object's **dependencies** (DI)



- » **XML configuration file**
- » **Java Annotations**
- » **Java Source Code**



- » **Configuring** your Spring beans
- » **Creating** a Spring container
- » **Retrieving** the beans from the container

Spring

**Object
Factory**



Step 1: Configuring your Spring beans



File: applicationContext.xml:

```
<beans>
    <bean id="myCoach"
        class="com.se.springdemo.BaseballCoach">
    </bean>
</beans>
```

Spring container is generally known as an **ApplicationContext**
Specialized implimentations:

- » `ClassPathXmlApplicationContext` ~ xml
- » `AnnotationConfigApplicationContext` ~ Annotaion
- » `GenericWebApplicationContext` ~ Java source code

Step 2: Creating a Spring Container



```
import org.springframework.context.support.ClassPathXmlApplicationContext;
public class SpringHelloApp {
    public static void main(String[] args) {
        // load the spring configuration file
        ClassPathXmlApplicationContext context=
            new ClassPathXmlApplicationContext
                ("applicationContext.xml");
        //retrieve bean from spring container
        Coach theCoach= context.getBean("myCoach",Coach.class);
        //call method on the bean
        System.out.println(theCoach.getDailyWorkout());
        //System.out.println(theCoach.getFortune());
        //close the context
        context.close();
    }
```

Step 3: Retrieving the beans from the container



```
import org.springframework.context.support.ClassPathXmlApplicationContext;
public class SpringHelloApp {
    public static void main(String[] args) {
        // load the spring configuration file
        ClassPathXmlApplicationContext context=
            new ClassPathXmlApplicationContext
                ("applicationContext.xml")
        //retrieve bean from spring container
        Coach theCoach= context.getBean("myCoach",Coach.class);
        //call method on the bean
    }
}
```

Interface

Implement class

```
<beans>
  <bean id="myCoach"
        class="com.se.springdemo.BaseballCoach">
  </bean>
</beans>
```

How to change another coach



Only change the implementation class (spring bean) in the config file

```
<bean id="myCoach"  
      class="com.se.springdemo.BaseballCoach">  
</bean>
```

Change to

```
<bean id="myCoach"  
      class="com.se.springdemo.TrackCoach">  
</bean>
```



QUESTIONS