

Lappeenranta University of Technology
Faculty of Industrial Engineering and Management
Degree Program in Computer Science

Bachelor's Thesis

Teemu Huovinen

SENSITIVITY OF RETINAL IMAGE SEGMENTATION ON GROUND TRUTH ACCURACY

Examiners: Lasse Lensu D.Sc. (Tech.)

Supervisor: Lasse Lensu D.Sc. (Tech.)

ABSTRACT

Lappeenranta University of Technology
Faculty of Industrial Engineering and Management
Degree Program in Computer Science

Teemu Huovinen

Sensitivity of retinal image segmentation on ground truth accuracy

Bachelor's Thesis

2014

27 pages, 64 figures, 1 table, and 2 appendices.

Examiners: Lasse Lensu D.Sc. (Tech.)

Keywords: eye fundus, image segmentation, sensitivity analysis, ground truth

Notice that the page, figure, table and appendix counts are for the whole work, including title page, appendices, figures in appendices, etc. You have to count the numbers yourself, except for pages. Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

TIIVISTELMÄ

Lappeenrannan teknillinen yliopisto
Tuotantotalouden tiedekunta
Tietotekniikan koulutusohjelma

Teemu Huovinen

Silmänpohjakuvien segmentoinnin herkkyys pohjamerkintöjen tarkkuudelle

Kandidaatin työ

2014

27 sivua, 64 kuvaa, 1 taulukko ja 2 liitettä.

Tarkastajat: TKT Lasse Lensu

Hakusanat: silmänpohja, segmentointi, herkkyysanalyysi, pohjamerkintä
Keywords: eye fundus, image segmentation, sensitivity analysis, ground truth

Tähän kirjoitetaan ytimekäs tiivistelmä: tausta, tavoite, tulokset ja johtopäätökset. Tiivistelmässä kannattaa käyttää lyhyen nasevia lauseita. Itse tekstissä voi käyttää monimutkaisempia lauseita. Tiivistelmä-sivu on yksi sivu ja tiivistelmäteksti on yksi kappale, ei useita kappaleita. On hyvä kertoa työn tavoitteet. Mikäli työ sisältää oleellisia aiheen rajauksia, ne kannattaa mainita jo tiivistelmässä. Työn tulokset ja johtopäätökset luetellaan lukijan mielenkiinnon lisäämiseksi. Opinnäytetyö kirjoitetaan passiivissa tyyliin “tässä työssä tutkitaan..” aktiivin sijaan “minä tutkin...” ja marginaalit tasataan aina sekä vasemmalle että oikealle. Työn numerointi aloitetaan kansilehdeltä, mutta tätä roomalaista numeroa ei merkitä näkyviin.

PREFACE

Tässä voidaan mainita työn tekopaikka, kiittää työtä tukeneita henkilöitä ja muita tahoja, jne. tyyliin “Työ on tehty Lappeenrannan teknillisen yliopiston ... Kiitän työkavereita ja rakasta vaimoani tuesta ...”

Lappeenranta, October 19th, 2014

Teemu Huovinen

CONTENTS

1	INTRODUCTION	7
1.1	Background	7
1.2	Objectives and Restrictions	7
1.3	Structure of the Thesis	8
2	SEGMENTATION OF RETINAL IMAGES	9
2.1	Structure of the eye fundus	9
2.2	Optic disc detection	9
2.3	Blood vessel detection	10
2.4	Color transform	12
2.5	Unsupervised methods	12
2.6	Supervised methods	13
3	SENSITIVITY ANALYSIS OF IMAGE FEATURES	15
3.1	Evaluation methods	15
3.2	Effects of inaccurate ground truth	16
4	EXPERIMENTS AND RESULTS	17
4.1	Retinal Image Databases	17
4.2	The Ground Truth	17
4.3	Experiment 1	18
4.4	Experiment 2	18
5	DISCUSSION	19
5.1	Segmentation Results	19
5.2	Sensitivity of Image Features	19
5.3	Future Work	19
6	CONCLUSIONS	20
	REFERENCES	21
	APPENDICES	
	Appendix 1: Appendix Guidelines	
	Appendix 2: Frame Schematics	
	Appendix 3: The Second	

ABBREVIATIONS AND SYMBOLS

RGB	Red Green Blue
TP	True Positive
TN	True Negative
FP	False Positive
FN	False Negative
FPR	False Positive Rate
FNR	False Negative Rate
CLAHE	Contrast Limited Adaptive Histogram Equalization

1 INTRODUCTION

1.1 Background

The growing amount of diabetes patients and (arguably) more importantly the estimated amount of undiagnosed patients motivate the research for an effective mass screening method for early detection of diabetes. Diabetic retinopathy is a complication of diabetes that causes abnormalities in the eye, and detecting these abnormalities in the eye fundus is a promising mass screening method. Images where ophthalmologists have marked these abnormalities, such as exudates, are used as ground truths in eye fundus image segmentation research.

Optimal ground truth would be a pixel-accurate binary representation of the abnormalities, but as ground truths are done by a human hand, such accuracy is unrealistic. Because the marking of an accurate ground truth takes a good amount of time and patience, we often have to settle for rough markings of the present abnormalities. Clusters of exudates are circled, rather than each small finding specified separately.

1.2 Objectives and Restrictions

The objective of this thesis is to evaluate how big of an impact inaccurate ground truth has on various image features and segmentation methods.

Ground truth accuracy is explored only from the perspective of exudate detection, and Bristol database is used as it has accurate ground truths of exudates. Blood vessel detection is explored only to create a mask for them. A rough method for optic disk detection is also implemented as a preprocessing step for masking reasons.

Both supervised and unsupervised segmentation methods are used. In supervised methods, ground truths are used to label observations as either exudate or background. In unsupervised methods, ground truth is used to evaluate segmentation results. Best parameters for each method are chosen based on their performance.

1.3 Structure of the Thesis

Section 2 takes a look at the different features of eye fundus images, and how they are relevant in this thesis. It also explains the theory behind the applied pre-processing and segmentation methods. Section 3 details how sensitivity analysis is done in this thesis, and also explains the used evaluation methods. Section 4 describes the experiments in detail, and presents the results for each experiment. Section 5 sums up and interprets the results, and discusses the impact of this thesis and possible future work this thesis might invoke.

2 SEGMENTATION OF RETINAL IMAGES

Korkeemmalta tasolta, mikä työssä on tehtävä (myös herkkyysanalyysi). Kirjallisuuskatsaus.

2.1 Structure of the eye fundus

Tarpeellista käydä läpi?

2.2 Optic disc detection

Optic disc is very similar to exudates in terms of color and intensity, so detection and masking of the optic disc is an important preprocessing step in exudate detection. There are papers dedicated to the localisation of the optic disc [1], and it is also covered in papers concerning the detection of other parts of the eye fundus, such as exudates [2].

This method is based on the brightness of the optic disc, and the vertical blood vessels inside it. The horizontal image gradient is calculated using Sobel gradient operator, the result is shown in Figure 1a. Image is then divided into slightly overlapping square areas with a side of 140 pixels (size is adjusted when operating close to image borders). The area with the highest sum of gradients is considered as region of interest, i.e. to hold the optic disc. This is because the dark blood vessels inside the bright optic disc result in a strong horizontal gradient. Images with a “camera glare“, i.e. a high intensity strip in the corner of the eye fundus are problematic, as that area also has a high horizontal gradient. Region of interest is shown in Figure 1b.

Inside this area of highest sum of horizontal gradients, the pixel with the highest intensity is considered to be inside the optic disc. This pixel is then used as a center of a circle that will mask out the optic disc. Final masking result is shown in Figure 1c.




Figure 1. Locating and masking the optic disk: (a) Horizontal gradient (b) Region of interest (c) Optic disk masked out

2.3 Blood vessel detection

The purpose of blood vessel detection in this thesis is to create a mask, and to use that mask to remove false positives from exudate segmentation results. For example, edge detection techniques often highlight the borders of vessels as well as exudates.

The mask is formed by first using contrast limited adaptive histogram equalization (CLAHE) [3] to enhance contrast in the green channel of the image, the result for this is shown in Figure 2a. This contrast enhanced image is then thresholded with Otsu's method [4], which separates the image into foreground and background by minimizing the intra-class

variance. This results in all the vessels and other darker areas showing as black (or background), and all brighter areas as white (foreground). This is shown in Figure 2b. To create a binary mask of the darker areas, we use the complement of this thresholded image. Final version of the mask is shown in Figure 2c.

This method is inadequate for blood vessel detection as it also includes other darker areas of the image, such as the fovea. As a mask however, it clearly reduces the amount of false positives in exudate segmentation results. It also doesn't remove true positives, as only the darker areas of the image are included in the mask.




Figure 2. Phases in creating the blood vessel mask: (a) CLAHE (b) Thresholding using Otsu's method (c) Final mask, complement of thresholded image

2.4 Color transform

The human eye is capable of correcting the effect of varying light sources (illuminants) in perception of color. This is why a red chair will look (more or less) red in the sun and in the moonlight. In contrast, an image of an object taken under different light sources is perceived differently in terms of color by a computer. This is why color features need to be normalized in image sets where there's high variation in color properties.

The illumination and general color properties of the eye fundus images in Bristol database vary quite heavily. To be able to effectively use color features in teaching a classifier, the variance between image needs to be minimized. This is achieved by estimating the illuminant by applying the gray-world assumption [5]: *the average reflectance in a scene under a neutral light source is achromatic*. Color feature normalization was then done by multiplying each channel with a coefficient defined as $K_r = I_{avg}/r_{avg}$, where I_{avg} is the mean of all RGB-values in the image, and r_{avg} is the mean of the specific channel. Results are shown in Figure 3.

2.5 Unsupervised methods

An unsupervised method doesn't hold any information of the features it seeks, nor does it have any "expectations" of the image. It perform the same operations on each image with the object of clustering the data into meaningful sets.

Most edge detection methods are unsupervised algorithms. Edge is defined as a sharp change in image and color intensity, and the purpose of an edge detection algorithm is to emphasize and detect those sharp changes in an image. In an eye fundus image, this would include the exudates, but also the borders of the blood vessels and optic disc. Edge detection as such isn't sufficient for exudate detection. These unwanted regions need to be subtracted from the initial result.

Edge: Kirsch Tophat Mehdi

Jaafar (kmeans?) ravishankar sauvola




Figure 3. Color space transform: Original images on the left, adjusted images on the right.

2.6 Supervised methods

K-Nearest Neighbor / Naive-Bayes / Gaussian Mixture Model Bayes

Before a supervised method (or its classifier) can be used in classification, it needs to be trained. A specific training set of labeled images is used to teach the classifier. The method then extracts features from the training images, and generally forms a model for each used label. For example, to describe a fruit you might use its color and shape. You "teach" the method what each fruit looks like by labeling a set of training images. The classifier learns which features describe each label. Yellow and round equals orange, yellow and long equals banana, green and round equals apple. After training, the classifier

can be used to classify new images.

3 SENSITIVITY ANALYSIS OF IMAGE FEATURES

3.1 Evaluation methods

In evaluation, correctly classified samples can be split into true positives and true negatives. Errors are then similarly split into false positives and false negatives. In this thesis, true positives are findings correctly classified as exudates in the segmentation results, and true negatives are consequently findings correctly classified as background. False negatives are classified as background in results, but are actually positive (classified as exudate) in ground truth, and false positives are classified as positive in results, when they are in fact background [6].

There exists a multitude of ways to evaluate segmentation results. In this thesis, it was desired to have a single number describing the "goodness" of segmentation results to enable easier comparison and ranking of results. Different values, such as sensitivity, specificity and precision (defined in [6]) were considered, but these were ignored as they tended to only describe one aspect of the result, either the amount of samples correctly positive or negative. The used coefficient would have to describe the "goodness" in a more wholesome way, and for that reason, the Dice coefficient, Jaccard index and F-score were considered. These coefficients are defined as follows:

$$Dice = \frac{2|A \cap B|}{|A| + |B|} \quad (1)$$

$$Jaccard = \frac{|A \cap B|}{|A \cup B|} \quad (2)$$

$$F - score = \frac{2PR}{P + R} \quad (3)$$

where A is the segmented set, and B is the ground truth, P stands for precision and R stands for recall (sensitivity).

Dice coefficient and F-score values are interchangeable in practice as their values are exactly equal, and Jaccard index behaves similarly to the two. Dice coefficient was chosen as it is very simple to implement and understand. It can have values from the range $[0,1]$, where 0 indicates no similarities, and 1 indicates perfect agreement.

3.2 Effects of inaccurate ground truth

When researching feature sensitivity to ground truth accuracy, standard segmentation with unsupervised methods isn't really useful as it doesn't use the ground truth. In this thesis, the ground truth is used in finding the best parameters for unsupervised methods. First, the images used for teaching are segmented with each method and a large set of parameters. The results are then evaluated with the ground truth. Parameters with the highest Dice (see Eq. 1) coefficient are then selected to be used in experiments.

The accuracy of ground truth has a direct impact on training and performance of supervised methods. In general, inaccurate ground truth will mean a significant amount of background samples close to exudates will be categorized as positive. This will result in higher variation of feature distributions and an increase of false positives.

4 EXPERIMENTS AND RESULTS

4.1 Retinal Image Databases

4.2 The Ground Truth

The ground truth of exudates in Bristol database is very accurate, and to enable comparison of results and sensitivity analysis, more inaccurate ground truths were made by hand. Instead of the original color images, markings for the inaccurate ground truth were made on the black-and-white images of Bristol ground truth. This was to ensure every exudate present in the Bristol ground truth was also present in the inaccurate ground truth. Markings were done in a way that estimated the way doctors marked their findings when given the freedom to make inaccurate markings. Essentially this means that clusters of exudates are grouped together, and single exudates were more loosely circled. This is illustrated in Figure 4.

To create a basis for more comprehensive testing, different stages of inaccurate ground truths were created by dilating the accurate ground truth. Three different stages were created; one, three and five iterations of dilation by a disk-shaped structuring element, with a radius of 1 pixel. The dilation was restricted to stay inside the inaccurate ground truth.




Figure 4. Original accurate ground truth on the left, inaccurate ground truth on the right

4.3 Experiment 1

First experiment was done with minimal preprocessing; only the green timestamp was removed. In unsupervised methods, the mask described in Section 2.3 was used to reduce the amount of false positives. In supervised methods, features describing color values and the presence of edges were used. The original value of red channel and the contrast enhanced values of green and blue channel were used to describe color. For edge detection, local standard deviation of a 3-by-3 neighborhood of each channel was used.

4.4 Experiment 2

5 DISCUSSION

We have to discuss what we learned.

Notice the automatic page breaks.

5.1 Segmentation Results

5.2 Sensitivity of Image Features

5.3 Future Work

Tehtiin laitokselle osana projektia, tulevaisuudessa saatu ground truth on todennäköisesti epätarkkaa ja piti tietää miten se vaikuttaa tuloksiin. It is always nice to give some ideas for the future.

6 CONCLUSIONS

Finally the conclusions. This is more compact than the Discussion, a sort of summary about how things went on a general level.

Now you can delete all this crap content and write your own. Have fun!

REFERENCES

- [1] Sribalamurugan Sekhar, Waleed Al-Nuaimy, and Asoke K Nandi. Automated localisation of retinal optic disk using hough transform. In *Biomedical Imaging: From Nano to Macro, 2008. ISBI 2008. 5th IEEE International Symposium on*, pages 1577–1580. IEEE, 2008.
- [2] Thomas Walter, J-C Klein, Pascale Massin, and Ali Erginay. A contribution of image processing to the diagnosis of diabetic retinopathy-detection of exudates in color fundus images of the human retina. *Medical Imaging, IEEE Transactions on*, 21(10):1236–1243, 2002.
- [3] Ali M Reza. Realization of the contrast limited adaptive histogram equalization (clahe) for real-time image enhancement. *Journal of VLSI signal processing systems for signal, image and video technology*, 38(1):35–44, 2004.
- [4] Nobuyuki Otsu. A threshold selection method from gray-level histograms. *Automatica*, 11(285-296):23–27, 1975.
- [5] Gershon Buchsbaum. A spatial processor model for object colour perception. *journal of the Franklin institute*, 310(1):1–26, 1980.
- [6] Tom Fawcett. An introduction to roc analysis. *Pattern recognition letters*, 27(8):861–874, 2006.

Appendix 1. Appendix Guidelines

The appendices part starts with the command `\appendix`. Then, each appendix must be started with `\section{Appendix Name}` and ended with `\sectionend` to have the continues/continued markings right. For example, see the multi-page appendices after this one.

Appendix 2. Frame Schematics

This is an appendix. If you need more appendices, just make a new section here (the section command).




Figure A2.1. Overall design, only one half drawn.

huhu

Reference testing: Figures A2.1, A2.2, and A3.1. Table A3.1.

(continues)

Appendix 2. (continued)




Figure A2.2. Another picture.

Appendix 3. The Second

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.




Figure A3.1. The same picture once more.

Table A3.1. Appendix test table.

minimum distance	10	px
------------------	----	----

Appendix 3. (continued)

Aaand two more pages, to test the continues/continued marks.

Appendix 3. (continued)

Aaand one more page, to test the continues/continued marks.