What's in the database?

EXPLORATORY DATA ANALYSIS IN SQL




Christina Maimone
Data Scientist





PostgreSQL




Database client























































Select a few rows

```
SELECT *
FROM company
LIMIT 5;
```

```
id | exchange | ticker |
                                             | parent_id
                                name
 1 | nasdaq
                      PayPal Holdings, Inc.
              PYPL
 2 | nasdaq
              AMZN
                      Amazon.com, Inc.
 3 | nasdaq
             MSFT
                      | Microsoft Corporation |
 4 | nasdaq
              MDB
                      | MongoDB Inc.
 5 | nasdaq
            DBX
                      | Dropbox, Inc.
(5 rows)
```

Code	Note
NULL	missing

Code	Note
NULL	missing
IS NULL, IS NOT NULL	don't use = NULL

Code	Note
NULL	missing
IS NULL, IS NOT NULL	don't use = NULL
count(*)	number of rows

Code	Note
NULL	missing
IS NULL, IS NOT NULL	don't use = NULL
count(*)	number of rows
<pre>count(column_name)</pre>	number of non-NULL values

Code	Note
NULL	missing
IS NULL, IS NOT NULL	don't use = NULL
count(*)	number of rows
<pre>count(column_name)</pre>	number of non-NULL values
<pre>count(DISTINCT column_name)</pre>	number of different non-NULL values

Code	Note
NULL	missing
IS NULL, IS NOT NULL	don't use = NULL
count(*)	number of rows
count(column_name)	number of non-NULL values
<pre>count(DISTINCT column_name)</pre>	number of different non-NULL values
SELECT DISTINCT column_name	distinct values, including NULL

Let's start exploring

EXPLORATORY DATA ANALYSIS IN SQL



The keys to the database


EXPLORATORY DATA ANALYSIS IN SQL



Christina Maimone
Data Scientist





Foreign keys




Foreign keys


- Reference another row
 - In a different table or the same table
 - Via a unique ID
 - >> Primary key column containing unique, non-NULL values
- Values restricted to values in referenced column OR NULL




























fortune500	
title title	varchar
Tank	int
name	varchar
ticker ticker	char(5)
Ⅲ url	varchar
Ⅲ hq	varchar
sector	varchar
industry	varchar
employees	int
revenues	int
mrevenues_change	e real
m profits	numeric
mprofits_change	real
assets	numeric
equity	numeric














Coalesce function

```
coalesce(value_1, value_2 [, ...])
```

- Operates row by row
- Returns first non-NULL value

Coalesce function

```
SELECT *
  FROM prices;
 column_1 | column_2
                  10
       22 |
        3 |
                   4
SELECT coalesce(column_1, column_2)
  FROM prices;
 coalesce
       10
```



22

3

Time to keep exploring!

EXPLORATORY DATA ANALYSIS IN SQL



Column Types and Constraints

EXPLORATORY DATA ANALYSIS IN SQL



Christina Maimone
Data Scientist



Column constraints

- Foreign key: value that exists in the referenced column, or NULL
- Primary key: unique, not NULL
- Unique: values must all be different except for NULL
- Not null: NULL not allowed: must have a value
- Check constraints: conditions on the values
 - column1 > 0
 - o columnA > columnB

Data types

Common

- Numeric
- Character
- Date/Time
- Boolean

Special

- Arrays
- Monetary
- Binary
- Geometric
- Network Address
- XML
- JSON
- and more!


Numeric types: PostgreSQL documentation

Table 8-2. Numeric Types

Name	Storage Size	Description	Range
smallint	2 bytes	small-range integer	-32768 to +32767
integer	4 bytes	typical choice for integer	-2147483648 to +2147483647
bigint	8 bytes	large-range integer	-9223372036854775808 to +9223372036854775807
decimal	variable	user-specified precision, exact	up to 131072 digits before the decimal point; up to 16383 digits after the decimal point
numeric	variable	user-specified precision, exact	up to 131072 digits before the decimal point; up to 16383 digits after the decimal point
real	4 bytes	variable-precision, inexact	6 decimal digits precision
double precision	8 bytes	variable-precision, inexact	15 decimal digits precision
smallserial	2 bytes	small autoincrementing integer	1 to 32767
serial	4 bytes	autoincrementing integer	1 to 2147483647
bigserial	8 bytes	large autoincrementing integer	1 to 9223372036854775807



Types in entity relationship diagrams





Casting with CAST()

Format

```
-- With the CAST function

SELECT CAST (value AS new_type);
```

Examples

```
-- Cast 3.7 as an integer

SELECT CAST (3.7 AS integer);
```

4

```
-- Cast a column called total as an integer

SELECT CAST (total AS integer)

FROM prices;
```



Casting with ::

Format

```
-- With :: notation
SELECT value::new_type;
```

Examples

```
-- Cast 3.7 as an integer

SELECT 3.7::integer;

-- Cast a column called total as an integer

SELECT total::integer

FROM prices;
```

Time to practice!

EXPLORATORY DATA ANALYSIS IN SQL

