

City Pager / Lisbon Events Calendar

Pacote de replicacao - Dados Sheets & Supabase

Terminus — Dados: Google Sheets & Supabase

Documento: 3 de 6 — Storage & Contratos de Dados

1. Filosofia de storage

Sistema | Papel

Google Sheets | Calendário (Processed / Clean) + catálogo Venues/Promoters até seed Supabase; Fontes IG só fallback

Supabase | Utilizadores, social, artefatos do pipeline, e (mig 025) tabelas venues / promoters como SoT de scrape + catálogo

CSV publicado | Contrato estável da app pública enquanto Clean/Venues CSV existem

Pipeline escreve Processed (staging) e, via publish, Clean (live). App lê Clean via CSV; Venues/Promoters via Supabase (CATALOG_SOURCE=auto) com fallback CSV.

2. Google Sheets — tabs

Tab | SoT? | Escrita | Leitura

Venues | Até seed Supabase; depois espelho/ops | Humano + profile-images + admin | Scrape + resolve + app (fallback CSV)

Promoters | Idem | Idem | Scrape + app

Fontes IG - Venues / Promoters | Fallback legado | — | Só se catálogo sem handles (WATCHLIST_SOURCE=auto)

Fontes IG / Watchlist | Fallback combinado | — | Idem

Processed Events | Staging | Pipeline auto-pass + review approve | publish (gated), admin

Events Clean New | Live calendar | npm run publish (safe + verified\ | human_approved) or Tier 6 approve append | CSV → app

Events Clean Quarantine | Archive | quarantine-publish-unsafe --apply | Ops

Admin transparency: /admin/venues + /admin/promoters (Supabase após seed). Scrapers mostra a watchlist derived (read-only).

Setup Sheets

1. Criar spreadsheet; partilhar com service account (Editor).
 2. Preencher Venues / Promoters (ids, aliases, address, instagram_handle, is_active).
 3. Opcional: manter Fontes IG até npm run diff-watchlist passar.
 4. File → Share → Publish to web → CSV para Clean, Venues, Promoters, tags.
 5. Copiar URLs CSV (não a URL /edit) para .env.local.
 6. Aplicar migração 025_catalog_venues_promoters.sql; cd pipeline && npm run seed-catalog.
-

3. Contrato CSV de eventos (docs/SCHEMA.md)

Obrigatórios (mínimo): event_id (ou legacy id), title, start_datetime.

Campos importantes: end_datetime, timezone (default Europe/Lisbon), status, venue_id/venue_name, geo, category, tags (pipe, max 5), promoter, preço, is_free (tri-state: true/false/empty unknown), ticket_url, primary_image_url, source_name/source_url, confidence_score (calculado), publish_auth.

Status: scheduled | cancelled | postponed | sold_out | draft | archived.

Legacy: needs_review → draft (nunca público).

Colunas de rastreio do pipeline (ignoradas pelo loader UI)

Coluna | Significado

post_pattern | Classificação Tier 0

extraction_source | caption / vision / merged

on_slide_text_evidence | Texto lido no slide

_raw_model_text | Debug de prompts

fingerprint | Dedupe (source-scoped quando possível)

publish_auth | human_approved ou vazio; publish também aceita clean Tier 5 verified

Venues CSV: venue_id, name, aliases, instagram_handle, is_active, primary_image_url, tags, geo...

Promoters CSV: promoter_id, name, handle, images, is_active.

Schema code: src/data/schema/eventColumns.ts, venueColumns.ts.

4. Caminho de leitura na app

CSV URL → PapaParse (loaders) → Event[] / Venue[]

→ VenueIndex resolve

→ eventsAdapter (NormalizedEvent, filter, night collapse)

→ /api/events | UI Calendar / For You

- Cache server: ~5 min (unstable_cache) em fetchEvents.
 - Cap listagem: max 15 eventos por venue após collapse “night”.
 - collapseSameVenueDayEvents: ≥2 no mesmo venue+dia → card de noite com lineup.
-

5. Supabase — domínio utilizador / social

Migrations em supabase/migrations/ (correr em ordem).

Mig | Conteúdo

001 | profiles, follow venues/promoters (legado), wishlist, likes

002 | event_user_actions (going, interested, saved, reminder)

003–010 | perfil extend (display_name, ...), cover/username, storage, notifications, onboarding

011–013 | friend_requests + visibility + policies

012 | user_interactions (modelo unificado de actividade)

014 | drop user-to-user follows

015–017 | event_shares, chats, event-images bucket

018 | event_review_feedback

019 | pipeline store

020–022 | venue-images bucket, venue_profile_images, mode profile-images

023 | recommendation telemetry (recommendation_sessions / events)

024 | user_bug_reports → /admin/bugs

025 | venues + promoters catalog SoT

026 | pipeline_catalog_candidates → /admin/catalog-candidates

027 | display_name backfill + signup trigger sync

Conceitos sociais (as-built)

Conceito | Tabela / API | Natureza

Friends | friend_requests (accepted) | Mútuo; vê going/saved conforme visibility
Follow venue/promoter | user_interactions (e legado follow tables) | Preferência privada de discovery
Like / save / going / interested / reminder | user_interactions (+ facades) | Sinais para UI e For You
Chat | 016_chats | Só entre amigos

Não existe grafo de followers entre users (removido na 014).

6. Supabase — pipeline store (019+)

Tabela | Conteúdo

pipeline_posts | Posts scrapados; processing_status: new / discarded / needs_review / processed
pipeline_extractions | Artefacto por tier: pre_filter, caption, vision, ocr, video_transcript, merge, validation
pipeline_review_queue | Fila Tier 6; review_status pending/approved/rejected
pipeline_verifications | Auditoria Tier 5 (nunca auto-apply)
pipeline_runs | Fila de jobs: queued → running → success/error/aborted
pipeline_config | JSON config + worker_heartbeat_at
venue_profile_images | Mapa handle → URL (backup se Sheets falhar)
pipeline_catalog_candidates | Propostas de venue/promoter (026)
venues / promoters | Catalog SoT (025) + admin CRUD

Storage buckets

Bucket | Uso

event-images | Imagens de posts/eventos persistidas
venue-images | Avatars venue/promoter + _index.json
Profile assets | Avatars/covers de users (007)

7. Quem escreve o quê

Actor | Sheets | Supabase

scrape | — | posts + images
extract | Processed (pass) | extractions, post status, review queue
verify | — | verifications (+ review se unclean)
Tier 6 approve | Processed | review_status
publish | Events Clean New | —
profile-images | Venues/Promoters URLs | bucket + venue_profile_images
App user | — | profiles, interactions, friends, chats
Admin UI | — | venues/promoters CRUD, runs, review, config, candidates, bugs

Gate Sheets write: PIPELINE_SHEETS_WRITE (default on) + SA com acesso. Se write off, passes vão para review com hint de paste manual.

8. Imagens

1. Eventos: CDN IG → archive via EVENT_IMPORT_API_KEY + APP_BASE_URL → bucket → URL estável no row.
 2. Venues/promoters: Apify profile → venue-images → Sheets primary_image_url; UI também faz merge do _index.json se a sheet tiver placeholder.
 3. Repair sem Apify: npm run profile-images -- --sheets-only.
-

9. Env vars de dados (resumo)

App

- NEXT_PUBLIC_EVENTS_CSV_URL (obrigatório para calendário)
- NEXT_PUBLIC_VENUES_CSV_URL, NEXT_PUBLIC_PROMOTERS_CSV_URL, tags CSVs
- NEXT_PUBLIC_SUPABASE_URL, NEXT_PUBLIC_SUPABASE_ANON_KEY
- SUPABASE_SERVICE_ROLE_KEY, ADMIN_EMAILS
- GOOGLE_SHEETS_ID, GOOGLE_SHEETS_SERVICE_ACCOUNT_JSON

Pipeline

- Mesmo Sheets + Supabase service role
- APIFY_*, OPENAI_API_KEY, vision/OCR opcionais
- EVENT_IMPORT_API_KEY, APP_BASE_URL
- CATALOG_SOURCE=auto, WATCHLIST_SOURCE=catalog (SoT catálogo vs Fontes legado)

Checklist completo: docs/SETUP.md, pipeline/.env.example, .env.example.

10. Dedupe e identidade de venue

- Fingerprint partilhado pipeline ↔ eventsLoader.
 - VenueIndex (src/data/venueIndex.ts): venue_id → IG handle → exact name → alias.
 - Venues catalog (instagram_handle + is_active) é SoT de scrape + resolve; Fontes só fallback. Ver docs/PIPELINE.md cutover.
-

11. Publicação para produção

Depois de extract / Tier 5 / approve:

```
cd pipeline && npm run publish
```

publish não copia tudo o que está em Processed: só linhas mecanicamente seguras (isPublishSafe) e autorizadas (publish_auth=human_approved ou verificação Tier 5 limpa). Auto-pass fica em staging até verify ou humano.

Confirmar que o CSV publicado (gid da tab Clean) reflecte as novas linhas. A app refresca no próximo cache miss (~5 min) ou restart.

Para limpar Clean legado inseguro:

```
npx tsx scripts/quarantine-publish-unsafe.ts # dry-run
npx tsx scripts/quarantine-publish-unsafe.ts --apply
```

Nunca apontar NEXT_PUBLIC_EVENTS_CSV_URL para a URL de edição do Sheet — tem de ser Publish to web → CSV.