



U.S. ARMY


DISSOLVED OXYGEN CASE STUDY

Barry Bunch, DE, PE

U.S. Army Engineer Research and Development
Center, Environmental Laboratory

CE-QUAL-W2 Workshop

July 18 - 20, 2023




US Army Corps
of Engineers




CE-QUAL-W2 DO

- Complete model DO process
- Typically reduced suite of variables and processes
- Minimum required:
 - Dissolved Oxygen
 - Reaeration
 - Oxygen demand



CE-QUAL-W2 DO



DO Modeling Requirements

- Typical Sources:
 - Boundary Conditions for all inflows
 - Initial Conditions for water body
 - Reaeration
- Typical Sinks
 - Water quality variables that utilize DO in their kinetic processes
 - CBOD, DOM, POM, SOD, etc...
- Interactions in the DO cycle are temperature dependent.
- Efforts to model DO without reasonable temperature model are futile.




DO Modeling Requirements (cont.)

- Dissolved Oxygen Observed Data
 - Boundary conditions
 - Estimates of initial conditions
 - In-situ comparisons with model predictions for Calibration/Validation
 - Understanding of system behavior and model performance
- Oxygen Sinks
 - Boundary conditions and in-situ values
 - External loadings (Point and Non-point source)
 - Sediments
- Meteorological Data


Model DO Performance

- Compare Model output with observations
- Evaluate Model DO performance using:
 - Time Series
 - Water Column Profiles
 - Statistics
- Incorporate model Temperature performance in assessment, aka does it look right?




Minnesota River DO

Segment 23




Segment 46




Minnesota River DO (cont.)

Segment 68



Segment 83



Evaluating Model DO Performance

- DO is culmination of all other processes occurring in model.
- DO Predictions sensitive or insensitive depending upon location and conditions in model.
- Proceed slowly



Questions?



US Army Corps of Engineers • Engineer Research and Development Center