

Machine Learning for Numeric Weather Prediction

Group Members:

Yuqi Fang, Ali Cem Çakmak, Muhammad Fakhar, Diego Garces, Deepak Sorout

Table of Contents

1. Introduction
2. Methods Overview
3. Linear Regression
4. Random Forest
5. Neural Network
6. Model Comparison
7. Conclusion
8. Questions

Problem & Objective

Goal: Predict future temperature using machine learning

Approach:

- Compare 3 machine learning methods
- Predict mean daily temperature
- Evaluate on real-world data
(2023-2025)

Data Source:

- European Climate Assessment & Dataset (ECA&D)
- Station: Köln-Bonn, Germany
- Period: 1957-2025 (68 years)
- Variables: 10 weather features

Methods Overview

Linear Regression

Diego Garces

Muhammad Fakhar

Random Forest

Yuqi Fang

Deepak Sorout

Neural Network

Ali Cem Çakmak

Linear Regression

[Linear Regression Content]

This section will be filled by Diego and Muhammad

Random Forest

[Random Forest Content]

This section will be filled by Yuqi and Deepak

Neural Network

Approach

Architecture:

- Sequence-to-Sequence GRU (Gated Recurrent Unit) with Attention
- Encoder-Decoder structure
- Hidden dimension: 64 units
- Single layer

Task:

- Input: 15 days of weather history
- Output: 3-day temperature forecast
- Autoregressive prediction
- Benchmarked against baselines

Benchmark Models

Persistent Model

Approach: Tomorrow = Today

$$\hat{y}_{t+1} = y_t$$

- Simplest baseline
- No training required
- Assumes weather stays constant

SARIMA Model

Approach: Statistical time series model

- Captures seasonal patterns
- Traditional forecasting method
- Widely used in meteorology

Results: Day 1 Forecast

Model	MAE (°C)	RMSE (°C)	R ²
GRU	1.61	2.06	0.901
Persistent	1.78	2.30	0.877
SARIMA	1.72	2.22	0.885

Key Results:

- 9.6% improvement over Persistent
- 6.4% improvement over SARIMA
- Explains 90% of variance
- Best performance on all metrics

Results: Day 3 Forecast

Model	MAE (°C)	RMSE (°C)	R ²
GRU	2.58	3.26	0.753
Persistent	3.04	3.86	0.652
SARIMA	2.73	3.47	0.719

Key Results:

- 15.1% improvement over Persistent
- 5.5% improvement over SARIMA
- Performance degrades gracefully
- Maintains advantage at longer horizon

Execution Time


Model	Time	vs SARIMA
GRU (to best)	227.8s	42.7% faster
Persistent	10.2ms	-
SARIMA	397.9s	baseline

GRU time includes full training

Key Observations:

- GRU trains in ~3.8 minutes
- Nearly twice as fast as SARIMA
- Achieves better accuracy in less time
- Persistent is instantaneous (no training)
- GRU offers best accuracy-to-time ratio

5. Neural Network



Model Comparison


Performance Summary

Model	MAE (°C)	RMSE (°C)	R ²
Random Forest	1.59	2.07	0.901
GRU	1.61	2.06	0.902
Linear Regression	1.73	2.23	0.885
SARIMA	1.73	2.23	0.885
Persistent	1.78	2.30	0.878

Key Observations:


- GRU and RF achieve comparable top performance
- Both ML models outperform traditional methods
- 10% improvement over Persistent baseline
- 7% improvement over SARIMA baseline
- All models maintain R² > 0.87

6. Model Comparison




6. Model Comparison


Actual vs Predicted Temperature - Model Comparison



All Models: Time Series (Full Range)



All Models: Time Series (2025 Detail)



Conclusion

Key Findings:

- GRU and Random Forest achieved top performance ($R^2 > 0.90$)
- All ML methods outperformed persistent by 3-12%
- GRU: Better accuracy-to-time ratio (43% faster than SARIMA)

Future Directions:

- Multi-station data for spatial patterns
- Extend forecast horizon beyond 3 days
- Ensemble methods combining approaches

8. Questions?

Questions?