

Empirical Analysis of the Role of Energy in Economic Growth

Caleb Reese^a, Lucas Timmer^a, Matthew Kuperus Heun^{a,*}

^a*Engineering Department, Calvin College, Grand Rapids, MI 49546, USA*

Abstract

***** Add abstract *****

Keywords: economic growth, energy, cobb-douglas, CES, LINEX

```
#####  
# This function loads data given a country name.  
#  
# countryName = the name of the country for which data is to be loaded. The file r  
#   named <countryName>Data.txt. The file is assumed to exist in a subfolder of th  
#  
# returns a matrix with the data that has been loaded  
##  
loadData <- function(countryName){  
  # Read the data file as a table with a header.  
  fileName <- paste("data/", countryName, "Data.txt", sep="")  
  dataTable <- read.table(fileName, header = TRUE)  
  # Identifies the header names associated with dataTable  
  names(dataTable)  
  return(dataTable)  
}
```

*Corresponding author

Email address: mkh2@calvin.edu, tel: +1 (616) 526-6663, fax: +1 (616)
526-6501 (Matthew Kuperus Heun)

1. Cobb-Douglas Without Energy

```
cobbDouglas <- function(countryName){  
  
  # Load the data that we need.  
  dataTable <- loadData(countryName)  
  
  # Establish guess values for alpha and lambda.  
  lambdaGuess <- 0.0 # guessing lambda = 0 means there is no technological progress  
  alphaGuess <- 0.3 # a typical value for alpha, the coefficient on capital stock  
  
  # Runs a non-linear least squares fit to the data. We've replaced beta with 1-alpha  
  modelCD <- nls(iGDP ~ exp(lambda*iYear) * iCapStk^alpha * iLabor^(1 - alpha),  
                 start=(list(lambda=lambdaGuess,alpha=alphaGuess)),  
                 data=dataTable)  
  
  # Checks validity of the model. AIC stands for Akaike's Information Criterion.  
  aicCD <- AIC(modelCD, k=2); aicCD  
  
  summaryCD <- summary(modelCD) # Gives the nls summary table.  
  print(summaryCD)  
  ciCD <- confint(modelCD, level = 0.95); ciCD # Displays confidence intervals for  
  
  # Calculate beta and its confidence interval and report it.  
  alpha <- as.numeric(coef(modelCD)["alpha"])  
  beta <- 1.0 - alpha  
  beta.est <- deltaMethod(modelCD, "1 - alpha"); beta.est # Estimates beta and its  
  # Now calculate a confidence interval on beta  
  dofCD <- summaryCD$df[2]; dofCD # Gives the degrees of freedom for the model.  
  tvalCD <- qt(0.975, df = dofCD); tvalCD  
  betaCICD <- with(beta.est, Estimate + c(-1.0, 1.0) * tvalCD * SE); betaCICD # Gives  
  
  coef(modelCD)  
  
  # Combine all estimates and their confidence intervals into data frames with int  
  estCD <- data.frame(lambda = coef(modelCD)["lambda"], alpha = coef(modelCD)["alpha"],  
                      row.names(estCD) <- "Cobb-Douglas")
```

```

#row.names(estCD) <- "Cobb-Douglas: $y = e^{\lambda t}k^{\alpha}l^{1-\beta}$"
# The [1] subscripts pick off the lower confidence interval
lowerCD <- data.frame(lambda = ciCD["lambda", "2.5%"], alpha = ciCD["alpha", "2.5%"])
row.names(lowerCD) <- "- 95% CI"
# The [2] subscripts pick off the lower confidence interval
upperCD <- data.frame(lambda = ciCD["lambda", "97.5%"], alpha = ciCD["alpha", "97.5%"])
row.names(upperCD) <- "+ 95% CI"

# Now create the data for a table.
dataCD <- rbind(upperCD, estCD, lowerCD); dataCD
colnames(dataCD) <- c("$\lambda$", "$\alpha$", "$\beta$", "$\gamma$")
tableCD <- xtable(dataCD, caption=paste(countryName, " Cobb-Douglas, 1980-2011"),
return(tableCD)
}

tableCD <- cobbDouglas("US")

Formula: iGDP ~ exp(lambda * iYear) * iCapStk^alpha * iLabor^(1 - alpha)

Parameters:
      Estimate Std. Error t value Pr(>|t|)
lambda 0.010256   0.000682  15.03 1.7e-15
alpha  0.270030   0.028311   9.54 1.4e-10

Residual standard error: 0.0178 on 30 degrees of freedom

Number of iterations to convergence: 4
Achieved convergence tolerance: 3.81e-07

Waiting for profiling to be done...

countries <- c("US", "CN")
tablesCD <- apply(countries, 1, cobbDouglas)

Error: dim(X) must have a positive length

```

```
print(tableCD, caption.placement="top")
```

Table 1: US Cobb-Douglas, 1980-2011				
	λ	α	β	γ
+ 95% CI	0.0116	0.33	0.79	
Cobb-Douglas	0.0103	0.27	0.73	0.0
- 95% CI	0.0089	0.21	0.67	

```
# According to http://cran.r-project.org/web/packages/xtable/vignettes/xtableGallery.html
# be able to use the "sanitize.text.function" parameter to allow markup in column
# line is not working at the present time. --MKH, 18 Jan 2012.
# print(tableCD, caption.placement="top", sanitize.text.function = function(x){x})
```

2. Cobb-Douglas With Energy

We can force α , β , and γ to be in $[0, 1]$ by a reparameterization:

$$a \in [0, 1], b \in [0, 1], \alpha = \min(a, b), \beta = |b - a|, \gamma = 1 - \max(a, b)$$

```
#####
# This function fits the Cobb Douglas production function including energy to historical data
# The functional form is
#
# iGDP = exp(lambda * itime) * iCapStk^alpha * iLabor^beta * iEnergy^gamma
#
# iYear: time indexed to 0.0 at the first year [years since beginning of data set]
# iGDP = time series GDP data indexed to 1.0 at the first year [-]
# iCapStk = time series capital stock data indexed to 1.0 at the first year [-]
# iLabor = time series labor data indexed to 1.0 at the first year [-]
# iEnergy = time series energy data indexed to 1.0 at the first year [-].
#       This may be any of heat (iQ), exergy (iX), or useful work (iU).
#
# returns a data object containing three rows and 5 columns.
```

```

#   col 1: lambda
#   col 2: alpha
#   col 3: beta
#   col 4: gamma
#   row 1: -95% CI for each parameter
#   row 2: estimate for each parameter
#   row 3: +95% CI for each parameter
#
# countryName is a string containint the 2-letter abbreviation for the country, e.
# energyColumnName is the name of the column to be used for energy.
#   This may be any of heat ("iQ"), exergy ("iX"), or useful work ("iU").
# energyString is the string to be used in table captions representing the type of
##
cobbDouglasEnergy <- function(countryName, energyColumnName, energyString){

  # Load the data that we need.
  dataTable <- loadData(countryName)

  # Reparameterize to ensure that we meet the constraints:
  # * alpha + beta + gamma = 1.0.
  # * alpha, beta, and gamma are all between 0.0 and 1.0.
  # To do this, we reparameterize as
  # * 0 < a < 1
  # * 0 < b < 1
  # * alpha = min(a, b)
  # * beta = b - a
  # * gamma = 1 - max(a, b)
  iEnergy <- dataTable[energyColumnName] #grabs the desired energy column
  lambdaGuess <- 0.0 # guessing lambda = 0 means there is no technological progress
  alphaGuess <- 0.3 # a typical value for alpha
  betaGuess <- 0.7 # a typical value for beta
  modelCDe <- nls(iGDP ~ exp(lambda*iYear) *
                  iCapStk^min(a,b) * iLabor^abs(b-a) *
                  iEnergy^(1.0 - max(a,b)),
                  algorithm = "port",
                  start = list(lambda=lambdaGuess, a=alphaGuess, b=alphaGuess+betaGuess),
                  lower = list(lambda=-Inf, a=0, b=0),

```

```

        upper = list(lambda=Inf, a=1, b=1),
        data = dataTable)
aicCDe <- AIC(modelCDe, k=2) # Checks validity of the model. AIC stands for Akai
print(aicCDe)

summaryCDe <- summary(modelCDe) # Gives the nls summary table
print(summaryCDe)

# Provides confidence intervals on lambda, a, and b. But, we need CIs on alpha a
ciCDe <- confint(modelCDe, level = 0.95)
print(ciCDe)

a <- as.numeric(coef(modelCDe)["a"])
b <- as.numeric(coef(modelCDe)["b"])
lambda <- as.numeric(coef(modelCDe)["lambda"])
alpha <- a
beta <- b - a
gamma <- 1.0 - alpha - beta

# Report results with SE
beta.est <- deltaMethod(modelCDe, "b-a") # Reports results for beta, because bet
gamma.est <- deltaMethod(modelCDe, "1-b") # Reports results for gamma, because g

# Now calculate confidence intervals.
dofCDe <- summaryCDe$df[2] # Gives the degrees of freedom for the model.
print(dofCDe)
tvalCDe <- qt(0.975, df = dofCDe)
print(tvalCDe)
betaCICDe <- with(beta.est, Estimate + c(-1.0, 1.0) * tvalCDe * SE) # Gives the
print(betaCICDe)
gammaCICDe <- with(gamma.est, Estimate + c(-1.0, 1.0) * tvalCDe * SE) # Gives th
print(gammaCICDe)

# Combine all estimates and their confidence intervals into data frames with int
estCDe <- data.frame(lambda = lambda, alpha = alpha, beta = beta, gamma = gamma)
print(estCDe);
#row.names(estCDe) <- "Cobb-Douglas with e: $y = e^{\lambda t}k^{\alpha}l^{\beta}b^{\gamma}$"

```

```

row.names(estCDe) <- paste("C-D with ", energyString, sep="")
# The [1] subscripts pick off the lower confidence interval
lowerCDe <- data.frame(lambda = ciCDe["lambda", "2.5%"], alpha = ciCDe["a", "2.5%"])
row.names(lowerCDe) <- "- 95% CI"
# The [2] subscripts pick off the lower confidence interval
upperCDe <- data.frame(lambda = ciCDe["lambda", "97.5%"], alpha = ciCDe["a", "97.5%"])
row.names(upperCDe) <- "+ 95% CI"

# Now create the data for a table.
dataCDe <- rbind(upperCDe, estCDe, lowerCDe)
print(dataCDe)

return(dataCDe)
}

```

2.1. Cobb-Douglas with Q

```

countryName <- "US"
energyColumn <- "iQ"; energyString <- "q"
dataCDq <- cobbDouglasEnergy(countryName, energyColumn, energyString)

[1] -161.1

Formula: iGDP ~ exp(lambda * iYear) * iCapStk^min(a, b) * iLabor^abs(b -
a) * iEnergy^(1 - max(a, b))

Parameters:
      Estimate Std. Error t value Pr(>|t|)
lambda  0.01049   0.00108   9.67  1.4e-10
a        0.26322   0.03795   6.94  1.3e-07
b        0.97890   0.07647  12.80  1.9e-13

Residual standard error: 0.0181 on 29 degrees of freedom

Algorithm "port", convergence message: relative convergence (4)

Waiting for profiling to be done...

```

```

          2.5%  97.5%
lambda 0.00885 0.0127
a       0.18580 0.3283
b       0.82175      NA
[1] 29
[1] 2.045
[1] 0.5947 0.8367
[1] -0.1353 0.1775
      lambda alpha  beta  gamma
1 0.01049 0.2632 0.7157 0.0211
      lambda alpha  beta  gamma
+ 95% CI  0.01270 0.3283 0.8367 0.1775
C-D with q 0.01049 0.2632 0.7157 0.0211
- 95% CI  0.00885 0.1858 0.5947 -0.1353

# TODO Develop a better caption for the table based on the data automatically.
tableCDq <- xtable(dataCDq, caption=paste(countryName, ", 1980-2011.", sep=""), digits=2)
#estCDe <- dataCDe[2]
#dataAll <- rbind(estCD, estCDe); dataAll
#tableAll <- xtable(dataAll, caption="U.S. 1980-2011, All Models.", digits = c(4, 4))

print(tableCDq, caption.placement="top")

```

	lambda	alpha	beta	gamma
+ 95% CI	0.0127	0.33	0.84	0.177
C-D with q	0.0105	0.26	0.72	0.021
- 95% CI	0.0089	0.19	0.59	-0.135

```

# According to http://cran.r-project.org/web/packages/xtable/vignettes/xtableGallery
# be able to use the "sanitize.text.function" parameter to allow markup in column
# line is not working at the present time. --MKH, 18 Jan 2012.
# print(tableCDe, sanitize.text.function = function(x){x})

```



```
#print(tableAll, caption.placement="top")
```

2.2. Cobb-Douglas With X

```
energyColumn <- "iX"; energyString <- "x"
dataCDx <- cobbDouglasEnergy(countryName, energyColumn, energyString)
```

[1] -161.4

Formula: $iGDP \sim \exp(\lambda * iYear) * iCapStk^{\min(a, b)} * iLabor^{\max(b - a, 0)} * iEnergy^{(1 - \max(a, b))}$

Parameters:

	Estimate	Std. Error	t value	Pr(> t)
lambda	0.01071	0.00105	10.16	4.6e-11
a	0.25689	0.03666	7.01	1.0e-07
b	0.95700	0.07467	12.82	1.8e-13

Residual standard error: 0.018 on 29 degrees of freedom

Algorithm "port", convergence message: relative convergence (4)

Waiting for profiling to be done...

	2.5%	97.5%
lambda	0.008902	0.01287
a	0.182137	0.32622
b	0.803506	NA

[1] 29

[1] 2.045

[1] 0.5791 0.8211

[1] -0.1097 0.1957

	lambda	alpha	beta	gamma
1	0.01071	0.2569	0.7001	0.043

	lambda	alpha	beta	gamma
+ 95% CI	0.012867	0.3262	0.8211	0.1957
C-D with x	0.010714	0.2569	0.7001	0.0430
- 95% CI	0.008902	0.1821	0.5791	-0.1097

```
tableCDx <- xtable(dataCDx, caption=paste(countryName, ", 1980-2011.", sep=""), di

print(tableCDx, caption.placement="top")
```

	lambda	alpha	beta	gamma
+ 95% CI	0.0129	0.33	0.82	0.196
C-D with x	0.0107	0.26	0.70	0.043
- 95% CI	0.0089	0.18	0.58	-0.110

2.3. Cobb-Douglas With U

```
energyColumn <- "iU"; energyString <- "u"
dataCDu <- cobbDouglasEnergy(countryName, energyColumn, energyString)

Error: Missing value or an infinity produced when evaluating the
model

tableCDu <- xtable(dataCDu, caption=paste(countryName, ", 1980-2011.", sep=""), di

Error: object 'dataCDu' not found
```

```
print(tableCDu, caption.placement="top")

Error: error in evaluating the argument 'x' in selecting a method
for function 'print': Error: object 'tableCDu' not found
```

3. CES With Q

```

# Establish guess values for alpha, beta, and lambda.
phiGuess <- -20
betaGuess <- 0.5 # a typical value for beta (exponent on labor)
zetaGuess <- 0.0004 # a small value
lambda_LGuess <- 0.007 #assuming no technical progress on the labor-capital portio
lambda_EGuess <- 0.008 #assuming no technical progress on the energy portion of th

# Runs a non-linear least squares fit to the data with constraints
modelCESQ <- nls(iGDP ~ ((1-zeta) * (exp(lambda_L*iYear) * iLabor^beta * iCapStk^
      + zeta*(exp(lambda_E*iYear) * iQ)^phi)^(1/phi),
      algorithm = "port",
      control = nls.control(maxiter = 500, tol = 1e-06, minFactor = 1/1
        printEval = FALSE, warnOnly = FALSE),
      start = list(phi=phiGuess, beta=betaGuess, zeta=zetaGuess, lambda
        lambda_E=lambda_EGuess),
      lower = list(phi=-Inf, beta=0, zeta=0, lambda_L=-Inf, lambda_E=-1
      upper = list(phi=0, beta=1, zeta=1, lambda_L=Inf, lambda_E=Inf),
      data=dataTable)

Error: object 'dataTable' not found

# Gives the nls summary table
summary(modelCESQ)

Error: object 'modelCESQ' not found

xyplot( resid(modelCESQ) ~ fitted(modelCESQ) )

Error: object 'modelCESQ' not found

histogram( ~resid(modelCESQ) )

Error: object 'modelCESQ' not found

qqmath( ~resid(modelCESQ) )

Error: object 'modelCESQ' not found

```