

# Using R effectively

---

13 October 2020

EARNConversations

Ben Zipperer

Economic Policy Institute

[bzipperer@epi.org](mailto:bzipperer@epi.org)

[@benzipperer](https://twitter.com/benzipperer)

*[https://economic.github.io/data\\_bootcamp/](https://economic.github.io/data_bootcamp/)*

## 1. Review last time

- American Community Survey data
- Low-wage workers in Virginia

## 2. Recoding new variables with “if” conditions

## 3. Combining and transforming datasets: stacking, joining, and reshaping

## Last time: review, data cleaning

```
# Load the ACS data from IPUMS
acs <- read_dta("/home/benzipperer/Downloads/acs_2018.dta")

# Clean up the data
acs_clean <- acs %>%
  # keep only workers
  filter(incwage > 0 & incwage < 999998) %>%
  filter(uhrswork > 0) %>%
  # full-year workers only
  filter(wkswork2 == 6) %>%
  # restrict analysis to VA
  filter(statefip == 51) %>%
  # define wages and low-wage workers
  mutate(wage = incwage / (uhrswork * 51)) %>%
  mutate(low_wage = wage <= 15)
```

*# Shares of low-wage workers, overall and by demographic cuts*

```
acs_clean %>%
```

```
  summarize(weighted.mean(low_wage, perwt))
```

```
acs_clean %>%
```

```
  group_by(sex) %>%
```

```
  summarize(weighted.mean(low_wage, perwt))
```

```
acs_clean %>%
```

```
  group_by(race) %>%
```

```
  summarize(weighted.mean(low_wage, perwt))
```

# Recoding new variables using “if” conditions

## Specific tasks

1. Redefine race category to identify Hispanics
  - a. define indicator for Hispanic ethnicity/origin
  - b. redefine “race” to be more coarse and include Hispanic origin
2. Expand analysis to use all workers rather than just full-year

## Examples

1. define 0-1 Hispanic ethnicity from detailed country of origin
2. define aggregated race variable from detailed race
3. define “average” weeks worked, based on binned weeks worked

## Useful functions

- `ifelse()`
- `case_when()`

### Useful functions

- `ifelse(test, yes, no)` creates values=yes/no corresponding to test=true/false
- `case_when(test1 ~ value1, test2 ~ value2, ...)`  
assigns value if test true

For complex recoding, *always* double-check the results

- something like `count(oldvar, newvar)` can be very helpful

## Specific tasks

1. Create single summary dataset with race-specific *and* overall shares of low-wage workers
2. Add more summary statistics: population counts and sample sizes
3. How does VA compare to the US overall?
4. How does VA compare to nearby states?

## Useful functions

- `bind_rows()`, `is.na()`
- `summarize()` summary functions `sum()` and `n()`
- `rename()` and `full_join()`
- multiple groups in `group_by()`
- `pivot_wider()`



Directories

R projects

Do not automatically save/restart your workspace