

Facts

$$\frac{n}{a} \cdot a^r k = \frac{a^{r+1}n - a}{a-1} \quad \text{for } r \notin \{0, 1\}$$

Loop Invariant
 A property that holds before and after each loop iteration. **Initialization:** Holds before the first iteration. **Maintenance:** If it holds before an iteration, it holds after. **Termination:** When the loop ends, the invariant helps prove correctness.

Divide and Conquer
 An algorithmic paradigm with three steps:
 1. **Divide:** Split the problem into smaller subproblems.
 2. **Conquer:** Solve each subproblem recursively.
 3. **Combine:** Merge the subproblem solutions into the final result. The recurrence relation is:

$$T(n) = \Theta(1) + D(n) + C(n) \quad \text{if } n \leq c,$$

$$a \cdot T(n/b) + D(n) + C(n) \quad \text{otherwise,}$$
 where:
 a : number of subproblems,
 n/b : size of each subproblem,
 $D(n)$: time to divide,
 $C(n)$: time to combine.

Solving Recurrences
 To solve a recurrence using the substitution method:
 1. **Guess** the solution's form (e.g., $\Theta(n^2)$).
 2. **Prove the upper bound** by induction using a constant and the guessed form.
 3. **Prove the lower bound** similarly.
 4. **Conclude** that the guess is correct. **Example:**
 $T(n) = T(n-1) + cn \Rightarrow \Theta(n^2)$

Stack
 A stack is a last-in/first-out (LIFO) data-structure.

Supported operations:
 • **Push:** Insert an element at head.
 • **Pop:** Retrieve head.

Master Theorem
 Let $a \geq 1$, $b > 1$, and let $T(n)$ be defined by the recurrence:

$$T(n) = aT(n/b) + f(n)$$
 Then $T(n)$ has the following asymptotic bounds:
 1. If $f(n) = O(n^{\log_b a - \epsilon})$ for some $\epsilon > 0$, then $T(n) = \Theta(n^{\log_b a})$.
 2. If $f(n) = \Theta(n^{\log_b a} \log^k n)$ for some $k \geq 0$, then $T(n) = \Theta(n^{\log_b a} \log^{k+1} n)$.
 3. If $f(n) = \Omega(n^{\log_b a + \epsilon})$ for some $\epsilon > 0$, and if $a f(n/b) \leq c f(n)$ for some $c < 1$ and large n , then $T(n) = \Theta(f(n))$.

Insertion Sort
Steps:
 1. Start with an empty (or trivially sorted) sublist.
 2. Insert the next element in the correct position by comparing backwards.
 3. Repeat for all elements.
Complexity:
 Space: $\Theta(n)$, Time: $\Theta(n^2)$
Pseudocode:
Require: $A = \langle a_1, a_2, \dots, a_n \rangle$
 1: for $i \leftarrow 2$ to n do
 2: $key \leftarrow A[i]$
 3: $j \leftarrow i - 1$
 4: while $j \geq 1$ and $A[j] > key$ do
 5: $A[j+1] \leftarrow A[j]$
 6: $j \leftarrow j - 1$
 7: end while
 8: $A[j+1] \leftarrow key$
 9: end for

Heap Sort
 A heap is a nearly complete binary tree where each node satisfies the **max-heap property**: For every node i , its children have smaller or equal values. The height of a heap is the length of the longest path from the root to a leaf. **Useful Index Rules (array-based heap):**
 • Root is at index $A[1]$
 • Left child of node i : index $2i$
 • Right child of node i : index $2i+1$
 • Parent of node i : index $\lfloor i/2 \rfloor$
Complexity:
 Space: $\Theta(n)$, Time: $\Theta(n \log n)$
Pseudocode:
 1: procedure MAX-HEAPIFY(A, i, n)
 2: $l \leftarrow \text{Left}(i)$
 3: $r \leftarrow \text{Right}(i)$
 4: $largest \leftarrow i$
 5: if $l \leq n$ and $A[l] > A[largest]$ then
 6: $largest \leftarrow l$
 7: end if
 8: if $r \leq n$ and $A[r] > A[largest]$ then
 9: $largest \leftarrow r$
 10: end if
 11: if $largest \neq i$ then
 12: Exchange $A[i] \leftrightarrow A[largest]$
 13: MAX-HEAPIFY($A, largest, n$)
 14: end if
 15: end procedure
 1: procedure BUILD-MAX-HEAP($A[1..n]$)
 2: for $i \leftarrow \lfloor n/2 \rfloor$ downto 1 do
 3: MAX-HEAPIFY(A, i, n)
 4: end for
 5: end procedure
 1: procedure HEAPSORT($A[1..n]$)
 2: BUILD-MAX-HEAP(A)
 3: for $i \leftarrow n$ downto 2 do
 4: exchange $A[1]$ with $A[i]$
 5: MAX-HEAPIFY($A, 1, i-1$)
 6: end for
 7: end procedure
Injective Functions
 Let $f: \{1, 2, \dots, q\} \rightarrow M$ be a function chosen uniformly at random, where $|M| = m$. If $q > 1.78\sqrt{m}$, then the probability that f is injective is at most $\frac{1}{2}$.

Merge Sort
 Uses the divide and conquer paradigm. **Complexity:**
 Space: $\Theta(n)$, Time: $\Theta(n \log n)$
Pseudocode:
 1: procedure SORT(A, p, r)
 2: if $p < r$ then
 3: $q \leftarrow \lfloor (p+r)/2 \rfloor$
 4: SORT(A, p, q)
 5: SORT($A, q+1, r$)
 6: MERGE(A, p, q, r)
 7: end if
 8: end procedure
 1: procedure MERGE(A, p, q, r)
 2: $n_1 \leftarrow q - p + 1$, $n_2 \leftarrow r - q$
 3: Let $L[1..n_1+1], R[1..n_2+1]$ be new arrays
 4: for $i \leftarrow 1$ to n_1 do $L[i] \leftarrow A[p+i-1]$
 5: end for
 6: for $j \leftarrow 1$ to n_2 do $R[j] \leftarrow A[q+j]$
 7: end for
 8: $L[n_1+1], R[n_2+1] \leftarrow \infty$
 9: $i, j \leftarrow 1$
 10: for $k \leftarrow p$ to r do
 11: if $L[i] \leq R[j]$ then
 12: $A[k] \leftarrow L[i]$; $i \leftarrow i + 1$
 13: else
 14: $A[k] \leftarrow R[j]$; $j \leftarrow j + 1$
 15: end if
 16: end for
 17: end procedure

Maximum Subarray Problem (Kadane's Algorithm)
Idea: Iterate from left to right, maintaining: - endingHereMax: best subarray ending at current index - currentMax: best seen so far
Observation: At index $j+1$, the maximum subarray is either:
 • the best subarray in $A[1..j]$, or
 • a subarray ending at $j+1$, i.e., $A[i..j+1]$
Formula:

$$\text{maxSub}(A[1..n]) = \max(\text{maxSub}(A[1..n-1]), \max_{1 \leq i \leq n} \text{sum}(A[i..n]))$$

Complexity: Time $\Theta(n)$, Space $\Theta(1)$
Pseudocode:
 1: procedure SUBARRAY($A[1..n]$)
 2: $\text{current_max} \leftarrow -\infty$
 3: $\text{ending_here_max} \leftarrow -\infty$
 4: for $i \leftarrow 1$ to n do
 5: $\text{ending_here_max} \leftarrow \max(A[i], \text{ending_here_max} + A[i])$
 6: $\text{current_max} \leftarrow \max(\text{current_max}, \text{ending_here_max})$
 7: end for
 8: return current_max
 9: end procedure
Queue
 A queue is a first-in, first-out (FIFO) collection.
 • **enqueue:** Insert an element at tail.
 • **dequeue:** Retrieve head.
 1: procedure ENQUEUE(Q, x)
 2: $Q.Q.\text{tail} \leftarrow x$
 3: if $Q.\text{tail} = Q.\text{length}$ then
 4: $Q.\text{tail} \leftarrow 1$
 5: else
 6: $Q.\text{tail} \leftarrow Q.\text{tail} + 1$
 7: end if
 8: end procedure
 10: procedure DEQUEUE(Q)
 11: $x \leftarrow Q.Q.\text{head}$
 12: if $Q.\text{head} = Q.\text{length}$ then
 13: $Q.\text{head} \leftarrow 1$
 14: else
 15: $Q.\text{head} \leftarrow Q.\text{head} + 1$
 16: end if
 17: return x
 18: end procedure
Dynamic Programming
 Two key approaches: **Top-down** and **Bottom-up**.
 • **Top-down:** Starts from the problem n and solves subproblems recursively, storing results (memoization).
 • **Bottom-up:** Starts from base cases (e.g., 0) and iteratively builds up to the final solution.
 The core idea is to **remember previous computations** to avoid redundant work and save time.

Hash Functions and Tables
 Tables are a special kind of collection that associate keys to values, allowing the following operations:
 1. Insert a new key-value pair.
 2. Delete a key-value pair.
 3. Search for the value associated with a given key.
Direct-Address Tables. We define a function $f: K \rightarrow \{1, \dots, |K|\}$ and create an array of size $|K|$ where each position corresponds directly to a key, allowing constant-time access.
Hash Tables. Hash tables use space proportional to the number of stored keys $|K'|$, i.e., $\Theta(|K'|)$, and support the above operations in expected time $O(1)$ in the average case. To achieve this, we define a hash function $h: K \rightarrow \{1, \dots, M\}$ and use an array of size M where each entry contains a linked list of key-value pairs (k, v) .

Strassen's Algorithm for Matrix Multiplication
 Instead of performing 8 recursive multiplications as in the naive divide-and-conquer matrix multiplication, Strassen's algorithm reduces it to 7, which improves the time complexity.
Definitions:
 $M_1 = (A_{11} + A_{22})(B_{11} + B_{22})$
 $M_2 = (A_{21} + A_{22})B_{11}$
 $M_3 = A_{11}(B_{12} - B_{22})$
 $M_4 = A_{22}(B_{21} - B_{11})$
 $M_5 = (A_{11} + A_{12})B_{22}$
 $M_6 = (A_{21} - A_{11})(B_{11} + B_{12})$
 $M_7 = (A_{12} - A_{22})(B_{21} + B_{22})$
Resulting matrix:
 $C_{11} = M_1 + M_4 - M_5 + M_7$
 $C_{12} = M_3 + M_5$
 $C_{21} = M_2 + M_4$
 $C_{22} = M_1 - M_2 + M_3 + M_6$
Complexity:
 Time: $\Theta(n^{\log_2 7}) \approx \Theta(n^{2.81})$, Space: $\Theta(n^2)$
Priority Queue
 A priority queue maintains a dynamic set S of elements, each with an associated key that defines its priority. At each operation, we can access the element with the highest key. **Supported operations:**
 • **Insertion:** Insert an element x into S .
 • **Maximum:** Return the element in S with the largest key.
 • **Extract-Max:** Remove and return the element with the largest key.
 • **Increase-Key:** Increase the key of an element x to a new value k (assuming $k \geq \text{current key}$).
Pseudocode:
 1: procedure HEAP-MAXIMUM(S)
 2: return $S[1]$
 3: end procedure
 1: procedure HEAP-EXTRACT-MAX(S, n)
 2: if $n < 1$ then
 3: error "heap underflow"
 4: end if
 5: $\text{max} \leftarrow S[1]$
 6: $S[1] \leftarrow S[n]$
 7: $n \leftarrow n - 1$
 8: MAX-HEAPIFY($S, 1, n$)
 9: return max
 10: end procedure
 1: procedure HEAP-INCREASE-KEY(S, i, key)
 2: if $\text{key} < S[i]$ then
 3: error "new key is smaller than current key"
 4: end if
 5: $S[i] \leftarrow \text{key}$
 6: while $i > 1$ and $S[\text{Parent}(i)] < S[i]$ do
 7: exchange $S[i]$ with $S[\text{Parent}(i)]$
 8: $i \leftarrow \text{Parent}(i)$
 9: end while
 10: end procedure
 1: procedure MAX-HEAP-INSERT(S, key, n)
 2: $n \leftarrow n + 1$
 3: $S[n] \leftarrow \infty$
 4: HEAP-INCREASE-KEY(S, n, key)
 5: end procedure

Linked List
 A linked list is a linear data structure where each element (node) points to the next. Unlike arrays, it is not index-based and allows efficient insertions and deletions.
Operations:
 • **Search:** Find an element with a specific key $\leftarrow \Theta(n)$
 • **Insert:** Insert an element at the head $\leftarrow \Theta(1)$
 • **Delete:** Remove an element $\leftarrow \Theta(1)$
Pseudocode:
 1: procedure LIST-SEARCH(L, k)
 2: $x \leftarrow L.\text{head}$
 3: while $x \neq \text{NIL}$ and $x.\text{key} \neq k$ do
 4: $x \leftarrow x.\text{next}$
 5: end while
 6: return x
 7: end procedure
 8: procedure LIST-INSERT(L, x)
 9: $x.\text{next} \leftarrow L.\text{head}$
 10: if $L.\text{head} \neq \text{NIL}$ then
 11: $L.\text{head}.\text{prev} \leftarrow x$
 12: end if
 13: $L.\text{head} \leftarrow x$
 14: $x.\text{prev} \leftarrow \text{NIL}$
 15: end procedure
 16: procedure LIST-DELETE(L, x)
 17: if $x.\text{prev} \neq \text{NIL}$ then
 18: $x.\text{prev}.\text{next} \leftarrow x.\text{next}$
 19: else
 20: $L.\text{head} \leftarrow x.\text{next}$
 21: end if
 22: if $x.\text{next} \neq \text{NIL}$ then
 23: $x.\text{next}.\text{prev} \leftarrow x.\text{prev}$
 24: end if
 25: end procedure
Binary Search Trees
 A binary search tree (BST) is a binary tree where each node has a key and satisfies the following properties:
 • For any node x , all keys in its left subtree are less than $x.\text{key}$.
 • All keys in its right subtree are greater than or equal to $x.\text{key}$.
Pseudocode:
 1: procedure OPTIMAL-BST(p, q, n)
 2: let $e[1..n+1][0..n]$, $w[1..n+1][0..n]$, and $\text{root}[1..n][1..n]$ be new tables
 3: for $i \leftarrow 1$ to $n+1$ do
 4: $e[i][i-1] \leftarrow 0$
 5: $w[i][i-1] \leftarrow 0$
 6: end for
 7: for $l \leftarrow 1$ to n do
 8: for $i \leftarrow 1$ to $n-l+1$ do
 9: $j \leftarrow i+l-1$
 10: $e[i][j] \leftarrow \infty$
 11: $w[i][j] \leftarrow w[i][j-1] + p[j]$
 12: for $r \leftarrow i$ to j do
 13: $t \leftarrow e[i][r-1] + e[r+1][j] + w[i][j]$
 14: if $t < e[i][j]$ then
 15: $e[i][j] \leftarrow t$
 16: $\text{root}[i][j] \leftarrow r$
 17: end if
 18: end for
 19: end for
 20: end for
 21: end procedure

Modify a Binary Tree
 1: procedure TREE-INSERT(T, z)
 2: $y \leftarrow \text{NIL}$
 3: $x \leftarrow T.\text{root}$
 4: while $x \neq \text{NIL}$ do
 5: $y \leftarrow x$
 6: if $z.\text{key} < x.\text{key}$ then
 7: $x \leftarrow x.\text{left}$
 8: else
 9: $x \leftarrow x.\text{right}$
 10: end if
 11: end while
 12: $z.p \leftarrow y$
 13: if $y = \text{NIL}$ then
 14: $T.\text{root} \leftarrow z$
 15: else if $z.\text{key} < y.\text{key}$ then
 16: $y.\text{left} \leftarrow z$
 17: else
 18: $y.\text{right} \leftarrow z$
 19: end if
 20: end procedure
 21: procedure TRANSPLANT(T, u, v)
 22: if $u.p = \text{NIL}$ then
 23: $T.\text{root} \leftarrow v$
 24: else if $u = u.p.\text{left}$ then
 25: $u.p.\text{left} \leftarrow v$
 26: else
 27: $u.p.\text{right} \leftarrow v$
 28: end if
 29: if $v = \text{NIL}$ then
 30: $v.p \leftarrow u.p$
 31: end if
 32: end procedure
 33: procedure TREE-DELETE(T, z)
 34: if $z.\text{left} = \text{NIL}$ then
 35: TRANSPLANT($T, z, z.\text{right}$)
 36: else if $z.\text{right} = \text{NIL}$ then
 37: TRANSPLANT($T, z, z.\text{left}$)
 38: else
 39: $y \leftarrow \text{TREE-MINIMUM}(z.\text{right})$
 40: if $y.p \neq z$ then
 41: TRANSPLANT($T, y, y.\text{right}$)
 42: $y.\text{right} \leftarrow z.\text{right}$
 43: $y.\text{right}.p \leftarrow y$
 44: end if
 45: TRANSPLANT(T, z, y)
 46: $y.\text{left} \leftarrow z.\text{left}$
 47: $y.\text{left}.p \leftarrow y$
 48: end if
 49: end procedure
Building a Binary Search Tree
 Given a sequence $k = \langle k_1, k_2, \dots, k_n \rangle$ of n distinct sorted keys and, for every k_i , a probability p_i , find a binary search tree T that minimizes:

$$E[\text{search cost in } T] = \sum_{i=1}^n (\text{depth}_T(k_i) + 1) p_i$$
 This is solved via dynamic programming.
Time complexity: $O(n^3)$
 1: procedure OPTIMAL-BST(p, q, n)
 2: let $e[1..n+1][0..n]$, $w[1..n+1][0..n]$, and $\text{root}[1..n][1..n]$ be new tables
 3: for $i \leftarrow 1$ to $n+1$ do
 4: $e[i][i-1] \leftarrow 0$
 5: $w[i][i-1] \leftarrow 0$
 6: end for
 7: for $l \leftarrow 1$ to n do
 8: for $i \leftarrow 1$ to $n-l+1$ do
 9: $j \leftarrow i+l-1$
 10: $e[i][j] \leftarrow \infty$
 11: $w[i][j] \leftarrow w[i][j-1] + p[j]$
 12: for $r \leftarrow i$ to j do
 13: $t \leftarrow e[i][r-1] + e[r+1][j] + w[i][j]$
 14: if $t < e[i][j]$ then
 15: $e[i][j] \leftarrow t$
 16: $\text{root}[i][j] \leftarrow r$
 17: end if
 18: end for
 19: end for
 20: end for
 21: end procedure

Rod Cutting
 Given a rod of length n and a table of prices p_i for rods of length $i = 1, \dots, n$, determine the optimal way to cut the rod to maximize profit.
 The optimal revenue function $r(n)$ is defined as:

$$r(n) = \begin{cases} 0 & \text{if } n = 0, \\ \max_{1 \leq i \leq n} \{p_i + r(n-i)\} & \text{if } n \geq 1. \end{cases}$$
 1: procedure EXTENDED-BOTTOM-UP-CUT-ROD(p, n)
 2: let $r[0..n]$ and $s[0..n]$ be new arrays
 3: $r[0] \leftarrow 0$
 4: $s[0] \leftarrow 0$ \triangleright Usually $s[0]$ isn't explicitly used for solution reconstruction, but included as per your pseudocode
 5: for $j \leftarrow 1$ to n do
 6: $q \leftarrow -\infty$
 7: for $i \leftarrow 1$ to j do
 8: if $q < p[i] + r[j-i]$ then
 9: $q \leftarrow p[i] + r[j-i]$
 10: $s[j] \leftarrow i$
 11: end if
 12: end for
 13: $r[j] \leftarrow q$
 14: end for
 15: return r and s
 16: end procedure
Counting Sort
 Counting Sort assumes the input consists of n integers in the range 0 to k and sorts them in $O(n+k)$ time. It is stable and non-comparative.
 1: procedure COUNTING-SORT(A, B, n, k)
 2: let $C[0..k]$ be a new array
 3: for $i \leftarrow 0$ to k do
 4: $C[i] \leftarrow 0$
 5: end for
 6: for $j \leftarrow 1$ to n do
 7: $C[A[j]] \leftarrow C[A[j]] + 1$
 8: end for
 9: for $i \leftarrow 1$ to k do
 10: $C[i] \leftarrow C[i] + C[i-1]$
 11: end for
 12: for $j \leftarrow n$ downto 1 do
 13: $B[C[A[j]]] \leftarrow A[j]$
 14: $C[A[j]] \leftarrow C[A[j]] - 1$
 15: end for
 16: end procedure
Matrix-Chain Multiplication
 Given a chain $\langle A_1, A_2, \dots, A_n \rangle$ of n matrices, where for $i = 1, 2, \dots, n$, matrix A_i has dimensions $p_{i-1} \times p_i$, find the most efficient way to fully parenthesize the product $A_1 A_2 \dots A_n$ so as to minimize the total number of scalar multiplications.
 The optimal substructure is defined by the recurrence:

$$m[i, j] = \min_{i \leq k < j} (m[i, k] + m[k+1, j] + p_{i-1} p_k p_j) \quad \text{if } i < j$$
 1: procedure MATRIX-CHAIN-ORDER(p)
 2: $n \leftarrow p.\text{length} - 1$
 3: let $m[1..n][1..n]$ and $s[1..n][1..n]$ be new tables
 4: for $i \leftarrow 1$ to n do
 5: $m[i][i] \leftarrow 0$
 6: end for
 7: for $l \leftarrow 2$ to n do $\triangleright l$ is the chain length
 8: for $i \leftarrow 1$ to $n-l+1$ do
 9: $j \leftarrow i+l-1$
 10: $m[i][j] \leftarrow \infty$
 11: for $k \leftarrow i$ to $j-1$ do
 12: $q \leftarrow m[i][k] + m[k+1][j] + p[i-1] \cdot p[k] \cdot p[j]$
 13: if $q < m[i][j]$ then
 14: $m[i][j] \leftarrow q$
 15: $s[i][j] \leftarrow k$
 16: end if
 17: end for
 18: end for
 19: end for
 20: end procedure
Time complexity: $O(n^3)$
Space complexity: $O(n^2)$

Longest Common Subsequence

Given as input two sequences $X = \langle x_1, \dots, x_m \rangle$ and $Y = \langle y_1, \dots, y_n \rangle$, we want to find the longest common subsequence (not necessarily contiguous, but in order).

```
1: procedure LCS-LENGTH( $X, Y, m, n$ )
2:   let  $b[1..m][1..n]$  and  $c[0..m][0..n]$  be new tables
3:   for  $i \leftarrow 1$  to  $m$  do
4:      $c[i][0] \leftarrow 0$ 
5:   end for
6:   for  $j \leftarrow 1$  to  $n$  do
7:      $c[0][j] \leftarrow 0$ 
8:   end for
9:   for  $i \leftarrow 1$  to  $m$  do
10:    for  $j \leftarrow 1$  to  $n$  do
11:      if  $X[i] = Y[j]$  then
12:         $c[i][j] \leftarrow c[i-1][j-1] + 1$ 
13:      else
14:         $b[i][j] \leftarrow \infty$   $\triangleright$  North-west arrow
15:        if  $c[i-1][j] \geq c[i][j-1]$  then
16:           $c[i][j] \leftarrow c[i-1][j]$ 
17:           $b[i][j] \leftarrow \nwarrow$   $\triangleright$  Up arrow
18:        else
19:           $c[i][j] \leftarrow c[i][j-1]$ 
20:           $b[i][j] \leftarrow \swarrow$   $\triangleright$  Left arrow
21:        end if
22:      end if
23:    end for
24:  end for
25:  return  $c[m][n]$  and  $b$ 
26: end procedure
```

Time complexity: $O(mn)$ Space complexity: $O(mn)$

Graph

A graph $G = (V, E)$ consists of a vertex set V and an edge set E that contains (ordered) pairs of vertices.

	Undirected	Directed	Acyclic
Connectivity	Yes	Yes	Yes
Connected Component	Yes	Yes	Yes
Complete Graph	Yes	Yes	Yes
Strongly Connected Components	No	Yes	No
Vertex Cut	Yes	Yes	Yes
Flow Network	Yes	Yes	Yes
Spanning Tree	Yes	Yes	Yes
Shortest Path	Yes	Yes	Yes
Minimum Spanning Tree	Yes	Yes	Yes
Dynamic Programming	Yes	Yes	Yes

Connectivity: A graph is said to be connected if every pair of vertices in the graph is connected.

Connected Component: A connected component is a maximal connected subgraph of an undirected graph.

Complete Graph: A complete graph is a simple undirected graph in which every pair of distinct vertices is connected by a unique edge.

Vertex Cut: A vertex cut or separating set of a connected graph G is a set of vertices whose removal renders G disconnected.

Breadth-First Search

Given as input a graph $G = (V, E)$, a source vertex $s \in V$, we want to find v, d , the smallest number of edges d (distance) from s to v , for all $v \in V$.

1. Send a wave out from s ,
2. first hit all vertices at 1 edge from s ,
3. then, from there, hit all vertices at 2 edges from s , and so on.

```
1: procedure BFS( $V, E, s$ )
2:   for each  $v \in V \setminus \{s\}$  do
3:      $u, d \leftarrow \infty$ 
4:   end for
5:    $s, d \leftarrow 0$ 
6:   let  $Q$  be a new queue
7:   ENQUEUE( $Q, s$ )
8:   while  $Q \neq \emptyset$  do
9:      $u \leftarrow$  DEQUEUE( $Q$ )
10:    for each  $v \in G.Adj[u]$  do
11:      if  $v, d = \infty$  then
12:         $v, d \leftarrow u, d + 1$ 
13:      ENQUEUE( $Q, v$ )
14:    end if
15:  end for
16: end while
17: end procedure
```

Time complexity: $O(|V| + |E|)$

Depth-First Search

Given, as input, a graph $G = (V, E)$, either directed or undirected, we want to output two timestamps on each vertex:

- v, d — discovery time (when v is first encountered),
- v, f — finishing time (when all vertices reachable from v have been fully explored).

Each vertex has a color state:

- **WHITE:** undiscovered,
- **GRAY:** discovered but not finished,
- **BLACK:** fully explored.

```
1: procedure DFS( $G$ )
2:   for each  $u \in G.V$  do
3:      $u, color \leftarrow$  WHITE
4:   end for
5:   time  $\leftarrow 0$ 
6:   for each  $u \in G.V$  do
7:     if  $u, color =$  WHITE then
8:       DFS-VISIT( $G, u$ )
9:     end if
10:  end for
11: end procedure
```

```
12: procedure DFS-VISIT( $G, u$ )
13:   time  $\leftarrow$  time + 1
14:    $u, d \leftarrow$  time  $\triangleright$  Discovery time
15:    $u, color \leftarrow$  GRAY
16:   for each  $v \in G.Adj[u]$  do
17:     if  $v, color =$  WHITE then
18:       DFS-VISIT( $G, v$ )
19:     end if
20:   end for
21:    $u, color \leftarrow$  BLACK  $\triangleright$  Finishing time
22:   time  $\leftarrow$  time + 1
23:    $u, f \leftarrow$  time
24: end procedure
```

Time complexity: $O(|V| + |E|)$

Topological Sort

Given a directed acyclic graph (DAG) $G = (V, E)$, the goal is to produce a linear ordering of its vertices such that for every edge $(u, v) \in E$, vertex u appears before v in the ordering.

- A graph is a DAG if and only if a DFS yields no back edges.
- The topological sort is obtained by performing DFS and ordering vertices in decreasing order of their finishing times.

Algorithm:

```
1. Run DFS on  $G$  to compute finishing times  $v, f$  for all  $v \in V$ .
2. Return the vertices sorted in descending order of  $v, f$ .
```

Running Time: $\Theta(|V| + |E|)$, same as DFS.

Strongly Connected Components

A **strongly connected component** (SCC) of a directed graph $G = (V, E)$ is a maximal set of vertices $C \subseteq V$ such that for every pair $u, v \in C$, there is a path from u to v and from v to u .

Transpose of a Graph: The transpose of G , denoted $G^T = (V, E^T)$, has all edges reversed:

$$E^T = \{(u, v) \mid (v, u) \in E\}$$

G and G^T share the same SCCs. Computing G^T takes $\Theta(|V| + |E|)$ time with adjacency lists.

Algorithm (Kosaraju's):

```
1. Run DFS on  $G$  to compute finishing times  $u, f$  for all  $u \in V$ .
2. Compute the transpose  $G^T$ .
3. Run DFS on  $G^T$ , but visit vertices in order of decreasing  $u, f$  (from step 1).
4. Each tree in the resulting DFS forest is an SCC.
```

Time Complexity: $\Theta(|V| + |E|)$

Flow Network

We model the movement of flow through a network of edges, where each edge has a **capacity**—the maximum flow allowed. Our goal is to maximize the total flow from a source vertex s to a sink vertex t .

Flow Function: A flow is a function $f: V \times V \rightarrow \mathbb{R}$ that satisfies:

1. **Capacity Constraint:** For all $u, v \in V$,
 $0 \leq f(u, v) \leq c(u, v)$, where $c(u, v)$ is the capacity of edge (u, v) .
2. **Flow Conservation:** For all $u \in V \setminus \{s, t\}$,
 $v \in V, f(u, v) = v \in V, f(v, u)$, i.e., the total flow into u equals the total flow out of u (except for source and sink).

Value of the Flow:

$$|f| = \sum_{v \in V} f(s, v) - \sum_{v \in V} f(v, s)$$

This represents the total net flow out of the source s .

Ford-Fulkerson Method (1954)

The Ford-Fulkerson method finds the maximum flow from a source s to a sink t in a flow network $G = (V, E)$.

Algorithm:

1. Initialize flow $f(u, v) = 0$ for all $(u, v) \in E$.
2. While there exists an **augmenting path** p from s to t in the residual network G_f :

- Compute the **bottleneck capacity** $c_f(p)$ (the minimum residual capacity along p).
- Augment flow f along p by $c_f(p)$.

Residual Network:

Given flow f , define residual capacity c_f as:

$$c_f(u, v) = \begin{cases} c(u, v) - f(u, v) & \text{if } (u, v) \in E \\ f(v, u) & \text{if } (v, u) \in E \\ 0 & \text{otherwise} \end{cases}$$

Then the residual graph is $G_f = (V, E_f)$ where $E_f = \{(u, v) \in V \times V : c_f(u, v) > 0\}$.

Cuts and Optimality:

- A cut (S, T) of the network is a partition of V with $s \in S, t \in T$.
- The flow across the cut is:
 $f(S, T) = \sum_{u \in S, v \in T} f(u, v) - \sum_{u \in T, v \in S} f(v, u)$
- The capacity of the cut is:
 $c(S, T) = \sum_{u \in S, v \in T} c(u, v)$

For any flow f and any cut (S, T) , we have: $|f| \leq c(S, T)$.

Max-Flow Min-Cut Theorem:

The value of the maximum flow equals the capacity of the minimum cut.

Bipartite Graphs

A **bipartite graph** (or bigraph) is a graph $G = (U, V, E)$ whose vertices can be partitioned into two disjoint sets U and V such that every edge connects a vertex from U to one in V .

Properties:

- U and V are called the **parts** of the graph.
- Bipartiteness can be tested using BFS:

- Label the source s as even.
- During BFS, label each unvisited neighbor of a vertex with the opposite parity (even \leftrightarrow odd).
- If a conflict arises (a vertex is visited twice with the same parity), the graph is not bipartite.

Spanning Trees

Spanning Tree: A spanning tree T of an undirected graph $G = (V, E)$ is a subgraph that:

- Includes all vertices of G .
- Is a tree: connected and acyclic.

Minimum Spanning Tree (MST): An MST is a spanning tree of a weighted graph with the minimum total edge weight among all spanning trees of the graph.

Key Properties:

- Every connected undirected graph has at least one MST.
- An MST connects all vertices using the lightest possible total edge weight without forming cycles.

Prim's Algorithm

Goal: Find a Minimum Spanning Tree (MST) of a connected, weighted undirected graph.

Idea:

1. Start from an arbitrary root vertex r .
2. Maintain a growing tree T , initialized with r .
3. Repeatedly add the minimum-weight edge that connects a vertex in T to a vertex outside T .

Data Structures: Uses a min-priority queue to select the next lightest edge crossing the cut.

```
1: procedure PRIM( $G, w, r$ )
2:   let  $Q$  be a new min-priority queue
3:   for each  $u \in G.V$  do
4:      $u, key \leftarrow \infty$ 
5:   end for
6:   ENQUEUE( $Q, u$ )
7:   end for
8:   DECREASE-KEY( $Q, r, 0$ )
9:   while  $Q \neq \emptyset$  do
10:     $u \leftarrow$  EXTRACT-MIN( $Q$ )
11:    for each  $v \in G.Adj[u]$  do
12:      if  $v \in Q$  and  $w(u, v) < v, key$  then
13:         $v, key \leftarrow$  DECREASE-KEY( $Q, v, w(u, v)$ )
14:      end if
15:    end for
16:  end while
17: end procedure
```

Runtime: $\Theta((V + E) \log V)$ with binary heaps, $\Theta(E + V \log V)$ with Fibonacci heaps.

Kruskal's Algorithm

Goal: Find a Minimum Spanning Tree (MST) in a connected, weighted undirected graph.

Idea:

1. Start with an empty forest A (each vertex is its own tree).
2. Sort all edges in non-decreasing order of weight.
3. For each edge (u, v) , if u and v are in different trees (i.e., no cycle is formed), add the edge to A .
4. Use a disjoint-set (Union-Find) data structure to efficiently check and merge trees.

```
1: procedure KRUSKAL( $G, w$ )
2:    $A \leftarrow \emptyset$ 
3:   for each  $u \in G.V$  do
4:     MAKE-SET( $u$ )
5:   end for
6:   sort the edges of  $G, E$  into non-decreasing order by weight  $w$ 
7:   for each  $(u, v) \in$  sorted edge list do
8:     if FIND-SET( $u$ )  $\neq$  FIND-SET( $v$ ) then
9:        $A \leftarrow A \cup \{(u, v)\}$ 
10:    UNION( $u, v$ )
11:  end if
12: end if
13: end for
14: end procedure
```

Runtime: $\Theta(|E| \log |E|)$ due to sorting, plus nearly linear time for Union-Find operations (with union by rank and path compression).

Bellman-Ford Algorithm

Goal: Compute shortest paths from a single source s to all other vertices in a weighted graph $G = (V, E)$, allowing negative edge weights.

Key Idea:

- Relax all edges repeatedly (up to $|V| - 1$ times).
- After that, check for negative-weight cycles: if we can still relax an edge, a negative cycle exists.

Initialization:

```
1: procedure BELLMAN-FORD( $G, s$ )
2:   for each  $v \in G.V$  do
3:      $v, d \leftarrow \infty$   $\triangleright$  distance estimate
4:   end for
5:    $s, \pi \leftarrow$  NIL  $\triangleright$  predecessor
6:   end for
7: end procedure
```

Relaxation:

```
1: procedure RELAX( $u, v, w$ )
2:   if  $v, d > u, d + w(u, v)$  then
3:      $v, d \leftarrow u, d + w(u, v)$ 
4:      $v, \pi \leftarrow u$ 
5:   end if
6: end procedure
```

Main Algorithm:

```
1: procedure BELLMAN-FORD( $G, w, s$ )
2:   INIT-SINGLE-SOURCE( $G, s$ )
3:   for  $i \leftarrow 1$  to  $|G.V| - 1$  do
4:     for each edge  $(u, v) \in G.E$  do
5:       RELAX( $u, v, w$ )
6:     end for
7:   end for
8:   for each edge  $(u, v) \in G.E$  do
9:     if  $v, d > u, d + w(u, v)$  then
10:      return false  $\triangleright$  Negative-weight cycle detected
11:    end if
12:  end for
13:  return true
14: end procedure
```

Runtime: $\Theta(|V||E|)$

Handles: Negative weights (but no negative cycles)

Dijkstra's Algorithm

Goal: Compute the shortest paths from a single source s to all other vertices in a weighted graph $G = (V, E)$ with non-negative edge weights.

Key Idea:

- Greedily grow a set S of vertices with known shortest paths.
- At each step, pick the vertex $u \notin S$ with the smallest tentative distance u, d .
- Relax all edges (u, v) from u to update distance estimates.

Pseudocode:

```
1: procedure DIJKSTRA( $G, w, s$ )
2:   INIT-SINGLE-SOURCE( $G, s$ )
3:    $S \leftarrow \emptyset$ 
4:    $Q \leftarrow G.V$   $\triangleright$  insert all vertices into priority queue  $Q$ 
5:   while  $Q \neq \emptyset$  do
6:      $u \leftarrow$  EXTRACT-MIN( $Q$ )
7:      $S \leftarrow S \cup \{u\}$ 
8:     for each  $v \in Adj[u]$  do
9:       RELAX( $u, v, w$ )
10:    end for
11:  end while
12: end procedure
```

The Hiring Problem

Problem: We interview n candidates for a position, one by one in random order. After each interview, we decide immediately whether to hire the candidate. We want to compute the expected number of times we hire someone (i.e., when they are better than all previous candidates).

Indicator Random Variable:

Given a sample space and an event A , the indicator random variable for A is defined as:

$$I\{A\} = \begin{cases} 1 & \text{if } A \text{ occurs,} \\ 0 & \text{if } A \text{ does not occur.} \end{cases}$$

Then: $E[I\{A\}] = P(A)$

Expected Number of Hires:

Let X be the total number of hires. Define $X = \sum_{i=1}^n I_i$, where $I_i = 1$ if the i -th candidate is hired (i.e., better than all previous $i - 1$), and 0 otherwise.

$$[X] = \sum_{i=1}^n [I_i] = \sum_{i=1}^n \frac{1}{i} = H_n$$

Conclusion: The expected number of hires is $\Theta(\log n)$, even though there are n candidates.

Quick Sort

Quick Sort is a divide-and-conquer algorithm with the following steps:

1. **Divide:** Partition $A[p, \dots, r]$ into two (possibly empty) subarrays $A[p, \dots, q - 1]$ and $A[q, \dots, r]$ such that each element in the first subarray is $\leq A[q]$ and each element in the second subarray is $\geq A[q]$.
2. **Conquer:** Recursively sort the two subarrays by calling Quick Sort on them.
3. **Combine:** No work is needed to combine the subarrays since the sorting is done in-place.

Algorithm:

```
1: procedure PARTITION( $A, p, r$ )
2:    $x \leftarrow A[r]$ 
3:    $i \leftarrow p - 1$ 
4:   for  $j \leftarrow p$  to  $r - 1$  do
5:     if  $A[j] \leq x$  then
6:        $i \leftarrow i + 1$ 
7:       exchange  $A[i]$  with  $A[j]$ 
8:     end if
9:   end for
10:  exchange  $A[i + 1]$  with  $A[r]$ 
11:  return  $i + 1$ 
12: end procedure
```

Runtime:

```
1: procedure QUICK-SORT( $A, p, r$ )
2:   if  $p < r$  then
3:      $q \leftarrow$  PARTITION( $A, p, r$ )
4:     QUICK-SORT( $A, p, q - 1$ )
5:     QUICK-SORT( $A, q + 1, r$ )
6:   end if
7: end procedure
```

Randomized Partition:

```
1: procedure RANDOMIZED-PARTITION( $A, p, r$ )
2:    $i \leftarrow$  RANDOM( $p, r$ )
3:   exchange  $A[r]$  with  $A[i]$ 
4:   return PARTITION( $A, p, r$ )
5: end procedure
```

Randomized Quick-Sort:

```
1: procedure RANDOMIZED-QUICK-SORT( $A, p, r$ )
2:   if  $p < r$  then
3:      $q \leftarrow$  RANDOMIZED-PARTITION( $A, p, r$ )
4:     QUICK-SORT( $A, p, q - 1$ )
5:     QUICK-SORT( $A, q + 1, r$ )
6:   end if
7: end procedure
```

Expected Runtime:

After observing losses $\ell_i^t \in [0, 1]$, weights are updated as:

$$w_i^{t+1} = w_i^t \cdot e^{-\eta \ell_i^t}$$

where $\eta > 0$ is the learning rate.

Guarantees: For any expert i , the regret after T rounds is bounded by:

$$\text{Regret} \leq \eta T + \frac{\log n}{\eta}$$

Setting $\eta = \frac{\log n}{\sqrt{T}}$ gives regret of order $O(\sqrt{T \log n})$.

Use cases: Adversarial learning, portfolio selection, online convex optimization.

Online Algorithms

An **online algorithm** processes its input piece-by-piece in a serial fashion, i.e. it does not have access to the entire input from the start. Instead, it must make decisions based only on the current and past inputs without knowledge of future inputs.

Characteristics:

- Decisions are made in real-time.
- Cannot revise past decisions once new input arrives.
- Often evaluated using *competitive analysis*, comparing performance to an optimal offline algorithm.

Competitive Ratio:

If C_{online} is the cost incurred by the online algorithm and C_{opt} is the cost incurred by an optimal offline algorithm, then the competitive ratio is defined as:

$$\text{Competitive Ratio} = \max_{\text{input}} \frac{C_{\text{online}}}{C_{\text{opt}}}$$

An algorithm is said to be r -competitive if this ratio is at most r for all inputs.

Weighted Majority Algorithm

The **Weighted Majority Algorithm** (WMA) is an online learning algorithm that maintains a set of "experts" (prediction strategies), each assigned a weight. The algorithm predicts based on a weighted vote of the experts and penalizes those who make incorrect predictions.

Setup:

- n experts, each with an initial weight $w_i \leftarrow 1$.
- At each time step t , each expert i makes a prediction.
- The algorithm makes its own prediction based on a weighted majority.
- After the outcome is revealed, experts that predicted incorrectly are penalized by multiplying their weight by a factor $\beta \in (0, 1)$.

Guarantees: If there is an expert that makes at most m mistakes, then the number of mistakes made by the algorithm is at most:

$$M \leq (1 + \log n) \cdot m$$

(up to constant factors depending on β)

Use cases:

Binary prediction problems, stock forecasting, game playing.

Hedge Algorithm

The **Hedge Algorithm** generalizes Weighted Majority to handle real-valued losses and probabilistic predictions. It is used in adversarial multi-armed bandit and online optimization settings.

Setup:

- n actions (or experts), each with weight w_i^t