Octave vs. Python for Example 1.11

Below, we present an example file to show that, for our purposes, Python isn't that much different from Octave/MATLAB On the left side, we show the the script written using Octave (MATLAB compatibility requires breaking out the subfunctions), while on the right, we show the script rewritten to use Python+Casadi (with a bit of `mpc-tools-casadi` as well).

```
% cstr.m applies offset free linear MPC
% to the linearized and
% nonlinear CSTR.
% See Pannocchia and Rawlings, AIChE J, 2002.
%
% Edits by Michael Risbeck (April 2015).

global F F0 r E k0 DeltaH rhoCp T0 c0 U Tc hs

% parameters and sizes for the nonlinear system
delta = 1;
n = 3;
m = 2;
nmeas = n;
np = 1;
small = 1e-5; % Small number.


F0 = 0.1; %           m^3/min
T0 = 350; %           K
c0 =  1;  %           kmol/m^3
r  = 0.219; %         m
k0 = 7.2e10; %        minâĽŠ1
E  =  8750; %         K
U  =  54.94; %        kJ/(min m^2 K)
rho = 1e3;   %        kg/m^3
Cp  = 0.239;  %       kJ/(kg K)
DeltaH = -5e4; %      kJ/kmol
Tcs = 300; %          K
hs = 0.659; %         m
ps = 0.1*F0; %         m^3/min


rhoCp = rho*Cp;
function df = partial(x)
    global F F0 r E k0 DeltaH rhoCp T0 c0 U Tc
    c = x(1);
    T = x(2);
    h = x(3);
    k = k0*exp(-E/T);
    kprime = k*E/(T^2);
    Fprime = F0/(pi*r^2*h);
    df = [
        -Fprime - k, -kprime*c, ...
        -Fprime*(c0-c)/h, ...
        0, 0, (c0-c)/(pi*r^2*h);
        %
        -k*DeltaH/rhoCp, -Fprime ...
           - kprime*c*DeltaH/(rhoCp) ...
           - 2*U/(r*rhoCp), ...
        -Fprime*(T0-T)/h, ...
        2*U/(r*rhoCp), 0, (T0-T)/(pi*r^2*h);
        %
        0, 0, 0, 0, -1/(pi*r^2), 1/(pi*r^2)
```

```python
# Example 1.11 from Rawlings and Mayne.
import mpctools as mpc
import numpy as np
from scipy import linalg
import matplotlib.pyplot as plt
from matplotlib import gridspec



# Define some parameters and then the CSTR model.
Nx = 3
Nu = 2
Nd = 1
Ny = Nx
Delta = 1
eps = 1e-5 # Use this as a small number.


T0 = 350
c0 = 1
r = .219
k0 = 7.2e10
E = 8750
U = 54.94
rho = 1000
Cp = .239
dH = -5e4








def ode(x,u,d):
    # Grab the states, controls, and disturbance.
    [c, T, h] = x[0:Nx]
    [Tc, F] = u[0:Nu]
    [F0] = d[0:Nd]

    # Now create the ODE.
    rate = k0*c*np.exp(-E/T)

    dxdt = [
        F0*(c0 - c)/(np.pi*r**2*h) - rate,
        F0*(T0 - T)/(np.pi*r**2*h)
            - dH/(rho*Cp)*rate
            + 2*U/(r*rho*Cp)*(Tc - T),
        (F0 - F)/(np.pi*r**2)
    ]
    return np.array(dxdt)

# Turn into casadi function and simulator.
ode_casadi = mpc.getCasadiFunc(ode,
```

```octave
    ];
endfunction

function rhs = massenbalstst(x)
    global F F0 r E k0 DeltaH rhoCp T0 c0 U Tc hs
    c = x(1);
    T = x(2);
    h = x(3);
    k = k0*exp(-E/T);
    rate = k*c;
    dcdt = F0*(c0-c)/(pi*r^2*h) - rate;
    dTdt = F0*(T0-T)/(pi*r^2*h) - ...
        DeltaH/rhoCp*rate + ...
        2*U/(r*rhoCp)*(Tc-T);
    % fix the reactor height
    dhdt = h - hs;
    rhs = [dcdt; dTdt; dhdt];
endfunction

function rhs = massenbal(t, x)
    global F F0 r E k0 DeltaH rhoCp T0 c0 U Tc
    c = x(1);
    T = x(2);
    h = x(3);
    k = k0*exp(-E/T);
    rate = k*c;
    dcdt = F0*(c0-c)/(pi*r^2*h) - rate;
    dTdt = F0*(T0-T)/(pi*r^2*h) - ...
       DeltaH/rhoCp*rate + ...
       2*U/(r*rhoCp)*(Tc-T);
    dhdt = (F0 - F)/(pi*r^2);
    rhs = [dcdt; dTdt; dhdt];
endfunction
%% find the steady-state
Fs = F0; F = F0;
Tc = Tcs;
z0 = [c0; Tc; hs];
[z, fval, info] = fsolve(@massenbalstst, z0);
if ( info ~= 1 )
    warning('failure to find steady state!')
endif
cs = z(1);
Ts = z(2);
hs = z(3);
zs = [cs; Ts; hs];




%check the linear model
G = partial(zs);
Ac =  G(:, 1:n);
Bc = G(:, n+1:n+2);
Bpc = G(:,n+3:end);
C = eye(n);
sys = ss(Ac, [Bc, Bpc], C, ...
```

```python
    [Nx,Nu,Nd],["x","u","d"],funcname="ode")
cstr = mpc.DiscreteSimulator(ode, Delta,
    [Nx,Nu,Nd], ["x","u","d"])


# We don't need to take any derivatives by hand
# because Casadi can do that.
```

```python
# Steady-state values.
cs = .878
Ts = 324.5
hs = .659
Fs = .1
Tcs = 300
F0s = .1

# Update the steady-state values a few times to make
# sure they don't move.
for i in range(10):
    [cs,Ts,hs] = cstr.sim([cs,Ts,hs],[Tcs,Fs],
        [F0s]).tolist()
xs = np.array([cs,Ts,hs])
us = np.array([Tcs,Fs])
ds = np.array([F0s])

# Now get a linearization at this steady state.
ss = mpc.util.getLinearizedModel(ode_casadi,
    [xs,us,ds], ["A","B","Bp"], Delta)
A = ss["A"]
B = ss["B"]
Bp = ss["Bp"]
C = np.eye(Nx)
```

```octave
      zeros(size(C,1),size([Bc, Bpc],2)));
dsys = c2d(sys, delta);
A = dsys.a;
B = dsys.b(:,1:m);
Bp = dsys.b(:,m+1:end);

% set up linear controller
Q = diag(1./zs.^2);
R = diag(1./[Tcs; Fs].^2);
[K, P] = dlqr(A, B, Q, R);
K = -K;

% Pick whether to use good disturbance model.
useGoodDisturbanceModel = true();


if useGoodDisturbanceModel
    % disturbance model 6; no offset
    nd = 3;
    Bd = zeros(n, nd);
    Bd(:,3) = B(:,2);
    Cd = [1 0 0; 0 0 0; 0 1 0];
else
    % disturbance model with offset
    nd = 2;
    Bd = zeros(n, nd);
    Cd = [1 0; 0 0; 0 1];
end

Aaug = [A, Bd; zeros(nd, n), eye(nd)];
Baug = [B; zeros(nd, m)];
Caug = [C, Cd];
naug = size(Aaug,1);


% detectability test of disturbance model
detec = rank([eye(n+nd) - Aaug; Caug]);
if (detec < (n+nd))
  warning ('augmented system is not detectable\n')
endif
```

```python
# Weighting matrices for controller.
Q = np.diag(xs**-2)
R = np.diag(us**-2)

[K, Pi] = mpc.util.dlqr(A,B,Q,R)

# Define disturbance model.
useGoodDisturbanceModel = True


# Bad disturbance model with offset.
if useGoodDisturbanceModel:
    Nid = Ny # Number of integrating disturbances.
else:
    Nid = Nu


Bd = np.zeros((Nx,Nid))
Cd = np.zeros((Ny,Nid))

if useGoodDisturbanceModel:
    Cd[0,0] = 1
    Cd[2,1] = 1
    Bd[:,2] = B[:,1] # or Bp[:,0]
else:
    Cd[0,0] = 1
    Cd[2,1] = 1

# Augmented system. Trailing .A casts to array type.
Aaug = np.bmat([[A,Bd],
    [np.zeros((Nid,Nx)),np.eye(Nid)]]).A
Baug = np.vstack((B,np.zeros((Nid,Nu))))
Caug = np.hstack((C,Cd))

# Check rank condition for augmented system.
# See Lemma 1.8 from Rawlings and Mayne (2009).
svds = linalg.svdvals(np.bmat([[np.eye(Nx) - A,
                                 -Bd],[C,Cd]]))
rank = sum(svds > 1e-10)
if rank < Nx + Nid:
    print "*Warning: system not detectable!"
```

```octave
% set up state estimator; use KF
Qw = zeros(naug);
Qw(1:n,1:n) = small*eye(n);
Qw(n+1:end,n+1:end) = small*eye(nd); Qw(end,end)=1.0;
Rv = diag((5e-4*zs).^2);
[L, M, P] = dlqe(Aaug, eye(naug), Caug, Qw, Rv);
Lx = L(1:n,:);
Ld = L(n+1:end,:);


ntimes = 50;
x0 = zeros(n, 1);
x = zeros(n, ntimes);
x(:, 1) = x0;
```

```python
# Build augmented penalty matrices for KF.
Qw = eps*np.eye(Nx + Nid)
Qw[-1,-1] = 1
Rv = eps*np.diag(xs**2)

# Get Kalman filter.
[L, P] = mpc.util.dlqe(Aaug, Caug, Qw, Rv)
Lx = L[:Nx,:]
Ld = L[Nx:,:]

# Now simulate things.
Nsim = 50
t = np.arange(Nsim+1)*Delta
x = np.zeros((Nsim+1,Nx))
```

```matlab
y = zeros(nmeas, ntimes);
u = zeros(m, ntimes);
randn('seed', 0);
v = zeros(nmeas, ntimes);
xhat_ = zeros(n, ntimes);
dhat_ = zeros(nd, ntimes);
xhat = xhat_;
dhat = dhat_;
time = (0:ntimes-1)*delta;
xs = zeros(n, ntimes);
us = zeros(m, ntimes);
ys = zeros(nmeas, ntimes);
etas = zeros(nmeas, ntimes);
options = [];

% Disturbance and setpoint.
p = [zeros(np, 10), ps*ones(np, ntimes-10)];
yset = zeros(nmeas,1);


% Steady-state target matrices.
H = [1 0 0; 0 0 1];
Ginv = inv([eye(n)-A, -B; ...
    H*C, zeros(size(H,1), m)]);



for i = 1: ntimes
    %% measurement
    y(:,i) = C*x(:,i) + v(:,i);

    %% state estimate
    ey = y(:,i) - C*xhat_(:,i) -Cd*dhat_(:,i);
    xhat(:,i) = xhat_(:,i) + Lx*ey;
    dhat(:,i) = dhat_(:,i) + Ld*ey;

    % Stop if at last time.
    if (i == ntimes) break; endif

    %% target selector
    tmodel.p = dhat(:,i);

    qs = Ginv*[Bd*dhat(:,i); H*(yset-Cd*dhat(:,i))];
    xss = qs(1:n);
    uss = qs(n+1:end);
    xs(:,i) = xss;
    us(:,i) = uss;
    ys(:,i) = C*xss + Cd*dhat(:,i);

    %% control law
    x0 = xhat(:,i) - xs(:,i);
    u(:,i) = K*x0 + us(:,i);

    %% plant evolution
    t = [time(i); mean(time(i:i+1)); time(i+1)];
    z0 = x(:,i) + zs;
    Tc = u(1,i) + Tcs;
    F  = u(2,i) + Fs;
```

```python
u = np.zeros((Nsim,Nu))
y = np.zeros((Nsim+1,Ny))
err = y.copy()
v = y.copy()
xhat = x.copy() # State estimate after measurement.
xhatm = xhat.copy() # ... before measurement.
dhat = np.zeros((Nsim+1,Nid))
dhatm = dhat.copy()







# Pick disturbance and setpoint.
d = np.zeros((Nsim,Nd))
d[:,0] = (t[:-1] >= 10)*.1*F0s
ysp = np.zeros(y.shape)
contVars = [0,2] # Concentration and height.

# Steady-state target selector matrices.
H = np.zeros((Nu,Ny))
H[range(len(contVars)),contVars] = 1
Ginv = np.array(np.bmat([
    [np.eye(Nx) - A, -B],
    [H.dot(C), np.zeros((H.shape[0], Nu))]
]).I) # Take inverse.

for n in range(Nsim + 1):
    # Take plant measurement.
    y[n,:] = C.dot(x[n,:]) + v[n,:]

    # Update state estimate with measurement.
    err[n,:] = (y[n,:] - C.dot(xhatm[n,:])
        - Cd.dot(dhatm[n,:]))
    xhat[n,:] = xhatm[n,:] + Lx.dot(err[n,:])
    dhat[n,:] = dhatm[n,:] + Ld.dot(err[n,:])

    # Make sure we aren't at the last timestep.
    if n == Nsim: break

    # Steady-state target.
    rhs = np.concatenate((Bd.dot(dhat[n,:]),
        H.dot(ysp[n,:] - Cd.dot(dhat[n,:]))))
    qsp = Ginv.dot(rhs)
    xsp = qsp[:Nx]
    usp = qsp[Nx:]



    # Regulator.
    u[n,:] = K.dot(xhat[n,:] - xsp) + usp

    # Simulate with nonlinear model.
    x[n+1,:] = cstr.sim(x[n,:] + xs, u[n,:] + us,
        d[n,:] + ds) - xs
```

```
    F0 = p(:,i) + Fs;
    if exist('OCTAVE_VERSION','builtin')
        z = lsode(@(x,t) massenbal(t,x), z0, t);
        tout = t;
    else
        [tout, z] = ode15s(@massenbal, t, ...
            z0, options);
    end
    if sum(tout ~= t)
        warning('integrator failed!')
    end
    x(:,i+1) = z(end,:)' - zs;

    %% advance state estimates
    xhat_(:,i+1) = A*xhat(:,i) + ...
        Bd*dhat(:,i) + B*u(:,i);
    dhat_(:,i+1) = dhat(:,i);
end
u(:,end) = u(:,end-1); % Repeat for stair plot.

% dimensional units
yd = y + kron(ones(1, ntimes), zs);
ud = u + kron(ones(1, ntimes), [Tcs; Fs]);


% *** Plots ***
figure()
axmul = eye(4) + .05*[1,-1,0,0; ...
    -1,1,0,0;0,0,1,-1;0,0,-1,1];
subplot(3,2,1)
plot(time, yd(1,:), '-or')
ylabel('c (kmol/m^3)')
axis(axis()*axmul)
subplot(3,2,3)
plot(time, yd(2,:), '-or')
ylabel('T (K)')
axis(axis()*axmul)
subplot(3,2,5)
plot(time, yd(3,:), '-or')
ylabel('h (m)')
xlabel('Time')
axis(axis()*axmul)
subplot(3,2,2)
stairs(time, ud(1,:), '-r')
ylabel('Tc (K)')
axis(axis()*axmul)
subplot(3,2,4)
stairs(time, ud(2,:), '-r')
ylabel('F (m^3/min)')
xlabel('Time')
axis(axis()*axmul)
print('cstr_octave.pdf','-dpdf','-S720,600')
```

```
        # Advance state estimate.
        xhatm[n+1,:] = (A.dot(xhat[n,:])
            + Bd.dot(dhat[n,:]) + B.dot(u[n,:]))
        dhatm[n+1,:] = dhat[n,:]


# Define plotting function.
def cstrplot(x,u,ysp=None,contVars=[],title=None):
    u = np.concatenate((u,u[-1,:]))
    t = np.arange(0,x.shape[0])*Delta
    ylabelsx = ["$c$ (mol/L)", "$T$ (K)", "$h$ (m)"]
    ylabelsu = ["$T_c$ (K)", "$F$ (kL/min)"]

    gs = gridspec.GridSpec(Nx*Nu,2)

    fig = plt.figure(figsize=(10,6))
    for i in range(Nx):
        ax = fig.add_subplot(gs[i*Nu:(i+1)*Nu,0])
        ax.plot(t,x[:,i] + xs[i],'-ok')
        if i in contVars:
            ax.step(t,ysp[:,i] + xs[i],'-r',
                    where="post")
        ax.set_ylabel(ylabelsx[i])
        mpc.plots.zoomaxis(ax,yscale=1.1)
        mpc.plots.prettyaxesbox(ax)
        mpc.plots.prettyaxesbox(ax,
            facecolor="white",front=False)
    ax.set_xlabel("Time (min)")
    for i in range(Nu):
        ax = fig.add_subplot(gs[i*Nx:(i+1)*Nx,1])
        ax.step(t,u[:,i] + us[i],'-k',where="post")
        ax.set_ylabel(ylabelsu[i])
        mpc.plots.zoomaxis(ax,yscale=1.25)
        mpc.plots.prettyaxesbox(ax)
        mpc.plots.prettyaxesbox(ax,
            facecolor="white",front=False)
    ax.set_xlabel("Time (min)")
    fig.tight_layout(pad=.5)
    if title is not None:
        fig.canvas.set_window_title(title)
    return fig
fig = cstrplot(x,u,ysp=None,contVars=[],title=None)
mpc.plots.showandsave(fig,"cstr_python.pdf",facecolor="none
```