

v17.56.7 Backend Upgrade Report

Dual Mode Alert System + Tracker Integrity Upgrade

Date: June 2, 2026

Version: v17.56.7

Status:  Complete — All tests passing

Changes Summary

1. Database Schema Migration

- **New columns on opportunities :** `mode` (TEXT), `session_tag` (TEXT), `valid` (INTEGER)
- **New columns on signals :** `mode` (TEXT), `session_tag` (TEXT), `valid` (INTEGER)
- **Default values for historical data:** `mode='DATA'` , `session_tag='NY'` , `valid=1`
- **New indexes:** `idx_opportunities_mode` , `idx_opportunities_session_tag` , `idx_signals_mode` , `idx_signals_session_tag`
- **Schema update:** `status` CHECK constraint now includes `'INVALID'`
- Migration is idempotent — safe to re-run on existing databases

2. v17.56.7 Payload Decoder

- New `normalize_v17_56_7_payload()` handles dual-mode JSON format
- Detects v17.56.7 via `direction` + `setup` + version fields
- **Direction taken EXACTLY from JSON** — no inference or flipping
- `htf_bias` string values ("BULLISH"/"BEARISH") handled alongside numeric codes
- Full backward compatibility with v17.56.6 payloads (auto-default: `mode=DATA`, `session=NY`, `valid=true`)

3. Trade Classification Fix (CRITICAL)

- Missing `entry` / `sl` / `tp` (value = 0 or null) → `status = "INVALID"` with `rr = 0` , `pnl = 0`
- Previously these would have been classified as `"LOST"` — **fixed**

4. Zombie Trade Prevention

- `valid: false` payloads are logged as informational events but **not stored** as trades
- Returns `{"status": "ignored", "reason": "invalid signal (valid=false)"}` with HTTP 200
- Prevents POI=0 or invalidated zones from creating junk records

5. EXECUTION-Only Performance Stats

- New `GET /api/v1/stats` endpoint — defaults to `mode=EXECUTION`
- Supports `?mode=ALL` for combined stats, `?mode=DATA` for data-only
- `get_performance_summary_filtered()` function in `database.py`

6. Session-Based Analytics

- New `GET /api/v1/session-performance` endpoint
- Returns London vs NY comparison with `win_rate`, `avg_rr`, `total_trades`, `expectancy`
- Always filters by `mode=EXECUTION` for accurate performance

7. Updated API Endpoints

Endpoint	Method	Change
/api/v1/health	GET	Version bumped to v17.56.7, features list added
/api/v1/signal	POST	v17.56.7 payload support + zombie prevention
/api/v1/signals	GET	New filters: ? mode=EXECUTION&session=LONDON
/api/v1/stats	GET	NEW — EXECUTION-only performance stats
/api/v1/session-performance	GET	NEW — London vs NY comparison

Files Modified

File	Changes
app.py	Version bump, new endpoint logging
src/database.py	Migration function, new columns, filtered queries
src/oie_processor.py	v17.56.7 normalizer, direction-exact, backward compat
src/oie_database.py	Insert with mode/session_tag/valid columns
src/tracker/processor.py	INVALID classification, mode/session passthrough
src/webhook_server/routes.py	Zombie prevention, session analytics, stats endpoint
schemas/schema.sql	INVALID added to status CHECK
schemas/migrate_v17_56_7_dual_mode.sql	NEW — migration script

Test Results

- ✓ v17.56.7 Normalize ☐ correct parsing of all fields
- ✓ DB insert ☐ mode/session_tag/valid stored correctly
- ✓ v17.56.6 backward compat ☐ defaults applied (DATA/NY/true)
- ✓ Zombie prevention ☐ valid=false ☐ ignored
- ✓ Legacy bridge ☐ mode/session passed to signals table
- ✓ INVALID classification ☐ missing EP/SL/TP ☐ INVALID (not LOST)
- ✓ Direction exact ☐ SHORT taken from JSON, no flipping
- ✓ Health check ☐ v17.56.7 with features list
- ✓ Session performance ☐ London vs NY endpoint functional
- ✓ Stats endpoint ☐ defaults to EXECUTION mode
- ✓ Signals filter ☐ mode/session query params working

v17.56.7 Payload Format

```
{
  "version": "v17.56.7",
  "mode": "EXECUTION",
  "session": "LONDON",
  "symbol": "GBPUSD",
  "direction": "LONG",
  "setup": "A+ SNIPER",
  "poi": 6,
  "align": "WITH_TREND",
  "htf_bias": "BULLISH",
  "ltf_bias": "BULLISH",
  "timestamp": "2026-06-02T10:00:00Z",
  "entry": 1.34195,
  "sl": 1.33800,
  "tp": 1.35385,
  "valid": true
}
```

Deployment Ready

- All migrations are idempotent (safe for Railway auto-deploy)
- No breaking changes to existing data
- Historical records preserved with default values