

v17.56.8 Backend Upgrade Report

HUD Sync + AMD Context Awareness + Daily Counters

Date: June 3, 2026

Version: v17.56.8

Status:  Complete — All tests passing (53/53)

Overview

v17.56.8 syncs the backend with the new TradingView HUD by capturing three additional fields on every alert payload:

Field	Type	Description	Default
<code>amd_state</code>	TEXT	Market AMD / Wyckoff state	<code>ACCUMULATION</code>
<code>sniper_today</code>	INTEGER	Count of A+ SNIPER alerts fired today (HUD counter)	<code>0</code>
<code>execution_today</code>	INTEGER	Count of EXECUTION-mode alerts fired today (HUD counter)	<code>0</code>

Valid `amd_state` values: `ACCUMULATION`, `MANIPULATION`, `DISTRIBUTION`, `MARKUP`, `MARKDOWN`.
Any unknown / missing value is normalized to the default `ACCUMULATION`.

This release is **fully backward compatible** with v17.56.7 (and earlier) payloads — missing HUD fields receive safe defaults.

Changes Summary

1. Single Source of Truth — `src/version.py` (NEW)

- `VERSION = "v17.56.8"` — used by `app.py`, `/health`, and `GET /signal`.
- `FEATURES` list, exposed via `get_features()`:
`dual_mode`, `session_analytics`, `zombie_prevention`, `invalid_classification`,
`amd_context_awareness`, `hud_sync`, `daily_counters`.
- `VALID_AMD_STATES`, `DEFAULT_AMD_STATE`, and `normalize_amd_state(value, default)` helper (case-insensitive, trims whitespace, falls back to default on invalid input).

2. Database Schema Migration

- New columns on `signals`:** `amd_state` (TEXT, default `'ACCUMULATION'`),
`sniper_today` (INTEGER, default `0`), `execution_today` (INTEGER, default `0`).

- **New columns on opportunities** : same three columns / defaults.
- **New index:** `idx_signals_and_state`.
- Runtime migration `_run_hud_sync_migration()` in `database.py` is **idempotent** — it checks `PRAGMA table_info()` before each `ALTER TABLE` (SQLite 3.40.x does not support `ADD COLUMN IF NOT EXISTS`), so it is safe to re-run on Railway auto-deploy. Reference SQL lives in `schemas/migrate_v17_56_8_hud_sync.sql`.
- Historical rows are backfilled with the column defaults.

3. v17.56.8 Payload Decoder

- `normalize_v17_56_7_payload()` now also parses `amd_state` / `sniper_today` / `execution_today` (the dual-mode format is shared by v17.56.7 and v17.56.8).
- New explicit decoder API in `src/oie_processor.py` :
- `decode_v17_56_8_payload()` — parses the new HUD fields.
- `decode_v17_56_7_payload()` — applies safe defaults for older payloads.
- `decode_legacy_payload()` — defaults for v17.25 / v17.14 / legacy.
- `decode_payload()` — **universal dispatcher** that routes by `version`.
- `amd_state` is normalized via `normalize_amd_state()` ; counters via `_to_int()`.

4. Backward Compatibility

- v17.56.7 payloads (which lack the HUD fields) decode cleanly with `amd_state='ACCUMULATION'`, `sniper_today=0`, `execution_today=0`.
- Existing `test_oie_integration.py` continues to pass unchanged (no regression).

5. Persistence (both pipelines)

- `insert_opportunity()` stores the three new fields on the `opportunities` table.
- The legacy bridge (`oie_to_legacy_compact` → `expand_compact_entry` → `insert_signal`) carries the fields through to the `signals` table.

6. API Responses & Filtering

- `/api/v1/signals` and `/api/v1/signals/<id>` use `SELECT *`, so the new columns appear automatically in responses.
- `GET /api/v1/signals` gains an optional `?amd_state=` filter (backed by `get_signals()` / `count_signals()`); the active filters are echoed back in the response.

7. Updated API Endpoints

Endpoint	Method	Change
/api/v1/health	GET	Version → v17.56.8 ; features now include amd_context_awareness , hud_sync , daily_counters
/api/v1/signal	GET	Version string sourced from src/version.py
/api/v1/signal	POST	Parses + stores amd_state / sniper_today / execu- tion_today
/api/v1/signals	GET	New optional filter ? amd_state=MANIPULATION ; new fields in rows

Files Modified / Created

File	Changes
<code>src/version.py</code>	NEW — VERSION + FEATURES + AMD helpers (single source of truth)
<code>schemas/migrate_v17_56_8_hud_sync.sql</code>	NEW — reference migration script
<code>schemas/schema.sql</code>	New columns + index on <code>signals</code>
<code>schemas/migrate_v17_14_oie.sql</code>	New columns on <code>opportunities</code> CREATE TABLE
<code>src/database.py</code>	<code>_run_hud_sync_migration()</code> , <code>insert_signal</code> cols, <code>amd_state</code> filter
<code>src/oie_processor.py</code>	v17.56.8 detection + parsing + explicit decoder API
<code>src/oie_database.py</code>	<code>insert_opportunity</code> stores new fields; version default bump
<code>src/tracker/processor.py</code>	<code>expand_compact_entry</code> passthrough of HUD fields
<code>src/webhook_server/routes.py</code>	<code>/health</code> from <code>version.py</code> ; <code>?amd_state=</code> filter
<code>app.py</code>	Startup banner uses <code>VERSION</code>
<code>test_v17_56_8.py</code>	NEW — full test suite (53 checks)

Test Results

```

STEP 1: version.py single source of truth ..... 
STEP 2: DB migration adds columns (signals + opps) ..  (idempotent)
STEP 3: v17.56.8 payload decodes new fields ..... 
STEP 4: v17.56.7 backward compat (defaults) ..... 
STEP 5: decode_payload() universal dispatcher ..... 
STEP 6: Opportunity insert/retrieve roundtrip ..... 
STEP 7: Signal insert/retrieve roundtrip (bridge) ... 
STEP 8: /health returns v17.56.8 + features ..... 
STEP 9: /signals API includes new fields ..... 
-----
RESULTS: 53 passed, 0 failed

```

Run with: `python3 test_v17_56_8.py` (from repo root).

v17.56.8 Payload Format

```
{
  "version": "v17.56.8",
  "mode": "EXECUTION",
  "session": "NY",
  "symbol": "EURUSD",
  "direction": "LONG",
  "setup": "A+ SNIPER",
  "poi": 6,
  "align": "WITH_TREND",
  "htf_bias": "BULLISH",
  "ltf_bias": "BULLISH",
  "timestamp": "2026-06-03T14:30:00Z",
  "entry": 1.08550,
  "sl": 1.08250,
  "tp": 1.09450,
  "valid": true,
  "amd_state": "MANIPULATION",
  "sniper_today": 3,
  "execution_today": 5
}
```

Deployment Notes

- All migrations are **idempotent** and run automatically on startup (`init_db()` → `_run_hud_sync_migration()`), so Railway auto-deploy from `main` applies the schema changes with no manual step required.
- No breaking changes — historical records are preserved and backfilled with defaults (`ACCUMULATION` / `0` / `0`).
- Stacks on top of v17.56.7 (Dual Mode Alert System).