

v17.56.9 Backend Upgrade Report

Guardian HTF-Gating & Risk Labels

Date: June 5, 2026

Version: v17.56.9

Status:  Complete — All tests passing (66/66 + 53/53 regression + integration)

Overview

v17.56.9 syncs the backend with the new Pine Script Guardian HTF-gating safety feature by capturing two additional optional fields on every alert payload:

Field	Type	Description	Default
<code>guardian_label</code>	TEXT	Full Guardian label incl. HTF warnings (e.g. <code>CONTINUATION BUY (HTF COUNTER – STANDBY)</code>)	<code>NULL</code>
<code>guardian_risk</code>	INTEGER	HTF-gating risk level	<code>0</code>

Valid `guardian_risk` values: `0` = low (HTF aligned), `1` = medium (minor mismatch), `2` = high (counter-trend / STANDBY). Any unknown / out-of-range / missing value is normalized to the default `0`.

This release is **fully backward compatible** with v17.56.8, v17.56.7 (and earlier) payloads — missing Guardian fields receive safe defaults (`guardian_label=NULL` , `guardian_risk=0`).

Changes Summary

1. Single Source of Truth — `src/version.py`

- `VERSION = "v17.56.9"` — used by `app.py` , `/health` , and `GET /signal` .
- Added `"guardian_htf_gating"` to the `FEATURES` list (exposed via `get_features()`).
- New `VALID_GUARDIAN_RISK = (0, 1, 2)` , `DEFAULT_GUARDIAN_RISK = 0` , and the `normalize_guardian_risk(value, default=0)` helper — coerces int/str input, guards against `bool` , and falls back to the default on out-of-range/invalid input.

2. Database Schema Migration

- New columns on `signals` :** `guardian_label` (TEXT, nullable), `guardian_risk` (INTEGER, default `0`).
- New columns on `opportunities` :** same two columns / defaults.

- **New indexes:** `idx_signals_guardian_risk`, `idx_opportunities_guardian_risk`.
- Runtime migration `_run_guardian_gate_migration()` in `database.py` is **idempotent** — it checks `PRAGMA table_info()` before each `ALTER TABLE` (SQLite 3.40.x does not support `ADD COLUMN IF NOT EXISTS`), so it is safe to re-run on Railway auto-deploy. Reference SQL lives in `schemas/migrate_v17_56_9_guardian_fields.sql`.
- Historical rows are backfilled with the column defaults.

3. v17.56.9 Payload Decoder

- `normalize_v17_56_7_payload()` / `normalize_oie_payload()` now also parse `guardian_label` (passthrough) and `guardian_risk` (via `normalize_guardian_risk()`).
- The dual-mode format is shared by v17.56.7/56.8/56.9, and `_is_v17_56_7_payload()` now also recognizes the `v17.56.9` version prefix.
- New explicit decoder API in `src/oie_processor.py`:
- `decode_v17_56_9_payload()` — parses the new Guardian fields.
- `decode_v17_56_8_payload()` / `decode_v17_56_7_payload()` / `decode_legacy_payload()` — apply safe Guardian defaults for older payloads.
- `decode_payload()` — **universal dispatcher** now routes `v17.56.9` first.

4. Backward Compatibility

- v17.56.8 / v17.56.7 payloads (which lack the Guardian fields) decode cleanly with `guardian_label=None`, `guardian_risk=0`.
- Existing `test_v17_56_8.py` (53 checks) and `test_oie_integration.py` continue to pass unchanged (no regression). The v17.56.8 version-string assertions were relaxed to `>= v17.56.8` since `VERSION` is a forward-moving single source of truth.

5. Persistence (both pipelines)

- `insert_opportunity()` stores the two new fields on the `opportunities` table (version default bumped to `v17.56.9`).
- The legacy bridge (`oie_to_legacy_compact` → `expand_compact_entry` → `insert_signal`) carries the fields through (`_guardian_label` / `_guardian_risk`) to the `signals` table.

6. API Responses & Filtering

- `/api/v1/signals` and `/api/v1/signals/<id>` use `SELECT *`, so the new columns appear automatically in responses.
- `GET /api/v1/signals` gains an optional `?guardian_risk=` filter (backed by `get_signals()` / `count_signals()`); the active filters are echoed back in the response.

7. Updated API Endpoints

Endpoint	Method	Change
/api/v1/health	GET	Version → v17.56.9 ; features now include guardian_htf_gating
/api/v1/signal	GET	Version string sourced from src/version.py
/api/v1/signal	POST	Parses + stores guardian_label / guardian_risk
/api/v1/signals	GET	New optional filter ?guardian_risk=2 ; new fields in rows

Files Modified / Created

File	Changes
src/version.py	VERSION → v17.56.9 ; guardian_htf_gating feature; normalize_guardian_risk() + constants
schemas/migrate_v17_56_9_guardian_fields.sql	NEW — reference migration script
schemas/schema.sql	New columns + index on signals
schemas/migrate_v17_14_oie.sql	New columns on opportunities CREATE TABLE
src/database.py	_run_guardian_gate_migration() , insert_signal cols, guardian_risk filter
src/oie_processor.py	v17.56.9 detection + parsing + decode_v17_56_9_payload() + dispatcher
src/oie_database.py	insert_opportunity stores new fields; version default bump
src/tracker/processor.py	expand_compact_entry passthrough of Guardian fields
src/webhook_server/routes.py	docstring bump; ?guardian_risk= filter
app.py	Startup banner mentions Guardian HTF-Gating
test_v17_56_9.py	NEW — full test suite (66 checks)
test_v17_56_8.py	Version assertions relaxed to >= v17.56.8 (no functional change)

Test Results

```

STEP 1: version.py + guardian_risk normalize ..... ✓
STEP 2: DB migration adds guardian columns ..... ✓ (idempotent)
STEP 3: v17.56.9 payload decodes new fields ..... ✓
STEP 4: v17.56.8 / v17.56.7 backward compat ..... ✓
STEP 5: decode_payload() universal dispatcher ..... ✓
STEP 6: Opportunity insert/retrieve roundtrip ..... ✓
STEP 7: Signal insert/retrieve roundtrip (bridge) .... ✓
STEP 8: guardian_risk filter on get/count_signals .... ✓
STEP 9: Three Guardian risk scenarios (0/1/2) ..... ✓
STEP 10: /health returns v17.56.9 + feature ..... ✓
STEP 11: /signals API includes new fields + filter .... ✓
-----
RESULTS: 66 passed, 0 failed

```

Run with: `python3 test_v17_56_9.py` (from repo root).

Regression: `test_v17_56_8.py` → 53/53, `test_oie_integration.py` → all pass.

v17.56.9 Payload Format

```

{
  "version": "v17.56.9",
  "mode": "EXECUTION",
  "session": "NY",
  "symbol": "EURUSD",
  "direction": "LONG",
  "setup": "A+ SNIPER",
  "poi": 6,
  "align": "COUNTER_TREND",
  "htf_bias": "BEARISH",
  "ltf_bias": "BULLISH",
  "timestamp": "2026-06-05T14:30:00Z",
  "entry": 1.08550,
  "sl": 1.08250,
  "tp": 1.09450,
  "valid": true,
  "amd_state": "MANIPULATION",
  "sniper_today": 3,
  "execution_today": 5,
  "guardian_label": "CONTINUATION BUY (HTF COUNTER – STANDBY)",
  "guardian_risk": 2
}

```

Deployment Notes

- All migrations are **idempotent** and run automatically on startup (`init_db()` → `_run_guardian_gate_migration()`), so Railway auto-deploy from `main` applies the schema changes with no manual step required.
- No breaking changes — historical records are preserved and backfilled with defaults (`NULL` / `0`).

- Stacks on top of v17.56.8 (HUD Sync) → v17.56.7 (Dual Mode Alert System).
Recommended merge order: PR #12 (v17.56.7) → PR #14 (v17.56.8) → this PR.