

# Sharing Project Settings

Qt Creator stores user-specific project settings in a *.user* file. You can share these settings between several projects as a *.shared* file. It has the same XML structure as a *.user* file, but only contains the settings to share.

## Creating Shared Settings File

The easiest way to create a *.shared* file is to copy settings from the *.user* file. Typically, you would share some of the values in the `ProjectExplorer.Project.EditorSettings` section.

**Note:** You must always specify the `ProjectExplorer.Project.Updater.FileVersion` variable and use the same value for it as in the *.user* file.

You can then deliver the *.shared* file to other developers or copy it to other development PCs.

The following is an example of a *.shared* file:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE QtCreatorProject>
<qtcreator>
  <data>
    <variable>ProjectExplorer.Project.EditorSettings</variable>
    <valuemap type="QVariantMap">
      <value type="bool" key="EditorConfiguration.SpacesForTabs">true</value>
      <value type="bool" key="EditorConfiguration.AutoSpacesForTabs">>false</value>
      <value type="int" key="EditorConfiguration.TabSize">14</value>
      <value type="int" key="EditorConfiguration.IndentSize">4</value>
    </valuemap>
  </data>
  <data>
    <variable>ProjectExplorer.Project.Updater.FileVersion</variable>
    <value type="int">10</value>
  </data>
</qtcreator>
```

## Updating Shared Settings

If you receive a *.shared* file and do not want to use a particular setting in it, you can change it. Qt Creator marks it a *sticky* setting. The next time you open a project, the setting is not updated. Qt Creator tracks sticky settings in the *.user* file and removes the mark if the values in the user and shared files eventually become identical. This is to avoid a permanent sticky setting that was created just because you wanted to try something out.

[< Using Custom Output Parsers](#)[Managing Sessions >](#)

© 2022 The Qt Company Ltd. Documentation contributions included herein are the copyrights of their respective owners. The documentation provided herein is licensed under the terms of the [GNU Free Documentation License version 1.3](#) as published by the Free Software Foundation. Qt and respective logos are trademarks of The Qt Company Ltd in Finland and/or other countries worldwide. All other trademarks are property of their respective owners.

[Contact Us](#)

## Company

- [About Us](#)
- [Investors](#)
- [Newsroom](#)
- [Careers](#)
- [Office Locations](#)

## Support

- [Support Services](#)
- [Professional Services](#)
- [Partners](#)
- [Training](#)

## Community

- [Contribute to Qt](#)
- [Forum](#)
- [Wiki](#)
- [Downloads](#)
- [Marketplace](#)

## Licensing

- [Terms & Conditions](#)
- [Open Source](#)
- [FAQ](#)

## For Customers

- [Support Center](#)
- [Downloads](#)
- [Qt Login](#)
- [Contact Us](#)
- [Customer Success](#)

