


Debugging a Qt Quick Example Application

This section uses the [Same Game](#) example application to illustrate how to debug Qt Quick applications in the **Debug** mode.

For more information about all the options you have, see [Debugging Qt Quick Projects](#).

The Same Game demo shows how to write a game in QML, using JavaScript for all the game logic. Open the demo project in Qt Creator to debug it:


1. To look at the code that starts a new game, place a breakpoint in `samegame.qml` by clicking between the line number and the window border on the line where where the `startNewGame()` function is called (1).




The red circle indicates that a breakpoint is now set on that line number.


2. Select **Debug > Start Debugging > Start Debugging of Startup Project** or press **F5**.
3. Once the Same Game application starts, select **Puzzle** to start a new game.








4. When the debugger hits the breakpoint, it interrupts the application. Qt Creator displays the nested function calls leading to the current position as a call stack trace (1).



5. Click the  (Step Into) button on the toolbar or press F11 to step into the code in the stack. The samegame.js file opens in the code editor at the function that starts a new game.



6. Examine the local variables in the **Locals** view. Step through the code to see how the information changes in the view.
7. Add a breakpoint at the end of the `startNewGame()` function, and click  (Continue) to hit the breakpoint.




```

137 .....loadMap(map);
138 .....else//Note that we load them in reverse order for correct visual stacking
139 .....for(var column:=maxColumn-1; column>=0; column--)
140 .....for(var row:=maxRow-1; row>=0; row--)
141 .....createBlock(column, row);
142 .....if(gameMode==="puzzle") .....
143 .....getLevelHistory();//Needs to be after map load
144 .....gameDuration:=new Date();
145 }


```

8. To execute JavaScript commands in the current context, open the **QML Debugger Console**.



9. To remove a breakpoint, right-click it and select **Delete Breakpoint**.

10. In the **Locals** view, explore the object structure at runtime.



11. Select **Debug > Show Application on Top** to keep the application visible while you interact with the debugger.

12. Select **Debug > Select** to activate selection mode and then click the **Menu** button to move into the **menuButton** component in the **Locals** view and the code editor.

13. In the **Locals** view, double-click the value of a property to change it.



Contact Us

Company

- About Us
- Investors
- Newsroom
- Careers
- Office Locations

Support

- Support Services
- Professional Services
- Partners
- Training

Community

- Contribute to Qt
- Forum
- Wiki
- Downloads
- Marketplace

Licensing

- Terms & Conditions
- Open Source
- FAQ

For Customers

- Support Center
- Downloads
- Qt Login
- Contact Us
- Customer Success